


86 - 567 - 40

| VARADA ENERGIES PVT LTD. <b>PRODUCT TEST CERTIFICATE</b> |                          |                             |                               |
|----------------------------------------------------------|--------------------------|-----------------------------|-------------------------------|
| <b>GENERAL INFORMATION</b>                               |                          |                             |                               |
| Customer Name                                            |                          | Customer Order No.          |                               |
|                                                          |                          | Test Cell No.               | 2                             |
| <b>PRODUCT INFORMATION</b>                               |                          |                             |                               |
| Model                                                    | VEPL-40-CDP              | Genset Serial No.           | VEPL/2021-22/0071             |
| Engine Serial No.                                        | MBHM 113215              | Alternator Serial No.       | G21K 467926                   |
| Brand Name                                               | Ashok Leyland            | Alternator Make.            | STAMFORD                      |
| Fuel Type                                                | HSD                      | Controller Type             | DEEP SEA                      |
| Gowoner Type                                             | MECHANICAL               | Cooling System Type         | WATER COOLED                  |
| <b>TEST CONDITION</b>                                    |                          |                             |                               |
| Altitude (Meters ASL)                                    | 1000                     | Oil Specifications          | Ley Power 15 W 40 - Synthetic |
| Ambient Temp. (C)                                        | 38                       | Humidity (%)                | 38                            |
| Air Filter Inlet Temp (C)                                | 42                       | Coolant Mix                 | 50 : 50                       |
| <b>PRODUCT OPTIONS CHECKED</b>                           |                          |                             |                               |
| (*) Emergency Stop                                       | (o) Panel Heater         | (o) Low Coolant Warning     | (o) High Fuel S/Down          |
| (*) Over Load Protection                                 | (*) High Water Temp      | (*) LET Warning             | (o) High Fuel Warning         |
| (*) Over Speed Protection                                | (*) Low Lub Oil Pressure | (o) Low Fuel S/Down         | (o) Parallel Bus PT Module    |
| (*) Under Voltage Protection                             | (o) Low Coolant S/Down   | (o) Low Fuel Warning        | (o) Earth Fault S/Down        |
| <b>TECHNICAL DATA (Declared)</b>                         |                          |                             |                               |
| Service Rating                                           | 40 kVA                   | Power Factor                | 0.8                           |
| Power Output (kW)                                        | 32                       | Rated Output (kW)           | 32                            |
| Rated Voltage (V)                                        | 400                      | Rated Current (A)           | 45                            |
| Frequency (Hz)                                           | 60                       | Speed (RPM)                 | 1800                          |
| Number of Phases                                         | 3                        | Performance Class           | H                             |
| <b>TECHNICAL DATA (Measured)</b>                         |                          |                             |                               |
| Results (No Load)                                        |                          |                             |                               |
| Voltage                                                  | 1 - 2 : 401 Volts        | 2 - 3 : 400 Volts           | 1 - 3 : 400 Volts             |
| No Load Frequency                                        | 61.3                     | No Load Coolant Temp. (C)   | 75 deg Cen                    |
| No Load Lube Press                                       | 3.93 Bar                 |                             |                               |
| Result (Full Load)                                       |                          |                             |                               |
| Voltage                                                  | 1 - 2 : 400 Volts        | 2 - 3 : 401 Volts           | 1 - 3 : 400 Volts             |
| Current                                                  | 1 : 46 Amps              | 2 : 46 Amps                 | 3 : 46 Amps                   |
| Full Load Frequency                                      | 60.1 Hz.                 | Full Load Coolant Temp. (C) | 87                            |
| Full Load Lube Press                                     | 3.75 Bar                 | Power Factor                | 1.0                           |
| Prime set tested to 110% of Full Load (if required)      |                          | NA                          |                               |
| Tested By                                                |                          | Date                        | 16-Jan-22                     |
|                                                          |                          | RUN HOURS                   | 45 mins                       |



| VARADA ENERGIES PVT LTD. <b>PRODUCT TEST CERTIFICATE</b> |                          |                             |                            |
|----------------------------------------------------------|--------------------------|-----------------------------|----------------------------|
| <b>GENERAL INFORMATION</b>                               |                          |                             |                            |
| Customer Name                                            |                          | Customer Order No.          |                            |
|                                                          |                          | Test Cell No.               |                            |
| <b>PRODUCT INFORMATION</b>                               |                          |                             |                            |
| Model                                                    |                          | Genset Serial No.           |                            |
| Engine Serial No.                                        |                          | Alternator Serial No.       |                            |
| Brand Name                                               |                          | Alternator Make.            |                            |
| Fuel Type                                                |                          | Controller Type             |                            |
| Gowoner Type                                             |                          | Cooling System Type         |                            |
| <b>TEST CONDITION</b>                                    |                          |                             |                            |
| Altitude (Meters ASL)                                    |                          | Oil Specifications          |                            |
| Ambient Temp. (C)                                        |                          | Humidity (%)                |                            |
| Air Filter Inlet Temp (C)                                |                          | Coolant Mix                 |                            |
| <b>PRODUCT OPTIONS CHECKED</b>                           |                          |                             |                            |
| (*) Emergency Stop                                       | (o) Panel Heater         | (o) Low Coolant Warning     | (o) High Fuel S/Down       |
| (*) Over Load Protection                                 | (*) High Water Temp      | (*) LET Warning             | (o) High Fuel Warning      |
| (*) Over Speed Protection                                | (*) Low Lub Oil Pressure | (o) Low Fuel S/Down         | (o) Parallel Bus PT Module |
| (*) Under Voltage Protection                             | (o) Low Coolant S/Down   | (o) Low Fuel Warning        | (o) Earth Fault S/Down     |
| <b>TECHNICAL DATA (Declared)</b>                         |                          |                             |                            |
| Service Rating                                           |                          | Power Factor                |                            |
| Power Output (kW)                                        |                          | Rated Output (kW)           |                            |
| Rated Voltage (V)                                        |                          | Rated Current (A)           |                            |
| Frequency (Hz)                                           |                          | Speed (RPM)                 |                            |
| Number of Phases                                         |                          | Performance Class           |                            |
| <b>TECHNICAL DATA (Measured)</b>                         |                          |                             |                            |
| Results (No Load)                                        |                          |                             |                            |
| Voltage                                                  |                          |                             |                            |
| No Load Frequency                                        |                          | No Load Coolant Temp. (C)   |                            |
| No Load Lube Press                                       |                          |                             |                            |
| Result (Full Load)                                       |                          |                             |                            |
| Voltage                                                  |                          |                             |                            |
| Current                                                  |                          |                             |                            |
| Full Load Frequency                                      |                          | Full Load Coolant Temp. (C) |                            |
| Full Load Lube Press                                     |                          | Power Factor                |                            |
| Prime set tested to 110% of Full Load (if required)      |                          |                             |                            |
| Tested By                                                |                          | Date                        |                            |
|                                                          |                          | RUN HOURS                   |                            |