

56-568-40

VARADA ENERGIES PVT LTD. **PRODUCT TEST CERTIFICATE**

|                                                     |                          |                             |                               |
|-----------------------------------------------------|--------------------------|-----------------------------|-------------------------------|
| <b>GENERAL INFORMATION</b>                          |                          |                             |                               |
| Customer Name                                       |                          | Customer Order No.          |                               |
|                                                     |                          | Test Cell No.               | 3                             |
| <b>PRODUCT INFORMATION</b>                          |                          |                             |                               |
| Model                                               | VEPL-40-CDP              | Genset Serial No.           | VEPL/2021-22/0069             |
| Engine Serial No.                                   | MBHM 112660              | Alternator Serial No.       | G21K 467968                   |
| Brand Name                                          | Ashok Leyland            | Alternator Make.            | STAMFORD                      |
| Fuel Type                                           | HSD                      | Controller Type             | DEEP SEA                      |
| Governor Type                                       | MECHANICAL               | Cooling System Type         | WATER COOLED                  |
| <b>TEST CONDITION</b>                               |                          |                             |                               |
| Altitude (Meters ASL)                               | 1000                     | Oil Specifications          | Ley Power 15 W 40 - Synthetic |
| Ambient Temp. (C)                                   | 38                       | Humidity (%)                | 38                            |
| Air Filter Inlet Temp (C)                           | 42                       | Coolant Mix                 | 50 : 50                       |
| <b>PRODUCT OPTIONS CHECKED</b>                      |                          |                             |                               |
| (●) Emergency Stop                                  | (o) Panel Heater         | (o) Low Coolant Warning     | (o) High Fuel S/Down          |
| (●) Over Load Protection                            | (●) High Water Temp      | (●) LET Warning             | (o) High Fuel Warning         |
| (●) Over Speed Protection                           | (●) Low Lub Oil Pressure | (o) Low Fuel S/Down         | (o) Parallel Bus PT Module    |
| (●) Under Voltage Protection                        | (o) Low Coolant S/Down   | (o) Low Fuel Warning        | (o) Earth Fault S/Down        |
| <b>TECHNICAL DATA (Declared)</b>                    |                          |                             |                               |
| Service Rating                                      | 40 kVA                   | Power Factor                | 0.8                           |
| Power Output (kW)                                   | 32                       | Rated Output (kW)           | 32                            |
| Rated Voltage (V)                                   | 400                      | Rated Current (A)           | 45                            |
| Frequency (Hz)                                      | 60                       | Speed (RPM)                 | 1800                          |
| Number of Phases                                    | 3                        | Performance Class           | H                             |
| <b>TECHNICAL DATA (Measured)</b>                    |                          |                             |                               |
| <b>Results (No Load)</b>                            |                          |                             |                               |
| Voltage                                             | 1 - 2 : 400 Volts        | 2 - 3 : 401 Volts           | 1 - 3 : 403 Volts             |
| No Load Frequency                                   | 61.7                     | No Load Coolant Temp. (C)   | 78 deg Cen                    |
| No Load Lube Press                                  | 3.93 Bar                 |                             |                               |
| <b>Result (Full Load)</b>                           |                          |                             |                               |
| Voltage                                             | 1 - 2 : 403 Volts        | 2 - 3 : 401 Volts           | 1 - 3 : 401 Volts             |
| Current                                             | 1 : 46 Amps              | 2 : 46 Amps                 | 3 : 43 Amps                   |
| Full Load Frequency                                 | 60 Hz.                   | Full Load Coolant Temp. (C) | 89                            |
| Full Load Lube Press                                | 3.7 Bar                  | Power Factor                | 1.0                           |
| Prime set tested to 110% of Full Load (if required) |                          | NA                          |                               |
| Tested By                                           |                          | Date                        | 14-Jan-22                     |
|                                                     |                          | RUN HOURS                   | 45 Hrs                        |

