





LIFTING EQUIPMENT INSPECTION REPORT		RPO No. PO	Org. Code	CRM No.	Report No: TS-ABB-26-12017		
		Area :	Inspection Date:	Inspection Time:	Previous sticker	Issued by	
		Riyadh	12/May/2026	12:30 PM	TUV-SUD-10738	TUV SUD	
Department/Contractor	Equipment No	Equipment Location:	Equipment Result :	Inspection Result :	New sticker No.		
Sudhir Equipment Rental Company	S44AD-1898	ARAMCO RIYADH REFINERY	Pass	Pass	TUV-SUD-13865		
Manufacturer:	Model:	Capacity:	Type:	Equipment Serial No.	Sticker Expiration Date:		
DINGLI 2024	BA44RT	272 KGS	MEWP	BART024100188	11/Nov/2026		
Above equipment was inspected by TÜV sÜD for Safety Engineering accordance with applicable Saudi Aramco GI's, ASME and API standards. Deficiencies that require corrective action listed below. Specific repairs to correct each deficiency should be noted in the corrective action taken column.							
NO.	DEFICIENCIES			CORRECTIVE ACTION TAKEN			
1	Periodic visual inspection and functional test carried out as per GI7.030, ANSI A92.5						
2	Max working height:44m max wind speed 12.5m/s						
3	Verified all safety switches and found Satisfactory						
4	Anti-Entrapment device installed and tested found satisfactory.						
5	Found satisfactory at the time of inspection						
RECEIVER NAME	Naseem Kiyani			TECHNICAL REVIEWER NAME:	Mohamad Moaen Deeb	INSPECTOR NAME	Abdalla El said
BADGE No	-			Received Date:	12/05/2026	SAP NUMBER	80019108
TELEPHONE No	0570292956			Reviewed Date:	12/05/2026	SIGNATURE	
SIGNATURE				SIGNATURE			
When re-inspection is requested, a complete copy of this report should be ready reviewed by the inspector							

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORT ELEVATING WORK PLATFORM		SAIC-U-7002	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE ARAMCO RIYADH REFINERY		WBS/BI/JO NUMBER	INSPECTION COMPANY TÜV SÜD for Safety Engineering	

EQUIPMENT ID NUMBER S44AD-1898	EQUIPMENT DESCRIPTION/TYPE MEWP	SERIAL NO. BART024100188	REPORT No.: TS-ABB-26-12017
CAPACITY (SWL) 272 KGS	MANUFACTURER DINGLI 2024	FACILITY / LOCATION Riyadh. /ARAMCO RIYADH REFINERY	
REQUESTED INSPECTION DATE 07/May/2026	RFI No.	TASK COMPLETED DATE 12/May/2026	EQUIPMENT OWNER Sudhir Equipment Rental Company

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remarks
1	GENERAL REQUIREMENTS					
1.1	Equipment documentation is available	ANSI/SAIA A92.5, Sec: 4.16.1.1 G.I. 7.030	✓			
1.2	Previous inspection reports are checked	ANSI/SAIA A92.5, Sec: 5.11.1.3 G.I. 7.030	✓			
1.3	Daily pre-operational inspection checklists are checked (if applicable)	GI 7.030 Para: 5.1.2	✓			
1.4	Preventive Maintenance is established and updated records are maintained	ANSI/SAIA A92.5, Sec: 6.4.1	✓			
1.5	Equipment is operated by a qualified operator	ANSI/SAIA A92.5 Sec: 4.13.13	✓			
1.6	Warning notice, cautions or restrictions for safe operation and maintenance are clearly displayed and legible	ANSI/SAIA A92.5 Sec: 4.13.1	✓			
1.7	A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice	G.I. 7.030 Para: 5.6.2	✓			
1.8	Manufacturer name, address, serial number and model are clearly marked or tagged	ANSI/SAIA A92.5 Sec: 4.13.2	✓			
1.9	Safe working load and number of persons are clearly marked on the work platform	ANSI/SAIA A92.5, Sec: 4.13.3	✓			
1.10	Maximum platform height and reach are clearly marked	ANSI/SAIA A92.5 Sec: 4.13.4 & 5	✓			
1.11	Maximum travel height and travel directions are clearly marked	ANSI/SAIA A92.5 Sec: 4.13.9	✓			
1.12	Power rating are provided and marked (for AC and/or DC)	ANSI/SAIA A92.5 Sec: 4.13.6	✓			
1.13	Platform and guardrails electrical insulation data are provided	ANSI/SAIA A92.5 Sec: 4.13.10	✓			
2	INSPECTION POINTS					
2.1	Platform surfaces are at least 18" (width & length) and are slip-resistant	ANSI/SAIA A92.5 4.12.1	✓			
2.2	Platform guardrails are provided and secure	ANSI/SAIA A92.5 4.12.2	✓			
2.3	Platform guardrails are 42" height (+/- 3")	ANSI/SAIA A92.5 Sec: 4.12.2.1	✓			
2.4	Platform toeboard is fitted and at least 4" high	ANSI/SAIA A92.5 Sec: 4.12.3	✓			
2.5	Moving parts are guarded	ANSI/SAIA A92.5 Sec: 4.11	✓			
2.6	Personnel on the platform is protected against the hazards of moving parts of the aerial platforms.	ANSI/SAIA A92.5 Sec: 7.10	✓			
2.7	Access to the platform is provided	ANSI/SAIA A92.5 Sec: 4.12.4	✓			

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORT ELEVATING WORK PLATFORM		SAIC-U-7002	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE ARAMCO RIYADH REFINERY		WBS/BI/JO NUMBER	INSPECTION COMPANY TÜV SÜD for Safety Engineering	

EQUIPMENT ID NUMBER S44AD-1898	EQUIPMENT DESCRIPTION/TYPE MEWP		SERIAL NO. BART024100188	REPORT No.: TS-ABB-26-12017
CAPACITY (SWL) 272 KGS	MANUFACTURER DINGLI 2024		FACILITY / LOCATION Riyadh. /ARAMCO RIYADH REFINERY	
REQUESTED INSPECTION DATE 07/May/2026	RFI No.	TASK COMPLETED DATE 12/May/2026	EQUIPMENT OWNER Sudhir Equipment Rental Company	

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remarks
2.8	Access gates or openings shall be properly closed per the manufacturer's instructions	ANSI/SAIA A92.5 Sec: 4.12.4	✓			
2.9	Electrical cables, wiring and components are undamaged	ANSI/SAIA A92.5 Sec:8.3	✓			
2.10	Safety harness anchorage is fitted in the platform	ANSI/SAIA A92.5 Sec: 4.12.5.1	✓			
2.11	Battery is secure, guarded and ventilated	ANSI/SAIA A92.5 Sec: 4.15.2	✓			
2.12	Outrigger position microswitches and interlocks are fully functional at their control pane	ANSI/SAIA A92.5 Sec: 4.7			✓	
2.13	Air, Hydraulic and fuel systems are not leaking	ANSI/SAIA A92.5 Sec: 6.6.5	✓			
2.14	Emergency stop button is available at ground control station	ANSI/SAIA A92.5 Sec: 4.6.3	✓			
2.15	There are no loose nuts, bolts, missing, worn or damaged parts around the structure	ANSI/SAIA A92.5 Sec: 6.6.2	✓			
2.16	The equipment is free of defective and/or corroded members/joints	ANSI/SAIA A92.5 Sec:6.4.3	✓			
2.17	Working environment is hazard free and machine ca be safely operated	ANSI/SAIA A92.5 Sec:7.9	✓			
2.18	An hour meter is fitted	ANSI/SAIA A92.5 Sec:4.15.3	✓			
2.19	A fire extinguisher is fitted (type depends on operating location)	ANSI/SAIA A92.5 Genera	✓			
2.20	All moving parts are lubricated	ANSI/SAIA A92.5 Sec: 6.6.5	✓			
2.21	All fluid levels for oil, water and hydraulic are adequate	ANSI/SAIA A92.5 Sec: 6.6.5	✓			
2.22	Platform controls operate the machine correctly	ANSI/SAIA A92.5 Sec: 6.6.1	✓			
2.23	Platform controls are clearly marked with direction and mode of operation	ANSI/SAIA A92.5 Sec: 4.6.1.6	✓			
2.24	Platform controls accessable to the operator	ANSI/SAIA A92.5 Sec: 4.6.1.1	✓			
2.25	Platform controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5 Sec: 4.6.1.4	✓			
2.26	Platform controls are protected agains inadvertent operation	ANSI/SAIA A92.5 Sec: 1.3	✓			
2.27	Over-ride control for power functions is fitted at ground level control panel	ANSI/SAIA A92.5 Sec: 4.6.2.1	✓			
2.28	Lower controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5 Sec: 4.6.2.4	✓			
2.29	Lower controls are clearly marked for direction and mode of operation	ANSI/SAIA A92.5 Sec: 4.6.2.6	✓			
2.30	Lower controls do not include drive and steering functions	ANSI/SAIA A92.5 Sec: 4.6.2.2	✓			

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORT ELEVATING WORK PLATFORM		SAIC-U-7002	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE ARAMCO RIYADH REFINERY		WBS/BI/JO NUMBER	INSPECTION COMPANY TÜV SÜD for Safety Engineering	

EQUIPMENT ID NUMBER S44AD-1898	EQUIPMENT DESCRIPTION/TYPE MEWP		SERIAL NO. BART024100188	REPORT No.: TS-ABB-26-12017
CAPACITY (SWL) 272 KGS	MANUFACTURER DINGLI 2024		FACILITY / LOCATION Riyadh. /ARAMCO RIYADH REFINERY	
REQUESTED INSPECTION DATE 07/May/2026	RFI No.	TASK COMPLETED DATE 12/May/2026	EQUIPMENT OWNER Sudhir Equipment Rental Company	

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remarks
2.31	Lower controls are protected against inadvertent operation	ANSI/SAIA A92.5 Sec: 4.6.2.5	✓			
2.32	Boom raise/extend is operable from platform and ground control	ANSI/SAIA A92.5 Sec: 4.6.2.2	✓			
2.33	Boom lower/retract is operable from platform and ground control	ANSI/SAIA A92.5 Sec: 4.6.2.2	✓			
2.34	Platform rotation is operable from both platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.2.2	✓			
2.35	Emergency stop button is operable from both platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.3	✓			
2.36	Auxiliary/emergency lowering is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	✓			
2.37	Auxiliary/emergency retracting is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	✓			
2.38	Auxiliary/emergency rotating is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	✓			
2.39	Hydraulic/Pneumatic systems are leak-free with platform raised	ANSI/SAIA A92.5 Sec: 4.10.2	✓			
2.40	Tilt alarm is operable (5 degrees out of level) (manually depress the edge of the tilt switch to cause alarm condition)	ANSI/SAIA A92.5 Sec: 4.7.3	✓			
2.41	Aerial platforms is fitted with a warning device at the platform which activates automatically when the aerial platform is at and beyond the slope	ANSI/SAIA A92.5 Sec: 4.6.6	✓			
2.42	Tilt alarm is not combined with boom raise cut-out (dependent on machine manufacturer)	ANSI/SAIA A92.5 Sec: 4.6.6	✓			
2.43	Steering is properly working when moving forward and in reverse directions	ANSI/SAIA A92.5 Sec: 6.6.3.1	✓			
2.44	Brakes are in good working condition and can hold the machine on any slope (parking and moving)	ANSI/SAIA A92.5 Sec: 4.14.1	✓			
2.45	Extendable axles function is satisfactory (where fitted)	ANSI/SAIA A92.5 Sec: 7.3.3.8	✓			
2.46	Outriggers (stabilizers) extension-retraction operation is satisfactory	ANSI/SAIA A92.5 Sec: 7.10.3			✓	
2.47	Extendable elevating assembly operation is satisfactory (retracted vs. extended)	ANSI/SAIA A92.5 Sec: 4.2.1	✓			
2.48	8 Elevating assembly operation is satisfactory (elevated vs. lowered)	ANSI/SAIA A92.5 sec: 4.2.1(c)	✓			
2.49	Wheels and tires are serviceable and undamaged	ANSI/SAIA A92.5 Sec: 7.3.3 (6)	✓			
2.50	Travel alarm is operable	ANSI/SAIA A92.5 Sec: 6.6 (4)	✓			
2.51	Platform lowering alarm is operable	ANSI/SAIA A92.5 Sec: 6.6 (4)	✓			



SATISFACTION SURVEY

Thank you for your feedback

#	Question	Answer
1	Did the Service provider Co. provide the right inspector with a valid qualification card?	Yes
2	Did the service provider Co. respond for inspection within the expected time frame?	Yes
3	Was the inspector wearing the required personal protective (Yes/No) equipment (PPE) during the inspection?	Yes
4	Did the inspection conducted safely and in accordance with Aramco standard?	Yes



TÜV SÜD for Safety Engineering
شركة توف سود لهندسة السلامة
Al Jubail – 31951, Kingdom of Saudi Arabia
Tel +966 13 3612121, Fax No:+966 13 3632555



NO. : TUV-SUD-13865

Equipment No.: S44AD-1898

Equipment S.N: BART024100188

Equipment SWL:272 KGS

Date Inspected: 12/May/2026

Next Inspection Date: 11/Nov/2026

Inspected by:Abdalla El said

Inspector / SAP NO. 80019108

S.A. INSPECTION DEPARTMENT APPROVED CONTRACTOR AGENCY

NOTE: THIS STICKER IS INTENDED AND VALID FOR ARAMCO PREMISES AND PROJECTS ONLY