



Bureau Veritas, Saudi Arabia

8th Floor, Danah Business Tower, Olaya District, Al Khobar, Kingdom of Saudi Arabia

Tel No : +966 13 882 1071

Web : <https://middle-east.bureauveritas.com>



Report No.: 247683

LIFTING EQUIPMENT INSPECTION REPORT	Area DAMMAM	Inspection Date 28/10/2025		Inspection Time 13:00	Previous Sticker	
					No.24-7359	Issue By BV
Department / Contractor SUDHIR EQUIPMENT RENTAL CO.	Equipment Number SRC-STC-080-018	Equipment Location DMM YARD		Inspection Result Pass	New Sticker No. BV-2440	
Manufacturer SANY	Model STC800T5	Capacity 80 TON	Type Mobile Crane	Equipment Serial Number TC2080CD0578	Sticker Expiration Date 27/01/2026	

Above Equipment was inspected by **Bureau Veritas** in accordance with applicable Saudi Aramco GI's, ASME and API Standards. Deficiencies that require corrective action are listed below. Specific repairs to correct each deficiency should be noted in the corrective action taken column.

No.	DEFICIENCIES / NOTES	Corrective Action Taken
1	PERIODIC INSPECTION AND FUNCTION TEST FOR MOBILE CRANE AS PER AS S.ARAMCO GI 7.030 AND ASME B30.5 -MAIN HOOK BLOCK S/N:TQ22118005019 , SWL: 80 TON @ 6 FALLS - AUX HOOK S/N:YM2022113005 , SWL: 6.5TON @ 1FALL - FLY JIB WAS STOWED -PLATE# 3775 AAA -EQUIPMENT WAS FOUND SATISFACTORY AT THE TIME OF INSPECTION -FOLLOW PROPER PM REGULARLY	
Receiver Name : ARIF		Inspector Name : MOHAMED OMARA
Badge No.: -	Telephone No.: -	Telephone : 055 078 7628

When re-inspection is requested, a complete copy of this report should be ready review by the inspector.

SAUDI ARAMCO INSPECTION CHECKLIST			SAIC NUMBER SAIC-U-7007		ISSUE DATE 12-Jan-23		DISCIPLINE ELEVATING/LIFTING EQUIPMENT	
MOBILE / CRAWLER CRANES								
PROJECT TITLE			WBS/BI/JO NUMBER		INSPECTION COMPANY Bureau Veritas, Saudi Arabia			
EQUIPMENT ID NUMBER : SRC-STC-080-018		EQUIPMENT DESCRIPTION/TYPE : Mobile Crane			SERIAL NO. : TC2080CD0578		REPORT No.: 247683	
CAPACITY (SWL) : 80 TON		MANUFACTURER : SANY			FACILITY / LOCATION : DMM YARD			
REQUESTED INSPECTION DATE :		RFI No.		TASK COMPLETED DATE : 28/10/2025		EQUIPMENT OWNER : SUDHIR EQUIPMENT RENTAL CO.		

ACCEPTANCE CRITERIA

1.0 GENERAL REQUIREMENTS

		REFERENCE	PASS	FAIL	NA	REMARKS
1.1	Equipment documentation is available	ASME B30.5	✓			
1.2	Preventive Maintenance is established and updated records are maintained	ASME B30.5 Sec:5-2.3.1	✓			
1.3	Daily pre-operational inspection checklists are checked	GI 7.030 Para: 5.1.2	✓			
1.4	Vehicle government registration card (ISTIMARA) and Government periodic inspection are maintained and valid at all times for equipment that has a vehicle plate.	GI 7.030 Para: 7.1.2 Note:5	✓			
1.5	Durable load chart is provided in an accessible location	ASME B30.5	✓			
1.6	Work areas chart is available	ASME B30.5	✓			
1.7	Operator is certified (for the inspected crane type/model) and licensed	G.I. 7.025	✓			
1.8	A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice	G.I. 7.030	✓			
1.9	Crane is painted safety yellow	SAES-B067			✓	
1.10	Crane is painted safety yellow-and-black stripes on offshore facilities	SAES-B067			✓	

		REFERENCE	PASS	FAIL	NA	REMARKS
1.11	Rated capacity of crane is marked (Arabic & English)	SAES-B067	✓			
1.12	Fire extinguisher is in place with minimum rating 10 BC	ASME B30.5	✓			
1.13	Markings and direction of all control levers are clearly displayed	ASME B30.5	✓			
1.14	Crane backward stability is in accordance with manufacturers standard (minimum radius and no load condition)	ASME B30.5	✓			

2.0 INSPECTION POINTS (MOBILE & CRAWLER CRANES)

		REFERENCE	PASS	FAIL	NA	REMARKS
2.1	Load- holding check valve for boom is operational	ASME B30.5	✓			
2.2	Two (2) full wraps of rope remain on the drum when hook is in the extreme low position	ASME B30.5	✓			
2.3	Swing control is smoothly operating on acceleration and deceleration	ASME B30.5	✓			
2.4	Swing braking operates, as well as positive locking devices (manual and auto)	ASME B30.5	✓			
2.5	Travel controls are properly operating/functioning	ASME B30.5	✓			
2.6	Auxiliary travel controls function correctly for multiple control- station cranes	ASME B30.5	✓			
2.7	Travel brakes and locks for crawler cranes are correctly operating	ASME B30.5			✓	
2.8	Travel brakes and locks for wheel-mounted cranes are correctly operating	ASME B30.5	✓			
2.9	Power plant controls of superstructure -mounted power plant working properly	ASME B30.5	✓			
2.10	Rotation-resistant and fiber-core ropes are not used for boom hoist reeving	ASME B30.5			✓	

		REFERENCE	PASS	FAIL	NA	REMARKS
2.11	Sheave grooves have surface smoothness without any defects	ASME B30.5	✓			
2.12	Sheave guards are in place on the lower block	ASME B30.5	✓			
2.13	All sheaves can be lubricated (except permanently lubricated types)	ASME B30.5	✓			
2.14	All cab glazing's are safety glazing material	ASME B30.5	✓			
2.15	Verify cab doors functionality and condition	ASME B30.5	✓			
2.16	Seat belt is fitted and in good condition	ASME B30.5	✓			
2.17	Walking platforms and areas of structure are skid-resistance	ASME B30.5	✓			
2.18	Guard rails are fitted for crawler cranes	ASME B30.5			✓	
2.19	Fixed or telescoping bumper for boom stop is functional (if fitted)	ASME B30.5			✓	
2.20	Shock absorbing bumper for boom stop is functional (if fitted)	ASME B30.5			✓	
2.21	Hydraulic boom elevating cylinder, used as boom stop, is functional (if fitted)	ASME B30.5	✓			
2.22	Boom angle indicator is fitted, operable, and can be read from the operator station	ASME B30.5	✓			
2.23	Boom shut-off or hydraulic relief is provided for high angle boom condition	ASME B30.5	✓			
2.24	Boom length indicator is fitted for telescoping booms and is working	ASME B30.5	✓			
2.25	Anti-two-blocking devices are fitted and working (main and auxiliary)	ASME B30.5	✓			
2.26	Operation and accuracy of the fitted LMI (compare with load chart over a range of angles and radii)	ASME B30.5	✓			

		REFERENCE	PASS	FAIL	NA	REMARKS
2.27	LMI is fitted, operational and accurate for bool length, rated load, angle, radius, etc. (for 3 ton cranes or more)	ASME B30.5 Sec: 5-1.9.10.2	✓			
2.28	Outriggers and jacks are not leaking oil	ASME B30.5	✓			
2.29	Jack is in good operating condition at each outrigger	ASME B30.5	✓			
2.30	Each outrigger jack locking device is functional (if fitted)	ASME B30.5	✓			
2.31	No leakage from each jack seal when the crane is jacked up	ASME B30.5	✓			
2.32	Outrigger jack bolts are fully secure	ASME B30.5	✓			
2.33	All road wheel nuts are fully secure	ASME B30.5	✓			
2.34	All tyres are serviceable and without damage or excess wear	ASME B30.5	✓			
2.35	Fuel tank supports and straps are secure	ASME B30.5	✓			
2.36	Hydraulic oil tank supports and straps are secure	ASME B30.5	✓			
2.37	Underside of chassis shows no obvious faults	ASME B30.5	✓			
2.38	Outrigger boxes are not cracked	ASME B30.5	✓			
2.39	Front and rear steering cylinder anchor points and pins are secure	ASME B30.5	✓			
2.40	Track rod end joints are not worn and are secure	ASME B30.5	✓			
2.41	Axle bolts and nuts are fully secure	ASME B30.5	✓			
2.42	Wheel hub oil seals are not leaking	ASME B30.5	✓			
2.43	Brake linings are not oil contaminated	ASME B30.5	✓			
2.44	Brake hoses have not deteriorated, e.g. cracks, splits, leaks, etc.	ASME B30.5	✓			

		REFERENCE	PASS	FAIL	NA	REMARKS
2.45	All chassis cross members are not cracked or corroded	ASME B30.5	✓			
2.46	Transmission mounting bolts and bushings are secure	ASME B30.5	✓			
2.47	All drive shaft bolts and universal joints are not worn	ASME B30.5	✓			
2.48	Ring gear bolts are fully secure	ASME B30.5	✓			
2.49	All hydraulic hoses under chassis have not deteriorated (cracks , splits , leaks)	ASME B30.5	✓			
2.50	Engine shows no major oil leakage	ASME B30.5	✓			
2.51	Radiator does not leak water	ASME B30.5	✓			
2.52 (a)	Rope is free of damages: 1 broken wire protruding from the core Wear of 1/3 of the original diameter of outside individual wires Kinking, crushing, birdcaging or other distortion	ASME B30.5	✓			
2.52 (b)	For running ropes: Max of 6 randomly broken wires in 1 lay or 3 broken wires in 1 strand of 1 lay, For rotation resistance ropes: 2 randomly distributed broken wires in six rope diameters or 4 randomly distributed broken wires in 30 rope diameters	ASME B30.5	✓			
2.52(c)	Evidence of any heat damage from any cause Reduction below nominal diameter	ASME B30.5	✓			
2.53	Main hoist drum mounting bolts are secure	ASME B30.5	✓			
2.54	Rear telescope side and top wear pads are serviceable	ASME B30.5	✓			
2.55	Bottom and side wear pads of telescope sections are serviceable	ASME B30.5	✓			
2.56	Center swivel coupling pipes and hoses do not leak	ASME B30.5	✓			
2.57	Center swivel coupling bolts are all secure	ASME B30.5	✓			
2.58	Boom lift cylinder anchor bolts and bushings are secure	ASME B30.5	✓			

		REFERENCE	PASS	FAIL	NA	REMARKS
2.59	Swing gearbox mounting bolts are secure	ASME B30.5	✓			
2.60	Swing gearbox bottom oil seal and drive gear are in a serviceable condition (Should be well lubricated)	ASME B30.5	✓			
2.61	Wire rope clips shall be drop-forged steel of the single saddle U bolt or doubled saddle type clip for end termination.	ASME B30.5	✓			
2.62	Emergency switch / Power take off switch need to be verified	ASME B30.5	✓			

3.0 CRANE CAB

		REFERENCE	PASS	FAIL	NA	REMARKS
3.1	Horn and wind speed anemometer are working	ASME B30.5	✓			
3.2	Crane level indicator is fitted and working	ASME B30.5	✓			
3.3	Engine gauges and associated indicators are working	ASME B30.5	✓			
3.4	The warning sign stating power line required clearances is visible to the operator	ASME B30.5	✓			
3.5	Load block sheaves turn freely and are undamaged	ASME B30.5	✓			
3.7	Hook assemblies are equipped with safety latches	ASME B30.5	✓			
3.8	Hook assembly labeling and manufacturer data is clearly marked	ASME B30.10	✓			
3.9	Hook's weight is clearly marked/printed on the hook	ASME B30.10	✓			
3.10	Safe working load of hook is clearly marked on the item	ASME B30.10	✓			
3.11	Hook does not show defects such as nicks, cracks and gouges	ASME B30.10	✓			
3.12	Hook is not bent or twisted	ASME B30.10	✓			

		REFERENCE	PASS	FAIL	NA	REMARKS
3.13	Hook is not distorted in the throat opening - Max. allowable throat opening is 15% compared to new hook, or as per manufacturer recommendations	ASME B30.10	✓			
3.14	Maximum wear in the hook bowl is not exceeding 10% (compared to new hook) or as per manufacturer recommendations	ASME B30.10	✓			
3.15	Hook is not cracked, gouged or shows nicks	ASME B30.10	✓			
3.16	Hook can lock (if it is a self-locking hook)	ASME B30.10			✓	
3.17	Inoperative latch (if provided) — any damaged latch or malfunctioning latch that does not close the hook's throat	ASME B30.10 Sec : 10-1.10.5 (i)	✓			
3.18	Rope guards and locked in position with pins (hook block)	ASME B30.5	✓			
3.19	Dead end rope anchor is fitted with a lock pin (hook block)	ASME B30.5	✓			
3.20	Dead end rope anchor is correctly made with a suitable wedge socket and loop- back termination	ASME B30.5	✓			
3.21	Reverse travel alarm is operational	ASME B30.5	✓			
3.22	Turning signals and indicators are working correctly	ASME B30.5	✓			
3.23	Road lighting, including spotlights, are in good condition and operable	ASME B30.5	✓			
3.24	Dry friction brakes and clutches shall be protected against rain and other liquids such as oil and lubricants	ASME B30.5 Sec 5-1.9.8	✓			

4.0 CRAWLER CRANE

		REFERENCE	PASS	FAIL	NA	REMARKS
4.1	Track pads are undamaged	ASME B30.5			✓	
4.2	Drive sockets and tumblers are serviceable	ASME B30.5			✓	
4.3	Top and bottom swing rollers and tracks are in good overall condition (Should be well lubricated)	ASME B30.5			✓	
4.4	Track idlers are serviceable	ASME B30.5			✓	
4.5	Back boom stops are functioning	ASME B30.5			✓	
4.6	Back A-Frame is in good condition	ASME B30.5			✓	
4.7	Boom cut-out (at maximum angle) is operable	ASME B30.5			✓	
4.8	Power low lowering is operational	ASME B30.5			✓	
4.9	Boom hoist safety auxiliary ratchet / pawl lock is engaging	ASME B30.5 Sec: 5-1.3.1(c)			✓	
4.10	Boom chords and lacings are undamaged (bent)	ASME B30.5			✓	
4.11	Sheave grooves are free from surface defects that could cause rope damage.	ASME B30.5 Sec: 5-1.7.4 (a)			✓	
4.12	Pendant ropes are showing no broken wires (see 2.0.55)	ASME B30.5			✓	
4.13	Operation of steering brakes is satisfactory	ASME B30.5			✓	
4.14	Main machinery guarding is in place	ASME B30.5			✓	
4.15	Main clutch is fully operational	ASME B30.5			✓	
4.16	Main boom and hoist drum brakes are fully functional	ASME B30.5			✓	

REMARKS

--

REFERENCE DOCUMENTS:

- 1- ASME B30.5 - 2021 Issue: Mobile & Locomotive Cranes
- 2- ASME B30.10 - 2019 Issue: Hooks
- 3- SAES-B067 - 2020 Issue: Safety Identification and Safety Colors
- 4- SA GI 7.025-2018 Issue: Heavy Equipment Operator and Rigger Testing and Certification
- 5- SA GI 7.030 - 2023 Issue: Inspection and Testing Requirements for Elevating/Lifting Equipment

Signature

Inspected / Witnessed by 3rd Party Certified Inspector

Name MOHAMED OMARA

Signature



Certificate No. 80019106

Company Bureau Veritas

User Representative

Name ARIF

Signature



Date 28/10/2025



Sticker No:
BV-2440

Bureau Veritas

Tel.: + 966 013 822
1071
Fax: + 966 013 822
1072
Al Khobar, Saudi
Arabia



EQUIP .S.N: TC2080CD0578

EQUIP .NO : SRC-STC-080-018

EQUIP.SWL : 80 TON

INSPECTION DATE : 28/10/2025

NEXT INSPECTION DATE :27/01/2026

INSPECTOR NAME: MOHAMED OMARA

SAP # 80019106

SA INSPECTION DEPARTMENT APPROVED CONTRACTOR AGENCY