



NATIONAL INSPECTION AND TESTING COMPANY (FAHSS), P.O. Box 3998, DAMMAM 32252, Kingdom of Saudi Arabia

Contacts: +966 (13) 340 7607 / +966 (12) 610 9014 / +966 (14) 325 1475 / +966 538400764

Report No - LIC-2026-5153

Email: info@fahss.com

LIFTING EQUIPMENT INSPECTION REPORT		Area:		Inspection Date:		Inspection Time:		Previous Sticker:		Issued by:	
		W.R		07-Feb-2026		8:30		24-3538		BV	
Department/Contractor:		Equipment No.:		Equipment Location:		RPO NO.		Inspection Result:		New Sticker No.:	
SUDHIR COMPANY FOR EQUIPMENTS RENTAL		S28SJ-1721		USFAN - SUDHIR YARD / SUDHIR YARD		FAHSS-26-1655		pass		FAHSS-A-000427	
Manufacturer:		Model:		Capacity:		Type:		Equipment Serial No.:		Sticker Exp Date:	
JLG		860 SJ		500 LBS		MANLIFT		B300027795		06-Aug-2026	
Above equipment was inspected by FAHSS in accordance with applicable Saudi Aramco GI's, ASME and API standards. Deficiencies that require corrective action are listed below. Specific repairs to correct each deficiency should be noted in the 'Corrective Action Taken' column.											
No	DEFICIENCIES								CORRECTIVE ACTION TAKEN		
*	PERIODIC INSPECTION								NONE		
*	A COMPREHENSIVE VISUAL INSPECTION AND FUNCTIONAL TEST WERE CONDUCTED AND FOUND TO BE SATISFACTORY AT TIME OF INSPECTION IN ACCORDANCE WITH ANSI/SAIA A92.5 AND SA. GI.7.030										
*	ANTI-ENTRAPMENT DEVICE ((PRESSURE SENSING CABLE)) WAS WORKING SATISFACTORY										
RECIEVER			TECHNICAL REVIEWER			INSPECTOR					
RECIEVER NAME	BADGE NO	MOBILE No	NAME	RECEIVED DATE	REVIEWED DATE	NAME	CERTIFICATE NO	MOBILE No			
SHMIR		0533326321	Aqeel Aldarwish	07-02-2026	07-02-2026	Yahya Khalid Yaseen Al-Khayri	80024627	966592028020			
											
RECEIVER SIGNATURE			TECHNICAL REVIEWER SIGNATURE			INSPECTOR SIGNATURE					

When re-inspection is requested, a complete copy of this report should be ready to be reviewed by the inspector.

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE USFAN - SUDHIR YARD		WBS/BI/JO NUMBER FAHSS-26-1655	INSPECTION COMPANY NATIONAL INSPECTION AND TESTING COMPANY (FAHSS)	

EQUIPMENT ID NUMBER	EQUIPMENT DESCRIPTION/TYPE MANLIFT	SERIAL NO. B300027795	REPORT No.: LIC-2026-5153
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG	FACILITY / LOCATION Onshore / SUDHIR YARD	
REQUESTED INSPECTION DATE	RFI No.	TASK COMPLETED DATE 07-Feb-2026	EQUIPMENT OWNER SUDHIR COMPANY FOR EQUIPMENTS RENTAL

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remarks
1	GENERAL REQUIREMENTS - BOOM SUPPORTED					
1.1	Equipment documentation is available	ANSI/SAIA A92.5, Sec: 4.16.1.1 G.I. 7.030	☒	☐	☐	
1.2	Previous inspection reports are checked	ANSI/SAIA A92.5, Sec: 5.11.1.3 G.I. 7.030	☒	☐	☐	
1.3	Daily pre-operational inspection checklists are checked (if applicable)	GI 7.030 Para: 5.1.2	☒	☐	☐	
1.4	Preventive Maintenance is established and updated records are maintained	ANSI/SAIA A92.5, Sec: 6.4.1	☒	☐	☐	
1.5	Equipment is operated by a qualified operator	ANSI/SAIA A92.5 Sec: 4.13.13	☒	☐	☐	
1.6	Warning notice, cautions or restrictions for safe operation and maintenance are clearly displayed and legible	ANSI/SAIA A92.5 Sec: 4.13.1	☒	☐	☐	
1.7	A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice	G.I. 7.030 Para: 5.6.2	☒	☐	☐	
1.8	Manufacturer name, address, serial number and model are clearly marked or tagged	ANSI/SAIA A92.5 Sec: 4.13.2	☒	☐	☐	
1.9	Safe working load and number of persons are clearly marked on the work platform	ANSI/SAIA A92.5, Sec: 4.13.3	☒	☐	☐	
1.10	Maximum platform height and reach are clearly marked	ANSI/SAIA A92.5 Sec: 4.13.4 & 5	☒	☐	☐	
1.11	Maximum travel height and travel directions are clearly marked	ANSI/SAIA A92.5 Sec: 4.13.9	☒	☐	☐	
1.12	Power rating are provided and marked (for AC and/or DC)	ANSI/SAIA A92.5 Sec: 4.13.6	☐	☐	☒	
1.13	Platform and guardrails electrical insulation data are provided	ANSI/SAIA A92.5 Sec: 4.13.10	☐	☐	☒	
2	INSPECTION POINTS - BOOM SUPPORTED					
2.1	Platform surfaces are at least 18" (width & length) and are slip-resestant	ANSI/SAIA A92.5 4.12.1	☒	☐	☐	
2.2	Platform guardrails are provided and secure	ANSI/SAIA A92.5 4.12.2	☒	☐	☐	
2.3	Platform guardrails are 42" height (+/- 3")	ANSI/SAIA A92.5 Sec: 4.12.2.1	☒	☐	☐	
2.4	Platform toeboard is fitted and at least 4" high	ANSI/SAIA A92.5 Sec: 4.12.3	☒	☐	☐	
2.5	Moving parts are guarded	ANSI/SAIA A92.5 Sec: 4.11	☒	☐	☐	

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE USFAN - SUDHIR YARD		WBS/BI/JO NUMBER FAHSS-26-1655	INSPECTION COMPANY NATIONAL INSPECTION AND TESTING COMPANY (FAHSS)	

EQUIPMENT ID NUMBER	EQUIPMENT DESCRIPTION/TYPE MANLIFT	SERIAL NO. B300027795	REPORT No.: LIC-2026-5153
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG	FACILITY / LOCATION Onshore / SUDHIR YARD	
REQUESTED INSPECTION DATE	RFI No.	TASK COMPLETED DATE 07-Feb-2026	EQUIPMENT OWNER SUDHIR COMPANY FOR EQUIPMENTS RENTAL

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remarks
2.6	Personnel on the platform is protected against the hazards of moving parts of the aerial platforms.	ANSI/SAIA A92.5 Sec: 7.10	☒	☐	☐	
2.7	Access to the platform is provided	ANSI/SAIA A92.5 Sec: 4.12.4	☒	☐	☐	
2.8	Access gates or openings shall be properly closed per the manufacturer's instructions	ANSI/SAIA A92.5 Sec: 4.12.4	☒	☐	☐	
2.9	Electrical cables, wiring and components are undamaged	ANSI/SAIA A92.5 Sec:8.3	☒	☐	☐	
2.10	Safety harness anchorage is fitted in the platform	ANSI/SAIA A92.5 Sec: 4.12.5.1	☒	☐	☐	
2.11	Battery is secure, guarded and ventilated	ANSI/SAIA A92.5 Sec: 4.15.2	☒	☐	☐	
2.12	Outrigger position microswitches and interlocks are fully functional at their control pane	ANSI/SAIA A92.5 Sec: 4.7	☐	☐	☒	
2.13	Air, Hydraulic and fuel systems are not leaking	ANSI/SAIA A92.5 Sec: 6.6.5	☒	☐	☐	
2.14	Emergency stop button is available at ground control station	ANSI/SAIA A92.5 Sec: 4.6.3	☒	☐	☐	
2.15	There are no loose nuts, bolts, missing, worn or damaged parts around the structure	ANSI/SAIA A92.5 Sec: 6.6.2	☒	☐	☐	
2.16	The equipment is free of defective and/or corroded members/joints	ANSI/SAIA A92.5 Sec:6.4.3	☒	☐	☐	
2.17	Working environment is hazard free and machine can be safely operated	ANSI/SAIA A92.5 Sec:7.9	☒	☐	☐	
2.18	An hour meter is fitted	ANSI/SAIA A92.5 Sec:4.15.3	☒	☐	☐	
2.19	A fire extinguisher is fitted (type depends on operating location)	ANSI/SAIA A92.5 General	☒	☐	☐	
2.20	All moving parts are lubricated	ANSI/SAIA A92.5 Sec: 6.6.5	☒	☐	☐	
2.21	All fluid levels for oil, water and hydraulic are adequate	ANSI/SAIA A92.5 Sec: 6.6.5	☒	☐	☐	
2.22	Platform controls operate the machine correctly	ANSI/SAIA A92.5 Sec: 6.6.1	☒	☐	☐	
2.23	Platform controls are clearly marked with direction and mode of operation	ANSI/SAIA A92.5 Sec: 4.6.1.6	☒	☐	☐	
2.24	Platform controls accessible to the operator	ANSI/SAIA A92.5 Sec: 4.6.1.1	☒	☐	☐	
2.25	Platform controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5 Sec: 4.6.1.4	☒	☐	☐	

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE USFAN - SUDHIR YARD		WBS/BI/JO NUMBER FAHSS-26-1655	INSPECTION COMPANY NATIONAL INSPECTION AND TESTING COMPANY (FAHSS)	

EQUIPMENT ID NUMBER	EQUIPMENT DESCRIPTION/TYPE		SERIAL NO.	REPORT No.: LIC-2026-5153
	MANLIFT		B300027795	
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG		FACILITY / LOCATION Onshore / SUDHIR YARD	
REQUESTED INSPECTION DATE	RFI No.	TASK COMPLETED DATE 07-Feb-2026	EQUIPMENT OWNER SUDHIR COMPANY FOR EQUIPMENTS RENTAL	

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remarks
2.26	Platform controls are protected against inadvertent operation	ANSI/SAIA A92.5 Sec: 1.3	☒	☐	☐	
2.27	Over-ride control for power functions is fitted at ground level control panel	ANSI/SAIA A92.5 Sec: 4.6.2.1	☒	☐	☐	
2.28	Lower controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5 Sec: 4.6.2.4	☒	☐	☐	
2.29	Lower controls are clearly marked for direction and mode of operation	ANSI/SAIA A92.5 Sec: 4.6.2.6	☒	☐	☐	
2.30	Lower controls do not include drive and steering functions	ANSI/SAIA A92.5 Sec: 4.6.2.2	☒	☐	☐	
2.31	Lower controls are protected against inadvertent operation	ANSI/SAIA A92.5 Sec: 4.6.2.5	☒	☐	☐	
2.32	Boom raise/extend is operable from platform and ground control	ANSI/SAIA A92.5 Sec: 4.6.2.2	☒	☐	☐	
2.33	Boom lower/retract is operable from platform and ground control	ANSI/SAIA A92.5 Sec: 4.6.2.2	☒	☐	☐	
2.34	Platform rotation is operable from both platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.2.2	☒	☐	☐	
2.35	Emergency stop button is operable from both platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.3	☒	☐	☐	
2.36	Auxiliary/emergency lowering is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	☒	☐	☐	
2.37	Auxiliary/emergency retracting is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	☒	☐	☐	
2.38	Auxiliary/emergency rotating is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	☒	☐	☐	
2.39	Hydraulic/Pneumatic systems are leak-free with platform raised	ANSI/SAIA A92.5 Sec: 4.10.2	☒	☐	☐	
2.40	Tilt alarm is operable (5 degrees out of level) (manually depress the edge of the tilt switch to cause alarm condition)	ANSI/SAIA A92.5 Sec: 4.7.3	☒	☐	☐	
2.41	Aerial platforms is fitted with a warning device at the platform which activates automatically when the aerial platform is at and beyond the slope	ANSI/SAIA A92.5 Sec: 4.6.6	☒	☐	☐	
2.42	Tilt alarm is not combined with boom raise cut-out (dependent on machine manufacturer)	ANSI/SAIA A92.5 Sec: 4.6.6	☒	☐	☐	
2.43	Steering is properly working when moving forward and in reverse directions	ANSI/SAIA A92.5 Sec: 6.6.3.1	☒	☐	☐	
2.44	Brakes are in good working condition and can hold the machine on any slope (parking and moving)	ANSI/SAIA A92.5 Sec: 4.14.1	☒	☐	☐	
2.45	Extendable axles function is satisfactory (where fitted)	ANSI/SAIA A92.5 Sec: 7.3.3.8	☐	☐	☒	

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE USFAN - SUDHIR YARD		WBS/BI/JO NUMBER FAHSS-26-1655	INSPECTION COMPANY NATIONAL INSPECTION AND TESTING COMPANY (FAHSS)	

EQUIPMENT ID NUMBER	EQUIPMENT DESCRIPTION/TYPE MANLIFT	SERIAL NO. B300027795	REPORT No.: LIC-2026-5153
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG	FACILITY / LOCATION Onshore / SUDHIR YARD	
REQUESTED INSPECTION DATE	RFI No.	TASK COMPLETED DATE 07-Feb-2026	EQUIPMENT OWNER SUDHIR COMPANY FOR EQUIPMENTS RENTAL


ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remarks
2.46	Outriggers (stabilizers) extension-retraction operation is satisfactory	ANSI/SAIA A92.5 Sec: 7.10.3	☐	☐	☒	
2.47	Extendable elevating assembly operation is satisfactory (retracted vs. extended)	ANSI/SAIA A92.5 Sec: 4.2.1	☒	☐	☐	
2.48	Elevating assembly operation is satisfactory (elevated vs. lowered)	ANSI/SAIA A92.5 sec: 4.2.1(c)	☒	☐	☐	
2.49	Wheels and tires are serviceable and undamaged	ANSI/SAIA A92.5 Sec: 7.3.3 (6)	☒	☐	☐	
2.50	Travel alarm is operable	ANSI/SAIA A92.5 Sec: 6.6 (4)	☒	☐	☐	
2.51	Platform lowering alarm is operable	ANSI/SAIA A92.5 Sec: 6.6 (4)	☒	☐	☐	
2.52	Auxiliary power source available (to use in event of primary power loss)	ANSI/SAIA A92.5 Sec; 4.15.2	☒	☐	☐	
2.53	Platform does not descend when in raised position and the power is off	ANSI/SAIA A92.5 Sec: 4.6.3	☒	☐	☐	
2.54	Machine is safely drivable from the platform when raised (fast, slow, forward and reverse modes)	ANSI/SAIA A92.5 Sec: 6.6.3.1	☒	☐	☐	
2.55	The platform does not descend when in raised position and the power is off	off ANSI/SAIA A92.5 Sec: 4.6.3	☒	☐	☐	
2.56	Engine powered machines fuel lines are supported to minimize chafing	ANSI/SAIA A92.5 Sec: 4.15.1	☒	☐	☐	
2.57	Engine powered machines fuel lines are positioned to minimize exposure to engine and exhaust heat	ANSI/SAIA A92.5 Sec: 4.15.1	☒	☐	☐	
2.58	Engine powered machines exhaust system is provided with muffler	ANSI/SAIA A92.5 Sec: 4.15.1	☒	☐	☐	
2.59	Installation of Anti- Entrapment device on work platform	ANSI/SAIA A92.5 Sec: 4.15.1	☒	☐	☐	

REMARKS:

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE USFAN - SUDHIR YARD		WBS/BI/JO NUMBER FAHSS-26-1655	INSPECTION COMPANY NATIONAL INSPECTION AND TESTING COMPANY (FAHSS)	

EQUIPMENT ID NUMBER	EQUIPMENT DESCRIPTION/TYPE MANLIFT	SERIAL NO. B300027795	REPORT No.: LIC-2026-5153
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG	FACILITY / LOCATION Onshore / SUDHIR YARD	
REQUESTED INSPECTION DATE	RFI No.	TASK COMPLETED DATE 07-Feb-2026	EQUIPMENT OWNER SUDHIR COMPANY FOR EQUIPMENTS RENTAL

REFERENCE DOCUMENTS:
1- ANSI/SAIA A92.5 - 2014 Issue: Boom - Supported Elevating Work Platforms 2- SAES-B067 - 2020 Issue: Safety Identification and Safety Colors 3- SA GI 7.025 -2018 Issue: Heavy Equipment Operator and Rigger Testing and Certification 4- SA GI 7.030 - 2023 Issue: Inspection and Testing Requirements for Elevating/Lifting Equipment

Load Tested By (If Applicable):		Inspector Signature: 	
Name :	Date:		
☐ Inspected by 3rd Party Certified Inspector/Inspected:	☐ Witnessed by 3rd Party Certified Inspector/Witnessed by 3rd Party Certified Inspector:		
Name of Inspector : Yahya Khalid Yaseen Al-Khayri Company: NATIONAL INSPECTION AND TESTING COMPANY (FAHSS)	Inspector ID: 80024627		
Client signature: 			
User Representative:			
Name : SHMIR	Date: 07-Feb-2026		



SATISFACTION SURVEY

Thank you for your feedback

#	Question	Answer	Remarks
1	Did the Service provider Co. provide the right inspector with a valid qualification card?	Yes	
2	Did the service provider Co. respond for inspection within the expected time frame?	Yes	
3	Was the inspector wearing the required personal protective (Yes/No) equipment (PPE) during the inspection?	Yes	
4	Did the inspection conducted safely and in accordance with Aramco standard?	Yes	



الشركة الوطنية للفحص والاختبار الفني

National Inspection & Technical Testing Company

TEL.: +966 (13) 340 7607 | +966 (12) 610 9014

+966 (14) 325 1475 | +966 538400764

NO.: FAHSS-A-000427

EQUIP.NO.: S28SJ-1721

EQUIP. S.N.: B300027795

DATE INSPECTED: 07-Feb-2026

NEXT INSPECTION DATE: 06-Aug-2026

INSPECTED BY: Yahya Khalid Yaseen Al-Khayri