


LIFTING EQUIPMENT INSPECTION REPORT	Area	Org. Code	Inspection Date	Inspection Time	Previous Sticker No	Issued By
	NORTH REGION		03-Sep. 2025	07:30:00	215557	BV
Department/Contractor	Equipment No.	Type		Inspection Result	New Sticker No./ Report No.	
SUDHIR	S28SJ-546	BOOM SUPPORTED ELEVATING WORK PLATFORM		Pass	FAHSS-006831	
Equipment Location	Model	Manufacturer	Capacity	Equipment Serial No.	Sticker Expiration Date	
TABUK	860SJ	JLG	500 LBS	B300003601	02-Mar. 2026	
Above equipment was inspected by Fahsstuv nord accordance with applicable Saudi Aramco GI’s, ASME and API standards. Deficiencies that require corrective action listed below. Specific repairs to correct each deficiency should be noted in the corrective action taken column.						

No	Notes / Deficiencies	Corrective Action Taken
	**PERIODIC VISUAL INSPECTION AND FUNCTIONAL TEST FOUND TO BE SATISFACTORY AS PER ANSI/ SAIA A92.5	NONE
	AND SA GI 7.030 AT INSPECTION TIME. ** ANTI-ENTRAPMENT DEVICE ((PRESSURE SENSING CABLE)) TYPE	
	WORKING SATISFACTORY AT INSPECTION TIME.	

Receiver Name	Badge No.	Telephone No.	Inspector Name	Certificate No.	Telephone No.
SURYA DEO		533326321	YAHYA ALKHAYRI	80024627	
 Receiver Signature			 Manual report No.: 19362		
					

INSPECTOR COMMENT : SATISFACTORY

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENNT
PROJECT TITLE		WBS/BI/O NUMBER	INSPECTION COMPANY	
			FAHSS	

EQUIPMENT ID NUMBER	EQUIPMENT DESCRIPTION/TYPE	SERIAL NO.	REPORT No.:
S28SJ-546	BOOM SUPPORTED ELEVATING WORK PLATFORM	080003601	FAHSS-006831
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG	FACILITY / LOCATION TABUK	
REQUESTED INSPECTION DATE 01-Sep. 2025	RFI No.	TASK COMPLETED DATE 03-Sep. 2025	EQUIPMENT OWNER SUDHIR

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remark
1	GENERAL REQUIREMENTS:					
1.1	Equipment documentation is available	ANSI/SAIA A92.5, Sec: 4.16.1.1 G.I. 7.030	X			
1.2	Previous inspection reports are checked	ANSI/SAIA A92.5, Sec: 5.11.1.3 G.I. 7.030	X			
1.3	Daily pre-operational inspection checklists are checked (if applicable)	GI 7.030 Para: 5.1.2	X			
1.4	Preventive Maintenance is established and updated records are maintained	ANSI/SAIA A92.5, Sec: 6.4.1	X			
1.5	Equipment is operated by a qualified operator	ANSI/SAIA A92.5 Sec: 4.13.13	X			
1.6	Warning notice, cautions or restrictions for safe operation and maintenance are clearly displayed and legible	ANSI/SAIA A92.5 Sec: 4.13.1	X			
1.7	A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice	G.I. 7.030 Para: 5.6.2	X			
1.8	Manufacturer name, address, serial number and model are clearly marked or tagged	ANSI/SAIA A92.5 Sec: 4.13.2	X			
1.9	Safe working load and number of persons are clearly marked on the work platform	ANSI/SAIA A92.5, Sec: 4.13.3	X			
1.10	Maximum platform height and reach are clearly marked	ANSI/SAIA A92.5 Sec: 4.13.4 & 5	X			
1.11	Maximum travel height and travel directions are clearly marked	ANSI/SAIA A92.5 Sec: 4.13.9	X			
1.12	Power rating are provided and marked (for AC and/or DC)	ANSI/SAIA A92.5 Sec: 4.13.6			X	
1.13	Platform and guardrails electrical insulation data are provided	ANSI/SAIA A92.5 Sec: 4.13.10			X	
2	INSPECTION POINTS:					
2.1	Platform surfaces are at least 18" (width & length) and are slip-resistant	ANSI/SAIA A92.5 4.12.1	X			
2.2	Platform guardrails are provided and secure	ANSI/SAIA A92.5 4.12.2	X			
2.3	Platform guardrails are 42" height (+/- 3")	ANSI/SAIA A92.5 Sec: 4.12.2.1	X			
2.4	Platform toeboard is fitted and at least 4" high	ANSI/SAIA A92.5 Sec: 4.12.3	X			

SAUDI ARAMCO INSPECTION CHECKLIST	SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM	SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE	WBS/BI/JO NUMBER	INSPECTION COMPANY FAHSS	

EQUIPMENT ID NUMBER S28SJ-546	EQUIPMENT DESCRIPTION/TYPE BOOM SUPPORTED ELEVATING WORK PLATFORM		SERIAL NO. F0800003601	REPORT No.: FAHSS-006831
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG		FACILITY / LOCATION TABUK	
REQUESTED INSPECTION DATE 01-Sep. 2025	RFI No.	TASK COMPLETED DATE 03-Sep. 2025	EQUIPMENT OWNER SUDHIR	

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remark
2.5	Moving parts are guarded	ANSI/SAIA A92.5 Sec: 4.11	X			
2.6	Personnel on the platform is protected against the hazards of moving parts of the aerial platforms.	ANSI/SAIA A92.5 Sec: 7.10	X			
2.7	Access to the platform is provided	ANSI/SAIA A92.5 Sec: 4.12.4	X			
2.8	Access gates or openings shall be properly closed per the manufacturer's instructions	ANSI/SAIA A92.5 Sec: 4.12.4	X			
2.9	Electrical cables, wiring and components are undamaged	ANSI/SAIA A92.5 Sec:8.3	X			
2.10	Safety harness anchorage is fitted in the platform	ANSI/SAIA A92.5 Sec: 4.12.5.1	X			
2.11	Battery is secure, guarded and ventilated	ANSI/SAIA A92.5 Sec: 4.15.2	X			
2.12	Outrigger position microswitches and interlocks are fully functional at their control panel	ANSI/SAIA A92.5 Sec: 4.7			X	
2.13	Air, Hydraulic and fuel systems are not leaking	ANSI/SAIA A92.5 Sec: 6.6.5	X			
2.14	Emergency stop button is available at ground control station	ANSI/SAIA A92.5 Sec: 4.6.3	X			
2.15	There are no loose nuts, bolts, missing, worn or damaged parts around the structure	ANSI/SAIA A92.5 Sec: 6.6.2	X			
2.16	The equipment is free of defective and/or corroded members/joints	ANSI/SAIA A92.5 Sec:6.4.3	X			
2.17	Working environment is hazard free and machine can be safely operated	ANSI/SAIA A92.5 Sec:7.9	X			
2.18	An hour meter is fitted	ANSI/SAIA A92.5 Sec:4.15.3	X			
2.19	A fire extinguisher is fitted (type depends on operating location)	ANSI/SAIA A92.5 General	X			
2.20	All moving parts are lubricated	ANSI/SAIA A92.5 Sec: 6.6.5	X			
2.21	All fluid levels for oil, water and hydraulic are adequate	ANSI/SAIA A92.5 Sec: 6.6.5	X			
2.22	Platform controls operate the machine correctly	ANSI/SAIA A92.5 Sec: 6.6.1	X			
2.23	Platform controls are clearly marked with direction and mode of operation	ANSI/SAIA A92.5 Sec: 4.6.1.6	X			

SAUDI ARAMCO INSPECTION CHECKLIST	SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM	SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE	WBS/BI/JO NUMBER	INSPECTION COMPANY FAHSS	

EQUIPMENT ID NUMBER S28SJ-546	EQUIPMENT DESCRIPTION/TYPE BOOM SUPPORTED ELEVATING WORK PLATFORM		SERIAL NO. F880003601	REPORT No.: FAHSS-006831
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG		FACILITY / LOCATION TABUK	
REQUESTED INSPECTION DATE 01-Sep. 2025	RFI No.	TASK COMPLETED DATE 03-Sep. 2025	EQUIPMENT OWNER SUDHIR	

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remark
2.24	Platform controls accessible to the operator	ANSI/SAIA A92.5 Sec: 4.6.1.1	X			
2.25	Platform controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5 Sec: 4.6.1.4	X			
2.26	Platform controls are protected against inadvertent operation	ANSI/SAIA A92.5 Sec: 1.3	X			
2.27	Over-ride control for power functions is fitted at ground level control panel	ANSI/SAIA A92.5 Sec: 4.6.2.1	X			
2.28	Lower controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5 Sec: 4.6.2.4	X			
2.29	Lower controls are clearly marked for direction and mode of operation	ANSI/SAIA A92.5 Sec: 4.6.2.6	X			
2.30	Lower controls do not include drive and steering functions	ANSI/SAIA A92.5 Sec: 4.6.2.2	X			
2.31	Lower controls are protected against inadvertent operation	ANSI/SAIA A92.5 Sec: 4.6.2.5	X			
2.32	Boom raise/extend is operable from platform and ground control	ANSI/SAIA A92.5 Sec: 4.6.2.2	X			
2.33	Boom lower/retract is operable from platform and ground control	ANSI/SAIA A92.5 Sec: 4.6.2.2	X			
2.34	Platform rotation is operable from both platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.2.2	X			
2.35	Emergency stop button is operable from both platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.3	X			
2.36	Auxiliary/emergency lowering is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	X			
2.37	Auxiliary/emergency retracting is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	X			
2.38	Auxiliary/emergency rotating is operable from platform and ground controls	ANSI/SAIA A92.5 Sec: 4.6.4	X			
2.39	Hydraulic/Pneumatic systems are leak-free with platform raised	ANSI/SAIA A92.5 Sec: 4.10.2	X			
2.40	Tilt alarm is operable (5 degrees out of level) (manually depress the edge of the tilt switch to cause alarm condition)	ANSI/SAIA A92.5 Sec: 4.7.3	X			
2.41	Aerial platforms is fitted with a warning device at the platform which activates automatically when the aerial platform is at and beyond the slope	ANSI/SAIA A92.5 Sec: 4.6.6	X			
2.42	Tilt alarm is not combined with boom raise cut-out (dependent on machine manufacturer)	ANSI/SAIA A92.5 Sec: 4.6.6	X			

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENT
PROJECT TITLE		WBS/BI/JO NUMBER	INSPECTION COMPANY FAHSS	

EQUIPMENT ID NUMBER S28SJ-546	EQUIPMENT DESCRIPTION/TYPE BOOM SUPPORTED ELEVATING WORK PLATFORM		SERIAL NO. F080003601	REPORT No.: FAHSS-006831
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG		FACILITY / LOCATION TABUK	
REQUESTED INSPECTION DATE 01-Sep. 2025	RFI No.	TASK COMPLETED DATE 03-Sep. 2025	EQUIPMENT OWNER SUDHIR	

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remark
2.43	Steering is properly working when moving forward and in reverse directions	ANSI/SAIA A92.5 Sec: 6.6.3.1	X			
2.44	Brakes are in good working condition and can hold the machine on any slope (parking and moving)	ANSI/SAIA A92.5 Sec: 4.14.1	X			
2.45	Extendable axles function is satisfactory (where fitted)	ANSI/SAIA A92.5 Sec: 7.3.3.8			X	
2.46	Outriggers (stabilizers) extension-retraction operation is satisfactory	ANSI/SAIA A92.5 Sec: 7.10.3			X	
2.47	Extendable elevating assembly operation is satisfactory (retracted vs. extended)	ANSI/SAIA A92.5 Sec: 4.2.1	X			
2.48	Elevating assembly operation is satisfactory (elevated vs. lowered)	ANSI/SAIA A92.5 sec: 4.2.1(c)	X			
2.49	Wheels and tires are serviceable and undamaged	ANSI/SAIA A92.5 Sec: 7.3.3 (6)	X			
2.50	Travel alarm is operable	ANSI/SAIA A92.5 Sec: 6.6 (4)	X			
2.51	Platform lowering alarm is operable	ANSI/SAIA A92.5 Sec: 6.6 (4)	X			
2.52	Auxiliary power source available (to use in event of primary power loss)	ANSI/SAIA A92.5 Sec: 4.15.2	X			
2.53	Platform does not descend when in raised position and the power is off	ANSI/SAIA A92.5 Sec: 4.6.3	X			
2.54	Machine is safely drivable from the platform when raised (fast, slow, forward and reverse modes)	ANSI/SAIA A92.5 Sec: 6.6.3.1	X			
2.55	The platform does not descend when in raised position and the power is off	ANSI/SAIA A92.5 Sec: 4.6.3	X			
2.56	Engine powered machines fuel lines are supported to minimize chafing	ANSI/SAIA A92.5 Sec: 4.15.1	X			
2.57	Engine powered machines fuel lines are positioned to minimize exposure to engine and exhaust heat	ANSI/SAIA A92.5 Sec: 4.15.1	X			
2.58	Engine powered machines exhaust system is provided with muffler	ANSI/SAIA A92.5 Sec: 4.15.1	X			
2.59	Installation of Anti- Entrapment device on work platform	Letter No. CIU-L-019/2016	X			

REMARKS: This check list will be applied for Vehicle Mounted Elevating Work Platform - ANSI/SAIA A92.2.

REFERENCE DOCUMENTS:

- 1- ANSI/SAIA A92.5 - 2014 Issue: Boom - Supported Elevating Work Platforms
- 2- SAES-B067 - 2020 Issue: Safety Identification and Safety Colors
- 3- SA GI 7.025 -2018 Issue: Heavy Equipment Operator and Rigger Testing and Certification

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER	ISSUE DATE	DISCIPLINE
BOOM SUPPORTED ELEVATING WORK PLATFORM		SAIC-U-7013	12-Jan-23	ELEVATING/LIFTING EQUIPMENNT
PROJECT TITLE		WBS/BI/O NUMBER	INSPECTION COMPANY	
			FAHSS	
EQUIPMENT ID NUMBER S28SJ-546	EQUIPMENT DESCRIPTION/TYPE BOOM SUPPORTED ELEVATING WORK PLAT	SERIAL NO. 080003601	REPORT No.:	
CAPACITY (SWL) 500 LBS	MANUFACTURER JLG	FACILITY / LOCATION TABUK	FAHSS-006831	
REQUESTED INSPECTION DATE 01-Sep. 2025	RFI No.	TASK COMPLETED DATE 03-Sep. 2025	EQUIPMENT OWNER SUDHIR	

ITEM No.	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	Remark
4- SA GI 7.030 - 2023 Issue: Inspection and Testing Requirements for Elevating/Lifting Equipment						

Load Tested By (If Applicable):

Name, Signature, & Date:

☒ Inspected
 ☐ Witnessed by 3rd Party Certified Inspector:

Name, Signature, Certificate No. & Company:

YAHYA ALKHAYRI

80024627


Fahss

User Representative:

Name, Signature, & Date:

SURYA DEO

03-Sep. 2025





No.: TÜV NORD-006831

EQUIP. NO.: S28SJ-546

EQUIP. S.N.: B300003601

DATE INSPECTED: 03-Sep. 2025

NEXT INSPECTION DATE: 02-Mar. 2026

INSPECTED BY: YAHYA ALKHAYRI

Inspector SAP No. :80024627

S.A INSPECTION DEPARTMENT APPROVED CONTRACTOR AGENCIES