

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER SAIC-U-7013	ISSUE DATE 1-Nov-17	DISCIPLINE ELEVATING/LIFTING EQUIPMENT	
BOOM SUPPORTED ELEVATING WORK PLATFORM					
PROJECT TITLE Dmm yard		REPORT NUMBER 102209	NEW STICKER NUMBER BV-21-2441		

ACCEPTANCE CRITERIA

1. GENERAL REQUIREMENTS

		REFERENCE	RESULT
1.1	Equipment documentation is available	ANSI/SAIA A92.5, G.I. 7.030	PASS
1.2	Previous inspection reports are checked	ANSI/SAIA A92.5, G.I. 7.030	PASS
1.3	Equipment is operated by a qualified operator	ANSI/SAIA A92.5	PASS
1.4	Warning notice, cautions or restrictions for safe operation and maintenance are clearly displayed and legible	ANSI/SAIA A92.5	PASS
1.5	A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice	G.I. 7.030	PASS
1.6	Manufacturer name, address, serial number and model are clearly marked or tagged	ANSI/SAIA A92.5	PASS
1.7	Safe working load and number of persons are clearly marked on the work platform	ANSI/SAIA A92.5, SAES-B067	PASS
1.8	Maximum platform height and reach are clearly marked	ANSI/SAIA A92.5	PASS
1.9	Maximum travel height and travel directions are clearly marked	ANSI/SAIA A92.5	PASS
1.10	Power rating are provided and marked (for AC and/or DC)	ANSI/SAIA A92.5	PASS
1.11	Platform and guardrails electrical insulation data are provided	ANSI/SAIA A92.5	N/A

2. INSPECTION POINTS

		REFERENCE	RESULT
2.1	Platform surfaces are at least 18" (width & length) and are slip-resestant	ANSI/SAIA A92.5	PASS
2.2	Platform guardrails are provided and secure	ANSI/SAIA A92.5	PASS
2.3	Platform guardrails are 42" height (+/- 3")	ANSI/SAIA A92.5	PASS
2.4	Platform toeboard is fitted and at least 4" high	ANSI/SAIA A92.5	PASS
2.5	Moving parts are guarded	ANSI/SAIA A92.5	PASS
2.6	Access to the platform is provided	ANSI/SAIA A92.5	PASS
2.7	Platform access gatelock (or bar) and self-closer function is satisfactory (gate to open inward only)	ANSI/SAIA A92.5	PASS
2.8	Electrical cables, wiring and components are undamaged	ANSI/SAIA A92.5	PASS
2.9	Safety harness anchorage is fitted in the platform	ANSI/SAIA A92.5	PASS
2.10	Battery is secure, guarded and ventilated	ANSI/SAIA A92.5	PASS
2.11	Outrigger position microswitches and interlocks are fully functional at their contril panel	ANSI/SAIA A92.5	N/A
2.12	Air, Hydraulic and fuel systems are not leaking	ANSI/SAIA A92.5	PASS
2.13	Emergency stop button is available at ground control station	ANSI/SAIA A92.5	PASS
2.14	There are no loose nuts, bolts, missing, worn or damaged parts around the structure	ANSI/SAIA A92.5	PASS
2.15	The equipment is free of defective and/or corroded members/joints	ANSI/SAIA A92.5	PASS
2.16	Working environment is hazard free and machine ca be safely operated	ANSI/SAIA A92.5	PASS

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER SAIC-U-7013	ISSUE DATE 1-Nov-17	DISCIPLINE ELEVATING/LIFTING EQUIPMENT	
BOOM SUPPORTED ELEVATING WORK PLATFORM					
PROJECT TITLE Dmm yard		REPORT NUMBER 102209	NEW STICKER NUMBER BV-21-2441		

		REFERENCE	RESULT
2.17	An hour meter is fitted	ANSI/SAIA A92.5	PASS
2.18	A fire extinguisher is fitted (type depends on operating location)	ANSI/SAIA A92.5	PASS
2.19	All moving parts are lubricated	ANSI/SAIA A92.5	PASS
2.20	All fluid levels for oil, water and hydraulic are adequate	ANSI/SAIA A92.5	PASS
2.21	Platform controls operate the machine correctly	ANSI/SAIA A92.5	PASS
2.22	Platform controls are clearly marked with direction and mode of operation	ANSI/SAIA A92.5	PASS
2.23	Platform controls accessible to the operator	ANSI/SAIA A92.5	PASS
2.24	Platform controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5	PASS
2.25	Platform controls are protected against inadvertent operation	ANSI/SAIA A92.5	PASS
2.26	Over-ride control for power functions is fitted at ground level control panel	ANSI/SAIA A92.5	PASS
2.27	Ground controls return to "off" or "neutral" position when released	ANSI/SAIA A92.5	PASS
2.28	Ground controls are clearly marked for direction and mode of operation	ANSI/SAIA A92.5	PASS
2.30	Ground controls are protected against inadvertent operation	ANSI/SAIA A92.5	PASS
2.31	Boom raise/extend is operable from platform and ground control	ANSI/SAIA A92.5	PASS
2.32	Boom lower/retract is operable from platform and ground control	ANSI/SAIA A92.5	PASS
2.33	Platform rotation is operable from both platform and ground controls	ANSI/SAIA A92.5	PASS
2.34	Emergency stop button is operable from both platform and ground controls	ANSI/SAIA A92.5	PASS
2.35	Auxiliary/emergency lowering is operable from platform and ground controls	ANSI/SAIA A92.5	PASS
2.36	Auxiliary/emergency retracting is operable from platform and ground controls	ANSI/SAIA A92.5	PASS
2.37	Auxiliary/emergency rotating is operable from platform and ground controls	ANSI/SAIA A92.5	PASS
2.38	Hydraulic/Pneumatic systems are leak-free with platform raised	ANSI/SAIA A92.5	PASS
2.39	Tilt alarm is operable (5 degrees out of level) (manually depress the edge of the tilt switch to cause alarm condition)	ANSI/SAIA A92.5	PASS
2.40	Tilt alarm is not combined with boom raise cut-out (dependent on machine manufacturer)	ANSI/SAIA A92.5	PASS
2.41	Steering is properly working when moving forward and in reverse directions	ANSI/SAIA A92.5	PASS
2.42	Brakes are in good working condition and can hold the machine on any slope (parking and moving)	ANSI/SAIA A92.5	PASS
2.43	Extendable axles function is satisfactory (where fitted)	ANSI/SAIA A92.5	N/A
2.44	Outriggers (stabilizers) extension-retraction operation is satisfactory	ANSI/SAIA A92.5	N/A
2.45	Extendable elevating assembly operation is satisfactory (retracted vs. extended)	ANSI/SAIA A92.5	N/A
2.46	Elevating assembly operation is satisfactory (elevated vs. lowered)	ANSI/SAIA A92.5	PASS
2.47	Wheels and tyres are serviceable and undamaged	ANSI/SAIA A92.5	PASS

SAUDI ARAMCO INSPECTION CHECKLIST		SAIC NUMBER SAIC-U-7013	ISSUE DATE 1-Nov-17	DISCIPLINE ELEVATING/LIFTING EQUIPMENT	
BOOM SUPPORTED ELEVATING WORK PLATFORM					
PROJECT TITLE Dmm yard		REPORT NUMBER 102209	NEW STICKER NUMBER BV-21-2441		

		REFERENCE	RESULT
2.48	Travel alarm is operable	ANSI/SAIA A92.5	PASS
2.49	Platform lowering alarm is operable	ANSI/SAIA A92.5	PASS
2.50	Auxiliary power source is available (ready to be used in event of primary power loss)	ANSI/SAIA A92.5	PASS
2.51	Machine is safely drivable from the platform when raised (fast, slow, forward and reverse modes)	ANSI/SAIA A92.5	PASS
2.52	The platform does not descend when in raised position and the power is off	ANSI/SAIA A92.5	PASS
2.53	Engine powered machines fuel lines are supported to minimize chafing	ANSI/SAIA A92.5	PASS
2.54	Engine powered machines fuel lines are positioned to minimize exposure to engine and exhaust heat	ANSI/SAIA A92.5	PASS
2.55	Engine powered machines exhaust system is provided with muffler	ANSI/SAIA A92.5	PASS
2.56	Installation of Anti- Entrapment device on work platform	Letter No. CIU-L-019/2016	PASS

REMARKS

-

Signature

Inspected / Witnessed by 3rd Party Certified Inspector

Name Mohamed OMARA
Signature 
Certificate No. ID-18-0009
Company Bureau Veritas

User Representative

Name Mahtab Khan
Signature  2470523922
Date 26/10/2021