Backtest integrity screening

Sample report | Fully synthetic data

Author	Nassim Berrahmane
Date	6 September 2026
Version	010bdecdfd82fe82742216471ba717106c95ae68
Verdict	FAIL

No client data, private strategy, position, API key, or private laboratory observation is included.

Audit question and scope

Does the supplied dataset satisfy the minimum chronology, instrument-life and file-integrity properties required to defend a reported backtest result?

Control	Verdict	Evidence
SHA-256 manifests	**PASS**	3 files verified per fixture
Contract-life catalogue	**PASS**	3 contract lives checked
Signal chronology	**FAIL**	LOOKAHEAD, row 2
Rows after cessation	**FAIL**	PHANTOM_POST_CESSATION_ROW, row 3
Real execution costs	**NOT VERIFIED**	Outside synthetic scope

Reproducible method

The same offline auditor is run on a clean reference and its contaminated variant. The clean control returns PASS with exit code 0. The variant returns FAIL with exit code 2 and two findings. No network or trading account is used.

Priority findings

F-01 | LOOKAHEAD | High severity

The feature window ends after the decision timestamp. The result cannot be defended as point-in-time. Remediation: rebuild the feature with an end time no later than the decision, then regenerate the result from frozen inputs.

F-02 | PHANTOM_POST_CESSATION_ROW | High severity

A flat zero-volume row exists after cessation of the first ABCUSDT contract life. Remediation: reject every row outside explicit life bounds and retain life_id in every join.

Traceability and conclusion

Inputs are frozen through SHA-256 manifests. Findings are localized by file, row, code and severity. The clean fixture passes the same controls, so the tool does not reject every input indiscriminately.

BOUNDED VERDICT: this report establishes dataset and chronology properties only. It does not certify future performance, economic causality, or suitability for live trading.

Contact: b.m.nassim85@gmail.com