

API Reference — Aveno Marketplace

This is the detailed companion to `API_CONTRACT.md`. That file is the *contract* (route, auth, one-line note) the Flutter app is built against — this file is the *manual*: what each endpoint actually does, exactly what to send it, and exactly what it sends back, with real example payloads.

Every endpoint below has been exercised against a running instance of this API (both directly with curl/PHP and via the automated test suite in `tests/Feature/`) — the shapes here are observed, not guessed.

Conventions used throughout

- **Base URL (local dev):** `http://localhost:8000/api`
- **Auth header:** `Authorization: Bearer <token>` (Laravel Sanctum personal access token, obtained from `/auth/register` or `/auth/login`). No cookies, no CSRF.
- **Always send** `Accept: application/json`.
- **List endpoints** that are paginated return Laravel's default paginator shape:

```
{
  "data": [ ... ],
  "links": { "first": "...", "last": "...", "prev": null, "next": null },
  "meta": { "current_page": 1, "from": 1, "last_page": 1, "per_page": 20, "to": 2,
    "total": 2, "path": "...", "links": [...] }
}
```

A few admin list endpoints (noted below) return the **full unpaginated set** instead — same `{"data": [...]}` wrapper, but no `links` / `meta`.

- **Single-item endpoints** return `{"data": { ... }}` (via a Laravel API Resource), except a handful of legacy actions that return a plain object or a `{"message": "..."} acknowledgment` — noted per endpoint.
- **Validation errors** → `422` with `{"message": "...", "errors": {"field": ["reason"]}}`.
- **Unauthenticated** → `401` with `{"message": "Unauthenticated."}`.
- **Forbidden** (wrong role / not the resource owner) → `403` with `{"message": "..."}.`
- **Not found** → `404` with `{"message": "..."} (also used deliberately for ads that exist but aren't publicly visible yet — see Ads below; that case returns an empty message).`
- **Not allowed in the current state** (e.g. marking a pending ad sold, approving an ad that isn't pending) → `422` with only `{"message": "..."} — no errors key, unlike a validation failure.`
- **Conflict** → `409` with `{"message": "..."} (deleting a category that still has ads).`
- A `UserResource` (used inside many responses below) always has this shape:

```
{
  "id": 3, "name": "Test User", "phone": "0999111222", "email": null,
  "avatar_url": null, "rating_average": 0, "rating_count": 0,
  "is_banned": false, "created_at": "2026-09-03T19:13:45.000000Z"
}
```

(`governorate` / `city` appear here too, only when the caller eager-loaded them — they don't on any endpoint below.)

Auth

POST /auth/register

Auth: none. **Does:** Creates a new user account and immediately logs them in (returns a usable token — no separate login step needed after registering). **Input (JSON body):**

Field	Required	Notes
<code>name</code>	yes	string, max 100
<code>phone</code>	yes	string, must be unique — this is the login identifier
<code>password</code>	yes	string, min 8
<code>email</code>	no	must be a valid, unique email if given
<code>governorate_id</code>	no	must exist in <code>governorates</code>
<code>city_id</code>	no	must exist in <code>cities</code>

Output — 201:

```
{
  "user": { "id": 3, "name": "Test User", "phone": "0999111222", "email": null, "avatar_url":
    null, "rating_average": 0, "rating_count": null, "is_banned": false, "created_at": "..."},
  "token": "4|JuyvPN0mHQqJir2X1y344aBi0wmr2R3ch7jGWf9K8775e271"
}
```

Errors: 422 if `phone` / `email` already taken or any rule fails.

POST /auth/login

Auth: none. **Does:** Authenticates by phone + password, returns a fresh token. Blocks banned users. **Input (JSON body):** `phone` (required), `password` (required). **Output — 200:** same shape as register (`{"user":`

..., "token": "..."}). **Errors:**

- 422 {"message": "بيانات الدخول غير صحيحة"} — wrong phone or password.
- 403 {"message": "تم إيقاف هذا الحساب"} — account is banned (is_banned = true).

POST /auth/logout

Auth: required. **Does:** Revokes the token used to make *this* request (other tokens/sessions for the same user, if any, stay valid). **Input:** none. **Output — 200:** {"message": "تم تسجيل الخروج"}.

GET /auth/me

Auth: required. **Does:** Returns the caller's own profile — the standard way to check "am I still logged in" and to read rating_average / rating_count after a rating event. **Input:** none. **Output — 200:** a single UserResource under data.

Categories

GET /categories

Auth: none. **Does:** Top-level (no parent), active categories only, with their immediate children — this is what feeds the home-screen category grid. **Input:** none. **Output — 200:**

```
{
  "data": [
    { "id": 1, "name_ar": "سيارات", "name_en": null, "slug": "cars", "icon_url": null,
      "is_active": true, "children": [] }
  ]
}
```

(No attributes key here — that only loads on the single-category endpoint below. No pagination wrapper — this returns the full active top-level list every time.)

GET /categories/{id}

Auth: none. **Does:** One category with its dynamic spec fields (attributes) and its children — this is what renders the "post an ad" form once a category is picked, so the Flutter app knows which fields to show and how to validate them client-side. **Input:** {id} path param. **Output — 200:**

```
{
  "data": {
    "id": 1, "name_ar": "سيارات", "name_en": null, "slug": "cars", "icon_url": null,
    "is_active": true,
    "children": [],
    "attributes": [
      { "id": 1, "key": "condition", "label_ar": "الحالة", "label_en": null, "type":
        "select", "options": ["مصدومة", "مستعملة", "جديدة"], "is_required": true },
      { "id": 3, "key": "year", "label_ar": "سنة الصنع", "label_en": null, "type": "number",
        "options": null, "is_required": true }
    ]
  }
}
```

`type` is one of `text|number|boolean|select|multiselect` — it tells the client how to render the field, and the server how to validate it on `POST/PUT /ads`. `options` is only non-null for `select` / `multiselect`.

Errors: `404` if the category doesn't exist.

Ads

This is the core of the app. `status` is one of `pending|approved|rejected|expired|sold` — every new ad starts `pending`, and only an admin approving it (see Admin ► Ads) makes it visible on the public feed.

`GET /ads`

Auth: none. **Does:** The public browse/search feed. **Only** `status = approved` ads are ever returned here. Default order (no `sort` given, or `sort=newest`) is featured ads first, then newest first — the same as before `sort` existed, so omitting it doesn't change anything for existing clients. **Input (all query params optional):**

Param	Type	Does
<code>category_id</code>	int	exact match
<code>governorate_id</code>	int	exact match
<code>city_id</code>	int	exact match
<code>min_price</code> / <code>max_price</code>	number	inclusive range on <code>price</code>
<code>q</code>	string	matches against <code>title</code> or <code>description</code> (<code>LIKE %q%</code>)
<code>sort</code>	string	one of <code>newest</code> (default), <code>price_asc</code> , <code>price_desc</code> , <code>popular</code> (by <code>views_count</code> descending), <code>nearest</code> . Picking any value other than <code>newest</code> replaces the default featured-first ordering entirely — it doesn't layer on top of it.
<code>lat</code> / <code>lng</code>	number	required when <code>sort=nearest</code> (422 otherwise) — the caller's own coordinates, to sort by. Only ads with both <code>latitude</code> and <code>longitude</code> set participate in <code>nearest</code> ; ads without a location are excluded from the results entirely for that sort (not pushed to the end). Distance is an unscaled flat-earth approximation (fine for sort order, not an actual km/mi value) — not returned in the response.
any category-attribute key (e.g. <code>fuel_type</code> , <code>condition</code>)	string	matches ads whose dynamic attribute of that key equals the given value. If the key is defined on more than one category (e.g. <code>condition</code> exists on both "cars" and "motorcycles"), matches are OR'd across all of them unless <code>category_id</code> is also given to disambiguate. Only attributes with <code>is_filterable = true</code> are matchable this way; unrecognized params are silently ignored (not an error).

Output — `200`: paginated list of `AdResource` (20/page). Each item (note: `description` is **omitted** here — only present on the single-ad `show` endpoint):

```
{
  "id": 1, "title": "كيا سبورتاج 2019 للبيع", "slug": "kia-sportage-2019-test",
  "price": 15000, "currency": "USD", "status": "approved", "is_featured": false,
  "views_count": 0,
  "latitude": null, "longitude": null,
  "category": { "id": 1, "name_ar": "سيارات", ... },
  "governorate": { "id": 1, "name_ar": "دمشق", ... },
  "city": { "id": 1, "governorate_id": 1, "name_ar": "دمشق", ... },
  "images": [ { "id": 1, "url": "http://.../storage/ads/1/xyz.jpg", "is_cover": true } ],
  "created_at": "...", "published_at": "..."
}
```

GET `/ads/{id}`

Auth: none. **Does:** Full ad detail — the only endpoint that includes `description`, and the only one that includes `attributes` (the dynamic spec values) and the seller's `user` info. Also increments `views_count` by 1 on every call (no dedup — a refresh counts again). **Input:** `{id}` path param. **Output** — **200**: a single `AdResource`, plus:

```
"attributes": [ { "key": "condition", "label_ar": "الحالة", "value": "مستعملة" }, { "key": "year", "label_ar": "سنة الصنع", "value": "2020" } ]
```

Also includes `favorites_count` and `conversations_count`. **Errors:** **404** (empty `message`) — either the ad genuinely doesn't exist, **or** its status isn't `approved` or `sold`. This applies to the owner too: a pending/rejected/expired ad is only visible to its owner through `GET /my/ads`.

`GET /ads/{id}/similar`

Auth: none. **Does:** A "you might also like" rail for the detail page: other `approved` ads in the same category. When the ad has a price, only ads priced within $\pm 30\%$ of it, closest price first; without a price, newest first. Never includes the ad itself. **Input:** `{id}` path param. **Output** — **200**: `{"data": [ ...AdResource ]}` — **unpaginated**, at most 10 items, each with `images`, `category`, `city`, `governorate`. **Errors:** **404** (empty `message`) under the same rule as `GET /ads/{id}`.

`GET /my/ads`

Auth: required. **Does:** The caller's own ads, **any status** (pending/approved/rejected/etc.) — this is how a seller sees "my listing was rejected" or checks review status. **Input:** none. **Output** — **200**: paginated `AdResource` collection (20/page), same shape as the public feed items plus `favorites_count` and `conversations_count`.

`GET /my/ads/stats`

Auth: required. **Does:** Aggregate numbers across all of the caller's ads, for a "your activity" card. **Output** — **200**:

```
{
  "data": {
    "total_ads": 2,
    "by_status": { "pending": 1, "approved": 1, "rejected": 0, "sold": 0, "expired": 0 },
    "total_views": 0, "total_favorites": 0, "total_conversations": 0
  }
}
```

POST /ads

Auth: required. **Content-Type:** `multipart/form-data` (it carries files). **Does:** Creates a new ad as `status = pending`, awaiting admin review. Validates the dynamic `attributes[]` against the chosen category's `category_attributes` (required-ness, `select / multiselect` option membership, `number` type-checking). Resizes/compresses every uploaded image (max 1600×1600, re-encoded JPEG q80) before storing it — see `app/Services/ImageService.php`. **Input (form fields):**

Field	Required	Notes
<code>category_id</code>	yes	must exist
<code>governorate_id</code>	yes	must exist
<code>city_id</code>	yes	must exist
<code>title</code>	yes	string, max 150
<code>description</code>	yes	string, max 5000
<code>price</code>	no	numeric ≥ 0
<code>currency</code>	no	3-letter code, defaults to <code>USD</code>
<code>latitude / longitude</code>	no	numeric, valid coordinate range
<code>images[]</code>	yes	1–12 image files, each ≤ 5MB (<code>max:5120</code> KB)
<code>attributes[<key>]</code>	conditionally	one field per dynamic spec on the category, e.g. <code>attributes[condition]=مستعملة&attributes[year]=2020</code> ; required keys depend on the category (see <code>GET /categories/{id}</code>)

Output — 201: a single `AdResource` with `status: "pending"`, including `images` and `attributes` (freshly created). **Errors:**

- `401` if not authenticated.
- `422` — either standard field validation, or `{"errors": {"attributes": [",", "مطلوب.", "\...\\" الحفل \\\\" قيمه \\\\" غير صالحة \\\\"." ]}}` for dynamic-attribute problems.

PUT/PATCH /ads/{id}

Auth: required, **must be the ad's owner**. **Does:** Partial update (only send the fields you're changing) — `title`, `description`, `price`, and/or `attributes`. Photos are **not** managed here — see `POST / DELETE /ads/{id}/images` below. **Any edit resets the ad to `status = pending`** and clears `rejection_reason / reviewed_by / reviewed_at`, forcing a fresh admin review. **Input (JSON or form body, all optional):** `title`, `description`, `price`, `attributes` (object — same dynamic-attribute rules as create, but required-ness isn't re-enforced on a partial edit; an empty value for a key clears that attribute). **Output — 200:** the updated `AdResource`. **Errors:** `403` if the caller isn't the owner; `422` on validation failure.

DELETE /ads/{id}

Auth: required, **must be the ad's owner**. **Does:** Soft-deletes the ad (recoverable in the DB, but gone from every endpoint immediately). **Input:** none. **Output — 200:** {"message": "تم حذف الإعلان"}. **Errors:** 403 if not the owner.

POST /ads/{id}/images

Auth: required, **must be the ad's owner**. **Content-Type:** multipart/form-data. **Does:** Adds one or more photos to an ad that already exists, **appending** to its current gallery rather than replacing it (so adding one more photo doesn't require re-sending the rest). Same resize/compression as ad creation (max 1600×1600, JPEG q80). If the ad had no images at all (shouldn't normally happen, since creation requires ≥1), the first image added becomes the cover; otherwise the existing cover is left alone. Like any other edit, **resets the ad to status = pending** for re-review. **Input (form fields):**

Field	Required	Notes
images[]	yes	1 or more image files, each ≤ 5MB. Total images on the ad (existing + new) cannot exceed 12.

Output — 200: the updated AdResource, including the full images array. **Errors:**

- 403 if the caller isn't the owner.
 - 422 — bad/undecodable file, or the 12-image cap would be exceeded.
-

DELETE /ads/{id}/images/{imageId}

Auth: required, **must be the ad's owner**. **Does:** Removes one photo from the ad. An ad must always keep **at least one** photo — removing the last one is rejected (delete the whole ad instead if that's the goal). If the removed photo was the cover, the next photo by sort_order is automatically promoted to cover. Like any other edit, **resets the ad to status = pending** for re-review. **Input:** none. {imageId} is the id from an item in the ad's images array. **Output — 200:** the updated AdResource. **Errors:**

- 403 if the caller isn't the owner.
 - 404 if {imageId} doesn't belong to this ad.
 - 422 {"message": "احذف الإعلان بالكامل إذا أردت"}. يجب أن يحتوي الإعلان على صورة واحدة على الأقل - احذف الإعلان بالكامل إذا أردت. if it's the ad's only remaining photo.
-

POST /ads/{id}/mark-sold

Auth: required, **must be the ad's owner**. **Does:** approved → sold. The ad leaves the public feed but GET /ads/{id} still shows it (with status: "sold"). **Input:** none. **Output — 200:** the updated

AdResource (status: "sold"). **Errors:**

- 403 if not the owner.
 - 422 {"message": "لا يمكن تحديد إعلان غير منشور كمباع"} if the ad isn't approved .
-

POST /ads/{id}/relist

Auth: required, **must be the ad's owner**. **Does:** sold / expired → pending : sends the ad back through admin review rather than republishing it instantly (the listing may be stale). Clears any previous review/rejection info. **Input:** none. **Output** — 200 : the updated **AdResource** (status: "pending").

Errors:

- 403 if not the owner.
 - 422 {"message": "يمكن إعادة النشر فقط للإعلانات المباعة أو منتهية الصلاحية"} for any other status.
-

POST /ads/{id}/report

Auth: required. **Does:** Flags the ad for admin review (Admin ► Reports). Takes no action by itself. Reporting the same ad again updates your existing report and reopens it (back to pending) instead of creating a duplicate. **Input:** reason (required, one of spam|inappropriate|scam|other), details (optional, max 1000). **Output** — 200 : {"message": "تم إرسال البلاغ"} . **Errors:**

- 404 (empty message) if the ad isn't approved or sold .
 - 422 {"message": "لا يمكنك الإبلاغ عن إعلانك الخاص"} for your own ad.
 - 422 validation error for a missing/unknown reason .
-

Favorites

GET /favorites

Auth: required. **Does:** The caller's saved/bookmarked ads. **Output** — 200 : paginated **AdResource** collection (only ads the caller favorited).

POST /ads/{id}/favorite

Auth: required. **Does:** Saves the ad to the caller's favorites. Idempotent — calling it twice doesn't create a duplicate. **Output** — 200 : {"message": "أُضيف إلى المفضلة"} . **Errors:** 404 if the ad isn't approved — a pending/rejected ad was never shown to anyone, so it can't be favorited, same rule as GET /ads/{id} .

DELETE /ads/{id}/favorite

Auth: required. **Does:** Removes the ad from the caller's favorites (no-op, still `200`, if it wasn't favorited).

Output — `200`: `{"message": "أُزيل من المفضلة"}`.

Chat

One conversation exists per `(ad, buyer)` pair — starting it twice for the same ad, as the same buyer, returns the same conversation rather than creating a second one.

GET /conversations

Auth: required. **Does:** All conversations the caller is part of, as either buyer or seller, newest-activity first.

Output — `200`: paginated `ConversationResource` collection:

```
{ "id": 1, "ad": { ...AdResource }, "buyer": { ...UserResource }, "seller": { ...UserResource }, "last_message_at": "2026-09-03T..." }
```

POST /ads/{id}/conversations

Auth: required. **Does:** Starts (or fetches the existing) conversation with the ad's owner about that ad. The caller becomes the `buyer`. **Output:** a `ConversationResource`. `201` the first time (new conversation), `200` on every subsequent call for the same ad+buyer (Laravel auto-201s a POST whose result was freshly created — treat both as success). **Errors:**

- `404` if the ad isn't `approved` — same visibility rule as `GET /ads/{id}` and favoriting; you can't message about an ad you couldn't have seen.
- `422` `{"message": "لا يمكنك مراسلة نفسك"}` if you try to message yourself about your own ad.

GET /conversations/{id}/messages

Auth: required, **must be a participant** (buyer or seller on that conversation). **Does:** Full message history, oldest first (paginated 50/page — intended for polling, not one-shot infinite scroll). **Output — `200`:** paginated `MessageResource` collection:

```
{ "id": 1, "conversation_id": 1, "sender": { ...UserResource }, "body": "Hello, is this still available?", "read_at": null, "created_at": "..." }
```

Errors: `403` if the caller isn't a participant.

POST /conversations/{id}/messages

Auth: required, **must be a participant**. **Does:** Sends a message, bumps the conversation's

`last_message_at`, and **notifies the other participant** (see Notifications — `type: "new_message"`). **Input:**

`{"body": "..."} (required, max 2000 chars). Output: a MessageResource (200 / 201, same auto-201 note as above). Errors: 403 if not a participant; 422 if body missing/too long.`

Ratings

`(rater, rated, ad)` is a unique triple — rating the same person again (for the same `ad_id`, including both `null`) **updates** the existing rating rather than creating a second one, and the target's `rating_average` / `rating_count` are recomputed from scratch every time (see `app/Services/RatingService.php`).

GET `/users/{id}/ratings`

Auth: none — shown on a public seller profile. **Output** — 200: paginated `RatingResource` collection:

```
{ "id": 2, "score": 4, "comment": "good seller", "rater": { ...UserResource }, "created_at": "..." }
```

POST `/users/{id}/ratings`

Auth: required. **Does:** Rates another user, then immediately recomputes their `rating_average` / `rating_count`, then **notifies them** (`type: "new_rating"`). **No proof of an actual transaction/conversation is required** — a rating can reference any ad the rater could plausibly have seen (home feed or search), which by definition means an approved one. **Input:** `score` (required, integer 1–5), `comment` (optional, max 1000), `ad_id` (optional — must be an `approved` ad if given; not required to have any connection to the rater/rated beyond existing and being approved). **Output:** a `RatingResource` (200 / 201). **Errors:**

- 422 `{"message": "لا يمكنك تقييم نفسك"}` if `{id}` is your own user id.
- 422 if `ad_id` is given but the ad isn't `approved`.

POST `/users/{id}/report`

Auth: required. **Does:** Flags a user for admin review — same rules as `POST /ads/{id}/report` (re-reporting reopens your existing report). **Input:** `reason` (required, one of `spam|inappropriate|scam|other`), `details` (optional, max 1000). **Output** — 200: `{"message": "تم إرسال البلاغ"}`. **Errors:** 422 `{"message": "لا يمكنك الإبلاغ عن نفسك"}` when `{id}` is you; 422 validation error for a missing/unknown `reason`.

Notifications

Backed by Laravel's standard database-notifications table (`Notifiable` trait on `User`). Every notification's `data` payload always has at least `type` and a human-readable Arabic `message` ; extra fields vary by type (see below).

type	Fired when	Extra data fields
ad_approved	Admin approves your ad	ad_id , title
ad_rejected	Admin rejects your ad	ad_id , title , reason
new_message	Someone messages you in a conversation	conversation_id , sender_id , sender_name , body
new_rating	Someone rates you	rating_id , rater_id , rater_name , score

GET /notifications

Auth: required. **Does:** The caller's notifications, newest first, read and unread mixed together (check `read_at` per item to distinguish). **Output** — **200** : paginated (30/page) raw notification rows (not a custom Resource — this is Laravel's default `DatabaseNotification` shape):

```
{
  "id": "141cc664-62f1-42cc-99c0-0f1a919f1ae6",
  "type": "App\\Notifications\\AdApproved",
  "notifiable_type": "App\\Models\\User", "notifiable_id": 3,
  "data": { "type": "ad_approved", "ad_id": 2, "title": "Test Car Ad", "message": "تمت
  \\"Test Car Ad\\" منشور \\"الموافقة على إعلانه",
  "read_at": null, "created_at": "...", "updated_at": "..."
}
```

Note `id` here is a UUID string, not an integer — pass it as-is to the two endpoints below.

POST /notifications/{id}/read

Auth: required. **Does:** Marks one notification read (`{id}` is the UUID from the list above). Silently succeeds even if the id doesn't exist or belongs to someone else (no-op, not an error — nothing to leak either way). **Output** — **200** : `{"message": "تم التحديث"}`.

POST /notifications/read-all

Auth: required. **Does:** Marks every one of the caller's unread notifications as read. **Output** — **200** : `{"message": "تم التحديث"}`.

Push notification device tokens

Push is code-complete but inactive until `FIREBASE_CREDENTIALS_JSON` is set (see `App\Services\PushNotificationService`). Push delivery is best effort: if Firebase is down, the action that triggered it (an approval, a message, a rating) still succeeds.

POST /device-tokens

Auth: required. **Does:** Registers this device's FCM token for the caller — call on app launch / after login. Keyed by token: if the same device was registered under another account, it moves to the caller. **Input:** `token` (required, max 255), `platform` (optional, one of `android|ios|web`). **Output — 200:** `{"message": "تم التسجيل"}`. **Errors:** 422 validation error (e.g. unknown `platform`).

DELETE /device-tokens

Auth: required. **Does:** Unregisters the token — call on logout, so the device stops receiving this account's pushes. Only affects the caller's own tokens; an unknown token is a silent no-op. **Input:** `token` (required). **Output — 200:** `{"message": "تم الحذف"}`.

Banning a user also deletes all of their device tokens (see Admin ► Users).

Banners (sponsored, home-screen carousel)

Separate from `ads` entirely — no owner, no approval workflow, no in-app payment. A business pays the admin directly (e.g. a Sham Cash transfer arranged outside the app, same as cash) for a slot in the home-screen carousel for an agreed window, and the admin creates the banner here. See `docs/HOW_IT_WORKS.md` § Sponsored Banners for the full story.

GET /banners

Auth: none. **Does:** The banners currently inside their `starts_at` / `ends_at` window **and** not paused (`is_active = true`) — exactly what the home-screen carousel should render. Ordered by `sort_order`, then creation order. **Output — 200:**

```
{
  "data": [
    { "id": 1, "title": "Pizza Palace", "image_url": "http://.../storage/banners/xyz.jpg",
      "link_url": "tel:+963911111111", "starts_at": "...", "ends_at": "...", "sort_order": 0,
      "is_active": true }
  ]
}
```

(Unpaginated — the full active set every time, like `/categories` and `/ad-packages`.)

GET /admin/banners

Auth: admin. **Does:** Every banner regardless of its window or `is_active` — the admin's own management list, not what the public carousel shows. **Output** — `200`: paginated (30/page) `BannerResource` collection.

POST /admin/banners

Auth: admin. **Content-Type:** `multipart/form-data` (carries the image). **Does:** Creates a banner. Resized/compressed the same way as ad photos (max 1600×1600, JPEG q80). **Input (form fields):**

Field	Required	Notes
<code>image</code>	yes	image file, ≤5MB
<code>title</code>	no	string, max 150 — admin-facing label, also returned to the client
<code>link_url</code>	no	must start with <code>https://</code> , <code>http://</code> , or <code>tel:</code> if given — whatever tapping the banner should open
<code>starts_at</code> / <code>ends_at</code>	yes	datetimes; <code>ends_at</code> must be ≥ <code>starts_at</code>
<code>sort_order</code>	no	integer, defaults to 0 — lower sorts first

Output — `201`: the new `BannerResource`. **Errors:** `422` on validation failure (including a rejected `link_url` scheme, e.g. `javascript:...`).

PUT/PATCH /admin/banners/{id}

Auth: admin. **Does:** Partial update of any of `title`, `link_url`, `starts_at`, `ends_at`, `sort_order`, `is_active`. Flipping `is_active` to `false` is how an admin pauses a banner early **without** recalculating its dates. Does **not** support replacing the image — delete and recreate the banner instead. **Output** — `200`: the updated `BannerResource`.

DELETE /admin/banners/{id}

Does: Deletes the banner and its stored image file. **Output** — `200`: `{"message": "تم الحذف"}`.

Payments (Sham Cash) — partially implemented

GET /ad-packages

Auth: none. **Does:** The active featured-ad packages (15/30/60-day boosts), cheapest/shortest first. **Output** — `200`: `{"data": [ { "id": 1, "name_ar": "...", "duration_days": 15, "price": 5.0, "currency": "USD" }, ... ]}` (unpaginated — the full active catalog every time).

POST /ads/{id}/checkout — stub

Auth: required, must be the ad's owner. **Input:** `{"ad_package_id": <id>}`. **Current behavior:** creates a pending Payment row, then **always returns** 501 `{"message": "Sham Cash integration pending – see app/Services/ShamCash/ShamCashClient.php"}`. Waiting on real Sham Cash API docs — see `app/Services/ShamCash/ShamCashClient.php`.

POST /payments/shamcash/webhook — stub

Auth: none (would be HMAC-signature-verified once implemented). **Current behavior:** **always returns** 501 `{"message": "Not implemented yet."}`.

Admin (requires the admin role in addition to auth — 403 {"message": "Admins only."} otherwise)

The 403 also applies to an admin account that has been banned. A browser session from the /admin-panel is never accepted here — these endpoints take bearer tokens only, like the rest of the API.

Admin ► Categories

GET /admin/categories

Does: Every category (regardless of `is_active`), each with `children` and `attributes` loaded — the full management view. **Output — 200:** `{"data": [ ...CategoryResource ]}` — **unpaginated**, full set every time.

POST /admin/categories

Input: `parent_id` (optional, must exist), `name_ar` (required, max 100), `name_en` (optional, max 100), `sort_order` (optional integer ≥ 0, defaults to 0). `slug` is auto-generated from `name_en / name_ar` + a random suffix. **Output — 201:** the new `CategoryResource`, with the stored defaults filled in:

```
{ "data": { "id": 3, "name_ar": "أثاث", "name_en": "Furniture", "slug": "furniture-Dsgq", "icon_url": null, "is_active": true } }
```

Errors: 422 validation error, e.g. `{"errors": {"sort_order": ["The sort order field must be at least 0."]}}`.

PUT/PATCH /admin/categories/{id}

Input (all optional): `name_ar`, `name_en`, `is_active`, `sort_order`. **Output — 200:** the updated `CategoryResource`.

DELETE /admin/categories/{id}

Output — 200: {"message": "تم الحذف"}. **Errors:** 409 {"message": "لا يمكن حذف هذه الفئة لوجود". "إعلانات مرتبطة بها أو بإحدى فئاتها الفرعية"} if any ad (directly or via a subcategory) still references this category.

POST /admin/categories/{id}/attributes

Does: Adds one dynamic spec field to the category. **Input:**

Field	Required	Notes
key	yes	max 60. Lowercase snake_case only (^[a-z][a-z0-9_]*\$, e.g. fuel_type) — it becomes a GET /ads query param. Must be unique within the category, and can't be one of the feed's own params: category_id, governorate_id, city_id, min_price, max_price, q, page, sort, lat, lng.
label_ar	yes	max 100
label_en	no	max 100
type	yes	one of text number boolean select multiselect
options	for select / multiselect	array of at least one distinct string (max 100 each). Ignored (stored as null) for the other types.
is_required	no	bool, defaults to false
is_filterable	no	bool, defaults to true — whether it's usable as a GET /ads query filter

Output — 201: the stored CategoryAttribute row as JSON, defaults included (not wrapped in {"data": ...}) — this one endpoint returns the model directly):

```
{
  "id": 1, "category_id": 1, "key": "material", "label_ar": "الخامة", "label_en": null,
  "type": "select", "options": ["معدن", "خشب"], "is_required": false, "is_filterable": true,
  "sort_order": 0, "created_at": "...", "updated_at": "..."
}
```

Errors (all 422, standard validation shape):

Problem	Field	Message
key already used in this category	key	هذا المفتاح مستخدم مسبقًا في هذه الفئة.
key not lowercase snake_case	key	المفتاح يجب أن يكون بأحرف إنجليزية صغيرة (مثل fuel_type) وأرقام و _ فقط، ويبدأ بحرف.
key is a reserved feed param	key	هذا المفتاح محجوز لفلاتر البحث العامة، اختر اسمًا آخر.
select / multiselect with no options	options	أدخل خيارًا واحدًا على الأقل لحقل الاختيار.
the same option twice	options.0, options.1, ...	الخيارات يجب ألا تتكرر.

Admin ► Users

GET /admin/users?q=

Does: Search/list users by name or phone (q optional — omit for the full paginated list). **Output — 200:** paginated `UserResource` collection (30/page).

POST /admin/users/{id}/ban

Does: Sets `is_banned = true`, immediately revokes every one of the user's existing Sanctum tokens (so a banned user is logged out everywhere right away, not just blocked from their next login), and deletes their push device tokens (so they stop receiving pushes). Admins can't ban other admins (including themselves) — there's no way to un-admin someone through this endpoint. **Output — 200:** the updated `UserResource` (`is_banned: true`). **Errors:** 422 {"message": "لا يمكن حظر مستخدم يمتلك صلاحيات إدارية"} if {id} has the `admin` role.

POST /admin/users/{id}/unban

Output — 200: the updated `UserResource` (`is_banned: false`).

Admin ► Ads

GET /admin/ads?status=

Does: The moderation queue. `status` optional — filters to `pending` / `approved` / `rejected` /etc., or omit for everything. **Output — 200:** paginated `AdResource` collection (30/page), each including `user` and `category`.

POST /admin/ads/{id}/approve

Does: `pending` → `approved`: stamps `published_at` / `reviewed_by` / `reviewed_at`, and **notifies the owner** (`type: "ad_approved"`, plus a push). Only a pending ad can be approved: a sold/expired ad comes back through relist, a rejected one through an owner edit — both put it back to `pending` first. The status check is atomic, so a double-click or a second admin can't approve (and notify) twice. **Output — 200**: the updated `AdResource` (`status: "approved"`). **Errors:** 422 {`"message": "يمكن الموافقة فقط على إعلان"`} if the ad isn't `pending`.

POST /admin/ads/{id}/reject

Does: `pending` or `approved` → `rejected`: stores the reason, stamps `reviewed_by` / `reviewed_at`, and **notifies the owner** (`type: "ad_rejected"`, plus a push). Rejecting an `approved` ad is how a live ad gets taken down, e.g. after a report. Atomic like approve. **Input:** {`"reason": "..."`} (required, max 500). **Output — 200**: the updated `AdResource` (`status: "rejected"`). **Errors:**

- 422 validation error if `reason` is missing.
- 422 {`"message": "يمكن رفض الإعلانات بانتظار المراجعة أو المنشورة فقط"`} if the ad is already `rejected`, or is `sold` / `expired`.

Admin ► Reports

Resolving or dismissing is only a triage marker — it never bans anyone or unlists anything. Follow up with `POST /admin/users/{id}/ban` or `POST /admin/ads/{id}/reject`.

GET /admin/reports?status=

Does: The report queue, newest first. `status` optional — `pending` / `resolved` / `dismissed`, or omit for everything. **Output — 200**: paginated (30/page) `ReportResource` collection:

```
{
  "id": 2, "reason": "scam", "details": "يطلب تحويلاً مسبقاً", "status": "pending",
  "reporter": { ...UserResource },
  "reportable_type": "ad",
  "reportable": { ...AdResource },
  "created_at": "...", "reviewed_at": null
}
```

`reportable_type` is `ad` or `user`; `reportable` is then an `AdResource` or a `UserResource`.

POST /admin/reports/{id}/resolve / **POST /admin/reports/{id}/dismiss**

Does: Sets `status` to `resolved` / `dismissed` and stamps `reviewed_at`. **Output — 200**: the updated `ReportResource` (without `reporter` / `reportable`).