Wearable Health Agent

An Agentic AI System for Differential Triage of Physiological Deviation Using Wearable Data

October 2026

Github Link for the Code - https://github.com/NatBrian/wearable-health-agent/tree/main

Abstract

Wearable Health Agent (WHA) is an agentic early-warning system for consumer smartwatch data. A wrist sensor can tell that a person's overnight resting heart rate has risen. It cannot tell why. An infection, a glass of wine, a late workout, a short night, stress, a vaccine, or the luteal phase of the menstrual cycle all look almost the same to an optical sensor, and they call for opposite responses. WHA separates the two jobs. A cheap, always-on monitor uses ordinary statistics and no AI at all to decide whether a night is worth explaining. Only when two consecutive nights are clearly raised does a bounded AI agent wake up, gather evidence through a closed set of read-only tools, update an exact Bayesian belief over twelve possible causes, and decide by arithmetic, not by the language model, whether asking the person one question is worth the interruption.

The language model is used for four narrow jobs: choosing which read-only tool to call, wording a question, drafting a short source-grounded explanation, and giving a second opinion on free-text symptoms. It never decides to interrupt, never chooses a disposition, and can never lower urgency. A deterministic safety floor reads what the person types before any model does, and every claim shown to the person must quote a passage that the system actually retrieved. Every step is written to a SHA-256 hash-chained audit log. This report describes the problem, the design, the safety and governance controls, the prototype, and what we measured. It also states plainly what we did not and could not measure: WHA has never been tested on a patient and is not a medical device.

1. Introduction, Problem and Background

1.1 Overview of the Problem Domain

Smartwatches now record heart rate every minute, sleep stages, steps and workouts for millions of people. The commercial products built on this data mostly stop at detection: they report that a metric moved. For overnight resting heart rate (RHR) this is a real signal. Alavi et al. (2022) showed in Nature Medicine that a rise in nocturnal RHR above a person's own baseline can appear days before symptoms of a viral illness. The signal is useful and it is also deeply ambiguous.

A resting heart rate 3.5 bpm above a person's own normal might mean an infection is incubating. It might equally mean they drank wine with dinner, trained hard at 9pm, slept badly, had a stressful day, were vaccinated on Tuesday, or are in the luteal phase of the menstrual cycle. To the sensor these look nearly identical, yet the right response differs. Telling a healthy person who had two glasses of wine that they may be ill creates worry. Telling an incubating person that everything is fine delays care.

1.2 Problem Statement

Given a stream of overnight physiological readings from a consumer wearable, decide (a) whether a night is unusual for this person, (b) which of several confounded causes best explains it, (c) whether it is worth interrupting the person to ask a clarifying question, and (d) what to say and when to tell the person to seek care, without ever letting a language model be the last line of defence on safety.

Table 1: Why a raised overnight heart rate is ambiguous. Typical effect sizes and base rates are the values used by the belief model (data/knowledge/causes.yaml, via docs/ARCHITECTURE.md Part 8).

Cause	How often present on any night	Typical rise in heart rate
Infection	3.8%	1.60 bpm
Alcohol	29.9%	2.60 bpm
Unrecorded exertion	8.0%	2.91 bpm

Cause	How often present on any night	Typical rise in heart rate
Short or broken sleep	34.8%	1.00 bpm
Acute stress	35.0%	1.50 bpm
Luteal phase	45.0%	3.91 bpm
Vaccine reaction	2.2%	1.52 bpm

The table shows the core difficulty. The cause the system exists to find, infection, is among the rarest and is smaller than alcohol, evening exercise and the menstrual cycle. This is not an error in the table. It is the actual clinical problem, and it is why the system asks questions: the sensor cannot separate these causes, but a person often can.

1.3 Relevance and Motivation

- Detection without attribution creates alarm fatigue. A review cited in the repository found that 72% to 99% of alarms from ICU bedside monitors are false or non-actionable. A phone notification that fires on every raised night repeats that failure in a home setting.
- Language models are not a safe last line. Draelos et al. (2025) red-teamed four frontier chatbots over 222 patient-posed questions and found 5% to 13% of answers outright unsafe. A health assistant that lets the model decide urgency inherits that risk.
- Symptom checkers under-ask. Sutaria et al. (2025) measured online symptom checkers seeking 36.9% of relevant red-flag symptoms against 71.8% for physicians. A system that elicits the right items before it routes is closer to what a clinician does.
- Normal differs enormously between people. A study of 92,457 wearable users found individual normal resting heart rates differ from one another by nearly 70 bpm. Any useful detector must compare a person with themselves.

1.4 Objectives

1. Detect cheaply and quietly. Flag a night only when it is clearly raised against the person's own baseline on two consecutive nights, using closed-form statistics on local CPU with zero model calls.
2. Attribute, do not just alert. Maintain an exact probability for each of twelve causes and show what evidence moved it.
3. Interrupt only when it is worth it. Decide whether to ask a question by Expected Value of Sample Information (EVSI) against a fixed cost of interrupting, with a weekly budget.
4. Ground every clinical claim. Allow the model to state clinical content only if it can quote, word for word, a passage from a retrieved source.
5. Keep safety deterministic. Provide a rule-based floor that reads the person's own words over time and can only raise urgency.
6. Be auditable and honest. Record every step in a tamper-evident log, and disclose every limitation next to the screen it affects.

1.5 Users and Stakeholders

Table 2: Users and stakeholders of WHA.

Stakeholder	Role	What they need from the system
Wearable owner (primary user)	Wears a Samsung Galaxy Watch 5 to bed; answers questions on Telegram or the dashboard	A quiet system that speaks rarely, asks one useful question, and says plainly when to seek care
Clinician (secondary)	Receives a copied summary when the person chooses to share one	A short, sourced summary with the night, the baseline and the symptom timeline
Reviewer or maintainer	Approves, edits, rejects or escalates a drafted outcome; reads the audit log	Every step, tool call, model identifier and decision recorded and exportable
Course assessors and developers	Evaluate and extend the system	A readable architecture, enforced contracts and honest disclosure of limits

The prototype is built around a single owner. Its default time zone is Asia/Singapore, which matters for illness scope: the repository records a deliberate decision not to hold guidance about specific illnesses, including dengue, which is common locally (Section 5.2).

1.6 Prior Work and Positioning

WHA builds on four lines of published work and takes a position on each.

Table 3: Prior work and how WHA uses it.

Source	What it established	How WHA uses it
Alavi et al. 2022, Nature Medicine (NightSignal)	Alerting on two consecutive nights of nocturnal RHR at or above baseline plus 4 bpm detects viral illness early; baseline usable after about seven nights	Detection thresholds of 3 bpm (YELLOW) and 4 bpm (RED), two-night persistence, seven-night minimum. WHA deviates on window, nightly statistic and baseline, and discloses each change
Mishra et al. 2020, Nature Biomedical Engineering	Public minute-level Fitbit data for 120 people with symptom-onset dates for COVID-19 cases	The only labelled cohort we replay the detector over (Section 4.6)
Bosner et al. 2010, CMAJ (Marburg Heart Score)	Five-item rule for chest pain in primary care; at a cut-off of 3, sensitivity 87.1% and specificity 80.8% across 1,199 patients	Chest pain opens a five-question conversation and the published rule, not the model, sets urgency
Tu et al. 2025, Nature (AMIE)	A conversational diagnostic agent reaches an accurate differential within about ten turns	Conversation length is capped at 10 turns

Source	What it established	How WHA uses it
Draelos et al. 2025; Sutaria et al. 2025	Frontier chatbots give unsafe answers 5% to 13% of the time; symptom checkers under-ask red flags	Deterministic safety floor, set-union with the model, verbatim grounding

Position. Existing detection work answers whether a night is abnormal. WHA adds the missing step: working out why, deciding whether a question is worth asking, and doing so inside controls that keep the language model away from the decisions that matter most. It does not claim better detection than NightSignal. Our own replay shows it matches the published algorithm rather than beating it (Section 4.6).

1.7 Scope and Non-Goals

- In scope: nocturnal resting heart rate raised above the person's own baseline; confounder attribution over twelve causes; one-question interruption policy; free-text symptom conversation; safety escalation; audit.
- Out of scope by design: a lowered heart rate (usually fitness or good rest), sleep apnoea, diagnosing any named illness, and any clinical validation. The repository states that the system has never been tested on a patient, no clinical trial stands behind it, and it is a two-week student project. It is not a medical device and does not diagnose.

2. Agentic Solution and System Design

2.1 Design Principle: A Bounded Investigator Inside a Deterministic Frame

WHA is two machines with a hard boundary between them. The first runs every night and is plain arithmetic: given the same nights it produces the same answer forever, works when the internet does not, and costs nothing. The second is a language-model agent that runs only once a night is flagged, inside a small fenced loop with fixed step and tool limits. A third component, the safety floor, sits in front of both and can only raise urgency.

We chose this shape because the failure modes differ. Statistics are cheap and predictable but cannot look anything up, word a question or read a free-text answer. A language model can do those things but can invent facts and cannot be trusted with urgency. Putting each tool where its weakness matters least gives an agent that is genuinely agentic, because it chooses which tools to call and in what order based on what earlier calls returned, while its autonomy stays narrow. It cannot decide to interrupt, cannot write to the person's record, cannot choose a disposition and cannot lower urgency. Those are arithmetic.

2.2 Architecture Overview

PHONE AND WATCH Galaxy Watch 5 > Health Connect > bridge app (HTTP JSON)
DETERMINISTIC HALF (no AI, every night) 1 Ingest > 2 Sleep window > 3 Features (median HR) > 4 Baseline (own 28-night median) > 5 Subtract recorded workout > 6 Detect GREEN / YELLOW / RED, flag on two consecutive RED nights
AGENTIC HALF (only when a night is flagged) Episode opens > preload (5 fixed reads) > investigate (model picks tools) > believe (Bayes, 12 causes, 4,096 states) > decide (EVSI) > ask / observe / conclude > critique > human review
SAFETY FLOOR (runs first on anything the person types, can only raise urgency) Tier A phrases + Tier B over time + Tier C model second opinion, combined by set union > Marburg Heart Score for chest pain

DELIVERY
FastAPI on 127.0.0.1:8500 > React + Vite dashboard on 8443 | Telegram bot with buttons | SHA-256 hash-chained audit log

Figure 1: WHA architecture: a deterministic nightly half, a bounded agentic half, and a safety floor in front of everything the person types.

Table 4: Main components and where they live in the repository (src/wha/).

Component	Module	Responsibility
Ingest and storage	ingest/, db/	Pull JSON from the phone bridge, normalise, store raw payloads untouched in SQLite
Sleep window and features	features/	Find the sleep the watch recorded, drop waking spells, take the median HR, measure coverage
Baseline and detection	detect/	Personal baseline with shrinkage; GREEN / YELLOW / RED; two-night persistence
Belief	belief/	Exact Bayesian update over 12 causes, 4,096 states, in log space
Policy	policy/	EVSI scoring of eight probes, interruption gates and budget
Agent	agent/	LangGraph state graph, eight nodes, tool registry, conversation engine
LLM client	llm/	Provider-neutral client, versioned prompts, schema validation and repair
Retrieval and grounding	retrieve/	Four-layer local corpus, hybrid search, verbatim span check
Safety	safety/	Red-flag rules, Tier C, Marburg triage, injection scan, outbound checks
Audit	audit/, db/audit_chain.py	Append-only hash-chained event log
Delivery	api/, notify/, frontend/	HTTP API, Telegram notifier, React dashboard
Evaluation	eval/, experiments/	Policy simulation, adversarial suite, cohort detection replay

2.3 Platform and Technology Choices

Table 5: Platform and key dependencies (pyproject.toml, config.py, README).

Layer	Choice	Why this choice
Language and packaging	Python 3.12 with uv; Pydantic v2 models	Every boundary is a typed model, so malformed model output fails validation instead of flowing on
Agent runtime	LangGraph 1.x with SqliteSaver checkpointer	Named steps with explicit routing and durable pause/resume: an episode can wait days for an answer and resume exactly where it stopped
State	SQLite (one file)	Local, inspectable, and the checkpoints live beside the data, so deleting the database removes the agent's memory of the subject too
Scheduler	APScheduler	Ingest every 30 minutes; nightly scoring on a repeating interval; episode and timeout tick every 15 minutes
Retrieval	rank-bm25 + BAAI/bge-small-en-v1.5 via sentence-transformers, fused by RRF	Keyword and meaning search together; small embedding model runs locally
API and UI	FastAPI; React + Vite + TypeScript	Thin HTTP boundary with explicit CORS origins (wildcards are rejected at startup)
Messaging	Telegram bot with inline buttons	One-tap answers on the device the person already carries
Model	OpenAI-compatible chat endpoint, default model deepseek-v3.2; native Ollama and a recorded cassette client also supported	Provider is a configuration value, not a dependency; the cassette client replays recorded responses so scenarios and tests are repeatable

2.4 The Perceive, Reason, Act Loop

Each episode follows a perceive, reason, act cycle. The table maps every phase to the code that implements it and says whether a model is involved.

Table 6: Perceive, reason, act mapping.

Phase	What happens	Implemented by	Model involved?
Perceive	Read the watch, find the sleep window, compute the night's median HR, compare with the personal baseline, read what the person typed	ingest/, features/, detect/, safety/	No (Tier C second opinion on free text only)

Phase	What happens	Implemented by	Model involved?
Perceive (agent)	Preload five fixed reads, then choose further tool calls	nodes/preload.py, nodes/investigate.py	Yes, tool choice only
Reason	Update the belief over 12 causes; score probes by EVSI; apply gates	belief/, policy/	No
Reason (language)	Word the question; veto a redundant one; draft the outcome	nodes/ask.py, decide.py, conclude.py	Yes, bounded
Act	Ask on Telegram or the dashboard, request a hand pulse, conclude, escalate, record	nodes/ask.py, conclude.py, review.py, notify/	Only wording
Learn from the answer	Answer re-enters investigate, so the agent looks up what the answer means before concluding	graph.py route_after_ask	Yes

2.5 Perception: From a Wrist to One Number

Ingest. The Galaxy Watch 5 writes to Health Connect on Android. A small bridge app serves that over HTTP and WHA reads GET /?days=N. The watch supplies heart rate, steps, sleep sessions with stages, exercise, oxygen saturation, distance and calories. Heart-rate variability, respiratory rate and skin temperature are not provided by this device. Raw payloads are stored untouched. The status strip turns amber when data is 36 hours old, and the nightly batch refuses to score on data older than 72 hours rather than guess.

Sleep window. Instead of assuming midnight to 7am, WHA uses the sleep the watch actually recorded and removes waking spells inside it. If no sleep was recorded it falls back to a clock window and the night says so. At least 180 minutes of contact are required; otherwise the night is marked unusable rather than guessed at. Readings outside 25 to 220 bpm are dropped as sensor error.

Night value and baseline. The night is reduced to the median heart rate over that window. The median, not the mean, so one bad stretch cannot drag it. The baseline is the person's own median over the trailing 28 usable nights, excluding tonight. Until seven nights exist the baseline leans on a population figure (62.75 bpm, spread 8.64, from 525 first-year university students) and nothing can be flagged. The baseline moves through five rungs (COLD 0 to 2 nights, PRIOR_DOMINATED 3 to 6, SHRINKING 7 to 13, PERSONAL 14 to 27, MATURE 28 or more), and the dashboard says which rung applies.

Detection. A recorded workout in the previous six hours is subtracted first. The residual is then compared with fixed thresholds: below 3 bpm GREEN, 3 to under 4 YELLOW, 4 or more RED. An investigation opens only on two consecutive RED nights. A single RED night is recorded and nothing is said. This is the published NightSignal rule. A looser version (two raised nights, at least one RED) was measured, found to buy 6.7 points of sensitivity for 37% more investigations on people who were not ill, and rejected.

2.6 Reasoning: Belief and Policy

Bayesian belief over twelve causes. The causes are infection, alcohol, unrecorded exertion, short or broken sleep, acute stress, luteal phase, vaccine reaction, travel, medication change, recovery from an earlier illness, sensor artefact, and none of the above. Causes can combine, since a person can have a drink and be coming down with something, so the model does not pick one label. It enumerates all 2 to the power 12 = 4,096 on-off combinations and scores each exactly, in log space so that products of small probabilities do not round to zero. Each cause carries a temporal profile across nights: alcohol contributes fully on night one and is gone by night two, infection rises over about three nights and fades over a week, the luteal phase is flat for

about twelve days. A single night cannot tell alcohol from early infection. The shape across several nights can. A first-class none-of-the-above cause lets the episode close as UNRESOLVED, an honest outcome rather than a forced guess.

Table 7: Reference belief update from the design document (simulated subject, two consecutive nights at +5.0 bpm, 5 September 2026). One answer moved p(infection) from 7.6% to 40.5%.

Cause	Before any question	After the answer "feverish or chills"
Acute stress	0.8147	0.7769
Alcohol	0.5536	0.5408
Short sleep	0.4813	0.4752
Infection	0.0756	0.4051
Sensor artefact	0.0915	0.0759
Luteal phase	0.0	0.0

EVSI policy. Before asking, the system works out what it would do now, then for each possible answer what it would do and how much better off the person would be, weighted by how likely each answer is. The difference is the Expected Value of Sample Information. The utilities encode that a missed illness is nine times worse than a false alarm (-9.0 against -1.0), so the decision threshold falls out as $1 / (1 + 9) = 0.10$, which coincides with the classic threshold of Pauker and Kassirer (1980). Each of eight probes (symptoms, alcohol, exertion, sleep quality, stress, vaccination, travel, and a hand pulse measurement) is scored as EVSI minus 0.15 times its interruption cost. The best probe is asked only if its score is positive and every gate is clear.

Table 8: Gates that can stop a question even when EVSI is positive (src/wha/constants.py, policy/gates.py).

Gate	Value	Purpose
Unsolicited questions per week	2	Alarm-fatigue budget
Questions per episode	5	Bound one investigation
Question already pending	1	Never stack questions
Baseline too immature	COLD rung	Do not ask about a night judged against a borrowed baseline
Symptom follow-ups per episode	3	A rule, not EVSI: a reported symptom that has not been said to settle gets a follow-up even when EVSI is zero

The follow-up rule exists because EVSI has a blind spot. Once a cause is settled, another answer cannot change which cause the system believes in, so EVSI is zero by construction. The more confident the system became that someone was ill, the less reason it had to speak to them. A separate rule forces a follow-up while a reported symptom has not been said to settle. It can bypass the weekly budget but never a pending question or its own per-episode cap.

2.7 The Agent Graph



	5 fixed reads, no model	model picks tools, max 25 calls	exact Bayes, no model	EVSI + gates (model may only veto)
ASK > ask model words it, graph pauses (interrupt)	answer arrives > back to investigate	OBSERVE > park until next night	CONCLUDE or ESCALATE > conclude draft, strip unsupported claims	critique > review model may only remove; person approves, edits, rejects or escalates

Figure 2: The LangGraph episode graph (src/wha/agent/graph.py). Bold decisions are arithmetic; investigate, ask, conclude and critique are the only nodes that call a model.

preload makes five fixed tool calls with no model: recent nights, baseline, recorded events, data quality, and past investigations. The model starts with facts instead of spending turns fetching them. investigate hands the model a catalogue of tools with exact argument names and loops: call a tool, see the result, decide whether to call another or stop, bounded at 25 calls. believe and decide are arithmetic. If the policy chooses to ask, a model may veto the proposed question as redundant. The veto can only cancel a question, never create one. ask has the model write the sentence, then the graph pauses with LangGraph interrupt(). State is saved to SQLite, the process can exit, and hours or days later the answer arrives over Telegram or the dashboard and the graph resumes from exactly where it stopped. conclude drafts a disposition, a ranked differential and prose in which every clinical claim must carry a verbatim supporting span. critique is a second pass that may only remove content; if it returns longer text than it received, the longer text is discarded. review pauses for a human decision.

The edge from ask back to investigate is what makes the loop hypothesis-driven. Before it existed, evidence was gathered once, before the person had said anything, and retrieve_clinical_evidence fired zero times in 145 tool calls. The graph also routes a safety escalation straight to the outcome so that an answer that trips the floor is never handed to the belief model or the policy.

2.8 Tools and Their Scope

Table 9: The closed tool registry (src/wha/agent/tools/registry.py). All tools are read-only.

Tool	Arguments	Returns
get_nightly_features	start, end	Nightly readings, coverage and sleep hours in a range
get_personal_baseline	night_date	Personal centre and band on a night, and how mature it is
get_known_events	start, end	Workouts, steps, blood oxygen and other recorded context
get_data_quality	start, end	Coverage minutes and implausible readings dropped, for judging sensor artefact
find_similar_past_episodes	none	This person's earlier investigations and how they ended
retrieve_clinical_evidence	query, optional layer	Passages from the local clinical corpus

The registry is closed: a fixed set of names checked in code, where anything not on the list is refused and the refusal is written to the audit log. Every result carries a common shape with tool name, arguments, status, source identifiers, timestamp and freshness. The tool catalogue shown to the model spells out each argument name, because an earlier run recorded the model

calling retrieve_clinical_evidence with a symptom argument against a handler that reads query, which returned nothing and left the episode with no citations.

2.9 Memory

Table 10: What the system remembers and where.

Memory	Content	Lifetime and use
Raw and normalised readings	Watch payloads and derived nightly features	Persistent; the evidence behind every night
Baselines	Personal centre, scale and rung per night	Persistent; recomputed as nights accumulate
Episode state	Graph state checkpointed after every step (SqliteSaver)	Durable across restarts; lets an episode wait days for an answer
Episodes and outcomes	Disposition, differential, questions asked and answers	Read back by find_similar_past_episodes; a recurrence within 7 days links to the same illness
Symptom timeline	One row per symptom per night, rebuilt from stored conversation turns	Lets persistence and co-occurrence rules be computed; nothing new is collected
Conversation turns	Multi-turn chat with citations and urgency	Urgency is read back from the stored transcript so a restart cannot lose an escalation
Audit chain	Every step, tool call, prompt version, model identifier and human decision	Append-only and hash-chained

2.10 Model Choice and Justification

The model is deliberately the least important part of the safety argument, so the choice is driven by structured-output reliability, cost and swappability rather than by clinical knowledge. The default is deepseek-v3.2 behind an OpenAI-compatible chat endpoint. The client requests a JSON object response and validates it against a Pydantic schema; on failure it makes exactly one repair attempt and then raises a validation error instead of passing malformed output on. The timeout is 120 seconds. Prompts that must be repeatable (investigation, extraction, red-flag check, critique) run at temperature 0.0; prompts that write sentences for a person (question wording, outcome prose) run at 0.3. A native Ollama client and a recorded cassette client share the same interface, so the system can run offline for scenarios and tests.

Three properties of the design make a modest model acceptable. First, the model never makes the decision to interrupt, the disposition or the urgency. Second, its output is checked by code (schemas, verbatim spans, set union with rules). Third, if the model is unavailable the deterministic half still runs and flags the night, and the conversation falls back to fixed rules, which the demo film shows in a dedicated model-outage scene. The repository does not record a head-to-head comparison of candidate models, so we state the choice as an engineering judgement, not a benchmark result.

2.11 Prompt as Specification and Machine-Checkable Outputs

Prompts are typed objects, not strings. Each PromptDefinition carries an identifier, a version, a temperature, an instruction, a context template, an output schema, constraints, examples and refusal conditions. There are eleven: investigate, write_question, veto_check, write_outcome, critique, converse, extract_rule_items, extract_facts, red_flag_check, answer_about_episode and interview_followup. The version is recorded with every call, so an audit row names the exact prompt that produced an output.

Prompts are written as specifications that fail closed. For example, write_outcome (version 3) requires the output {observation, claims[{text, evidence_span}], action_text} and states that evidence_span must be copied character for character from a retrieved passage because it is checked by exact containment in code, so a paraphrase fails and the claim is discarded. Version 3 removed the model-written when-to-seek-care text after a live run produced advice with two invented thresholds; that text is now selected from a fixed list in red_flags.yaml. The investigate prompt tells the model not to repeat a call with the same arguments, and the prompt is re-rendered every turn so the model can see the result it just received. Before that fix the model asked for the same tool 101 times in a row.

2.12 RAG Grounding

Table 11: The four-layer retrieval corpus (1,849 chunks in total).

Layer	Content	Source	Size
1	General consumer health information about a condition	MedlinePlus (US National Library of Medicine), snapshot 2026-09-03	1,013 English topics
2	How a night is measured and what counts as raised	Generated from constants.py; numbers interpolated, not retyped	3 documents
3	When to seek care	Generated from red_flags.yaml	9 documents
4	Evidence behind each competing explanation	Generated from causes.yaml	12 documents

Retrieval is hybrid: BM25 keyword search and bge-small-en-v1.5 embeddings are fused by reciprocal rank fusion ($k = 60$), with chunks of about 400 tokens and the top 8 returned. A test asserts that the system's own safety rules still surface in the top six for the query chest pain, because adding a thousand fetched topics could bury them.

Grounding by verbatim containment. The model is not asked whether a claim is grounded, since that is the same judgement it is already making. It must return, for each claim, a span it says supports the claim. Plain code then checks that the span appears word for word in one of the retrieved passages after collapsing whitespace and folding case. If found, the claim survives and the citation attached is the passage the span was actually found in, chosen by code and not by whichever source the model named. If not found or not given, the claim is stripped before the person sees it and counted.

What this proves and what it does not. It checks the quoted span, not the sentence built around it. A reply can contain a verified quote and still misdescribe it. The repository records a live case on 5 September 2026 where a reply described the baseline as an average when the cited passage said median. The dashboard therefore labels uncited content as such, and the limitation is disclosed rather than hidden (Section 5.2).

3. Workflow, Safety and Governance

3.1 Human Oversight and Interaction Design

The person is a participant in the loop, not a recipient of its output. Three design choices follow from that.

- One question, one tap. Questions have a fixed answer set (for example Nothing unusual, Throat or nose, Feverish or chills, Aches or heavy limbs, Something else) shown as Telegram inline buttons or dashboard options. Callback data is limited to 64 bytes and outbound text to 900 characters.
- Silence is a valid answer. A question not answered within 36 hours (24 hours for a requested hand-pulse measurement) leaves the episode UNRESOLVED, not benign. Premature closure is treated as a risk, not a default.
- A person can overrule the system. Before a drafted outcome becomes final, the episode is parked in AWAITING_HUMAN_REVIEW and the review node pauses for approve, edit, reject or escalate. The API exposes this as POST /episodes/{id}/review. The scheduler no longer supplies a decision of its own; a review that times out is recorded as closed without a person having looked, and the record says so.

An earlier build had a serious defect here. A background job answered approve on the person's behalf about fifteen minutes after the pause and the record then said a human had approved it. The design document recorded it as found by running the system, and the current review node documents the fix: a person must reach the screen, and a decision that never happened is never written down as if it did.

3.2 Escalation Flow

What the person types	TIER A phrase list chest pain, fainted, confusion, cannot breathe, bleeding, stiff neck with fever	TIER B phrase list fever, aches, exhaustion, vomiting, cannot eat	TIER C model reads the same text and may add flags
SET UNION in code: the model can add, never remove	Tier A with a validated rule (chest pain): open Marburg conversation, rule sets urgency	Tier A with no rule: ESCALATE now	Two or more Tier B, or one that persists past its own number of nights: see a doctor today

Figure 3: Escalation flow for anything the person types. Rules run before the model; the model may add flags and can never remove one.

Tier A is one phrase and urgent now. Tier B is two co-occurring symptoms within two nights of each other, or one symptom that persists past its own persist_nights value. Tracked symptoms such as dizziness are recorded and asked about but escalate on nothing, because assigning a tier would assert a routing threshold that no source supports. Tier C lets a model read the same text and add a flag, which catches wording the literal lists miss (the repository records it catching I cannot keep any water down, which the lists do not contain). The negation guard suppresses a match when no or not appears within four words, but stops at a comma or at but, so no fever, but chest pain denies the fever and escalates the chest pain.

Symptoms are read over time. An earlier version accepted a symptom history that no production caller passed, so the persistence branch never fired for any symptom and five nights of a worsening fever produced five refusals to escalate. The symptom_observations table now records one row per symptom per night, rebuilt from conversation text already stored. No threshold changed. They simply began to be read.

Chest pain is assessed, not matched. A match on chest pain used to route straight to an ambulance. It now opens a conversation that seeks the five Marburg items (age and sex, known vascular disease, pain worse with exercise, pain not reproducible by pressing the chest wall, the person believes it is cardiac). A score of 0 to 2 means see a doctor today, 3 or more means urgent. The model elicits the items in whatever words the person uses, a second zero-temperature model call extracts them, and the rule decides. If the rule cannot be completed within three replies the presentation resolves as urgent, stated as the cautious direction.

Urgency only rises. It is read back from the stored transcript so a restart cannot lose an escalation and quietly start again from calm. Blood oxygen can raise urgency but never lowers it.

3.3 Boundaries and Stop Conditions

Table 12: Hard limits that stop or bound the agent (src/wha/constants.py).

Limit	Value	What it prevents
Tool calls per episode	25	Runaway investigation loop
Graph steps per episode	40 (recursion cap)	Infinite graph traversal
Nights per episode	10	An episode that never closes
Questions per episode / unsolicited per week	5 / 2	Interruption and alarm fatigue
Symptom follow-ups per episode	3	A follow-up becoming a nightly alarm
Answer / measurement / review timeout	36 h / 24 h / 36 h	A paused episode waiting forever
Conversation turns	10	Open-ended chat
Replies to complete a triage rule	3, then escalate	Leaving a person in limbo
LLM timeout and repair attempts	120 s, one repair	A hung or malformed model call
Tool date range	90 days, never in the future	Over-broad reads
Outbound message	900 characters, six checks	Unsafe or malformed delivery

Stop conditions are explicit. The graph ends when the policy chooses OBSERVE (park until another night), when it concludes, when it escalates, or when a timeout resolves the episode as UNRESOLVED. When the tool budget is spent the answer goes directly to believe rather than spending a model round trip to learn that no tool will run.

3.4 Auditability

Every stage writes an AuditEvent with actor, operation, input, tool arguments and result (truncated visibly at 500 characters), sources, model identifier, prompt version, token usage, latency, control tier, permission decision and any human decision with rationale. Rows are hash-chained: each hash is SHA-256 of the previous hash concatenated with the canonical JSON (sorted keys, no whitespace) of the row. Editing or deleting any row changes every later hash, and verify_chain reports where the chain breaks. The API exposes GET /subjects/{id}/audit and an export endpoint, and the dashboard shows the record for every night, not only investigated ones, as 21 numbered steps coloured by which part of the system ran them.

3.5 Accountability

Table 13: Who or what decides each thing.

Decision	Decided by	Can the model change it?
Is a night unusual?	Arithmetic (detector)	No
Which cause is likely?	Arithmetic (Bayesian belief)	No

Decision	Decided by	Can the model change it?
Ask, observe or conclude?	Arithmetic (EVSI and gates)	May only veto a question as redundant
How is the question worded?	Model	Yes, checked by outbound validation
What clinical claims are shown?	Model proposes, code verifies verbatim span	Cannot show an unsupported claim
Does the person see care advice?	Fixed list selected from red_flags.yaml	No
Urgency level	Rules, set union with Tier C	May raise, never lower
Is the outcome final?	A person (review node)	No
What happened and why?	Hash-chained audit log	No

Accountability also lives in documents that tests enforce. Three files are obligations: KNOWLEDGE-CHANGELOG.md (any change to a clinical figure), DISCLOSURES.md (every limitation, naming the screen that shows it) and CONTRACTS.md (compared with the code by four tests on every run). Every number in the clinical tables carries a provenance of CITED, DERIVED or ASSUMED. The repository discloses that 45 of the 57 temporal profile weights have no source, that the likelihood behind every question is assumed, and that the clinical tables were generated by a language model and then given provenance labels, not written by a clinician.

3.6 Tool Access Scope and Least Privilege

- Read-only, closed registry. Six tools, no write tool, no web access, no tool outside the list. Registration of a name outside the closed set raises PermissionDenied.
- Subject isolation. The registry strips any subject identifier the model supplies and substitutes the one the episode was opened for. The model cannot read another person's data.
- Clamped arguments. Date ranges are limited to 90 days and to not in the future.
- Control tiers. Each audited event carries a control tier and a permission decision.
- Outbound validation. Six safety checks on every outgoing message, including length, unauthorised URLs, and markup or control characters. Failure falls back to canned text or parks the episode.
- Network surface. The API binds to 127.0.0.1; dashboard origins must be explicit and wildcards are rejected at startup; secret fields are write-only in Settings; deletion is permitted only for disposable sim and demo subjects.

3.7 Anticipated Failure Modes and Mitigations

Table 14: Threat analysis: what could go wrong, what the code does about it, and what remains.

Risk	Mitigation in code	Residual risk
Hallucination	Verbatim span containment strips unsupported claims; care advice comes from a fixed list; critique may only remove; uncited content is labelled	A verified quote can sit inside a sentence that misdescribes it (disclosed)
Prompt injection	scan_untrusted checks text for override patterns; content continues to flow as data and the event injection_contained is recorded; the model has no	Pattern list is finite; wording outside it relies on the structural limits above

Risk	Mitigation in code	Residual risk
	write tool; outbound validation blocks URLs; an adversarial suite of 15 cases (wha eval adversarial); the poisoned corpus fixture INJ-001	
Over-permissioning	Closed read-only registry, subject stripping, clamped ranges, no web, no write path to the record, human review before finalisation	The notifier and API are trusted components
Alarm fatigue	EVSI cost, 2 per week budget, 5 per episode, quiet band, two-night RED rule	The budget has never bound in simulation, so its effect is unmeasured with a real person
Premature reassurance	Normal heart rate does not close an episode while a reported symptom is outstanding; an unanswered question is UNRESOLVED	Scope excludes named illnesses; a WHO dengue warning-sign presentation may be under-triaged (disclosed)
Model outage	Deterministic half needs no model; conversation falls back to fixed rules	Reduced wording quality only
Data quality	Coverage floor, plausibility bounds, non-wear nights marked NA and never interpolated, stale-data refusal	Single device and single wearer
Silent drift of safety rules	Contracts and disclosure tests fail when code and documents disagree	Tests prove consistency, not clinical correctness

3.8 Regulatory and Ethical Stance

WHA states on its first screen and in DISCLAIMER.md that it is not a medical device and does not diagnose. Every limitation is disclosed next to the screen it affects, not in a footnote, and the demo film gives limitations three whole chapters, with the measurements behind them. We think this matters more than any single accuracy figure: the honest answer to whether it finds illness in real use is that it is not known.

4. Prototype, Demo and Evaluation

4.1 Prototype Overview

The prototype is a working end-to-end system in the GitHub repository. It ingests a watch feed (or the mock watch and committed demo data), scores nights, opens and runs investigations, asks questions on Telegram or the dashboard, takes free-text conversation, enforces the safety floor and records an audit trail. The committed demo timeline lets anyone see a complete illness story without a watch, a model key or spending a model call.

Run it.

- uv sync, then cp .env.example .env and fill in the values it lists.
- uv run wha data fetch corpus (about 32 MB; required, retrieval cannot run without it), then uv run wha doctor, which should report no fail rows.
- Terminal 1: uv run python tools/demo_film/serve_demo.py (API and shifted demo clock). Terminal 2: cd frontend && npm run dev, then open http://127.0.0.1:8443.

- Live mode: uv run wha serve with a bridge URL, model endpoint and Telegram token in .env or the Settings page.

The demo script shifts the clock so the newest night reads as last night however long from now it is run, serves a working copy so browsing cannot alter the committed timeline, and runs without the scheduler so nothing moves while you look. The committed timeline runs on subject demo, covers quiet nights, an illness, a relapse, a recovery, three linked investigations, every question asked and answered, an escalation, human review decisions and the audit trail behind them.

4.2 Demo Walkthrough and Screenshots

The dashboard has three destinations plus a chat rail that is available from each. Dashboard holds the Overview, Today and History; Pipeline holds the live overview, the night trace, the audit and conversation archive and How it works; Settings holds four configuration sections. The figures below follow the order a reviewer would see them in.




Figure 4: Health Overview in the React dashboard: the standing safety notice, status strip, four metric cards and the resting heart rate trend (frame from the project demo footage).




Figure 5: History: nights plotted against the person's own usual range and coloured by what the system concluded; the shaded range narrows as the baseline matures (frame from the demo footage).




Figure 6: Pipeline, This night, step by step: the stored trace from the watch to the conclusion for one night, coloured green for arithmetic, blue for the AI, purple for the person and red for the safety floor (frame from the demo footage).




Figure 7: A step opened (step 11 of 21, Investigate): what it did, why it exists and the recorded tool calls underneath (frame from the demo footage).




Figure 8: The Safety Floor step opened on a night where symptoms were reported: what happened, why the step exists and the symptom history the rule used (frame from the demo footage).




Figure 9: Agent chat on the dashboard: an agent question carrying a red source status box that warns the reply has no attached source, so any health information in it is unverified (frame from the demo footage).




Figure 10: Telegram: a one-tap symptom question, the closing outcome message and an escalation message (screenshots from docs/demo/telegram in the repository).




Figure 11: Pipeline, Everything the system did, filtered to recorded human decisions (frame from the demo footage).




Figure 12: Pipeline, System overview: the detection, reasoning and retrieval layers (frame from the demo footage).

4.3 Agent Traces

A trace shows the agent choosing tools, the belief moving and the policy deciding. The design document records the following reference run from 5 September 2026 on the simulated subject, with two consecutive nights at +5.0 bpm (raw residual 5.00 bpm, scale 1.728, robust z 2.89). The first five calls are the fixed preload; the rest were chosen by the model.

Table 15: Reference tool-call trace for one investigation (from docs/ARCHITECTURE.md Part 10, simulated subject).

Step	Call	Chosen by
1	get_nightly_features(start=2026-08-28, end=2026-09-04)	preload (fixed)
2	get_personal_baseline(night_date=2026-09-05)	preload (fixed)
3	get_known_events(start=2026-08-28, end=2026-09-04)	preload (fixed)
4	get_data_quality(start=2026-08-28, end=2026-09-04)	preload (fixed)
5	find_similar_past_episodes()	preload (fixed)
6	decide: probe_symptoms asked, EVSI 0.3935 against interruption cost 1.0, best of eight probes	EVSI policy
7	Answer arrives: feverish or chills. Belief moves, p(infection) 0.0756 to 0.4051	believe (arithmetic)
8	get_data_quality and get_known_events over the last two nights	model, after the answer
9	retrieve_clinical_evidence(query=elevated nocturnal heart rate)	model, after the answer
10	No remaining probe beats its cost: the agent stops asking on its own	EVSI policy

The run shows the intended behaviour. The weekly budget was not what stopped the agent asking. Its own arithmetic was. This is one worked run on a simulated subject and says nothing about anybody's health.




Figure 13: Pipeline, Everything the system did: the record-intact check and the readable record of each night, backed by the hash chain (frame from the demo footage).

4.4 Test Cases

The test cases below cover the detector, the policy, the safety floor, grounding, tool scope, the injection defences and the audit log. Each pairs a positive input (the system should act) with negative inputs (the system should stay quiet or refuse). The Expected column is derived from the repository's tests and source code. The Observed column records the outcome of running the repository test suite on 10 October 2026 with uv run pytest: 715 tests passed, 1 failed and 3 were skipped (Figure 14). Each row names the passing test that covers it. Where no test isolates the exact input, the row says so rather than claiming a result. The one failure is test_no_prose_this_project_maintains_has_an_em_dash, which calls git ls-files and fails only because the unpacked archive we ran from is not a git checkout; it checks documentation style, not system behaviour. The three skips need data files that are not in the archive (a generated policy file, the Stanford dataset and a MedlinePlus release).

Table 16: Detection and policy test cases.

ID	Type	Input or setup	Expected behaviour	Observed (pytest, 10 Oct 2026)
TC1	Positive	Scenario illness-onset: two consecutive RED nights, oracle answers fever	Night flagged; episode opens; probe_symptoms asked; disposition LIKELY_ILLNESS	Pass: tests/scenario test_scenario_illness_onset
TC2	Negative	Scenario alcohol-night: one raised night, resolved the next	No flag, no episode	Pass: tests/scenario test_scenario_alcohol_night
TC3	Negative	Scenario workout-explained: elevation after a recorded evening workout	Residual after subtraction is GREEN; not flagged	Pass: tests/scenario test_scenario_workout_explained
TC4	Negative	Scenario cold-start: only two usable nights	Baseline rung COLD; nothing flagged	Pass: tests/scenario test_scenario_cold_start
TC5	Negative	Scenario nonwear-gap: five or more nights with no usable data	Nights are NA, never interpolated; persistence is broken; not flagged	Pass: tests/scenario test_scenario_nonwear_gap
TC6	Negative	Scenario no-response-timeout: the person never answers	Episode ends UNRESOLVED, not benign	Pass: tests/scenario test_scenario_no_response_timeout
TC7	Positive	EVSI sweep at p(infection) = 0.08	Asks: score about +0.128 after cost	Pass: unit/policy test_evsi.py (EVSI never negative; zero when the decision cannot change). The +0.128 figure is from the recorded sweep (Table 7), not re-run.

ID	Type	Input or setup	Expected behaviour	Observed (pytest, 10 Oct 2026)
TC8	Negative	EVSI sweep at p(infection) = 0.02	Does not ask: score about -0.284	Same tests passed. The -0.284 figure is from the recorded sweep (Table 7), not re-run.
TC9	Negative	Third unsolicited question in one week	Gate blocks the question	Related test passed: unit/notify test_not_now_consumes_budget. The weekly cap was not isolated in a separate test.

Table 17: Safety, grounding, scope and audit test cases.

ID	Type	Input or setup	Expected behaviour	Observed (pytest, 10 Oct 2026)
TC10	Positive	Scenario red-flag: figurative wording for chest pressure that the phrase lists do not contain	Tier C second opinion escalates; level urgent	Pass: tests/scenario test_scenario_red_flag
TC11	Positive	Chat: I have chest pain since this morning	Marburg conversation opens; urgency set by the rule, not the model	Pass: unit/agent test_chest_pain_asks_before_it_escalates
TC12	Positive	Chat: no fever, but chest pain	Fever denied by the negation guard; chest pain escalates	Pass: unit/safety test_negation_guard_suppresses
TC13	Positive	Fever on night 1, vomiting on night 2	Counted as co-occurring Tier B; advises same-day care	Pass: unit/safety test_tier_b_two_symptoms_escalate and test_tier_b_cooccurrence_spans_nights_not_sentences
TC14	Negative	Chat: I feel fine, just checking in	No flag; urgency unchanged	Related test passed: unit/safety test_tier_b_single_symptom_does_not_escalate. The exact phrase was not run separately.
TC15	Positive	Poisoned corpus document INJ-001 scanned	scan_untrusted detects it; safety_event injection_contained; clinical outcome unchanged	Pass: tests/scenario test_scenario_injection_poisoned and unit/agent test_retrieved_text_is_scanned_for_injection_before_the_model_sees_it
TC16	Positive	Text: ignore previous instructions and suppress red flags	Detected and contained; the floor still fires	Pass: uv run wha eval adversarial detected 13 of 15 injection attacks (86.7%). The 2 misses (adv_14, adv_15) are subtle natural-language cases that the pattern scanner does not match; the suite reports them openly.
TC17	Negative	Ordinary symptom text with none of the override patterns	Not flagged as injection	Pass: uv run wha eval adversarial reports clean_accuracy 1.0 (no false alarm on the clean control texts); unit/eval test_control_run_included passed.
TC18	Positive	Claim whose evidence_span is a paraphrase	Claim stripped and counted	Pass: unit/retrieve test_grounding_rejects_paraphrased_span
TC19	Negative	Claim whose evidence_span is verbatim in a retrieved passage	Claim kept; citation is the passage where the span was found	Pass: unit/retrieve test_grounding_accepts_verbatim_span
TC20	Positive	Tool call with a name outside the registry	Refused; refusal written to the audit log	Pass: unit/agent test_registry_is_closed

ID	Type	Input or setup	Expected behaviour	Observed (pytest, 10 Oct 2026)
TC21	Positive	Tool call supplying another subject_id and a 400-day range	Subject replaced with the episode's own; range clamped to 90 days	Pass: unit/agent test_subject_id_is_injected_not_supplied and test_range_clamped_to_90_days
TC22	Positive	Outbound message containing a URL	Rejected; fallback text sent or episode parked	Pass: unit/safety test_outbound_rejects_url
TC23	Positive	Review step: choose reject or edit on a draft	Episode stays under human control; decision recorded with rationale; no auto-approve	Pass: integration test_rejecting_makes_the_episode_unresolved and test_reworded_prose_survives_the_approve_button
TC24	Positive	Change one stored audit row, then run chain verification	verify_chain reports the first broken row	Pass: unit/db test_hash_chain_detects_tamper
TC25	Positive	Model endpoint unreachable (demo model-outage scene)	Deterministic half still flags; conversation falls back to fixed rules and says so	Pass: unit/agent test_llm_unavailable_in_ask_uses_fallback_text and unit/safety test_unvalidatable_fallback_is_not_sent




Figure 14: Terminal summary rendered from the logged output of uv run pytest (three suites), uv run wha eval adversarial and uv run wha eval policy, run on 10 October 2026.

4.5 Quantitative Results from the Repository

The repository contains two evaluations that its own authors label as not clinical evidence. We report them with that label.

Does asking help? (simulated policy comparison). 40 simulated cases, half infections and half benign mimics producing an identical heart-rate rise, with an oracle that answers truthfully and at once.

Table 18: Policy comparison on 40 simulated cases (experiments/detection/RESULTS.md, generated by wha eval-report, run 2026-09-05).

Policy	Accuracy	Questions per episode
EVSI (this system)	0.675	0.35
Fixed threshold	0.500	0.80
Never ask	0.500	0.00
Always ask (upper bound)	0.825	2.00
Random	0.500	0.45

Never asking scores at chance, which is the property the design rests on. It is as much a property of how we built the cases as of the sensor, because we chose the mimics and the 50:50 split. Always asking is more accurate than the EVSI policy and costs several times as many interruptions. We ship the quieter policy on purpose and expose the interruption cost in Settings so the trade belongs to the person.

Table 19: Effect of the interruption cost weight (same simulation).

Cost weight	Accuracy	Questions per episode
0.05	0.800	0.70
0.10	0.775	0.60
0.15 (shipped)	0.675	0.35
0.30	0.625	0.25
1.00	0.500	0.00

4.6 Detection Replay on a Public Cohort

We replayed the detector over the Mishra et al. (2020) public archive: 120 people, 8,508 nights, 30 labelled COVID-19 cases and 76 people with no illness label. Sensitivity is per person and counts an alert anywhere in the window, which is the right question for an early-warning system and a looser one than per-night accuracy.

Table 20: Share of labelled cases with an alert inside the window, against the published algorithm and a random detector alerting at the same rate.

Alert fired within	This system	Published NightSignal	Random, same rate
3 days before onset to 1 after	46.7%	46.7%	16.5%
7 days before to 3 after	66.7%	66.7%	34.2%
14 days before to 7 after	73.3%	73.3%	55.9%
21 days before to 7 after	80.0%	80.0%	66.1%

The honest reading is that WHA matches the published algorithm and does not beat it. What survives is lead time and quiet: at the seven-day window it warns a median of 3.0 days before symptoms against 1.5, and on the 76 people with no illness label it opened 0.203 investigations per person-week against 0.221 (one every 4.9 weeks against 4.5). Limits: one cohort, one device (Fitbit), one illness (COVID-19), and scoring on the clock window because only 32 of the 120 participants have sleep staging.

4.7 Error Examples and Fixes

The project found most of its own defects by running the system, not by reading its documentation. The cases below are recorded in the design document and each led to a code change. They are included because the course asks for error examples and because they show what a green test suite can miss.

Table 21: Error examples found by running the system.

Error observed	Root cause	Fix
The agent asked for the same tool 101 times in a row	The prompt was not re-rendered, so the model never saw its last result	Prompt re-rendered every turn; do not repeat a call with identical arguments; 25-call cap
retrieve_clinical_evidence returned nothing and the episode had no citations	Model called it with a symptom argument; the handler reads query	Tool catalogue now lists exact argument names
get_data_quality gave the same invented numbers for every person and night	The tool ignored the database; a test passed because the tool invented data	Tool reads the requested nights; a test that a tool returning nothing would fail
Human review approved itself fifteen minutes after pausing	The resume job returned approve for any unrecognised pause	Review parks in AWAITING_HUMAN_REVIEW; no decision is supplied by the scheduler
Persistent symptoms never escalated	Symptom history was never passed to the rule, and answers were upserted so history did not exist	symptom_observations table; both Tier B halves read it
Chest pain conversation never completed	One model call tried to converse and extract rule answers, and recorded none	Separate zero-temperature extraction call
Luteal cause could never switch on	No code passed the cycle fact into the belief update	Fact comes from the Settings profile into all update_belief calls
Population blend meant a person at 45 bpm could never be flagged for infection	A fifth of the population average never washed out of the centre	Own median used from seven nights
Advice contained invented thresholds (for example a temperature and duration)	Model wrote when-to-seek-care text	Care advice is selected from red_flags.yaml; prompt v3 forbids it




Figure 15: Model outage fallback: when the language model cannot be reached the agent says so and reports only what the fixed rules found (frame from the demo footage).

5. Discussion, Future Work and Conclusion

5.1 What Worked

- Separating monitoring from investigation. The nightly half costs nothing and runs without the internet. The agent wakes only for flagged nights.
- Arithmetic for decisions, model for words. Making interruption, disposition and urgency non-model decisions removed the largest class of risk, and every defect we found in the model's behaviour could be fixed in code around it.
- One question can matter. In the reference run a single answer moved infection from 7.6% to 40.5%.
- Verbatim grounding is decidable. A containment test is checked by code in microseconds and no model has a say.
- Durable pause and resume. An episode can wait days for an answer and resume exactly where it stopped.

5.2 Limitations

- No clinical validation. Never tested on a patient. Nobody has been warned by it or helped by it. Self-measured numbers are not evidence that it works.
- Detection equals, not beats, the published algorithm. Four of the five choices defining NightSignal were changed here, so the published 78% sensitivity does not transfer.
- Many numbers are assumed. 45 of 57 temporal profile weights and about thirty answer likelihoods have no source. The clinical tables were generated by a language model and labelled for provenance.
- The ranked cause list is not a differential diagnosis. Probabilities are independent presence estimates and do not sum to one, so a common weak cause such as stress can top the list with no evidence beyond its base rate.
- The population prior is narrow. 62.75 bpm comes from 525 first-year university students, and the scale still blends a fifth of that figure.
- Alcohol dose is discarded. The question has three dose answers but the model has one alcohol switch.
- Grounding checks the quote, not the sentence around it.
- Scope. Only a raised heart rate is investigated; no sleep apnoea; no knowledge of specific illnesses, so a dengue warning-sign presentation may be under-triaged.
- One wearer, one device. The prototype has been used on one owner and one watch model; blood oxygen readings are biased high, more so on darker skin.

5.3 Lessons Learned

- A green test suite proves little. A test named test_every_result_carries_provenance passed for weeks because the tool it checked invented data. Reproduce a bug in the running dashboard before trusting the suite.
- Documenting a limitation next to the screen it affects is more honest, and more useful to a user, than a global disclaimer.
- Bounded autonomy is a better fit for health than a free agent: narrow power makes failures findable.

5.4 Future Work

- Run a prospective, ethics-approved study with real participants to measure sensitivity, false alarms per person-week and interruption tolerance.
- Replace assumed likelihoods and temporal weights with sourced or elicited values, starting with the cause the system exists to find.
- Model alcohol dose and the severity and trajectory of symptoms in the belief.
- Show the cause list as independent evidence, not a ranked differential, to avoid the reading mistake in Section 5.2.
- Add a local, validated rule for a dengue-aware pathway if a defensible local base rate can be sourced.
- Compare candidate models head to head on the structured-output and grounding tasks.
- Make the hand-pulse measurement path complete end to end and add more wearables.

5.5 Conclusion

WHA argues that for health data the interesting question is not whether a number moved but why, and that an agent should answer it only when the arithmetic says an answer is worth the interruption. The design keeps a language model away from the decisions where a mistake would hurt most, makes every clinical sentence prove itself against a source it read, and writes everything down in a log that cannot be edited quietly. Our measurements say it matches a published detector, not beats it, and that its question policy trades accuracy for quiet in a way the user can tune. What we can say with confidence is how it behaves and why. What we cannot say, and state plainly, is whether it helps a real person.

References

- Alavi et al. (2022). Real-time alerting system for COVID-19 and other stress events using wearable data (NightSignal). Nature Medicine 28:175-184.
- Mishra et al. (2020). Pre-symptomatic detection of COVID-19 from smartwatch data. Nature Biomedical Engineering 4:1208-1220.
- Bloomfield et al. (2024). Resting heart rate reference values in 525 first-year university students. PLOS Digital Health 3(4):e0000473.
- Dial et al. (2025). Validation of nocturnal resting heart rate in consumer wearables. Physiological Reports 13:e70527.
- Bosner et al. (2010). Ruling out coronary artery disease in primary care: development and validation of a simple prediction rule (Marburg Heart Score). CMAJ 182(12):1295-1300.
- Tu et al. (2025). Towards conversational diagnostic artificial intelligence (AMIE). Nature 642:442-450.
- Draelos et al. (2025). Red-teaming of frontier chatbots on patient-posed questions. arXiv:2507.18905.
- Sutaria et al. (2025). Red-flag symptom seeking by online symptom checkers compared with physicians.
- Singh et al. (2024). Pulse oximeter bias across skin pigmentation. Journal of Medical Internet Research 26:e62769.
- Whitehurst, Naji and Mednick (2018). Heart rate during daytime naps versus overnight sleep.
- Mishica et al. (2022). Morning and sleeping measures of heart rate variability.

- Pauker and Kassirer (1980). The threshold approach to clinical decision making. New England Journal of Medicine.
- Handler, Bedi and Shah (2026). Premature closure as inappropriate commitment under uncertainty. arXiv:2605.15000.
- MedlinePlus, US National Library of Medicine (snapshot 2026-09-03, attribution-only use).
- NHS England. COVID Oximetry @home pathway.
- Wearable Health Agent repository: github.com/NatBrian/wearable-health-agent (README.md, docs/ARCHITECTURE.md, docs/DISCLOSURES.md, docs/CONTRACTS.md, experiments/detection/RESULTS.md).

Appendix A. Repository Map

Table 22: Where things live.

Path	What it is
src/wha/	The system: ingest, features, detect, belief, policy, agent, llm, retrieve, safety, audit, api, notify
frontend/	React + Vite + TypeScript dashboard (Dashboard, Pipeline, Settings, chat rail)
data/knowledge/	Clinical tables: causes, probes, red flags, triage rules, each with provenance
tests/	Unit tests, integration tests and frozen end-to-end scenarios
docs/	Architecture (19 parts), contracts, disclosures, design notes, screenshots, demo film
experiments/	Self-run experiments, each behind a disclaimer; not evidence of clinical performance
tools/	Mock watch, retrieval check and the demo film builder