

TOULON ILE DU LEVANT, France

WMO: 076780

Lat: 43.023N

Lon: 6.460E

Elev: 131

StdP: 99.76

Time Zone: 1.00 (EUC)

Period: 01-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
2	3.3	4.9	-7.3	2.1	5.9	-5.3	2.4	6.9	22.9	9.0	20.6	9.8	8.0	290	0.585

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
8	6.6	30.1	21.9	28.9	21.6	27.9	21.4	24.2	27.4	23.6	26.7	22.9	26.0	5.1	260

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
23.2	18.3	26.1	22.6	17.5	25.5	21.8	16.8	25.0	73.7	27.7	70.9	26.6	68.4	26.1	26.6

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 20.1	17.9	15.7	DB	1.9	32.4	2.5	2.1	0.2	33.9	-1.3	35.1	-2.7	36.3	-4.5	37.9	(4)
(5)			WB	-1.2	25.1	1.8	1.0	-2.4	25.8	-3.4	26.4	-4.4	27.0	-5.7	27.8	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6)	Temperatures, Degree-Days and Degree-Hours	DBAvg	16.6	10.2	9.9	12.0	14.3	17.4	21.7	24.1	24.4	21.3	17.9	14.0	11.2	(6)
(7)		DBStd	5.59	2.19	2.30	2.07	2.02	2.18	2.44	1.88	1.99	2.05	2.30	2.31	2.51	(7)
(8)		HDD10.0	76	24	26	7	0	0	0	0	0	0	0	2	17	(8)
(9)		HDD18.3	1242	253	237	198	123	44	2	0	0	2	33	130	219	(9)
(10)		CDD10.0	2476	30	23	68	128	228	352	436	448	339	246	122	56	(10)
(11)		CDD18.3	598	0	0	0	1	14	104	178	189	91	21	0	0	(11)
(12)		CDH23.3	2923	0	0	0	0	28	448	1036	1168	236	7	0	0	(12)
(13)		CDH26.7	527	0	0	0	0	2	77	184	247	17	0	0	0	(13)
(14)	Wind	WSAvg	6.5	7.4	7.0	7.5	6.8	6.2	5.3	5.8	5.2	5.8	6.6	7.3	7.4	(14)
(15)	Precipitation	PrecAvg	786	89	60	55	59	46	35	12	19	71	99	129	94	(15)
(16)		PrecMax	1202	262	170	203	149	117	162	57	98	204	208	370	239	(16)
(17)		PrecMin	443	4	1	6	6	3	1	1	0	3	33	25	12	(17)
(18)		PrecStd	218	73	52	50	42	33	38	14	22	54	49	88	57	(18)
(19)	Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	16.9	16.1	19.4	21.9	26.2	31.2	31.2	32.6	28.5	24.2	19.7	17.1	(19)
(20)			MCWB	11.9	10.9	11.6	14.8	17.5	22.0	21.2	22.5	20.3	18.7	15.4	12.6	(20)
(21)		2%	DB	15.0	14.6	17.2	20.3	23.7	28.8	29.6	30.5	26.9	23.0	18.6	15.7	(21)
(22)			MCWB	11.0	10.6	11.7	14.5	17.2	20.9	21.7	22.3	20.0	18.2	15.2	12.4	(22)
(23)		5%	DB	14.0	13.6	16.0	18.9	22.2	27.3	28.6	29.1	25.7	21.9	17.7	15.0	(23)
(24)			MCWB	11.1	10.3	11.5	14.0	16.5	20.6	21.6	21.9	19.7	17.7	14.9	12.2	(24)
(25)		10%	DB	13.1	12.8	15.0	17.6	20.9	26.0	27.6	28.0	24.7	20.9	17.0	14.3	(25)
(26)			MCWB	10.6	10.0	10.9	13.3	16.0	20.3	21.5	21.9	19.3	17.5	14.4	11.9	(26)
(27)	Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	13.3	12.7	13.7	16.6	19.7	24.0	25.0	25.3	23.2	20.9	17.4	14.7	(27)
(28)			MCDWB	15.0	14.3	16.3	19.6	22.7	27.7	28.5	28.6	25.8	22.3	18.5	15.4	(28)
(29)		2%	WB	12.5	12.0	13.0	15.5	18.6	23.0	24.1	24.5	22.1	19.9	16.5	13.7	(29)
(30)			MCDWB	14.0	13.3	15.4	18.5	21.9	26.4	27.1	27.7	24.7	21.5	17.6	14.7	(30)
(31)		5%	WB	12.0	11.3	12.4	14.7	17.7	22.2	23.4	23.8	21.2	19.1	15.7	13.0	(31)
(32)			MCDWB	13.4	12.8	14.6	17.5	20.9	25.5	26.5	27.0	23.9	20.6	17.0	14.3	(32)
(33)		10%	WB	11.2	10.6	11.9	14.0	17.0	21.2	22.8	23.1	20.4	18.4	15.1	12.4	(33)
(34)			MCDWB	12.8	12.3	13.9	16.6	19.9	24.4	25.9	26.2	23.2	20.1	16.4	13.9	(34)
(35)	Mean Daily Temperature Range	5% DB	MDBR	3.9	4.7	5.3	5.6	6.1	6.7	6.8	6.6	5.9	4.7	4.0	3.8	(35)
(36)			MCDBR	4.2	5.3	6.4	7.1	7.6	8.2	7.7	7.7	6.7	5.6	4.4	3.8	(36)
(37)			MCWBR	3.6	4.1	3.9	4.1	4.5	4.1	4.1	4.4	4.1	3.5	3.5	3.2	(37)
(38)		5% WB	MCDWB	3.6	4.4	5.3	6.2	6.4	7.1	6.5	6.9	5.7	4.6	3.5	3.4	(38)
(39)			MCWBR	3.5	3.9	3.5	3.9	4.1	4.1	3.9	4.0	3.7	3.3	3.2	3.3	(39)
(40)	Clear-Sky Solar Irradiance	taub	0.325	0.342	0.376	0.398	0.406	0.406	0.401	0.397	0.389	0.384	0.351	0.322	(40)	
(41)		taud	2.491	2.444	2.366	2.327	2.345	2.379	2.396	2.414	2.422	2.423	2.461	2.503	(41)	
(42)		Ebn at Noon	811	854	863	869	868	867	867	860	840	793	768	779	(42)	
(43)		Edh at Noon	73	89	108	121	123	119	116	110	102	90	75	66	(43)	
(44)	All-Sky Solar Radiation	RadAvg	1.85	2.73	4.14	5.35	6.40	7.40	7.40	6.46	4.87	3.15	2.02	1.60	(44)	
(45)		RadStd	0.18	0.28	0.35	0.35	0.48	0.29	0.30	0.22	0.25	0.25	0.20	0.17	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (25 neighbors)		+0.29	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page