

LYUBAN, Russian Federation

WMO: 260780

Lat: 59.350N

Lon: 31.233E

Elev: 39

StdP: 100.86

Time Zone: 3.00 (E03)

Period: 90-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-23.2	-19.5	-25.6	0.4	-23.1	-21.7	0.5	-19.0	6.8	-1.1	6.1	-1.8	1.0	30	N/A

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	9.6	27.7	18.7	25.8	17.9	24.0	17.0	20.2	24.8	19.1	23.8	18.1	22.3	2.0	180

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
18.7	13.6	22.4	17.5	12.6	20.9	16.4	11.7	19.9	58.2	24.8	54.5	23.8	51.1	22.5	22.9

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	DB	WB
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 5.5	4.8	4.3	-25.1	29.3	4.9	2.1	-28.7	30.8	-31.5	32.0	-34.3	33.2	-37.9	34.7		
(5)			-25.3	21.6	4.9	0.8	-28.8	22.2	-31.7	22.6	-34.4	23.1	-37.9	23.7		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	5.4	-6.2	-3.9	-1.2	4.8	11.2	14.7	17.1	15.9	10.6	4.2	-0.8	-2.6		
	DBStd	9.22	6.64	5.82	4.74	4.06	4.26	3.71	3.17	3.04	3.56	4.28	5.31	5.33		
	HDD10.0	2372	501	391	348	160	36	5	0	1	34	183	323	392		
	HDD18.3	4779	759	624	607	404	223	118	62	87	234	438	573	650		
	CDD10.0	684	0	0	0	5	74	146	222	183	52	3	0	0		
	CDD18.3	49	0	0	0	0	3	10	24	12	1	0	0	0		
	CDH23.3	517	0	0	0	0	49	118	226	119	5	0	0	0		
	CDH26.7	91	0	0	0	0	11	21	42	16	1	0	0	0		
(14) Wind	WSAvg	2.0	2.3	2.2	2.3	2.0	2.0	1.9	1.7	1.6	1.7	2.0	2.2	2.3		
(15) Precipitation	PrecAvg	680	53	37	36	43	58	70	88	75	59	57	62	49		
	PrecMax	948	75	72	62	95	140	111	233	151	116	80	98	77		
	PrecMin	521	20	3	10	15	21	24	24	25	19	25	2	25		
	PrecStd	103	14	15	16	24	30	26	53	33	31	15	24	12		
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	4.9	6.2	11.9	20.7	28.2	29.2	29.9	28.5	23.1	15.1	8.7	8.0		
		MCWB	4.3	4.5	5.2	11.9	16.1	19.7	19.8	18.7	17.6	11.8	7.2	7.0		
	2%	DB	3.2	4.3	8.4	17.7	24.2	26.3	27.8	26.4	20.1	12.7	7.4	5.3		
		MCWB	2.3	2.7	4.4	9.9	14.9	17.9	19.1	18.5	15.5	10.3	6.5	4.4		
	5%	DB	2.2	3.0	6.0	15.2	22.2	24.3	26.0	24.5	18.0	11.4	6.2	4.1		
		MCWB	1.4	1.8	3.0	8.7	14.4	16.7	18.2	17.8	14.1	9.8	5.5	3.4		
	10%	DB	1.4	2.1	4.6	12.6	19.8	22.4	23.9	22.4	16.5	10.3	5.1	2.8		
		MCWB	0.7	1.1	2.4	7.7	13.0	15.6	17.7	16.7	13.3	9.0	4.4	2.2		
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	4.5	4.9	6.5	12.3	18.7	21.6	21.8	21.1	18.4	12.2	7.6	6.7		
		MCDB	5.0	6.1	9.4	18.4	23.9	27.2	26.6	26.3	22.6	13.9	8.3	8.0		
	2%	WB	2.6	3.1	5.0	10.9	16.4	19.4	20.5	19.3	16.2	11.1	6.6	4.6		
		MCDB	3.0	4.0	7.9	16.0	21.5	24.0	24.8	23.9	19.1	12.1	7.3	5.2		
	5%	WB	1.6	2.0	3.6	9.5	15.1	17.6	19.5	18.3	14.8	10.2	5.6	3.5		
		MCDB	2.0	2.8	5.5	14.1	20.4	22.3	24.1	22.6	17.1	11.2	6.1	4.0		
	10%	WB	0.8	1.2	2.6	8.0	13.9	16.4	18.5	17.4	13.6	9.0	4.5	2.2		
		MCDB	1.4	1.8	4.2	12.0	19.3	21.2	22.8	21.3	15.8	10.1	5.1	2.7		
(35) Mean Daily Temperature Range	5% DB	MDBR	5.3	5.4	7.4	9.8	11.2	10.3	9.6	9.5	7.9	5.7	3.8	3.9		
		MCDBR	3.8	4.6	8.9	15.3	15.3	13.9	13.5	13.5	11.5	7.6	4.3	3.8		
	5% WB	MCWBR	3.7	3.8	5.8	8.7	7.3	6.3	6.0	6.6	7.0	5.6	3.9	3.5		
		MCWBR	3.7	4.0	7.2	13.4	12.4	11.7	11.2	11.1	9.5	6.6	4.0	3.8		
(40) Clear-Sky Solar Irradiance	taub		0.276	0.314	0.337	0.379	0.372	0.368	0.394	0.390	0.359	0.336	0.307	0.264		
		taud	2.105	2.107	2.165	2.275	2.379	2.415	2.361	2.360	2.432	2.380	2.213	2.086		
	Edn at Noon		500	670	784	820	857	866	830	802	770	663	466	375		
		Edh at Noon	48	81	103	111	107	106	109	102	81	63	44	33		
(44) All-Sky Solar Radiation	RadAvg		0.29	0.91	2.34	3.70	5.07	5.33	5.11	4.04	2.48	1.02	0.30	0.16		
	RadStd		0.06	0.20	0.31	0.47	0.49	0.43	0.62	0.42	0.24	0.17	0.04	0.03		

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
(46)	Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47)	Regional (6 neighbors)	+0.52	N/A	N/A	N/A	N/A	N/A	-182	-195	N/A	N/A

Nomenclature: See separate page