

STARITSA, Russian Federation

WMO: 264990

Lat: 56.500N

Lon: 34.933E

Elev: 186

StdP: 99.11

Time Zone: 3.00 (E03)

Period: 01-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-25.6	-22.3	-27.9	0.3	-25.4	-24.6	0.4	-22.0	8.5	-2.0	7.9	-2.1	1.2	0	0.580

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	9.6	28.4	20.0	26.4	19.3	24.5	18.3	21.1	27.0	20.1	25.1	19.1	23.3	2.9	190

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
19.0	14.1	23.7	18.2	13.4	22.5	17.5	12.8	21.5	61.6	26.8	58.4	25.3	55.2	23.4	24.9

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
8.1	7.1	6.3	-29.8	30.3	4.1	2.5	-32.8	32.1	-35.2	33.6	-37.6	35.0	-40.6	36.8		
			DB	WB	DB	WB	DB	WB	DB	WB	DB	WB	DB	WB		
			-30.0	22.2	4.1	1.3	-32.9	23.1	-35.3	23.9	-37.6	24.6	-40.6	25.6		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
Temperatures, Degree-Days and Degree-Hours	DBAvg	5.3	-7.9	-7.4	-1.9	5.2	12.5	15.2	18.4	16.6	11.1	5.2	-0.1	-4.2
	DBStd	10.32	7.44	7.25	5.18	4.17	4.37	3.38	3.08	3.62	3.20	4.11	4.59	6.12
	HDD10.0	2517	556	487	369	153	24	2	0	1	24	156	304	440
	HDD18.3	4842	814	721	628	395	186	105	36	79	219	407	554	698
	CDD10.0	797	0	0	0	8	102	157	261	205	56	7	0	0
	CDD18.3	80	0	0	0	0	6	10	39	24	1	0	0	0
	CDH23.3	682	0	0	0	1	66	89	304	218	4	0	0	0
	CDH26.7	159	0	0	0	0	9	13	72	65	0	0	0	0
Wind	WSAvg	3.0	3.3	3.1	3.4	3.1	3.0	2.7	2.2	2.5	2.6	3.0	3.3	3.4
Precipitation	PrecAvg	672	39	35	32	32	67	78	88	81	65	65	49	41
	PrecMax	890	86	62	53	65	162	151	195	195	156	200	100	91
	PrecMin	433	13	11	12	5	20	11	7	6	27	17	1	15
	PrecStd	117	17	14	12	17	33	35	50	46	34	38	22	18
Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	4.8	3.8	12.7	21.1	28.1	28.5	31.5	32.4	23.3	18.0	10.9	8.1
		MCWB	4.0	2.2	6.6	11.0	19.4	19.5	21.4	22.3	17.8	12.3	9.7	7.3
	2%	DB	2.7	2.6	8.7	17.7	25.2	26.0	28.6	28.1	20.5	14.1	8.2	5.8
		MCWB	1.9	1.1	4.0	9.7	17.1	18.6	20.2	20.2	15.2	11.8	6.9	4.7
	5%	DB	1.7	1.8	6.4	15.4	22.6	23.8	26.4	25.4	18.6	12.5	6.8	4.0
		MCWB	0.9	0.6	3.0	8.4	15.3	17.2	19.7	19.3	14.3	10.6	5.5	3.1
	10%	DB	0.7	1.0	4.4	13.1	20.5	21.7	24.7	23.2	16.7	11.1	5.5	2.2
		MCWB	0.0	0.1	2.0	7.4	13.9	16.0	18.7	18.0	13.2	9.5	4.5	1.3
Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	4.1	2.7	7.2	12.0	20.7	21.0	22.1	22.6	18.8	13.4	10.0	7.2
		MCDB	4.7	3.5	12.0	16.2	27.2	26.0	28.5	28.7	21.2	15.1	10.5	8.1
	2%	WB	2.0	1.5	4.7	10.4	17.8	19.5	21.1	21.0	16.1	12.2	7.3	4.9
		MCDB	2.6	2.2	7.6	16.0	23.2	24.4	27.3	26.7	19.3	13.8	8.1	5.6
	5%	WB	1.0	0.8	3.3	9.3	16.3	18.2	20.3	19.8	14.8	10.8	5.8	3.2
		MCDB	1.6	1.5	5.7	14.6	21.0	21.9	25.3	24.6	17.7	12.4	6.5	3.9
	10%	WB	0.1	0.2	2.1	7.9	15.0	17.0	19.4	18.5	13.6	9.7	4.5	1.5
		MCDB	0.7	1.0	4.1	12.1	19.6	20.4	23.6	22.3	16.2	10.9	5.3	2.0
Mean Daily Temperature Range	5% DB	MDBR	5.2	6.5	7.4	9.5	10.2	9.2	9.6	9.1	8.4	6.0	4.0	4.2
		MCDBR	3.6	4.2	9.9	14.0	13.6	12.3	12.4	13.0	11.9	8.2	5.7	3.9
	5% WB	MCWBR	3.6	3.5	6.4	7.2	6.4	6.0	5.3	5.8	7.0	5.5	4.8	3.7
		MCWBR	3.3	3.7	8.5	12.1	12.2	10.4	10.7	11.8	10.7	6.9	4.9	3.8
Clear-Sky Solar Irradiance	taub	taub	0.282	0.318	0.339	0.396	0.386	0.369	0.403	0.409	0.365	0.343	0.316	0.277
		taud	2.129	2.090	2.163	2.197	2.329	2.399	2.318	2.291	2.388	2.382	2.246	2.135
	Ebn at Noon	Ebn at Noon	589	711	809	815	852	873	830	795	783	699	550	489
		Edh at Noon	58	91	109	124	115	109	116	112	88	69	53	45
All-Sky Solar Radiation	RadAvg	0.52	1.34	2.83	3.96	5.22	5.49	5.36	4.24	2.73	1.24	0.45	0.28	0.08
	RadStd	0.10	0.20	0.34	0.38	0.45	0.53	0.57	0.44	0.36	0.23	0.08	0.08	0.08

Historical Trends

	DBAvg	Heating			Cooling			Degree-Days			
		99% DB		99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (11 neighbors)	+0.69	N/A	N/A	N/A	N/A	N/A	N/A	-153	-223	N/A	N/A

Nomenclature: See separate page