

SERAFIMOVICH, Russian Federation

WMO: 343570

Lat: 49.567N

Lon: 42.733E

Elev: 129

StdP: 99.78

Time Zone: 4.00 (E04)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-22.1	-19.0	-25.2	0.4	-21.5	-22.4	0.5	-18.4	12.3	-1.4	11.2	-3.6	2.2	290	0.495

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	10.3	35.0	20.3	33.0	19.5	31.0	18.9	21.6	31.0	20.7	29.7	20.0	28.2	3.1	90

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
18.8	13.8	24.2	17.9	13.1	23.8	17.0	12.3	23.3	63.3	31.1	60.4	29.9	57.7	28.1	25.3

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 10.2	9.0	7.9	DB	-24.0	36.8	4.6	2.2	-27.3	38.4	-30.1	39.7	-32.7	40.9	-36.0	42.5	(4)
(5)			WB	-24.6	22.8	4.8	1.4	-28.0	23.8	-30.8	24.6	-33.5	25.4	-36.9	26.4	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	8.9	-6.3	-5.4	0.5	10.0	17.1	21.2	23.5	22.6	15.9	8.7	1.4	-3.8	(6)	
	DBStd	11.87	6.40	6.52	4.92	4.74	4.74	4.03	3.65	4.20	4.20	4.87	5.32	5.90	(7)	
	HDD10.0	2068	504	432	294	58	4	0	0	0	5	83	261	427	(8)	
	HDD18.3	3933	762	666	552	252	82	16	3	11	96	301	508	685	(9)	
	CDD10.0	1653	0	0	1	57	225	335	418	391	181	43	2	0	(10)	
	CDD18.3	476	0	0	0	1	43	101	163	143	22	1	0	0	(11)	
	CDH23.3	4707	0	0	0	13	400	959	1677	1481	169	7	0	0	(12)	
	CDH26.7	1939	0	0	0	1	125	386	744	653	30	1	0	0	(13)	
(14) Wind	WSAvg	3.0	3.4	3.8	3.9	3.5	2.9	2.5	2.2	2.3	2.5	2.8	3.2	3.4	(14)	
(15) Precipitation	PrecAvg	435	32	27	26	31	42	50	46	41	37	28	40	42	(15)	
	PrecMax	623	96	76	116	152	143	128	108	126	117	77	111	119	(16)	
	PrecMin	212	4	0	0	1	4	4	3	0	3	0	4	13	(17)	
	PrecStd	108	20	18	21	26	33	32	32	30	29	20	27	24	(18)	
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	6.7	7.5	14.9	25.6	32.6	35.9	37.5	37.7	29.6	23.7	15.2	8.1	(19)	
		MCWB	5.4	5.8	8.3	14.3	17.4	19.7	20.5	21.1	17.3	16.0	11.5	7.2	(20)	
	2%	DB	4.2	4.6	11.6	22.5	30.0	33.2	35.0	34.9	27.5	20.3	12.2	6.3	(21)	
		MCWB	3.5	3.2	6.8	13.4	17.1	19.4	20.5	20.2	16.7	14.0	9.7	5.4	(22)	
	5%	DB	2.5	3.0	9.2	19.8	27.6	30.8	33.0	32.5	25.4	17.9	10.2	4.6	(23)	
		MCWB	1.6	1.9	5.6	12.0	16.4	18.8	19.9	19.4	16.1	13.1	8.4	3.6	(24)	
	10%	DB	1.4	2.0	7.0	17.7	25.3	28.7	30.8	30.3	23.1	15.5	8.3	3.1	(25)	
		MCWB	0.6	1.1	4.5	10.8	15.8	18.2	19.4	18.8	15.2	11.7	6.8	2.2	(26)	
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	5.6	5.7	9.6	15.7	19.6	22.1	22.6	22.9	19.8	17.3	11.9	7.3	(27)	
		MCDB	6.4	7.2	13.2	22.9	28.7	31.5	31.5	34.0	25.1	22.0	13.9	8.0	(28)	
	2%	WB	3.5	3.5	7.6	14.0	18.4	20.9	21.7	21.4	18.2	15.2	10.2	5.4	(29)	
		MCDB	4.3	4.3	10.8	20.6	27.0	29.1	30.8	31.5	24.1	18.9	11.9	6.1	(30)	
	5%	WB	1.8	2.2	6.0	12.9	17.5	20.0	20.9	20.3	17.1	13.5	8.6	3.7	(31)	
		MCDB	2.4	2.8	8.8	18.5	25.3	28.2	30.1	29.8	22.9	16.7	10.1	4.4	(32)	
	10%	WB	0.7	1.2	4.6	11.6	16.5	19.0	20.2	19.3	16.0	11.9	6.9	2.3	(33)	
		MCDB	1.3	1.8	6.8	16.6	23.8	26.8	28.2	28.1	21.9	15.2	8.1	2.9	(34)	
(35) Mean Daily Temperature Range	5% DB	MDBR	4.9	5.6	6.5	9.1	10.0	9.8	10.3	11.0	9.7	7.2	5.1	4.6	(35)	
		MCDBR	3.7	4.9	9.7	11.8	12.8	12.8	13.2	13.6	12.6	10.6	6.6	4.5	(36)	
	5% WB	MCWBR	3.5	4.1	6.1	5.6	5.2	4.7	4.7	5.2	5.7	5.9	5.1	4.1	(37)	
		MCDWR	3.7	4.4	8.6	10.5	11.2	11.2	11.1	12.1	10.2	9.2	6.0	4.2	(38)	
(40) Clear-Sky Solar Irradiance	taub		0.319	0.352	0.379	0.440	0.407	0.399	0.422	0.428	0.394	0.363	0.339	0.320	(40)	
		taud	2.122	2.029	2.115	2.085	2.276	2.336	2.278	2.238	2.304	2.340	2.289	2.183	(41)	
	Ebn at Noon		688	755	813	802	852	861	833	807	796	754	675	631	(42)	
		Edh at Noon	83	117	128	148	127	121	126	126	106	86	71	69	(43)	
(44) All-Sky Solar Radiation	RadAvg		0.92	1.93	3.12	4.39	5.84	6.34	6.14	5.54	3.89	2.15	0.96	0.58	(44)	
	RadStd		0.21	0.40	0.45	0.41	0.56	0.61	0.39	0.38	0.36	0.30	0.19	0.12	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (6 neighbors)		+0.56	N/A	N/A	N/A	N/A	N/A	N/A	-141	+95	N/A

Nomenclature: See separate page