

QAZVIN, Iran, Islamic Republic of

WMO: 407310

Lat: 36.240N

Lon: 50.047E

Elev: 1275

StdP: 86.91

Time Zone: 3.50 (IRN)

Period: 95-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-9.4	-6.3	-14.1	1.3	-3.7	-12.1	1.5	-0.9	9.3	8.3	8.2	7.1	0.4	30	0.443

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	16.6	37.9	17.6	36.2	17.3	35.0	17.0	19.7	32.7	19.0	31.7	18.4	31.0	4.3	130

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
15.3	12.7	24.3	14.7	12.2	24.1	13.9	11.6	23.7	62.1	32.8	59.6	31.9	57.4	30.9	23.3

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 8.3	6.7	5.4	DB	-11.8	40.3	3.6	1.5	-14.4	41.4	-16.5	42.3	-18.6	43.2	-21.2	44.3	(4)
(5)			WB	-12.3	21.6	3.3	1.0	-14.7	22.3	-16.6	22.8	-18.5	23.4	-20.9	24.1	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	14.7	1.9	4.1	9.0	13.3	18.8	24.5	27.1	26.3	22.3	16.1	8.2	4.1	(6)	
	DBStd	9.39	4.36	4.02	4.08	3.57	2.86	2.56	2.27	2.11	2.74	3.36	3.75	3.20	(7)	
	HDD10.0	761	252	168	66	12	0	0	0	0	0	2	76	186	(8)	
	HDD18.3	2219	510	400	289	156	29	0	0	0	3	84	304	443	(9)	
	CDD10.0	2471	0	2	36	109	272	434	531	504	368	190	22	2	(10)	
	CDD18.3	886	0	0	1	4	43	184	273	246	121	14	0	0	(11)	
	CDH23.3	11427	0	0	11	61	631	2382	3535	3091	1478	237	1	0	(12)	
	CDH26.7	6023	0	0	1	11	185	1262	2103	1759	656	46	0	0	(13)	
(14) Wind	WSAvg	1.8	1.5	1.8	2.1	2.0	1.9	2.1	2.1	1.9	1.8	1.6	1.4	1.5	(14)	
(15) Precipitation	PrecAvg	336	35	40	53	56	33	6	4	3	2	23	39	42	(15)	
	PrecMax	507	72	79	128	124	117	31	22	46	13	91	192	101	(16)	
	PrecMin	198	4	12	7	17	2	0	0	0	0	0	2	5	(17)	
	PrecStd	74	18	20	25	31	26	8	6	9	3	23	39	23	(18)	
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	14.0	17.1	24.9	28.1	32.4	38.1	40.1	38.8	35.1	30.0	21.8	16.8	(19)	
		MCWB	6.3	8.0	11.1	13.6	15.5	17.0	18.3	17.4	16.3	13.8	10.3	7.8	(20)	
	2%	DB	12.1	14.7	21.1	24.9	30.2	36.0	38.2	37.0	33.7	28.0	19.1	13.2	(21)	
		MCWB	5.4	6.4	9.4	12.6	14.7	16.7	17.8	17.2	16.0	13.2	9.4	6.7	(22)	
	5%	DB	10.2	12.9	18.9	22.8	28.8	34.4	37.0	35.7	32.1	26.1	17.1	11.2	(23)	
		MCWB	4.5	5.6	8.6	11.9	14.4	16.4	17.7	17.2	15.4	12.6	8.8	5.6	(24)	
	10%	DB	8.4	11.0	16.8	20.8	27.0	33.0	35.2	34.2	30.8	24.0	15.1	9.8	(25)	
		MCWB	3.8	4.9	7.8	11.1	14.3	16.1	17.6	17.0	15.2	12.2	7.9	5.1	(26)	
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	7.9	8.7	11.8	14.9	17.5	19.2	21.0	20.3	18.8	15.3	12.3	8.9	(27)	
		MCDB	11.5	14.6	21.6	23.5	27.7	32.1	34.3	33.5	30.4	26.9	17.8	14.1	(28)	
	2%	WB	6.4	7.5	10.3	13.7	16.3	18.3	20.0	19.5	17.6	14.2	10.8	7.6	(29)	
		MCDB	10.1	12.5	19.0	21.5	26.6	31.5	33.4	32.2	29.7	24.7	15.9	12.1	(30)	
	5%	WB	5.2	6.5	9.4	12.8	15.6	17.7	19.3	18.8	16.8	13.4	9.8	6.5	(31)	
		MCDB	9.1	11.0	16.9	20.4	25.6	30.6	32.2	31.1	28.7	23.2	15.1	10.2	(32)	
	10%	WB	4.1	5.4	8.4	12.0	14.9	17.1	18.7	18.1	16.0	12.7	8.8	5.5	(33)	
		MCDB	7.9	9.9	15.1	18.8	24.7	29.7	31.4	30.5	27.8	21.8	14.0	8.7	(34)	
(35) Mean Daily Temperature Range	5% DB	MDBR	10.3	11.0	12.4	13.0	15.0	16.9	16.6	16.6	16.5	14.2	11.1	10.0	(35)	
		MCDBR	12.1	13.7	15.0	15.6	17.3	18.0	18.0	17.5	17.4	16.6	13.8	12.4	(36)	
	5% WB	MCWBR	7.2	7.3	7.1	6.7	6.4	5.5	5.3	5.7	6.4	6.8	6.8	7.2	(37)	
		MCWBR	10.7	11.3	13.0	13.5	15.8	17.2	17.0	16.7	16.8	15.0	11.5	10.8	(38)	
(40) Clear-Sky Solar Irradiance	taub		0.315	0.351	0.406	0.479	0.476	0.468	0.509	0.463	0.411	0.400	0.347	0.315	(40)	
	taud		2.321	2.212	2.072	1.924	1.968	2.003	1.920	2.039	2.164	2.154	2.279	2.351	(41)	
	Ebn at Noon		872	875	854	809	817	821	784	813	839	807	822	845	(42)	
	Edh at Noon		96	121	153	188	183	176	190	165	138	127	100	88	(43)	
(44) All-Sky Solar Radiation	RadAvg		2.49	3.23	4.18	5.19	6.50	7.61	7.38	6.85	5.67	4.03	2.67	2.17	(44)	
	RadStd		0.21	0.34	0.38	0.55	0.38	0.35	0.24	0.29	0.21	0.28	0.33	0.30	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (7 neighbors)		+0.32	N/A	N/A	+0.83	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page