

SEOUL OBSERVATORY, Korea, Republic of

WMO: 471080

Lat: 37.5714N

Lon: 126.9658E

Elev: 286

StdP: 14.54

Time Zone: 9.00 (E09)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	11.1	14.9	-9.5	3.3	17.2	-5.9	4.1	19.1	16.0	26.0	14.2	25.1	6.5	290	0.395

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
8	11.3	91.1	76.0	88.6	74.4	86.3	72.9	78.7	86.3	77.4	84.5	76.3	83.2	6.4	290

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
76.8	141.0	82.4	75.4	134.6	81.4	74.2	129.1	80.6	42.5	86.6	41.2	84.5	40.1	83.3	84.4

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 14.5	12.7	11.5	DB	6.7	94.4	4.9	2.9	3.2	96.6	0.3	98.3	-2.4	99.9	-5.9	102.0	(4)
(5)			WB	4.5	79.9	4.4	2.0	1.3	81.3	-1.2	82.5	-3.7	83.6	-6.8	85.1	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
Temperatures, Degree-Days and Degree-Hours	DBAvg	55.7	28.6	33.6	43.3	55.2	65.3	73.5	78.3	79.6	71.5	60.0	45.9	32.6
	DBStd	18.81	7.69	7.47	6.89	6.64	4.98	4.02	4.22	4.55	4.61	6.34	8.06	8.11
	HDD50	2094	665	460	226	24	0	0	0	0	0	9	169	541
	HDD65	4798	1129	879	673	300	57	2	0	0	7	174	572	1005
	CDD50	4184	0	1	18	180	475	705	877	918	644	319	47	0
	CDD65	1415	0	0	0	6	68	257	412	453	200	19	0	0
	CDH74	10891	0	0	0	39	405	1594	3443	4324	1036	50	0	0
	CDH80	3199	0	0	0	2	60	394	1058	1504	179	2	0	0
Wind	WSAvg	5.2	5.3	5.6	6.2	6.0	5.5	4.9	5.0	4.8	4.3	4.5	5.0	5.1
Precipitation	PrecAvg	54.8	0.7	1.0	1.7	3.3	3.9	5.3	15.6	12.4	6.0	2.0	2.0	0.9
	PrecMax	92.8	2.5	4.3	4.9	13.3	11.5	19.6	44.5	48.7	26.5	8.4	6.5	2.8
	PrecMin	30.0	0.0	0.0	0.1	0.3	0.3	0.6	4.5	2.6	0.2	0.0	0.3	0.1
	PrecStd	13.9	0.6	0.9	1.1	2.6	2.5	4.1	8.2	8.7	5.4	1.6	1.3	0.6
Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	49.2	56.3	66.3	78.3	85.3	89.3	95.0	95.1	86.8	78.7	67.4	53.1
		MCWB	41.9	46.6	51.6	59.0	62.3	68.4	76.9	76.4	70.4	63.3	56.6	45.3
	2%	DB	44.6	50.9	61.1	73.8	81.3	86.6	90.7	92.2	84.2	75.0	63.3	49.6
		MCWB	38.2	41.7	48.7	57.4	61.8	67.8	76.5	76.4	69.4	61.1	54.1	42.8
	5%	DB	41.7	47.4	57.4	69.9	78.5	84.4	87.9	89.6	82.0	72.2	60.3	46.8
		MCWB	36.1	39.1	46.3	54.4	60.6	67.2	75.3	75.8	68.1	59.8	52.4	40.9
	10%	DB	39.1	44.1	54.0	66.7	75.6	82.1	85.4	87.2	79.8	69.5	57.6	43.9
		MCWB	34.0	37.1	44.1	53.1	59.6	66.8	74.3	74.8	67.1	58.6	50.2	38.3
Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	43.5	50.0	55.5	63.9	68.3	73.8	81.0	80.4	75.6	67.3	59.9	47.4
		MCDB	47.4	53.5	63.1	72.9	76.9	79.7	87.7	87.3	81.9	73.5	64.4	51.1
	2%	WB	39.6	42.9	51.3	60.0	65.7	72.1	78.9	78.9	73.7	64.3	56.8	44.1
		MCDB	43.3	49.1	57.5	69.6	73.9	79.6	86.6	86.4	79.1	71.0	61.5	48.5
	5%	WB	37.1	40.2	47.8	57.5	63.9	70.8	77.3	77.9	71.8	62.3	53.7	41.4
		MCDB	41.0	45.8	54.8	65.8	72.6	78.8	84.1	85.3	77.8	68.9	58.9	46.1
	10%	WB	34.4	38.0	45.0	54.9	62.2	69.5	76.2	76.9	69.9	60.4	51.1	38.9
		MCDB	38.4	43.3	52.3	63.9	71.2	77.5	82.6	84.2	77.0	67.6	56.5	43.6
Mean Daily Temperature Range	5% DB	MDBR	12.2	13.4	14.7	16.1	16.7	14.5	10.7	11.3	13.9	15.4	13.4	12.2
		MCDBR	13.4	16.4	19.1	20.9	21.4	18.6	14.4	14.2	16.3	17.6	16.0	13.8
		MCWBR	9.4	9.9	10.3	9.3	8.2	6.4	5.1	4.8	6.2	7.5	9.7	10.1
	5% WB	MCDBR	11.9	14.2	16.8	17.0	16.2	13.6	11.1	11.6	12.0	14.0	13.5	12.7
		MCWBR	9.8	10.4	11.0	9.7	8.6	6.0	4.9	4.9	5.9	8.2	10.6	10.8
Clear-Sky Solar Irradiance	taub	0.435	0.490	0.573	0.619	0.631	0.702	0.671	0.583	0.510	0.503	0.483	0.433	
	taud	1.942	1.848	1.710	1.658	1.683	1.606	1.719	1.923	2.045	1.942	1.932	1.971	
	Ebn at Noon	221	225	219	219	220	205	210	226	235	219	203	211	
	Edh at Noon	44	55	70	77	77	83	74	59	49	49	45	40	
All-Sky Solar Radiation	RadAvg	793	1037	1352	1576	1772	1656	1289	1376	1310	1136	773	695	
	RadStd	49	82	134	111	164	171	197	194	143	80	76	48	

Historical Trends

	DBAvg	Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD50	HDD65	CDD50	CDD65
Station Only	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
Regional (47 neighbors)	N/A	N/A	-2.11	N/A	N/A	N/A	N/A	N/A	+171	+113
	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	+169	+90

Nomenclature: See separate page