

YUANMOU, China

WMO: 567630

Lat: 25.7224N

Lon: 101.8717E

Elev: 1120

StdP: 88.57

Time Zone: 8.00 (E08)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
12	5.2	6.6	-4.6	2.9	24.0	-3.1	3.3	23.5	7.6	22.4	6.9	22.9	0.5	90	0.298

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
6	8.6	36.1	19.4	34.8	19.4	33.7	19.6	23.7	29.0	23.2	28.6	22.9	28.3	3.7	160

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
22.6	19.8	25.5	22.1	19.2	25.1	21.6	18.7	24.9	78.2	29.1	76.2	28.7	74.5	28.3	29.0

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 7.0	6.1	5.3	DB	2.5	37.9	1.4	1.5	1.5	39.0	0.7	39.9	0.0	40.7	-1.0	41.7	(4)
(5)			WB	1.9	25.1	1.2	0.9	1.0	25.7	0.3	26.3	-0.4	26.8	-1.3	27.4	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6)	Temperatures, Degree-Days and Degree-Hours	DBAvg	22.4	15.6	18.3	21.6	24.9	26.7	27.1	26.3	26.2	25.0	22.7	18.5	15.4	(6)
(7)		DBStd	5.02	2.47	2.78	2.77	3.06	3.75	3.09	2.26	2.04	2.83	2.71	2.31	2.36	(7)
(8)		HDD10.0	3	1	1	0	0	0	0	0	0	0	0	0	1	(8)
(9)		HDD18.3	254	87	31	8	2	2	0	0	0	1	3	26	95	(9)
(10)		CDD10.0	4523	176	234	359	448	519	513	506	501	451	394	254	167	(10)
(11)		CDD18.3	1733	4	31	108	201	262	263	248	243	202	139	29	3	(11)
(12)		CDH23.3	16924	107	409	1202	2236	3033	2834	2181	2017	1585	949	296	74	(12)
(13)	CDH26.7	6958	6	82	423	1067	1543	1308	841	762	592	288	43	3	(13)	
(14)	Wind	WSAvg	2.0	2.2	2.6	2.7	2.5	2.2	1.6	1.4	1.5	1.7	1.5	1.8	(14)	
(15)	Precipitation	PrecAvg	619	4	3	5	13	40	114	141	125	92	57	20	7	(15)
(16)		PrecMax	907	17	13	29	70	121	228	302	312	189	230	93	42	(16)
(17)		PrecMin	287	0	0	0	0	0	14	45	58	30	2	0	0	(17)
(18)		PrecStd	125	5	4	7	17	32	53	59	54	43	45	23	10	(18)
(19)	Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	27.4	30.8	33.2	36.2	38.2	37.8	35.4	34.9	34.4	32.1	29.6	27.1	(19)
MCWB			12.7	13.9	15.0	17.0	19.5	21.1	21.9	22.0	21.5	19.8	16.3	13.2	(20)	
2%		DB	25.8	29.0	31.7	34.7	36.3	35.6	33.6	33.3	32.9	30.8	27.9	25.3	(21)	
		MCWB	12.0	13.3	14.6	16.4	18.8	21.2	22.3	22.1	21.4	19.2	16.0	13.0	(22)	
5%		DB	24.5	27.5	30.5	33.5	34.9	33.9	32.3	32.0	31.6	29.7	26.5	23.9	(23)	
		MCWB	11.8	12.8	14.2	16.2	18.8	21.4	22.3	22.0	21.1	19.0	15.6	12.6	(24)	
10%		DB	23.0	26.1	29.2	32.2	33.5	32.5	31.0	30.7	30.2	28.4	25.1	22.3	(25)	
		MCWB	11.3	12.3	13.9	15.9	18.7	21.5	22.3	21.9	20.9	18.7	15.1	12.5	(26)	
(27)	Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	14.2	15.4	16.6	18.8	22.5	24.1	24.5	24.2	23.2	21.6	19.2	15.4	(27)
MCD B			23.9	27.8	28.5	30.0	29.8	30.0	29.7	29.6	28.5	27.2	24.2	23.0	(28)	
2%		WB	13.2	14.1	15.7	17.9	21.6	23.4	23.8	23.5	22.6	20.9	18.0	14.2	(29)	
		MCD B	22.9	26.4	27.8	30.3	29.1	29.4	28.9	28.8	28.3	26.7	23.8	22.2	(30)	
5%		WB	12.5	13.4	15.2	17.3	21.0	22.9	23.3	23.1	22.1	20.4	17.1	13.5	(31)	
		MCD B	22.0	25.4	27.2	29.6	28.5	29.0	28.5	28.3	27.9	26.3	23.2	21.4	(32)	
10%		WB	11.9	12.7	14.6	16.8	20.4	22.5	22.9	22.6	21.7	19.9	16.2	12.8	(33)	
		MCD B	21.1	24.4	26.6	28.9	28.5	28.9	28.1	27.8	27.4	25.7	22.6	20.6	(34)	
(35)	Mean Daily Temperature Range	5% DB	MDBR	15.1	15.2	14.5	12.8	10.4	8.6	7.8	8.6	8.5	9.8	12.9	14.1	(35)
MCDBR			17.3	17.1	16.4	14.6	12.6	10.6	10.2	10.9	10.6	11.9	15.2	16.4	(36)	
MCWBR			6.2	5.6	4.8	3.7	3.0	2.8	2.7	2.6	2.4	3.0	4.8	5.9	(37)	
5% WB		MCD BR	15.7	15.8	14.0	12.6	9.7	8.6	8.3	8.9	8.8	9.0	12.1	14.3	(38)	
		MCWBR	6.2	5.6	4.5	3.6	3.2	3.2	2.9	2.7	2.6	2.7	4.4	5.7	(39)	
(40)	Clear-Sky Solar Irradiance	taub	0.339	0.357	0.499	0.501	0.457	0.435	0.455	0.496	0.469	0.430	0.377	0.360	(40)	
taud		2.398	2.355	1.922	1.994	2.222	2.337	2.266	2.124	2.185	2.265	2.340	2.347	(41)		
Ebn at Noon		913	920	802	811	844	857	839	805	819	833	862	870	(42)		
Edh at Noon		104	117	190	182	144	128	137	157	145	127	110	106	(43)		
(44)	All-Sky Solar Radiation	RadAvg	4.16	5.06	5.47	5.71	5.38	4.76	4.40	4.42	3.92	3.73	4.02	3.67	(44)	
(45)		RadStd	0.34	0.48	0.51	0.52	0.65	0.50	0.31	0.38	0.34	0.46	0.46	0.33	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46)	Station Only	+0.46	N/A	N/A	+0.99	-0.19	-0.32	N/A	N/A	N/A	N/A
(47)	Regional (6 neighbors)	+0.39	N/A	N/A	+0.82	N/A	-0.22	N/A	N/A	N/A	N/A

Nomenclature: See separate page