

SANYA LIUDAOLING, China

WMO: 599480

Lat: 18.2256N

Lon: 109.5914E

Elev: 420

StdP: 96.38

Time Zone: 8.00 (E08)

Period: 09-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	12.2	13.6	6.9	6.5	13.2	9.0	7.5	14.7	14.5	17.0	13.5	17.2	7.5	40	0.445

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
6	3.6	30.0	26.3	29.3	26.1	28.8	25.8	27.1	28.8	26.7	28.3	26.4	27.8	3.2	220

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
26.6	23.3	27.9	26.2	22.8	27.5	26.0	22.4	27.2	88.3	29.0	86.7	28.5	85.3	28.0	28.6

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature								
1%	2.5%	5%	Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years		
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	
13.0	11.6	10.4	DB	10.1	31.1	1.7	0.7	8.9	31.6	7.9	32.0	6.9	32.4	5.6	32.9
			WB	7.2	27.4	1.3	0.6	6.2	27.9	5.4	28.2	4.7	28.6	3.7	29.0

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
Temperatures, Degree-Days and Degree-Hours	DBAvg	23.4	18.8	19.9	21.7	24.1	26.1	26.7	26.0	25.9	25.5	23.8	22.3	19.7
	DBStd	3.17	2.21	2.38	2.05	1.53	1.24	1.09	1.32	1.12	1.13	1.16	1.48	2.31
	HDD10.0	1	1	0	0	0	0	0	0	0	0	0	0	0
	HDD18.3	53	21	12	4	0	0	0	0	0	0	0	1	16
	CDD10.0	4884	273	277	361	423	498	499	497	493	466	429	369	299
	CDD18.3	1896	35	56	107	173	240	249	238	235	216	171	121	57
	CDH23.3	10397	7	31	143	674	1757	2156	1804	1725	1365	544	165	25
CDH26.7	1288	0	0	1	39	268	354	256	200	149	21	1	0	
Wind	WSAvg	5.2	6.8	5.6	5.3	4.7	3.7	3.8	3.9	4.2	4.5	6.1	7.2	7.1
Precipitation	PrecAvg	1593	9	10	21	67	132	184	256	239	302	267	82	24
	PrecMax	2212	57	48	114	169	360	426	615	622	643	859	275	141
	PrecMin	1017	0	0	1	0	14	52	108	48	120	32	0	1
	PrecStd	308	12	12	28	49	87	85	110	119	145	183	84	31
Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	24.4	25.3	26.6	28.8	31.0	30.6	30.5	29.8	29.3	28.2	26.5	25.0
		MCWB	21.5	22.0	23.0	24.7	26.3	26.4	26.4	26.5	26.0	24.3	22.5	22.0
	2%	DB	23.0	24.2	25.6	27.7	29.7	29.9	29.5	29.0	28.7	27.2	25.7	24.1
		MCWB	20.2	21.6	22.8	24.5	26.0	26.4	26.1	26.1	25.7	23.6	22.7	21.5
	5%	DB	22.1	23.5	24.8	27.0	29.0	29.2	28.8	28.4	28.2	26.6	25.0	23.2
		MCWB	20.0	21.2	22.5	24.3	25.8	26.1	25.8	25.8	25.4	23.2	22.5	20.9
	10%	DB	21.4	22.6	24.1	26.2	28.2	28.6	28.1	27.9	27.6	25.9	24.3	22.4
		MCWB	19.6	20.9	22.2	24.1	25.5	25.9	25.5	25.4	25.1	22.9	22.2	20.5
Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	22.5	22.7	24.1	25.6	27.4	27.4	27.2	27.4	27.0	25.4	24.1	22.7
		MCDB	23.4	24.1	25.2	27.2	29.4	29.3	29.3	28.8	28.5	27.1	25.0	23.9
	2%	WB	21.4	22.2	23.5	25.1	26.7	27.0	26.6	26.7	26.4	24.7	23.6	22.1
		MCDB	22.1	23.3	24.6	26.5	28.4	28.8	28.5	28.2	27.9	26.1	24.5	23.2
	5%	WB	20.7	21.7	23.0	24.7	26.3	26.6	26.2	26.2	26.0	24.2	23.2	21.6
		MCDB	21.5	22.7	24.0	26.0	27.8	28.3	27.8	27.5	27.4	25.4	24.1	22.6
	10%	WB	20.1	21.4	22.6	24.4	26.0	26.3	25.9	25.9	25.6	23.7	22.9	21.1
		MCDB	21.1	22.3	23.6	25.6	27.3	27.7	27.4	27.1	26.9	24.9	23.8	22.1
Mean Daily Temperature Range	5% DB	MDBR	4.2	4.3	4.0	4.0	4.2	3.6	3.6	3.5	3.8	3.9	3.7	4.3
		MCDBR	4.4	4.4	4.4	4.4	4.9	4.4	4.4	4.2	4.6	4.7	4.3	4.3
		MCWBR	2.4	2.1	2.0	2.0	2.3	2.3	2.4	2.6	2.6	2.7	2.5	2.7
	5% WB	MCDBR	3.5	3.8	3.6	3.9	4.3	4.0	4.0	3.8	4.1	3.8	3.4	3.9
		MCWBR	2.3	1.9	1.8	2.0	2.3	2.4	2.4	2.6	2.6	2.4	2.0	2.6
Clear-Sky Solar Irradiance	taub		0.467	0.481	0.571	0.541	0.450	0.440	0.423	0.444	0.492	0.525	0.477	0.492
	taud		2.111	2.110	1.895	2.037	2.360	2.406	2.449	2.373	2.203	2.045	2.158	2.046
	Ebn at Noon		809	822	761	786	851	851	867	856	815	772	794	769
	Edh at Noon		150	158	202	176	126	119	114	124	146	166	142	156
All-Sky Solar Radiation	RadAvg		3.67	4.32	4.71	5.51	5.82	5.47	5.38	5.13	4.80	4.48	4.00	3.44
	RadStd		0.46	0.60	0.35	0.43	0.38	0.45	0.52	0.36	0.49	0.54	0.34	0.37

Historical Trends

	DBAvg	Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)
Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Regional (5 neighbors)	+0.26	N/A	N/A	+0.32	N/A	N/A	N/A	N/A	+90	+83

Nomenclature: See separate page