

SOUTH ALABAMA, AL, USA

WMO: 722275

Lat: 31.309N

Lon: 86.394W

Elev: 310

StdP: 14.53

Time Zone: -6.00 (NAC)

Period: 06-19

WBAN: 53843

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	28.1	31.6	10.0	9.3	36.1	14.5	11.6	41.0	20.8	49.4	18.8	47.9	5.1	0	0.356

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	19.1	98.3	76.1	96.6	76.1	94.9	75.8	79.6	92.3	78.7	90.9	78.1	89.8	6.1	310

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
76.4	139.2	84.8	75.5	135.2	84.0	74.9	132.2	83.5	43.1	92.5	42.3	91.0	41.6	90.1	82.4

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 17.1	14.8	12.3	DB	22.5	101.3	4.1	2.9	19.6	103.4	17.2	105.1	14.9	106.7	12.0	108.9	(4)
(5)			WB	19.9	81.0	3.9	1.2	17.1	81.8	14.8	82.5	12.7	83.2	9.8	84.0	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	69.2	51.3	56.1	62.2	68.2	76.1	82.7	83.9	83.9	80.1	70.5	59.2	55.6		
	DBStd	13.57	10.14	9.64	8.52	6.29	5.32	3.28	3.07	3.17	4.60	7.71	8.16	9.52		
	HDD50	226	104	45	11	1	0	0	0	0	0	0	15	50		
	HDD65	1470	435	275	157	37	4	0	0	0	0	37	210	315		
	CDD50	7246	146	216	388	547	810	980	1052	1050	904	637	291	225		
	CDD65	3015	12	25	69	134	349	530	587	585	454	208	37	25		
	CDH74	30698	43	145	554	1329	3468	5794	6451	6262	4401	1877	269	105		
	CDH80	14068	0	21	117	385	1585	2964	3202	3022	2040	683	43	6		
(14) Wind	WSAvg	4.6	5.8	5.7	5.6	5.1	4.1	3.7	3.5	3.5	3.9	4.7	4.7	5.3		
(15) Precipitation	PrecAvg	57.8	5.3	4.9	5.9	4.7	3.7	5.0	6.1	5.1	4.5	3.2	4.3	5.1		
	PrecMax	75.8	11.6	11.7	14.2	10.5	9.2	10.3	16.4	10.1	20.6	12.8	11.9	13.5		
	PrecMin	40.3	1.6	1.7	0.6	1.8	0.4	1.8	2.0	1.5	1.0	0.2	1.2	1.8		
	PrecStd	8.4	2.1	2.2	3.3	2.2	2.1	2.4	3.0	2.0	3.7	2.7	2.5	2.6		
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	78.3	82.9	86.8	89.3	96.6	100.4	100.2	100.5	98.6	93.9	84.8	80.4		
		MCWB	66.4	67.9	65.5	68.6	72.5	74.4	77.5	76.2	75.3	72.0	69.3	68.4		
	2%	DB	74.7	78.5	83.4	86.9	93.6	97.6	97.6	97.6	95.7	90.2	80.2	77.0		
		MCWB	65.5	65.1	65.9	67.8	71.6	75.7	77.1	76.9	75.1	71.6	67.4	67.8		
	5%	DB	71.8	74.8	80.2	84.5	91.1	95.6	95.8	95.5	93.2	87.2	77.0	73.9		
		MCWB	64.3	63.7	64.3	66.6	71.0	75.3	76.8	77.0	74.7	71.2	65.2	66.1		
	10%	DB	68.0	71.7	76.7	82.0	88.6	93.5	93.5	93.3	90.7	83.8	73.9	71.0		
		MCWB	61.2	62.2	62.8	65.3	70.4	75.0	76.5	76.7	74.6	69.2	63.7	65.0		
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	69.7	70.6	70.9	74.1	76.1	79.7	80.4	80.7	79.0	77.4	73.9	73.0		
		MCDB	74.6	77.4	78.7	82.6	87.9	92.5	93.5	92.8	91.1	85.3	79.3	77.8		
	2%	WB	67.8	68.7	69.1	72.1	75.0	78.4	79.4	79.8	77.8	75.6	71.1	69.7		
		MCDB	73.3	75.4	76.3	80.5	86.3	91.3	92.8	92.1	89.7	82.9	76.3	73.8		
	5%	WB	65.3	66.6	67.6	70.1	73.9	77.5	78.5	79.0	77.0	74.2	68.3	67.8		
		MCDB	70.5	73.0	74.9	79.1	85.4	90.4	91.0	90.7	88.1	82.2	74.8	72.2		
	10%	WB	62.5	64.3	65.7	68.5	72.8	76.7	77.8	78.2	76.1	72.7	65.7	65.3		
		MCDB	67.9	70.2	74.6	77.5	83.8	88.5	89.9	89.0	86.2	80.9	72.2	70.8		
(35) Mean Daily Temperature Range	5% DB	MDBR	21.4	22.1	23.4	23.8	22.7	20.3	19.1	18.6	19.6	22.3	23.9	19.8		
		MCDBR	21.6	23.1	24.6	26.0	25.5	23.4	21.8	22.0	22.3	23.3	24.3	20.9		
		MCWBR	14.1	13.0	10.8	10.6	8.6	6.9	6.4	6.6	7.1	9.2	13.9	13.8		
	5% WB	MCDBR	18.7	19.1	18.4	19.8	20.4	20.2	19.6	18.6	18.4	18.9	19.3	17.5		
		MCWBR	13.9	13.1	10.4	10.5	7.7	7.0	6.4	6.5	6.7	9.1	13.2	13.9		
(40) Clear-Sky Solar Irradiance	taub		0.325	0.335	0.359	0.383	0.431	0.467	0.523	0.502	0.433	0.372	0.345	0.329		
	taud		2.532	2.508	2.436	2.373	2.272	2.230	2.082	2.138	2.309	2.455	2.474	2.531		
	Ebn at Noon		287	294	293	288	273	262	247	251	266	277	276	279		
	Edh at Noon		27	30	35	39	43	45	52	49	39	32	29	26		
(44) All-Sky Solar Radiation	RadAvg		937	1120	1512	1849	2026	1948	1879	1748	1590	1383	1061	815		
	RadStd		63	143	128	154	131	160	115	113	115	157	93	86		

Historical Trends

	DBAvg	Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD50	HDD65	CDD50	CDD65
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)
Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Regional (47 neighbors)	+0.81	N/A	N/A	N/A	N/A	N/A	N/A	N/A	+284	+176

Nomenclature: See separate page