

VISALIA, CA, USA

WMO: 723896

Lat: 36.317N

Lon: 119.400W

Elev: 90

StdP: 100.25

Time Zone: -8.00 (NAP)

Period: 94-19

WBAN: 93144

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
12	-1.2	0.3	-5.0	2.5	5.5	-2.8	3.0	4.5	7.5	11.3	6.2	11.2	0.9	120	0.420

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	17.2	37.9	22.1	37.1	21.7	36.0	21.2	23.8	35.4	22.9	34.2	22.0	33.3	3.3	300

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
20.0	14.9	29.6	18.8	13.7	29.1	17.7	12.8	28.6	71.1	35.1	68.0	34.5	64.6	33.2	28.6

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
7.0	5.6	4.9	DB	-2.9	41.0	1.6	1.1	-4.0	41.8	-5.0	42.4	-5.9	43.0	-7.1	43.8	(4)
			WB	-3.5	25.2	1.8	1.0	-4.8	25.9	-5.9	26.5	-6.9	27.1	-8.2	27.8	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6)	Temperatures, Degree-Days and Degree-Hours	DBAvg	17.3	8.6	10.5	13.6	16.1	20.3	24.2	26.8	25.8	23.2	17.7	12.0	8.0	(6)
		DBStd	7.17	2.79	2.71	3.04	3.65	3.56	3.30	2.42	2.40	3.01	3.18	3.04	2.92	(7)
		HDD10.0	183	62	24	5	1	0	0	0	0	0	15	76		(8)
		HDD18.3	1341	302	220	151	86	21	2	0	2	48	189	319		(9)
		CDD10.0	2838	18	38	116	184	318	426	522	491	396	240	76	15	(10)
		CDD18.3	952	0	0	2	19	80	178	263	232	148	30	0	0	(11)
		CDH23.3	12813	0	1	67	346	1140	2427	3498	2970	1855	494	17	0	(12)
(14)	Wind	CDH26.7	6859	0	0	10	111	513	1345	2053	1702	965	159	1	0	(13)
		WSAvg	2.0	1.5	1.8	2.0	2.5	2.8	2.4	2.1	1.9	1.6	1.4	1.5		(14)
		PrecAvg	252	44	47	42	26	6	2	1	6	11	34	36		(15)
		PrecMax	460	196	147	128	122	57	19	6	39	49	90	96		(16)
		PrecMin	126	0	2	0	0	0	0	0	0	0	0	0		(17)
		PrecStd	88	41	43	33	28	12	4	2	11	13	25	24		(18)
		DB	19.0	22.6	27.9	32.5	37.2	39.5	39.9	39.0	37.5	33.7	25.6	19.0		(19)
(20)	Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	MCWB	12.5	15.2	17.0	17.7	20.7	22.5	23.1	22.9	21.1	19.2	15.5	13.1		(20)
		DB	17.3	20.0	25.1	29.6	34.0	37.5	37.9	37.4	36.0	30.9	23.0	17.2		(21)
		MCWB	12.3	14.4	15.9	17.2	19.1	21.2	22.6	22.0	20.5	18.0	14.9	12.0		(22)
		DB	15.8	17.8	22.8	27.4	32.2	36.0	37.1	36.2	34.0	28.0	21.0	15.0		(23)
		MCWB	12.0	13.0	14.9	16.0	18.2	20.5	22.2	21.5	20.0	16.8	14.2	11.1		(24)
		DB	13.8	16.2	21.1	24.8	29.3	33.7	35.7	34.4	32.5	26.3	18.6	13.2		(25)
		MCWB	11.0	12.0	14.2	15.2	17.3	19.5	21.6	20.9	19.5	16.2	13.2	10.3		(26)
(27)	Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	WB	15.3	16.3	18.3	19.5	21.8	24.2	25.5	24.8	23.3	20.4	17.1	14.8		(27)
		MCDB	17.3	20.6	25.8	29.3	35.2	37.0	37.0	36.2	33.9	30.4	22.9	17.4		(28)
		WB	13.3	15.0	16.9	17.9	20.2	22.6	24.1	23.4	21.8	19.0	15.9	13.0		(29)
		MCDB	15.7	18.8	23.7	27.6	32.3	35.1	35.5	34.6	32.6	28.4	21.4	15.5		(30)
		WB	12.3	13.8	15.6	16.7	19.0	21.4	23.1	22.5	20.8	17.8	14.7	11.9		(31)
		MCDB	14.5	17.3	21.8	25.9	30.2	33.3	34.4	33.7	32.1	26.7	19.8	14.2		(32)
		WB	11.3	12.5	14.4	15.6	17.9	20.3	22.3	21.7	20.0	16.8	13.6	10.7		(33)
(34)	Mean Daily Temperature Range	MCDB	13.7	15.7	20.0	23.8	28.3	32.0	33.4	32.8	31.1	24.8	17.9	12.9		(34)
		MDBR	9.3	10.7	12.9	14.3	15.4	17.1	17.2	17.7	17.2	15.6	12.4	9.9		(35)
		5% DB	12.5	13.4	16.2	18.1	18.7	19.3	18.0	18.6	18.9	18.5	15.8	12.6		(36)
		MCWBR	8.4	8.6	8.6	8.0	7.1	6.7	6.2	6.5	6.9	8.1	8.8	8.3		(37)
		5% WB	9.8	12.2	14.8	16.9	17.8	18.2	16.9	17.7	17.7	16.5	13.9	9.3		(38)
		MCWBR	7.1	8.2	8.3	7.8	7.1	6.7	6.3	6.6	6.9	7.4	8.3	6.5		(39)
		taub	0.366	0.377	0.376	0.386	0.386	0.377	0.402	0.377	0.376	0.395	0.376	0.364		(40)
(41)	Clear-Sky Solar Irradiance	taud	2.284	2.278	2.298	2.295	2.321	2.348	2.310	2.355	2.365	2.256	2.270	2.293		(41)
		Ebn at Noon	807	850	888	896	897	901	876	894	877	816	788	782		(42)
		Edh at Noon	101	114	122	129	128	125	129	120	113	115	102	95		(43)
(44)	All-Sky Solar Radiation	RadAvg	2.45	3.54	5.05	6.41	7.57	8.44	8.04	7.42	6.20	4.52	3.08	2.26		(44)
		RadStd	0.34	0.39	0.42	0.44	0.41	0.28	0.29	0.21	0.17	0.24	0.17	0.30		(45)

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
(46)	Station Only	+0.69	N/A	N/A	+0.48	N/A	N/A	N/A	N/A	N/A	N/A
(47)	Regional (21 neighbors)	+0.58	N/A	-1.08	+0.55	N/A	N/A	-29	-143	+195	+76

Nomenclature: See separate page