

RED BLUFF, CA, USA

WMO: 725910

Lat: 40.152N

Lon: 122.254W

Elev: 108

StdP: 100.04

Time Zone: -8.00 (NAP)

Period: 95-19

WBAN: 24216

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
12	-0.8	0.7	-11.1	1.5	13.5	-8.6	1.8	13.7	15.4	11.5	13.4	10.4	2.2	320	0.486

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	17.0	40.6	20.2	38.7	19.6	37.2	19.3	22.5	35.0	21.6	34.0	20.7	33.1	3.8	150

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
18.4	13.5	27.6	17.4	12.6	26.9	16.2	11.7	26.0	66.4	35.3	63.0	33.9	60.0	33.3	26.3

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	DB	WB
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 11.6	9.9	8.4	-3.6	44.0	1.6	1.4	-4.7	45.0	-5.7	45.8	-6.6	46.5	-7.8	47.5		
(5)			-4.6	24.3	1.8	1.1	-5.9	25.1	-7.0	25.8	-8.0	26.4	-9.3	27.2		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	17.5	8.7	10.4	12.8	15.4	20.0	25.0	27.9	26.7	23.9	18.3	12.1	8.5		
	DBStd	7.68	2.94	3.11	3.46	3.97	4.22	4.11	2.93	2.72	3.56	3.55	3.44	2.97		
	HDD10.0	187	61	29	12	3	0	0	0	0	0	0	17	64		
	HDD18.3	1379	299	222	174	106	31	3	0	0	3	45	189	306		
	CDD10.0	2927	19	41	98	164	311	449	556	519	417	256	79	17		
	CDD18.3	1078	0	0	3	18	83	203	297	261	170	43	2	0		
	CDH23.3	14823	3	8	69	294	1157	2776	4246	3496	2157	583	36	0		
	CDH26.7	8455	0	0	11	97	542	1602	2659	2118	1205	216	5	0		
(14) Wind	WSAvg	3.4	3.2	3.9	3.9	3.8	3.7	3.7	3.0	2.9	3.1	3.3	3.1	3.5		
(15) Precipitation	PrecAvg	575	105	92	75	36	20	10	2	5	13	33	85	93		
	PrecMax	1244	258	219	234	125	84	41	18	40	126	131	214	261		
	PrecMin	183	6	0	15	0	0	0	0	0	0	0	9	0		
	PrecStd	193	64	72	48	33	23	12	4	9	22	35	61	63		
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	23.1	24.7	28.1	32.3	37.5	42.4	43.3	42.2	40.2	34.7	27.2	20.6		
		MCWB	11.1	13.3	14.7	16.8	19.1	20.3	20.9	21.1	18.7	17.1	14.3	10.4		
	2%	DB	19.4	21.5	25.2	29.5	34.6	39.3	40.7	39.5	37.4	31.3	23.8	17.4		
		MCWB	9.9	11.8	13.9	15.7	18.1	19.5	20.6	19.7	18.3	15.8	13.4	9.6		
	5%	DB	16.3	18.7	22.8	27.0	32.3	37.0	38.9	37.6	35.6	29.1	21.2	15.2		
		MCWB	9.7	10.6	13.1	15.0	17.3	18.9	20.0	19.6	17.8	15.1	12.4	9.7		
	10%	DB	13.8	16.3	20.2	24.0	29.7	34.6	37.2	36.0	33.5	26.7	18.4	13.6		
		MCWB	9.2	10.2	12.0	13.8	16.3	18.2	19.9	18.9	17.4	14.2	11.5	9.7		
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	13.6	14.7	16.5	18.6	21.1	23.5	23.6	24.2	21.8	18.5	16.3	14.1		
		MCDB	16.2	19.5	23.7	27.9	32.6	35.5	36.1	37.1	33.2	29.8	23.3	15.6		
	2%	WB	12.1	13.5	15.2	16.9	19.6	21.7	22.6	22.0	20.1	17.3	14.9	12.8		
		MCDB	14.6	18.1	22.3	26.4	31.3	33.6	35.5	34.2	32.0	28.2	20.3	14.0		
	5%	WB	11.2	12.3	14.1	15.8	18.4	20.4	21.7	20.9	19.1	16.3	13.8	11.7		
		MCDB	13.9	16.4	20.4	24.6	29.7	32.5	34.6	33.0	31.6	25.8	18.3	13.2		
	10%	WB	10.4	11.3	13.0	14.6	17.2	19.5	20.9	20.1	18.2	15.3	12.8	10.6		
		MCDB	13.2	15.0	18.6	22.2	27.6	31.9	33.8	32.3	31.0	24.0	16.8	12.5		
(35) Mean Daily Temperature Range	5% DB	MDBR	9.5	10.2	11.6	12.9	14.3	15.4	17.0	17.3	16.8	14.4	11.2	9.2		
		MCDBR	15.4	15.4	16.4	17.7	18.5	18.4	19.2	19.4	19.6	18.3	16.0	13.3		
	5% WB	MCWBR	8.2	7.9	7.9	7.6	6.8	6.2	6.2	6.6	7.0	7.5	7.6	7.5		
		MCWBR	9.9	11.3	14.1	16.1	17.0	16.8	17.3	17.3	17.2	15.5	12.4	7.1		
(40) Clear-Sky Solar Irradiance	taub	taub	0.314	0.316	0.336	0.351	0.341	0.349	0.354	0.337	0.339	0.329	0.310	0.314		
		taud	2.528	2.530	2.478	2.428	2.497	2.478	2.452	2.494	2.480	2.522	2.553	2.527		
	Ebn at Noon	Ebn at Noon	855	907	921	924	935	924	915	926	904	878	854	825		
		Edh at Noon	74	85	99	111	106	108	110	103	98	84	71	69		
(44) All-Sky Solar Radiation	RadAvg	RadAvg	2.07	2.99	4.24	5.78	7.12	8.11	8.22	7.31	5.85	3.98	2.44	1.76		
	RadStd	RadStd	0.38	0.42	0.53	0.58	0.51	0.44	0.26	0.25	0.24	0.34	0.25	0.35		

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only		+0.59	N/A	-1.27	N/A	N/A	N/A	-41	-143	+202	+112
(47) Regional (23 neighbors)		+0.37	N/A	N/A	N/A	N/A	N/A	N/A	N/A	+116	+27

Nomenclature: See separate page