

DODGE COUNTY AP, WI, USA

WMO: 726509

Lat: 43.426N

Lon: 88.703W

Elev: 285

StdP: 97.94

Time Zone: -6.00 (NAC)

Period: 97-19

WBAN: 04898

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-21.2	-18.6	-26.2	0.4	-20.0	-23.6	0.5	-17.6	10.8	-2.9	9.4	-3.3	2.8	280	0.544

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	10.2	31.0	23.0	29.0	21.9	27.8	21.1	25.0	28.6	23.8	27.2	22.8	26.1	4.9	200

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
23.9	19.4	27.0	22.7	18.0	25.7	22.0	17.3	25.2	78.2	28.3	72.7	27.8	68.7	25.9	31.6

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	DB	WB
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 10.4	8.8	7.9	-25.4	33.2	3.5	1.6	-27.9	34.4	-29.9	35.4	-31.9	36.3	-34.5	37.5		
(5)			-25.6	26.4	3.4	1.9	-28.1	27.8	-30.1	28.9	-32.0	30.0	-34.4	31.4	(4)	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	8.3	-6.9	-5.1	1.2	7.8	14.1	19.3	21.6	20.4	17.0	9.9	3.0	-4.0	(6)	
	DBStd	11.21	6.58	6.32	6.27	5.02	4.67	3.69	2.95	2.87	4.35	5.01	5.44	6.26	(7)	
	HDD10.0	2061	523	423	283	99	14	0	0	0	3	64	216	436	(8)	
	HDD18.3	3978	781	656	533	318	147	32	6	12	76	264	459	694	(9)	
	CDD10.0	1430	0	1	9	33	141	279	360	324	212	63	7	1	(10)	
	CDD18.3	305	0	0	1	2	16	62	108	78	36	4	0	0	(11)	
	CDH23.3	2384	0	0	3	24	151	507	861	524	282	32	0	0	(12)	
	CDH26.7	582	0	0	0	3	31	134	233	109	67	4	0	0	(13)	
(14) Wind	WSAvg	3.5	3.7	3.8	3.8	4.2	3.8	3.1	2.6	2.4	2.9	3.5	3.7	3.7	(14)	
(15) Precipitation	PrecAvg	849	35	32	46	84	97	131	106	90	80	64	47	39	(15)	
	PrecMax	1060	75	77	122	166	249	330	236	290	155	141	153	89	(16)	
	PrecMin	671	4	0	4	16	25	28	36	36	13	14	7	5	(17)	
	PrecStd	107	19	18	32	39	50	64	52	62	36	37	31	21	(18)	
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	8.6	13.0	22.6	27.0	29.9	32.4	33.0	31.4	31.2	27.1	19.8	13.9	(19)	
		MCWB	6.9	10.2	16.3	16.2	19.7	22.1	23.7	24.1	22.4	20.8	13.6	12.7	(20)	
	2%	DB	5.1	7.9	17.3	22.5	27.3	29.9	31.1	29.1	28.3	23.0	16.2	9.8	(21)	
		MCWB	3.3	5.8	13.1	14.8	18.7	21.5	23.8	22.6	21.1	17.4	11.8	8.1	(22)	
	5%	DB	2.9	5.1	13.1	18.9	24.8	27.9	29.0	27.6	26.8	21.0	13.6	6.1	(23)	
		MCWB	1.9	3.2	9.6	12.5	17.2	20.7	22.4	21.6	20.0	16.6	10.3	4.7	(24)	
	10%	DB	2.0	2.7	10.1	16.4	22.5	26.4	27.6	26.3	24.4	17.9	11.3	3.6	(25)	
		MCWB	1.1	1.5	6.9	10.6	16.2	19.7	21.5	20.3	18.8	14.3	8.4	2.4	(26)	
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	7.0	11.1	17.5	18.1	22.2	25.7	27.9	25.9	24.4	22.2	15.7	12.9	(27)	
		MCDB	7.6	12.5	19.3	23.5	27.2	29.2	29.8	29.2	27.8	25.8	18.7	13.6	(28)	
	2%	WB	3.5	6.3	13.9	15.7	20.3	24.0	25.5	24.2	22.8	19.4	12.9	8.5	(29)	
		MCDB	4.6	7.7	16.5	20.6	24.9	27.4	29.0	27.7	26.6	21.9	15.3	9.4	(30)	
	5%	WB	2.2	3.5	10.7	13.7	19.0	22.3	24.0	23.2	21.3	17.3	10.9	4.8	(31)	
		MCDB	3.1	4.8	12.8	18.4	23.1	26.4	27.3	26.2	24.8	19.4	13.2	5.9	(32)	
	10%	WB	0.8	1.9	7.0	11.4	17.4	20.8	22.9	22.1	20.0	14.9	8.4	2.6	(33)	
		MCDB	1.6	2.9	9.5	15.7	20.7	24.8	26.1	24.8	23.3	17.7	10.7	3.6	(34)	
(35) Mean Daily Temperature Range	5% DB	MDBR	7.3	7.9	8.6	10.1	10.6	10.2	10.2	9.9	10.9	9.5	7.9	6.9	(35)	
		MCDBR	7.5	9.3	12.5	14.9	13.4	11.9	11.2	10.9	12.7	12.7	11.5	8.5	(36)	
	5% WB	MCWBR	6.5	7.4	8.7	8.7	7.0	6.2	6.0	5.9	6.4	7.5	8.2	7.3	(37)	
		MCWBR	7.0	8.6	11.5	13.3	11.5	10.7	9.9	9.5	10.9	10.8	10.7	7.9	(38)	
(40) Clear-Sky Solar Irradiance	taub	taub	0.275	0.316	0.334	0.377	0.399	0.415	0.410	0.400	0.370	0.333	0.295	0.274	(40)	
		taud	2.386	2.260	2.362	2.285	2.273	2.267	2.281	2.299	2.376	2.473	2.509	2.433	(41)	
	Ebn at Noon	Ebn at Noon	864	872	905	887	874	858	857	854	856	850	838	832	(42)	
		Edh at Noon	77	104	107	126	131	133	129	123	105	84	69	67	(43)	
(44) All-Sky Solar Radiation	RadAvg	RadAvg	1.63	2.69	3.78	4.55	5.38	6.01	6.11	5.25	4.27	2.72	1.76	1.26	(44)	
	RadStd	RadStd	0.23	0.28	0.43	0.41	0.42	0.43	0.28	0.33	0.35	0.31	0.15	0.12	(45)	

Historical Trends

		Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
(46) Station Only	DBAvg	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)
(47) Regional (56 neighbors)		(m)								
		-0.78	-2.06	-2.41	N/A	-1.68	-1.73	N/A	N/A	N/A
		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page