

SEMARANG AHMAD YANI, Indonesia

WMO: 968390

Lat: 6.9769S

Lon: 110.3778E

Elev: 4

StdP: 101.28

Time Zone: 7.00 (E07)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
2	22.5	23.2	15.0	10.7	31.7	16.5	11.8	30.6	10.0	29.7	8.9	29.6	1.3	120	0.373

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
10	8.1	34.8	23.5	33.9	24.0	33.2	24.3	27.1	31.0	26.7	30.7	26.6	30.5	5.0	90

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
26.1	21.5	29.5	25.7	21.0	29.2	25.4	20.5	28.9	85.7	31.1	84.2	31.0	83.2	30.8	31.0

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	DB	WB
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 8.0	7.1	6.3	20.3	36.6	1.7	1.1	19.0	37.3	18.1	37.9	17.1	38.5	15.9	39.3		
(5)			17.5	28.9	1.4	0.8	16.5	29.5	15.7	30.0	14.9	30.4	13.9	31.0		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	28.3	27.5	27.4	28.0	28.6	28.9	28.5	28.2	28.4	29.0	29.2	28.6	27.8		
	DBStd	1.09	0.97	0.94	0.84	0.85	0.89	0.89	0.87	0.88	0.98	1.10	1.12	0.87		
	HDD10.0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	HDD18.3	0	0	0	0	0	0	0	0	0	0	0	0	0		
	CDD10.0	6694	542	487	557	557	586	557	565	571	569	595	558	552		
	CDD18.3	3653	283	254	298	307	328	307	307	312	319	337	308	294		
	CDH23.3	40827	2829	2521	3226	3493	3923	3534	3441	3556	3696	4031	3500	3077		
	CDH26.7	15742	836	722	1078	1323	1646	1441	1399	1497	1613	1786	1398	1003		
(14) Wind	WSAvg	2.6	2.8	2.7	2.4	2.4	2.6	2.6	2.8	3.0	2.9	2.7	2.3	2.2		
(15) Precipitation	PrecAvg	1748	391	224	218	170	123	74	48	20	49	89	139	203		
	PrecMax	2612	869	504	466	376	331	160	184	112	299	261	487	548		
	PrecMin	882	175	71	74	25	17	0	0	0	0	0	39	96		
	PrecStd	564	237	121	114	106	87	60	52	33	88	80	117	123		
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	32.6	32.2	32.7	33.7	34.1	33.9	33.8	34.2	35.8	36.0	35.2	32.8		
		MCWB	26.0	26.2	25.8	25.9	25.5	24.3	23.5	22.8	22.4	22.8	24.8	26.0		
	2%	DB	31.6	31.2	31.9	32.9	33.2	33.1	33.1	33.7	34.8	34.6	33.8	31.9		
		MCWB	26.0	26.0	26.1	25.9	25.4	24.4	23.5	22.9	22.5	23.9	25.3	26.0		
	5%	DB	30.9	30.7	31.2	32.1	32.8	32.6	32.6	33.0	33.7	33.4	32.7	31.2		
		MCWB	25.8	25.9	26.0	25.9	25.3	24.5	23.6	23.1	23.1	24.5	25.6	26.0		
	10%	DB	30.2	30.1	30.7	31.4	32.1	32.0	31.9	32.2	32.5	32.5	31.8	30.7		
		MCWB	25.6	25.7	25.9	25.9	25.4	24.7	23.8	23.4	23.8	24.9	25.7	25.8		
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	27.0	26.9	27.2	27.4	27.5	27.1	26.5	26.4	26.5	26.7	27.2	27.0		
		MCDB	30.8	30.5	30.9	31.3	31.4	30.8	30.5	30.5	31.1	31.3	31.6	30.9		
	2%	WB	26.5	26.6	26.7	26.9	26.8	26.5	25.9	25.7	25.8	26.3	26.6	26.6		
		MCDB	30.2	30.0	30.4	30.8	31.0	30.5	30.1	30.1	30.4	31.0	31.1	30.4		
	5%	WB	26.1	26.2	26.4	26.6	26.5	26.2	25.4	25.3	25.5	26.0	26.2	26.2		
		MCDB	29.8	29.6	30.1	30.4	30.6	30.2	29.7	29.7	30.1	30.8	30.7	30.0		
	10%	WB	25.8	26.0	26.1	26.3	26.2	25.8	25.0	24.9	25.1	25.7	25.9	26.0		
		MCDB	29.3	29.3	29.7	30.1	30.2	29.8	29.3	29.3	29.7	30.3	30.3	29.7		
(35) Mean Daily Temperature Range	5% DB	MDBR	5.6	5.5	5.9	6.4	6.9	7.4	8.2	8.7	8.9	8.1	7.1	6.0		
		MCDBR	6.4	6.2	6.4	7.1	7.5	8.1	8.9	9.4	10.0	9.2	8.4	6.6		
	5% WB	MCWBR	2.6	2.6	2.6	2.5	2.6	3.0	3.4	3.7	3.7	3.2	2.8	2.6		
		MCWBR	5.9	5.8	6.0	6.5	6.9	7.7	8.1	8.4	7.9	7.2	6.1	6.1		
(40) Clear-Sky Solar Irradiance	taub	taub	0.535	0.542	0.542	0.554	0.526	0.515	0.518	0.549	0.580	0.662	0.645	0.578		
		taud	2.090	2.074	2.073	2.026	2.093	2.114	2.094	1.991	1.913	1.728	1.778	1.952		
	Ebn at Noon	Ebn at Noon	817	811	799	762	754	748	754	755	757	711	725	778		
		Edh at Noon	172	175	173	174	155	148	154	178	200	245	233	196		
(44) All-Sky Solar Radiation	RadAvg	RadAvg	4.58	4.63	5.02	5.12	5.05	4.86	5.17	5.77	6.17	5.88	5.21	4.61		
	RadStd	RadStd	0.45	0.40	0.30	0.31	0.28	0.33	0.31	0.22	0.34	0.53	0.49	0.39		

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days				
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3	
(46)	Station Only	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(46)
		+0.32	N/A	N/A	+0.39	+0.35	+0.47	N/A	N/A	N/A	N/A	
(47)	Regional (3 neighbors)	+0.32	N/A	N/A	+0.39	+0.35	+0.47	N/A	N/A	N/A	N/A	(47)

Nomenclature: See separate page