

KUPANG EL TARI, Indonesia

WMO: 973720

Lat: 10.1677S

Lon: 123.6704E

Elev: 108

StdP: 100.03

Time Zone: 8.00 (E08)

Period: 95-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	20.1	21.0	14.1	10.1	28.5	15.6	11.3	27.6	13.3	29.4	12.5	29.0	1.3	120	0.367

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
11	8.5	34.4	25.0	33.6	25.1	33.0	25.2	28.1	31.4	27.7	31.0	27.3	30.7	5.8	90

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
27.2	23.3	30.4	26.8	22.7	30.0	26.4	22.2	29.6	91.1	31.5	89.2	31.2	87.4	30.8	30.2

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	(q)
(4) 10.2	9.0	8.0	DB	17.7	36.3	1.4	0.6	16.7	36.7	15.9	37.1	15.1	37.4	14.1	37.8	(4)
(5)			WB	15.8	29.0	1.3	0.7	14.8	29.5	14.1	29.9	13.4	30.3	12.4	30.8	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	27.4	27.2	27.1	27.2	27.9	27.7	26.8	26.5	26.7	27.4	28.4	28.7	27.8		
	DBStd	1.27	1.13	1.05	1.02	0.99	0.97	1.29	1.18	1.08	1.19	1.17	0.95	1.19		
	HDD10.0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	HDD18.3	0	0	0	0	0	0	0	0	0	0	0	0	0		
	CDD10.0	6368	532	478	534	537	550	505	512	518	522	569	560	551		
	CDD18.3	3327	274	245	276	287	292	255	253	260	272	311	310	292		
	CDH23.3	33284	2685	2331	2631	2942	2895	2281	2157	2277	2817	3582	3649	3038		
	CDH26.7	12229	781	677	848	1157	1067	746	722	849	1185	1594	1587	1017		
(14) Wind	WSAvg	3.1	2.2	2.0	1.8	2.5	3.9	4.5	4.8	4.7	3.6	3.2	2.2	1.8		
(15) Precipitation	PrecAvg	1690	400	438	257	96	24	9	5	2	6	21	108	324		
	PrecMax	2367	668	858	487	247	105	71	30	29	47	110	334	1019		
	PrecMin	1244	120	160	33	0	1	0	0	0	0	0	1	87		
	PrecStd	344	142	201	127	73	30	16	7	5	13	31	73	183		
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	33.3	32.6	33.1	34.1	33.3	33.0	32.7	33.3	34.7	35.6	35.3	33.5		
		MCWB	26.7	27.2	26.5	25.1	24.4	24.5	23.7	23.1	23.7	24.8	25.1	27.1		
	2%	DB	31.7	31.6	32.2	33.2	32.6	32.0	31.8	32.4	33.6	34.5	34.1	32.5		
		MCWB	26.9	27.0	26.6	25.3	24.8	24.3	23.4	22.9	23.8	24.9	25.8	27.1		
	5%	DB	30.8	30.9	31.4	32.6	32.1	31.2	31.1	31.6	32.7	33.6	33.2	31.7		
		MCWB	26.7	26.9	26.5	25.4	24.9	24.1	23.2	22.9	23.9	25.0	26.1	27.1		
	10%	DB	30.1	30.1	30.5	31.7	31.4	30.4	30.3	30.8	31.8	32.6	32.4	30.8		
		MCWB	26.5	26.5	26.4	25.5	24.7	23.8	22.9	22.6	23.8	25.0	26.2	26.9		
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	28.2	28.3	28.3	28.2	27.6	26.2	26.2	25.9	26.5	27.7	28.2	28.6		
		MCDB	30.9	31.3	31.5	31.5	31.2	30.9	30.8	30.9	32.0	32.3	32.5	31.6		
	2%	WB	27.5	27.7	27.6	27.3	26.6	25.4	25.2	25.0	25.9	26.8	27.6	28.0		
		MCDB	30.4	30.6	30.8	31.1	30.6	30.2	29.9	30.5	31.3	31.9	31.9	31.1		
	5%	WB	27.1	27.2	27.1	26.7	25.9	24.9	24.4	24.2	25.3	26.3	27.2	27.6		
		MCDB	30.0	30.1	30.2	30.7	30.2	29.6	29.0	29.7	30.7	31.4	31.4	30.6		
	10%	WB	26.7	26.7	26.6	26.2	25.3	24.4	23.8	23.6	24.8	25.8	26.7	27.1		
		MCDB	29.4	29.4	29.6	30.1	29.6	29.0	28.3	28.9	30.0	30.8	30.9	30.0		
(35) Mean Daily Temperature Range	5% DB	MDBR	5.7	5.9	6.9	8.3	7.9	7.8	8.3	9.1	10.2	9.8	8.5	6.2		
		MCDBR	7.0	7.3	8.2	9.3	8.5	8.5	9.0	9.8	10.9	10.7	9.5	7.4		
		MCWBR	3.2	3.5	3.8	3.4	3.1	3.2	3.1	3.5	4.1	4.0	3.8	3.4		
	5% WB	MCDBR	6.4	6.5	7.2	8.0	7.9	7.7	8.1	9.0	10.0	9.7	8.6	6.7		
		MCWBR	3.3	3.5	3.8	3.9	3.6	3.3	3.7	4.1	4.7	4.7	4.2	3.5		
(40) Clear-Sky Solar Irradiance	taub		0.422	0.414	0.403	0.389	0.400	0.398	0.382	0.382	0.414	0.439	0.441	0.426		
	taud		2.467	2.486	2.512	2.549	2.507	2.491	2.521	2.499	2.399	2.335	2.359	2.438		
	Ebn at Noon		921	924	917	901	860	845	869	895	893	890	897	915		
	Edh at Noon		119	116	111	102	101	100	99	106	122	134	131	122		
(44) All-Sky Solar Radiation	RadAvg		5.52	5.74	5.73	5.88	5.39	4.99	5.34	6.17	6.83	7.04	6.85	5.82		
	RadStd		0.65	0.65	0.58	0.51	0.32	0.26	0.14	0.14	0.21	0.27	0.37	0.46		

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)
(46) Station Only			N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (0 neighbors)			N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page