

CAGAYAN DE ORO LUMBIA, Philippines

WMO: 987470

Lat: 8.409N

Lon: 124.612E

Elev: 188

StdP: 99.09

Time Zone: 8.00 (E08)

Period: 94-13

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	20.9	21.7	18.3	13.5	22.2	19.2	14.3	23.0	6.3	27.0	5.3	27.6	1.7	180	0.265

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
5	8.0	33.2	26.3	32.7	26.3	32.1	26.2	27.4	31.5	27.1	31.2	26.9	30.9	2.6	0

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
26.2	22.2	30.3	26.0	21.8	30.1	25.7	21.4	29.8	88.4	31.7	87.1	31.4	85.9	31.1	29.8

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	DB	WB
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 5.1	4.1	3.4	18.0	35.4	2.6	1.2	16.1	36.2	14.6	36.9	13.2	37.6	11.3	38.4		
(5)			17.0	28.7	1.8	0.7	15.7	29.2	14.6	29.7	13.6	30.1	12.3	30.6		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	26.9	25.7	25.9	26.6	27.5	27.9	27.3	27.0	27.2	27.1	27.0	26.7	26.4		
	DBStd	1.13	1.09	1.11	1.05	1.05	0.98	0.92	0.89	0.98	0.88	0.73	0.85	0.92		
	HDD10.0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	HDD18.3	0	0	0	0	0	0	0	0	0	0	0	0	0		
	CDD10.0	6156	487	446	514	525	555	519	527	534	513	527	502	507		
	CDD18.3	3114	229	213	256	275	297	269	269	276	263	268	252	249		
	CDH23.3	26815	1609	1609	2234	2772	2972	2383	2259	2405	2203	2279	2112	1976		
(13)	CDH26.7	8992	389	460	740	1072	1150	829	763	870	772	743	658	546		
(14)	Wind	WSAvg	1.4	1.5	1.5	1.6	1.6	1.3	1.3	1.3	1.3	1.3	1.4	1.5		
(15) Precipitation	PrecAvg	2009	121	100	79	85	165	257	261	220	248	190	154	144		
	PrecMax	2594	433	262	158	218	262	442	355	307	360	335	516	395		
	PrecMin	1413	20	14	15	17	53	137	181	132	130	105	37	14		
	PrecStd	344	96	69	41	65	56	77	53	53	63	58	115	100		
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	31.5	32.1	32.9	33.7	34.1	33.2	33.2	33.8	33.4	32.6	32.2	31.9		
		MCWB	25.4	25.4	25.2	26.3	26.5	26.8	26.2	26.5	26.6	26.3	26.2	26.2		
	2%	DB	30.6	31.1	31.9	32.9	33.1	32.2	32.0	32.4	32.1	31.8	31.5	31.0		
		MCWB	25.4	25.2	25.6	26.1	26.5	26.6	26.4	26.3	26.4	26.3	26.1	26.0		
	5%	DB	29.8	30.3	31.2	32.1	32.2	31.5	31.2	31.6	31.4	31.1	30.9	30.3		
		MCWB	25.1	25.1	25.5	25.9	26.4	26.4	26.2	26.2	26.2	26.1	26.0	25.8		
	10%	DB	28.9	29.5	30.4	31.4	31.6	30.8	30.4	30.8	30.6	30.3	30.1	29.6		
		MCWB	25.0	25.0	25.3	25.8	26.3	26.2	26.0	26.0	25.9	26.0	25.8	25.6		
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	26.6	26.7	27.1	27.6	27.7	27.7	27.5	27.6	27.5	27.2	27.2	27.1		
		MCDB	30.0	30.3	30.9	31.7	32.2	31.8	31.4	31.9	31.7	30.9	30.7	30.5		
	2%	WB	26.0	26.1	26.4	27.0	27.2	27.1	27.0	27.0	26.9	26.8	26.7	26.6		
		MCDB	29.3	29.7	30.3	31.4	31.7	31.2	30.9	31.2	31.2	30.5	30.3	30.0		
	5%	WB	25.6	25.7	26.0	26.5	26.9	26.7	26.6	26.6	26.5	26.5	26.3	26.2		
		MCDB	28.7	29.1	29.9	31.0	31.3	30.7	30.4	30.7	30.6	30.2	29.9	29.5		
	10%	WB	25.2	25.2	25.6	26.1	26.5	26.3	26.1	26.2	26.1	26.1	26.0	25.8		
		MCDB	28.1	28.5	29.4	30.5	30.8	30.2	29.9	30.3	30.1	29.8	29.5	29.0		
(35) Mean Daily Temperature Range	5% DB	MDBR	6.3	6.9	7.7	8.3	8.0	7.6	7.5	7.9	7.9	7.6	7.2	6.9		
		MCDBR	7.9	8.6	9.0	9.1	8.7	8.4	8.5	8.8	8.7	8.4	8.2	7.9		
	5% WB	MCWBR	4.2	4.5	4.6	4.5	4.1	4.3	4.6	4.6	4.6	4.5	4.5	4.3		
		MCWBR	7.0	7.5	8.0	8.5	8.2	8.0	7.9	8.4	8.3	7.9	7.7	7.3		
(40) Clear-Sky Solar Irradiance	taub	taub	0.397	0.394	0.396	0.408	0.418	0.408	0.407	0.427	0.426	0.434	0.405	0.398		
		taud	2.512	2.501	2.501	2.465	2.456	2.488	2.488	2.413	2.409	2.386	2.489	2.505		
	Ebn at Noon	Ebn at Noon	916	928	924	900	874	872	876	872	884	878	901	907		
		Edh at Noon	107	111	112	115	113	108	109	120	121	123	109	106		
(44) All-Sky Solar Radiation	RadAvg	RadAvg	4.15	4.87	5.49	5.87	5.44	5.03	4.96	5.16	5.12	4.93	4.62	4.33		
	RadStd	RadStd	0.53	0.54	0.42	0.32	0.33	0.24	0.27	0.34	0.34	0.32	0.39	0.38		

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46)	Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47)	Regional (11 neighbors)	+0.22	N/A	N/A	+0.44	+0.33	+0.31	N/A	N/A	N/A	N/A

Nomenclature: See separate page