

POINT RETREAT, AK, USA

WMO: 997797

Lat: 58.411N

Lon: 134.955W

Elev: 32

StdP: 100.94

Time Zone: -9.00 (NAK)

Period: 86-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-10.5	-8.5	-15.4	1.0	-8.7	-13.5	1.2	-6.9	22.5	-8.8	19.4	-7.8	13.2	320	N/A

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	4.9	20.7	15.4	19.0	14.5	17.5	13.9	16.1	19.6	15.2	18.2	14.4	16.8	3.2	230

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
14.5	10.4	17.3	13.8	9.9	16.3	13.2	9.5	15.5	45.0	19.6	42.5	18.2	40.3	17.0	24.1

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	DB	WB
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 15.9	13.6	11.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(5)			N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	
Temperatures, Degree-Days and Degree-Hours	DBAvg	6.6	0.0	0.2	2.2	5.1	9.1	12.3	14.2	14.0	10.9	6.8	3.1	0.9	
	DBStd	5.88	4.48	3.62	3.23	2.09	2.32	2.13	2.29	2.01	1.85	1.80	2.79	3.50	
	HDD10.0	1626	309	276	243	148	46	3	0	0	10	99	208	283	
	HDD18.3	4289	568	509	502	398	286	182	130	136	223	357	458	541	
	CDD10.0	383	0	0	0	1	18	72	131	123	37	1	0	1	
	CDD18.3	4	0	0	0	0	0	1	2	1	0	0	0	0	
	CDH23.3	9	0	0	0	0	0	2	4	3	0	0	0	0	
	CDH26.7	0	0	0	0	0	0	0	0	0	0	0	0	0	
Wind	WSAvg	4.1	6.3	5.9	5.2	3.3	2.7	2.7	2.5	2.6	3.1	4.2	5.6	5.8	
Precipitation	PrecAvg	2061	169	130	119	113	108	101	155	187	304	267	210	199	
	PrecMax	2503	332	223	179	211	229	197	284	322	437	453	414	364	
	PrecMin	1558	60	47	43	42	37	27	64	74	177	132	90	86	
	PrecStd	245	67	50	35	44	48	41	53	68	60	68	74	75	
Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	9.8	6.7	10.1	13.3	18.5	22.6	23.6	22.6	17.8	12.3	8.9	11.9	
		MCWB	7.1	5.0	6.5	8.9	12.1	15.4	16.7	16.1	13.5	11.3	7.8	8.8	
	2%	DB	7.6	5.7	7.6	10.8	16.2	18.9	21.1	20.3	16.0	11.1	8.1	6.4	
		MCWB	5.6	4.3	5.4	6.9	11.3	13.9	16.0	15.0	12.1	10.0	7.0	4.9	
	5%	DB	5.8	5.0	6.3	9.3	14.2	17.0	19.3	18.5	14.4	10.1	7.4	5.5	
		MCWB	4.6	3.7	4.2	6.1	10.3	12.8	15.1	14.5	11.8	8.9	6.4	4.3	
	10%	DB	4.8	4.1	5.4	8.0	12.5	15.4	17.5	16.9	13.5	9.3	6.5	4.9	
		MCWB	3.8	2.9	3.7	5.5	9.3	12.0	14.5	13.8	11.6	8.1	5.4	3.9	
	Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	7.7	5.6	7.5	9.1	12.8	16.2	18.0	17.4	14.1	11.6	8.1	9.0
			MCDB	9.7	6.3	9.9	12.9	16.8	21.4	22.3	20.3	16.4	12.0	8.4	12.0
2%		WB	5.7	4.7	5.6	7.5	11.7	14.6	16.5	15.8	13.0	10.2	7.4	5.3	
		MCDB	7.0	5.4	7.1	10.0	15.5	18.2	19.8	19.1	14.2	10.8	7.9	6.0	
5%		WB	4.8	3.9	4.8	6.6	10.7	13.3	15.5	15.1	12.4	9.2	6.6	4.6	
		MCDB	5.8	4.7	5.9	8.7	13.6	16.0	18.5	17.8	13.7	10.0	7.3	5.3	
10%		WB	3.9	3.2	4.0	5.8	9.7	12.4	14.7	14.3	11.8	8.3	5.6	4.0	
		MCDB	4.8	3.9	5.0	7.6	12.1	14.7	17.2	16.4	13.0	9.2	6.3	4.7	
Mean Daily Temperature Range		5% DB	MDBR	3.0	2.8	3.4	4.4	5.3	5.3	4.9	4.4	3.6	2.6	2.5	2.5
			MCDBR	4.9	3.2	4.6	6.5	8.1	8.0	7.8	7.2	5.6	3.3	2.8	3.6
	MCWBR		3.8	2.9	3.2	4.0	4.4	4.6	4.3	4.1	3.4	2.9	2.8	3.1	
	5% WB	MCDBR	4.7	2.7	4.1	5.7	7.2	7.0	7.0	6.5	4.4	3.1	2.6	3.4	
		MCWBR	3.8	2.6	3.2	3.9	4.3	4.4	4.3	4.1	3.3	3.1	2.8	3.1	
Clear-Sky Solar Irradiance	taub	0.289	0.333	0.324	0.383	0.401	0.412	0.416	0.379	0.363	0.329	0.285	0.262		
	taud	2.100	2.086	2.204	2.069	2.142	2.231	2.267	2.407	2.401	2.361	2.155	2.065		
	Ebn at Noon	512	660	813	813	827	824	810	820	771	685	516	416		
	Edh at Noon	52	86	101	137	137	128	121	98	84	65	48	38		
All-Sky Solar Radiation	RadAvg	0.38	1.11	2.32	3.88	4.95	4.95	4.23	3.46	2.20	1.15	0.51	0.26		
	RadStd	0.05	0.20	0.32	0.45	0.55	0.36	0.47	0.44	0.36	0.18	0.08	0.03		

Historical Trends

		DBAvg	Heating			Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP		HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(47) Regional (13 neighbors)		N/A	+1.17	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	

Nomenclature: See separate page