

LECK AP, Germany

WMO: 100220

Lat: 54.7903N

Lon: 8.9514E

Elev: 8

StdP: 101.23

Time Zone: 1.00 (EUC)

Period: 94-13

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
2	-9.3	-6.9	-11.2	1.4	-7.2	-9.0	1.7	-6.0	14.9	4.0	13.7	4.8	2.3	90	0.649

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	8.4	27.0	19.3	24.9	18.3	22.8	17.5	20.1	25.2	19.1	23.3	18.1	21.7	4.5	90

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
18.4	13.3	22.0	17.5	12.5	20.9	16.6	11.9	20.0	57.7	25.1	54.4	23.5	51.2	21.7	24.2

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 12.4	11.0	9.8	DB	-13.2	29.9	3.3	1.6	-15.5	31.1	-17.5	32.0	-19.3	32.9	-21.7	34.0	(4)
(5)			WB	-13.4	22.3	3.3	0.8	-15.7	22.9	-17.6	23.4	-19.5	23.9	-21.8	24.5	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	8.6	1.3	1.4	3.5	7.6	11.2	14.0	16.8	16.8	13.7	9.5	5.4	1.7	(6)	
	DBStd	6.58	4.02	4.01	3.31	3.36	2.95	2.81	2.73	2.71	2.50	3.25	3.41	4.24	(7)	
	HDD10.0	1270	269	242	202	87	21	1	0	0	2	49	141	256	(8)	
	HDD18.3	3588	527	475	460	322	222	134	66	64	141	275	389	514	(9)	
	CDD10.0	764	0	0	1	16	58	121	211	211	113	32	2	0	(10)	
	CDD18.3	41	0	0	0	0	1	4	18	17	1	0	0	0	(11)	
	CDH23.3	361	0	0	0	1	7	47	164	135	6	0	0	0	(12)	
	CDH26.7	64	0	0	0	0	0	6	33	26	0	0	0	0	(13)	
(14) Wind	WSAvg	4.5	5.1	5.3	5.4	4.7	4.4	4.3	3.8	3.7	4.0	4.4	4.6	4.6	(14)	
(15) Precipitation	PrecAvg	852	70	55	47	38	50	68	80	98	89	94	81	82	(15)	
	PrecMax	987	142	105	96	100	88	111	140	202	188	186	169	173	(16)	
	PrecMin	534	3	16	9	4	7	1	27	26	16	35	15	29	(17)	
	PrecStd	111	34	22	26	20	21	30	35	46	42	34	37	37	(18)	
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	9.5	9.5	14.2	21.6	24.3	27.5	29.9	29.2	24.0	18.3	13.8	10.7	(19)	
		MCWB	8.3	8.2	9.4	13.9	16.5	19.1	19.9	19.8	17.9	15.9	12.6	9.9	(20)	
	2%	DB	8.3	8.2	11.3	18.4	21.1	24.5	27.2	27.0	21.5	16.3	12.1	9.3	(21)	
		MCWB	7.4	7.4	8.5	12.0	14.8	17.9	19.3	19.4	16.9	14.4	11.0	8.5	(22)	
	5%	DB	7.3	7.4	9.2	15.8	19.1	21.7	25.1	24.5	19.4	15.1	11.0	8.3	(23)	
		MCWB	6.7	6.6	7.2	11.2	13.3	16.5	18.5	18.5	15.9	13.7	10.1	7.5	(24)	
	10%	DB	6.5	6.5	7.9	13.3	17.2	19.5	22.7	22.2	17.9	14.1	10.0	7.3	(25)	
		MCWB	5.9	5.8	6.6	10.0	12.6	15.5	17.6	17.9	15.1	12.7	9.1	6.6	(26)	
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	8.8	8.6	10.7	14.8	17.6	20.6	21.4	21.4	19.0	16.2	12.7	10.1	(27)	
		MCDB	9.4	9.2	12.9	20.1	22.2	25.6	26.8	26.4	22.4	17.6	13.4	10.6	(28)	
	2%	WB	7.6	7.5	8.9	13.0	15.6	18.8	20.2	20.0	17.5	15.0	11.2	8.7	(29)	
		MCDB	8.1	8.0	10.7	16.9	19.3	22.6	25.7	24.8	20.3	15.8	11.8	9.2	(30)	
	5%	WB	6.8	6.8	7.7	11.6	14.2	17.1	19.2	19.1	16.5	13.9	10.2	7.6	(31)	
		MCDB	7.2	7.3	8.9	14.9	17.7	20.6	23.7	23.1	18.9	14.8	10.8	8.1	(32)	
	10%	WB	6.0	5.8	6.8	10.3	13.1	15.8	18.0	18.2	15.6	13.0	9.3	6.7	(33)	
		MCDB	6.4	6.4	7.7	12.9	16.3	18.9	21.7	21.5	17.6	13.9	9.9	7.2	(34)	
(35) Mean Daily Temperature Range	5% DB	MDBR	4.1	4.6	6.0	8.3	8.6	7.8	8.4	8.5	7.3	6.2	4.7	4.6	(35)	
		MCDBR	3.7	4.1	8.3	12.3	12.5	12.4	13.2	12.3	9.7	6.5	4.6	3.9	(36)	
	5% WB	MCWBR	3.6	3.5	5.9	7.2	7.4	6.9	6.5	6.1	5.9	5.1	4.2	3.9	(37)	
		MCWBR	3.6	3.8	7.1	10.7	10.3	10.6	11.6	10.6	8.3	5.9	4.3	4.0	(38)	
(40) Clear-Sky Solar Irradiance	taub		0.325	0.344	0.369	0.402	0.393	0.391	0.406	0.405	0.384	0.361	0.338	0.315	(40)	
		taud	2.269	2.301	2.273	2.235	2.321	2.350	2.323	2.336	2.377	2.384	2.322	2.268	(41)	
	Ebn at Noon		596	728	795	819	851	856	833	809	775	701	577	522	(42)	
		Edh at Noon	59	80	102	122	118	116	117	109	92	73	56	48	(43)	
(44) All-Sky Solar Radiation	RadAvg		0.51	1.14	2.44	4.07	5.21	5.43	5.09	4.12	2.91	1.55	0.63	0.37	(44)	
	RadStd		0.07	0.16	0.22	0.46	0.51	0.44	0.58	0.31	0.32	0.18	0.08	0.03	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (46 neighbors)		N/A	N/A	N/A	N/A	N/A	N/A	N/A	-146	N/A	N/A

Nomenclature: See separate page