

WIEN INNERE STADT, Austria

WMO: 110340

Lat: 48.198N

Lon: 16.367E

Elev: 582

StdP: 14.39

Time Zone: 1.00 (EUC)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	18.2	21.7	9.2	9.0	20.7	13.6	11.2	24.5	24.3	42.7	22.0	43.5	7.0	320	0.469

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	15.0	90.4	71.1	87.1	69.8	84.1	68.4	73.2	86.5	71.4	83.7	69.8	81.0	7.7	140

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
68.7	107.9	80.1	67.1	101.9	78.4	65.6	96.6	76.8	37.1	87.0	35.5	83.7	34.2	81.1	79.2

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature								
1%	2.5%	5%	Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years		
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	
19.4	17.0	15.3	DB	15.6	95.5	5.4	3.7	11.7	98.1	8.5	100.3	5.4	102.4	1.5	105.1
			WB	13.9	75.3	5.0	1.9	10.3	76.7	7.4	77.8	4.6	78.9	1.0	80.3

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	54.2	34.8	38.3	45.3	55.0	62.6	69.3	73.0	72.4	63.1	53.9	45.1	37.0	(6)
	DBStd	15.18	7.98	8.52	7.94	7.68	6.76	6.75	6.28	6.06	6.32	6.88	7.09	7.31	(7)
	HDD50	1657	473	335	187	39	1	0	0	0	1	40	178	403	(8)
	HDD65	4705	936	748	612	307	128	34	9	9	110	347	598	867	(9)
	CDD50	3201	3	6	41	190	391	579	713	693	393	160	30	2	(10)
	CDD65	773	0	0	0	8	53	163	257	237	52	3	0	0	(11)
	CDH74	5598	0	0	0	49	310	1171	2056	1774	231	7	0	0	(12)
	CDH80	1777	0	0	0	6	50	342	735	606	38	0	0	0	(13)
(14) Wind	WSAvg	7.3	8.0	7.9	7.8	7.6	7.8	7.2	7.5	6.4	6.7	6.6	7.1	7.2	(14)
(15) Precipitation	PrecAvg	25.6	1.4	1.3	1.9	1.7	2.8	3.1	3.1	2.8	2.6	1.8	1.7	1.5	(15)
	PrecMax	34.1	3.4	2.9	4.7	3.9	6.6	7.0	8.9	6.7	7.9	3.8	3.4	2.7	(16)
	PrecMin	17.0	0.1	0.0	0.6	0.0	0.7	0.9	0.3	0.6	0.8	0.2	0.0	0.4	(17)
	PrecStd	4.4	0.8	0.9	1.1	1.1	1.4	1.5	1.7	1.6	1.6	0.9	0.7	0.7	(18)
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	58.1	60.6	68.4	79.2	84.8	91.7	94.7	95.0	84.4	74.2	65.5	57.1	(19)
		MCWB	49.9	47.9	53.7	61.3	67.9	71.8	72.9	70.5	67.6	61.7	56.1	49.8	(20)
	2%	DB	53.5	56.6	64.2	74.3	80.8	87.6	90.6	90.1	80.0	69.8	61.7	53.2	(21)
		MCWB	47.2	48.2	52.0	59.3	65.5	70.6	71.5	70.5	66.3	60.2	54.3	47.2	(22)
	5%	DB	49.3	52.9	60.2	70.3	77.5	83.9	87.2	86.3	76.2	66.6	57.9	49.5	(23)
		MCWB	44.3	46.2	50.2	57.1	63.8	68.4	69.9	69.4	64.8	58.7	52.2	44.4	(24)
	10%	DB	45.9	49.6	56.6	66.8	74.1	80.8	84.0	82.9	73.1	63.7	54.4	46.4	(25)
		MCWB	41.6	44.1	48.3	55.3	61.8	66.9	68.6	68.0	63.2	57.2	49.7	42.2	(26)
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	50.9	50.9	55.4	63.0	69.7	75.0	75.7	74.5	69.7	64.2	57.7	50.7	(27)
		MCDB	56.7	57.6	65.3	76.3	81.5	86.9	89.4	89.6	78.2	71.0	63.7	55.6	(28)
	2%	WB	47.5	48.5	52.9	60.2	66.9	72.4	73.5	72.3	67.6	61.6	55.1	47.5	(29)
		MCDB	52.9	54.9	61.7	72.6	78.4	84.6	87.1	85.7	77.0	67.7	60.4	52.6	(30)
	5%	WB	44.6	46.6	51.1	58.1	65.0	70.2	71.7	70.5	66.0	59.7	52.5	44.9	(31)
		MCDB	49.2	52.5	58.7	68.4	75.3	80.8	84.1	82.9	74.4	65.1	57.4	49.0	(32)
	10%	WB	41.8	44.4	49.2	56.4	63.1	68.2	69.9	69.1	64.3	57.9	50.1	42.6	(33)
		MCDB	45.5	49.5	56.0	65.4	72.4	78.6	81.2	80.5	71.6	62.9	53.9	45.9	(34)
(35) Mean Daily Temperature Range	5% DB	MDBR	6.5	8.5	11.1	13.8	14.0	14.3	15.0	14.6	12.1	10.3	7.0	6.4	(35)
		MCDBR	10.3	13.0	17.4	19.1	19.2	19.3	20.2	19.9	17.4	14.5	11.3	11.4	(36)
		MCWBR	7.4	8.0	9.2	8.8	8.2	7.4	6.7	6.8	7.1	7.3	6.7	7.8	(37)
	5% WB	MCDBR	10.2	12.1	16.0	17.6	18.2	17.7	18.9	18.4	16.3	13.3	10.6	10.8	(38)
		MCWBR	7.7	7.9	9.2	8.5	8.3	7.6	7.2	7.1	7.1	7.3	7.0	7.8	(39)
(40) Clear-Sky Solar Irradiance	taub		0.321	0.345	0.385	0.431	0.429	0.434	0.441	0.440	0.412	0.380	0.352	0.319	(40)
	taud		2.371	2.328	2.247	2.151	2.202	2.229	2.212	2.229	2.275	2.334	2.368	2.396	(41)
	Ebn at Noon		235	254	260	259	265	264	260	254	249	237	219	220	(42)
	Edh at Noon		22	29	36	44	44	43	43	41	35	29	23	19	(43)
(44) All-Sky Solar Radiation	RadAvg		312	573	942	1415	1664	1816	1752	1563	1118	681	351	245	(44)
	RadStd		38	76	123	144	179	138	163	151	137	78	35	28	(45)

Historical Trends

	DBAvg	Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD50	HDD65	CDD50	CDD65
Station Only	(d) N/A	(e) N/A	(f) N/A	(g) N/A	(h) N/A	(i) N/A	(j) N/A	(k) N/A	(l) N/A	(m) N/A
Regional (86 neighbors)	+0.99	N/A	N/A	N/A	+0.77	+0.67	-218	-286	+148	+72

Nomenclature: See separate page