

ZHITCKOVICHI, Belarus

WMO: 330270

Lat: 52.2144N

Lon: 27.8667E

Elev: 449

StdP: 14.46

Time Zone: 3.00 (E03)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a) 1	(b) -3.3	(c) 3.3	(d) -8.9	(e) 3.5	(f) -1.5	(g) -2.5	(h) 4.9	(i) 4.2	(j) 14.9	(k) 35.3	(l) 13.7	(m) 32.0	(n) 2.8	(o) 350	(p) 0.504

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a) 7	(b) 18.8	(c) 86.2	(d) 68.2	(e) 83.1	(f) 66.7	(g) 80.0	(h) 65.3	(i) 70.9	(j) 82.3	(k) 69.0	(l) 79.2	(m) 67.2	(n) 76.4	(o) 5.7	(p) 120

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a) 67.1	(b) 101.3	(c) 75.4	(d) 65.4	(e) 95.2	(f) 73.3	(g) 63.8	(h) 90.1	(i) 71.7	(j) 35.0	(k) 82.5	(l) 33.3	(m) 79.3	(n) 31.9	(o) 76.7	(p) 77.2

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature							
1%	2.5%	5%	Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years	
(a)	(b)	(c)	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
13.7	12.0	10.7	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
			-11.2	90.3	6.2	3.3	-15.6	92.7	-19.2	94.6	-22.7	96.5	-27.1	98.9
			-11.5	73.1	6.1	2.5	-15.9	74.9	-19.5	76.3	-22.9	77.7	-27.4	79.5
			DB											
			WB											

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	46.2	24.9	27.1	35.2	47.9	57.5	63.1	67.4	64.8	55.3	45.3	36.4	28.2		
	DBStd	16.91	10.55	10.41	8.34	7.75	7.64	6.03	5.58	5.69	6.20	7.49	8.64	10.09		
	HDD50	3321	777	641	461	129	20	0	0	0	22	183	412	676		
	HDD65	7118	1242	1061	923	514	254	109	37	73	295	610	859	1141		
	CDD50	1937	0	0	2	66	252	393	541	460	181	39	3	0		
	CDD65	258	0	0	0	1	21	51	113	68	4	0	0	0		
	CDH74	2481	0	0	0	23	258	489	1058	600	51	2	0	0		
	CDH80	651	0	0	0	4	56	107	318	162	4	0	0	0		
	WSAvg	4.8	5.3	5.4	5.5	5.0	4.8	4.7	4.2	4.0	4.0	4.4	5.0	5.1		
	PrecAvg	28.5	1.8	1.7	1.8	1.8	2.7	3.1	4.6	2.8	2.3	2.2	2.0	1.9		
(15) Precipitation	PrecMax	36.6	3.2	3.3	3.3	3.9	6.0	7.5	9.5	5.7	6.1	8.7	3.8	3.4		
	PrecMin	22.5	0.4	0.8	0.4	0.2	0.9	1.1	1.1	0.4	0.1	0.2	0.4	0.6		
	PrecStd	3.6	0.7	0.6	0.8	0.8	1.1	1.5	2.2	1.3	1.4	1.8	0.9	0.8		
	PrecStd	3.6	0.7	0.6	0.8	0.8	1.1	1.5	2.2	1.3	1.4	1.8	0.9	0.8		
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	45.2	48.9	61.0	77.1	85.6	87.4	91.1	89.9	80.0	71.5	58.2	48.4		
		MCWB	41.9	43.5	49.0	58.5	64.9	67.3	70.5	71.8	63.3	59.7	52.2	46.0		
	2%	DB	41.9	44.3	56.1	70.7	80.9	83.8	87.0	84.3	74.5	64.1	53.8	45.0		
		MCWB	39.3	40.8	45.8	54.9	63.9	66.3	69.0	68.5	61.6	56.4	50.8	43.1		
	5%	DB	39.4	41.5	51.3	66.4	76.3	80.1	83.6	80.1	70.2	60.0	50.2	42.7		
		MCWB	37.5	38.6	43.5	52.6	61.4	64.3	67.7	65.6	59.6	54.4	47.6	41.1		
	10%	DB	36.7	38.8	47.1	62.0	72.1	76.3	80.2	76.7	66.8	56.6	47.5	39.6		
		MCWB	35.4	36.5	41.2	50.4	58.9	63.5	66.5	64.3	58.0	52.3	45.4	38.0		
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	42.9	44.5	50.5	60.5	68.0	70.2	73.7	73.8	64.8	62.1	53.7	46.5		
		MCDB	44.9	48.0	58.4	73.8	81.0	82.0	85.5	85.4	75.2	69.3	56.4	47.7		
	2%	WB	39.8	41.3	46.9	56.7	65.0	68.3	71.4	70.7	62.6	58.0	50.8	43.5		
		MCDB	41.4	43.7	53.5	66.9	76.5	79.4	83.1	82.0	71.4	62.4	53.7	44.8		
	5%	WB	37.6	39.0	44.1	54.2	62.9	66.5	69.5	68.3	61.0	55.0	47.9	41.1		
		MCDB	39.1	41.0	50.2	63.2	74.1	76.2	79.8	77.0	68.2	59.3	49.9	42.5		
	10%	WB	35.4	36.7	41.9	51.9	60.6	64.7	67.7	66.2	59.2	52.4	45.6	38.1		
		MCDB	36.5	38.5	46.6	59.8	69.7	73.2	77.2	73.1	64.7	56.4	47.3	39.4		
(35) Mean Daily Temperature Range	5% DB	MDBR	8.0	10.3	13.3	18.6	19.8	18.2	18.8	19.0	17.6	14.0	8.2	7.5		
		MCDBR	7.7	11.4	20.7	26.5	26.6	24.8	24.8	24.9	24.1	19.7	12.8	8.7		
		MCWBR	7.0	8.4	12.1	12.7	11.4	9.9	9.7	10.5	12.7	12.1	9.6	7.6		
		MCDBR	7.1	10.1	18.2	22.3	23.5	20.4	21.7	21.1	20.3	17.3	11.7	8.5		
	5% WB	MCWBR	6.8	8.1	11.5	11.5	10.8	9.4	9.6	9.9	11.3	11.4	9.2	7.8		
		MCWBR	6.8	8.1	11.5	11.5	10.8	9.4	9.6	9.9	11.3	11.4	9.2	7.8		
(40) Clear-Sky Solar Irradiance	taub		0.303	0.337	0.371	0.422	0.410	0.399	0.428	0.429	0.394	0.359	0.342	0.304		
	taud		2.179	2.127	2.184	2.173	2.279	2.333	2.259	2.249	2.300	2.378	2.288	2.232		
	Ebn at Noon		212	238	256	257	267	271	260	252	247	233	198	191		
	Edh at Noon		22	32	37	42	40	38	40	39	33	25	21	18		
(44) All-Sky Solar Radiation	RadAvg		239	488	905	1323	1684	1818	1727	1501	1020	563	218	156		
	RadStd		39	91	128	142	148	129	147	120	128	98	23	38		

Historical Trends

	DBAvg	Heating			Cooling			Degree-Days			
		99% DB		99% DP	1% DB	1% WB	1% DP	HDD50	HDD65	CDD50	CDD65
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only	N/A	N/A	N/A	N/A	N/A	+2.00	+2.41	N/A	N/A	N/A	N/A
(47) Regional (8 neighbors)	+1.06	N/A	N/A	N/A	N/A	+1.28	+1.40	N/A	-315	+189	N/A

Nomenclature: See separate page