

DARAA, Syrian Arab Republic

WMO: 400950

Lat: 32.600N

Lon: 36.100E

Elev: 1781

StdP: 13.77

Time Zone: 2.00 (SYR)

Period: 94-11

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	33.9	36.7	14.4	12.2	50.1	19.4	15.6	54.7	24.8	55.4	20.5	50.9	1.3	150	0.365

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	22.8	97.6	66.7	94.9	66.9	92.5	67.2	73.3	88.3	71.9	86.0	70.8	84.1	8.4	270

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
69.2	114.8	77.3	68.1	110.3	76.8	67.0	106.0	76.1	38.2	87.1	36.9	86.3	35.9	84.0	87.1

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 20.4	17.4	15.0	DB	29.3	104.2	3.4	4.2	26.9	107.2	24.9	109.7	23.0	112.0	20.6	115.1	(4)
(5)			WB	26.8	76.5	3.7	4.0	24.2	79.4	22.0	81.7	20.0	83.9	17.3	86.9	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
Temperatures, Degree-Days and Degree-Hours	DBAvg	65.0	48.5	50.3	55.6	62.1	70.0	75.9	79.5	79.9	76.1	70.0	59.4	51.2
	DBStd	12.37	4.58	4.83	6.31	6.82	5.91	3.86	2.94	3.05	3.43	5.61	6.02	4.80
	HDD50	193	83	46	14	2	0	0	0	0	0	0	5	43
	HDD65	2010	513	412	302	134	19	0	0	0	0	18	183	429
	CDD50	5656	35	55	188	366	619	778	915	928	783	621	289	79
	CDD65	1997	0	0	11	48	173	328	450	463	333	174	16	1
	CDH74	20817	0	7	161	721	2141	3539	4654	4668	3078	1655	192	1
	CDH80	9481	0	0	39	246	929	1685	2293	2295	1316	644	34	0
Wind	WSAvg	4.5	4.4	4.5	4.8	5.0	5.2	5.5	6.3	5.3	3.8	2.9	2.9	3.3
Precipitation	PrecAvg	10.4	2.4	2.3	1.3	0.6	0.2	0.0	0.0	0.0	0.0	0.4	1.1	2.1
	PrecMax	18.4	6.6	6.6	3.4	5.4	1.1	0.7	0.2	0.0	0.2	1.3	5.2	5.6
	PrecMin	4.4	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.3
	PrecStd	4.3	1.6	1.7	1.0	1.1	0.2	0.2	0.0	0.0	0.0	0.4	1.3	1.7
Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	67.6	73.6	84.5	92.3	99.2	99.9	101.0	101.1	98.0	95.8	84.0	71.5
		MCWB	51.2	54.4	58.5	61.7	64.0	65.5	70.1	69.2	65.1	63.3	58.2	51.7
	2%	DB	63.4	66.8	78.6	86.4	93.4	96.3	96.0	95.6	93.6	90.6	79.1	66.1
		MCWB	50.2	51.0	56.3	59.5	62.7	65.0	69.3	70.0	65.4	61.7	56.7	50.6
	5%	DB	60.3	63.5	73.4	82.6	89.4	92.6	93.1	92.7	90.3	86.6	75.2	63.0
		MCWB	49.4	49.9	53.9	58.2	61.8	65.5	69.0	70.1	66.4	61.2	56.0	50.3
	10%	DB	57.5	60.0	68.9	77.9	85.4	89.1	90.9	90.4	87.2	82.9	72.0	60.3
		MCWB	48.1	49.3	53.2	57.2	60.9	65.5	68.5	69.4	66.1	61.6	55.0	49.8
Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	55.5	56.9	62.0	64.7	68.8	71.1	75.1	75.6	73.5	67.4	62.1	56.1
		MCDB	62.4	69.0	76.8	82.5	89.4	87.8	91.7	92.7	88.6	80.7	73.6	64.1
	2%	WB	52.3	53.3	58.2	62.1	65.6	69.3	72.9	73.6	70.9	65.9	60.1	54.2
		MCDB	58.8	62.9	72.1	79.8	86.2	86.2	89.1	88.0	83.2	79.3	71.7	61.2
	5%	WB	50.9	51.7	56.3	60.0	63.7	68.0	71.5	72.4	69.4	64.7	58.6	52.8
		MCDB	57.4	59.7	69.9	77.9	83.4	84.3	86.7	85.8	81.0	77.6	70.1	59.2
	10%	WB	49.4	50.3	54.3	58.3	62.2	66.9	70.3	71.3	68.3	63.6	57.2	51.4
		MCDB	55.7	57.2	65.8	75.6	81.1	83.2	84.3	83.8	79.7	76.5	68.5	57.5
Mean Daily Temperature Range	5% DB	MDBR	16.0	16.1	19.4	23.1	25.4	24.9	22.8	22.4	22.9	23.3	21.8	17.5
		MCDBR	21.2	23.5	28.4	31.0	32.4	31.2	26.4	25.5	28.3	29.9	27.3	22.4
		MCWBR	11.9	11.7	12.7	12.7	11.9	10.8	9.1	7.7	9.4	12.1	12.8	12.1
	5% WB	MCDBR	16.9	18.8	24.5	26.7	27.9	25.5	23.3	22.7	21.9	24.0	22.5	16.9
		MCWBR	10.8	10.6	12.2	12.8	11.4	9.3	8.1	6.9	8.0	10.8	11.6	10.4
Clear-Sky Solar Irradiance	taub		0.348	0.377	0.418	0.461	0.461	0.392	0.400	0.405	0.396	0.416	0.369	0.351
	taud		2.319	2.220	2.085	1.973	2.005	2.238	2.225	2.210	2.239	2.167	2.285	2.320
	Ebn at Noon		272	275	272	264	265	283	280	277	275	258	262	264
	Edh at Noon		33	40	49	58	56	44	45	45	42	42	34	31
All-Sky Solar Radiation	RadAvg		924	1171	1630	1997	2359	2631	2549	2331	1981	1489	1100	865
	RadStd		65	109	102	114	107	39	27	36	51	63	63	59

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD50	HDD65	CDD50	CDD65
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (21 neighbors)		+0.79	N/A	-3.11	N/A	N/A	N/A	N/A	-115	+284	+185

Nomenclature: See separate page