

SHIJIAZHUANG, China

WMO: 536980

Lat: 38.0733N

Lon: 114.3513E

Elev: 105

StdP: 100.07

Time Zone: 8.00 (E08)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-8.0	-6.5	-24.7	0.4	0.5	-22.4	0.5	0.6	6.6	1.5	5.7	1.6	1.2	0	0.378

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	7.8	36.2	22.1	34.6	22.6	33.2	22.8	27.1	31.6	26.3	30.6	25.5	29.8	2.6	160

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
25.9	21.6	30.1	25.1	20.4	29.2	24.2	19.4	28.6	86.8	31.6	83.0	30.8	79.5	29.8	30.0

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 5.8	4.9	4.1	DB	-10.5	38.9	2.0	1.6	-11.9	40.0	-13.0	41.0	-14.1	41.9	-15.6	43.0	(4)
(5)			WB	-11.7	28.5	1.8	0.7	-13.0	29.0	-14.1	29.4	-15.1	29.8	-16.4	30.3	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	14.8	-0.9	2.6	9.5	16.1	22.1	26.6	28.0	26.5	22.1	15.6	7.1	1.0	(6)	
	DBStd	10.71	3.23	3.65	4.30	3.93	3.41	2.98	2.70	2.51	3.03	3.55	4.28	3.27	(7)	
	HDD10.0	1000	338	209	61	3	0	0	0	0	3	106	279		(8)	
	HDD18.3	2387	597	442	275	88	8	0	0	0	6	98	336	538	(9)	
	CDD10.0	2736	0	1	46	186	376	497	558	511	364	176	20	0	(10)	
	CDD18.3	1080	0	0	1	21	126	247	300	253	119	13	0	0	(11)	
	CDH23.3	11049	0	0	14	183	1121	2771	3552	2516	812	78	1	0	(12)	
	CDH26.7	4667	0	0	2	42	394	1339	1686	966	227	11	0	0	(13)	
(14) Wind	WSAvg	1.7	1.6	1.7	2.1	2.2	2.2	1.8	1.7	1.5	1.5	1.5	1.5	1.6	(14)	
(15) Precipitation	PrecAvg	528	3	8	11	22	38	49	141	149	56	29	16	4	(15)	
	PrecMax	1049	13	41	44	129	162	188	281	752	177	142	58	20	(16)	
	PrecMin	229	0	0	0	1	3	5	49	22	2	1	0	0	(17)	
	PrecStd	170	4	10	12	27	40	39	69	127	38	29	16	6	(18)	
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	11.9	16.2	25.1	30.4	35.4	38.4	38.6	35.5	32.7	28.4	22.0	13.0	(19)	
		MCWB	4.1	6.4	11.5	16.3	17.9	21.0	22.2	24.6	22.1	16.3	10.4	4.3	(20)	
	2%	DB	8.3	13.4	22.1	27.5	32.3	36.3	36.3	33.6	30.7	25.6	18.4	10.4	(21)	
		MCWB	1.4	4.9	10.7	15.9	18.0	20.7	23.5	24.8	20.5	14.8	9.4	2.8	(22)	
	5%	DB	6.2	11.1	19.3	25.3	30.6	34.7	34.6	32.3	29.2	23.5	15.8	8.2	(23)	
		MCWB	0.2	4.0	9.6	14.7	17.9	20.8	24.1	24.4	20.2	14.1	8.5	1.9	(24)	
	10%	DB	4.3	8.9	16.8	23.3	28.9	33.0	33.2	31.2	27.6	21.6	13.5	6.1	(25)	
		MCWB	-0.8	2.7	8.2	14.1	17.7	20.8	24.3	24.1	19.6	13.8	7.6	0.7	(26)	
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	4.1	7.7	14.3	20.3	22.7	25.3	28.5	28.3	25.2	19.1	12.6	5.0	(27)	
		MCDB	11.3	13.4	21.3	26.6	29.7	32.9	32.8	32.5	29.6	23.6	16.5	11.6	(28)	
	2%	WB	1.8	5.8	12.2	18.3	21.5	24.1	27.4	27.1	23.6	17.5	10.9	3.5	(29)	
		MCDB	7.4	11.6	19.8	24.1	28.2	31.5	32.1	31.2	27.6	21.3	16.1	8.7	(30)	
	5%	WB	0.6	4.4	10.4	16.8	20.5	23.2	26.6	26.2	22.2	16.5	9.6	2.4	(31)	
		MCDB	5.4	10.3	17.9	22.5	27.1	30.1	31.2	30.2	26.5	20.5	14.2	7.0	(32)	
	10%	WB	-0.5	3.2	8.8	15.4	19.4	22.4	25.9	25.4	21.1	15.5	8.4	1.4	(33)	
		MCDB	3.8	8.4	15.8	20.9	25.9	29.2	30.3	29.3	25.4	19.5	12.7	5.3	(34)	
(35) Mean Daily Temperature Range	5% DB	MDBR	7.5	8.4	9.3	9.9	9.9	9.8	7.8	7.2	8.4	8.8	8.2	7.2	(35)	
		MCDBR	10.6	12.0	13.0	13.3	12.7	13.0	10.7	8.9	10.6	11.7	11.6	10.4	(36)	
	5% WB	MCWBR	6.2	6.7	6.4	6.2	5.3	3.8	3.3	3.6	4.0	4.7	5.7	5.7	(37)	
		MCWBR	9.9	10.9	11.9	11.2	10.5	9.8	7.8	7.4	8.2	8.2	10.0	9.4	(38)	
(40) Clear-Sky Solar Irradiance	taub		0.476	0.555	0.557	0.607	0.644	0.787	0.782	0.762	0.692	0.631	0.507	0.464	(40)	
		taud	1.853	1.714	1.740	1.683	1.649	1.461	1.510	1.526	1.599	1.661	1.845	1.913	(41)	
	Ebn at Noon		644	642	702	699	683	590	588	584	590	570	607	622	(42)	
		Edh at Noon	152	199	212	238	250	302	286	275	242	207	152	134	(43)	
(44) All-Sky Solar Radiation	RadAvg		2.53	3.15	4.51	5.37	5.92	5.35	4.73	4.57	4.03	3.31	2.62	2.31	(44)	
	RadStd		0.21	0.39	0.40	0.37	0.47	0.48	0.30	0.41	0.35	0.36	0.41	0.24	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)		
(46) Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (10 neighbors)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page