

GRATES COVE, NL, Canada

WMO: 713360

Lat: 48.1700N

Lon: 52.9400W

Elev: 46

StdP: 100.77

Time Zone: -3.50 (NAF)

Period: 94-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
2	-12.7	-11.1	-17.4	0.8	-11.5	-15.7	1.0	-10.1	22.9	-3.7	21.3	-1.4	9.2	300	0.944

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
8	5.8	22.9	18.3	21.5	17.8	20.4	17.3	19.8	21.5	18.9	20.6	18.1	19.7	8.3	230

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
19.1	14.0	20.8	18.2	13.2	20.0	17.3	12.4	19.2	56.9	21.7	54.0	20.7	51.3	19.7	23.6

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 18.8	16.5	15.1	DB	-15.5	25.9	2.9	1.4	-17.6	26.9	-19.3	27.8	-20.9	28.5	-23.1	29.6	(4)
(5)			WB	-15.2	21.6	2.1	1.2	-16.7	22.4	-18.0	23.1	-19.2	23.8	-20.7	24.6	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6)	Temperatures, Degree-Days and Degree-Hours	DBAvg	5.6	-3.0	-3.5	-2.1	1.7	5.4	10.2	15.6	16.5	13.1	8.4	4.2	-0.4	(6)
(7)		DBStd	7.69	3.97	4.00	3.47	2.91	3.38	3.73	3.34	2.50	2.99	3.11	3.37	3.77	(7)
(8)		HDD10.0	2176	402	377	375	249	149	44	3	0	6	71	176	323	(8)
(9)		HDD18.3	4683	661	611	633	499	401	246	96	66	158	308	423	581	(9)
(10)		CDD10.0	554	0	0	0	0	7	49	175	201	99	21	3	0	(10)
(11)		CDD18.3	20	0	0	0	0	0	0	9	9	2	0	0	0	(11)
(12)		CDH23.3	24	0	0	0	0	0	0	13	9	1	0	0	0	(12)
(13)		CDH26.7	0	0	0	0	0	0	0	0	0	0	0	0	0	(13)
(14)	Wind	WSAvg	7.7	9.1	8.6	8.3	7.4	6.4	6.3	6.7	6.7	7.4	7.9	8.4	8.9	(14)
(15)	Precipitation	PrecAvg	1419	140	126	116	107	97	97	102	98	122	139	134	141	(15)
(16)		PrecMax	1694	234	182	210	238	153	144	162	159	224	241	210	242	(16)
(17)		PrecMin	1125	79	66	51	45	41	47	64	47	53	42	60	62	(17)
(18)		PrecStd	138	40	29	34	44	27	25	26	29	40	45	36	44	(18)
(19)	Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	10.1	8.7	9.7	12.7	17.8	22.1	24.9	24.6	22.4	18.9	15.4	12.5	(19)
(20)		MCWB	9.5	8.3	8.1	9.3	12.5	17.2	18.7	19.3	18.8	17.3	14.3	11.8	(20)	
(21)		2%	DB	7.0	5.4	6.4	9.8	15.2	20.0	23.2	22.7	20.2	16.6	13.1	9.7	(21)
(22)		MCWB	6.5	5.0	5.2	7.8	11.1	15.6	18.2	18.4	17.2	15.3	12.4	9.1	(22)	
(23)		5%	DB	4.1	3.4	3.8	7.7	13.0	18.0	21.7	21.5	18.8	14.8	11.3	6.8	(23)
(24)		MCWB	3.5	3.0	2.8	6.0	9.9	14.5	17.8	18.1	16.6	13.5	10.6	6.1	(24)	
(25)		10%	DB	2.1	1.5	2.0	5.8	10.9	16.1	20.4	20.3	17.6	13.0	9.3	4.4	(25)
(26)		MCWB	1.5	0.9	1.1	4.0	8.2	13.4	17.3	17.6	15.6	11.6	8.4	3.6	(26)	
(27)	Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	9.7	9.2	8.5	11.0	14.6	18.7	21.1	21.1	19.6	17.9	14.5	12.2	(27)
(28)		MADB	10.1	9.4	9.1	11.9	16.7	21.1	23.3	22.6	21.1	18.8	15.2	12.7	(28)	
(29)		2%	WB	6.7	5.5	5.4	8.5	12.5	17.0	19.8	19.9	18.3	15.9	12.6	9.1	(29)
(30)		MADB	7.0	5.8	6.1	9.4	14.3	19.0	21.8	21.4	19.7	16.6	13.2	9.7	(30)	
(31)		5%	WB	3.5	3.4	2.8	6.4	10.3	15.4	18.9	19.0	17.3	13.8	10.7	6.2	(31)
(32)		MADB	3.9	3.7	3.4	7.6	12.9	17.1	20.8	20.4	18.6	14.7	11.4	6.7	(32)	
(33)		10%	WB	1.5	1.3	1.3	4.5	8.5	13.8	18.0	18.1	16.1	12.0	8.7	3.7	(33)
(34)		MADB	2.0	1.7	1.9	5.7	11.0	15.9	19.9	19.6	17.5	13.0	9.4	4.3	(34)	
(35)	Mean Daily Temperature Range	MDBR	5.8	5.2	5.0	5.1	6.3	6.9	6.9	5.8	5.5	4.4	4.7	4.8	(35)	
(36)		5% DB	MADB	9.7	8.2	8.1	8.6	10.3	10.3	8.6	7.6	7.1	6.8	7.8	8.9	(36)
(37)		MCWBR	9.6	8.2	7.4	6.8	7.3	6.5	5.2	4.7	5.2	6.3	7.9	9.4	(37)	
(38)		5% WB	MADB	9.4	8.0	7.6	8.3	9.9	9.2	7.6	6.8	7.1	7.0	7.8	8.7	(38)
(39)		MCWBR	9.7	8.3	7.4	7.4	7.6	7.2	5.4	5.1	5.9	6.9	7.9	9.2	(39)	
(40)	Clear-Sky Solar Irradiance	taub	0.317	0.313	0.337	0.367	0.372	0.403	0.428	0.399	0.373	0.348	0.323	0.311	(40)	
(41)		taud	2.325	2.417	2.356	2.350	2.416	2.354	2.331	2.418	2.463	2.476	2.454	2.354	(41)	
(42)		Ebn at Noon	739	847	878	883	890	860	832	842	833	795	738	698	(42)	
(43)		Edh at Noon	73	83	103	114	111	120	121	106	93	78	64	63	(43)	
(44)	All-Sky Solar Radiation	RadAvg	0.94	1.73	2.84	3.99	4.79	5.13	5.20	4.38	3.42	2.04	1.15	0.75	(44)	
(45)		RadStd	0.08	0.14	0.27	0.39	0.38	0.41	0.44	0.29	0.23	0.21	0.15	0.07	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)		
(46) Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(47) Regional (10 neighbors)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		

Nomenclature: See separate page