

CHESTER CATAWBA, SC, USA

WMO: 720599

Lat: 34.783N

Lon: 81.200W

Elev: 200

StdP: 98.94

Time Zone: -5.00 (NAE)

Period: 09-19

WBAN: 00192

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a) 1	(b) -5.9	(c) -2.8	(d) -16.3	(e) 0.9	(f) -1.5	(g) -12.7	(h) 1.3	(i) 0.7	(j) 7.6	(k) 11.3	(l) 6.9	(m) 8.2	(n) 1.4	(o) 0	(p) 0.362

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	10.8	35.0	23.7	33.0	23.2	32.4	23.0	27.2	30.4	25.7	29.2	24.9	29.1	2.1	260

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
26.2	22.2	29.2	25.0	20.6	27.1	23.7	19.0	25.7	87.0	30.0	80.2	29.4	76.5	30.2	30.3

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	DB	WB
(a) 7.1	(b) 5.7	(c) 5.0	(e) -8.4	(f) 36.5	(g) 2.4	(h) 2.1	(i) -10.1	(j) 38.0	(k) -11.6	(l) 39.3	(m) -12.9	(n) 40.5	(o) -14.7	(p) 42.0		
(a) 7.1	(b) 5.7	(c) 5.0	(e) -9.1	(f) 26.6	(g) 2.3	(h) 1.5	(i) -10.8	(j) 27.7	(k) -12.1	(l) 28.6	(m) -13.4	(n) 29.4	(o) -15.0	(p) 30.5		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6)	Temperatures, Degree-Days and Degree-Hours	DBAvg	16.8	5.8	8.3	11.2	16.9	21.4	25.4	26.7	25.8	23.4	16.9	10.8	8.1	(6)
(7)		DBStd	8.38	5.36	5.10	5.03	4.05	3.43	2.30	1.90	1.85	2.91	4.23	3.97	4.90	(7)
(8)		HDD10.0	424	152	86	47	3	0	0	0	0	3	37	98		(8)
(9)		HDD18.3	1616	390	282	227	74	16	0	0	3	77	228	319		(9)
(10)		CDD10.0	2892	21	39	84	209	354	462	517	490	403	216	60	38	(10)
(11)		CDD18.3	1042	1	2	6	31	111	212	259	232	156	31	1	1	(11)
(12)		CDH23.3	9097	1	8	57	292	890	1947	2461	1927	1262	247	4	1	(12)
(13)		CDH26.7	3701	0	0	5	57	298	849	1138	804	492	58	0	0	(13)
(14)	Wind	WSAvg	1.9	2.0	2.1	2.4	2.3	1.9	1.6	1.5	1.4	1.8	1.9	2.0	1.8	(14)
(15)	Precipitation	PrecAvg	1114	100	88	111	87	74	107	91	109	92	88	81	87	(15)
(16)		PrecMax	1397	178	152	212	201	192	231	195	247	238	319	175	183	(16)
(17)		PrecMin	726	23	35	30	33	25	17	36	13	1	0	10	34	(17)
(18)		PrecStd	179	42	34	52	48	39	55	36	61	58	69	45	39	(18)
(19)	Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	22.2	25.0	27.4	30.1	32.9	36.3	37.1	35.1	34.0	31.3	23.6	22.4	(19)
(20)		MCWB	16.3	17.1	16.2	19.0	20.9	23.3	23.9	23.8	22.1	21.6	16.7	18.3		(20)
(21)		2%	DB	18.7	22.1	25.1	27.9	32.0	34.1	35.2	32.9	32.6	27.7	22.0	20.2	(21)
(22)		MCWB	14.4	15.2	15.6	18.3	20.6	23.6	24.1	23.7	22.1	20.2	15.6	17.6		(22)
(23)		5%	DB	17.1	19.8	22.4	27.1	30.1	32.6	33.0	32.3	31.3	26.1	20.0	17.8	(23)
(24)		MCWB	13.5	13.6	14.4	17.9	20.7	23.2	23.4	23.7	22.0	18.7	15.7	15.7		(24)
(25)		10%	DB	14.8	17.3	20.0	25.0	27.9	31.3	32.4	31.2	30.0	23.8	17.7	16.2	(25)
(26)		MCWB	11.4	12.8	13.7	16.7	20.2	22.8	23.5	23.5	21.6	18.3	14.2	13.9		(26)
(27)	Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	18.1	18.0	18.5	21.7	24.7	28.1	28.5	28.6	25.3	23.8	19.9	20.5	(27)
(28)		MCDB	20.0	21.1	23.0	26.4	28.4	32.8	33.6	31.5	31.0	25.5	20.3	21.0		(28)
(29)		2%	WB	16.5	17.1	17.3	20.6	23.2	26.6	26.8	27.1	24.3	22.6	18.0	18.7	(29)
(30)		MCDB	17.5	19.8	21.0	24.3	27.2	30.1	30.3	29.0	29.4	24.7	19.5	20.0		(30)
(31)		5%	WB	14.1	15.5	16.3	19.6	22.3	25.1	25.4	25.4	23.3	21.4	17.2	16.9	(31)
(32)		MCDB	16.5	18.7	19.7	23.9	26.2	28.6	30.0	28.5	27.2	24.1	18.5	17.5		(32)
(33)		10%	WB	11.9	13.4	15.1	18.7	21.5	23.8	24.6	24.6	22.6	20.1	15.5	14.3	(33)
(34)		MCDB	13.1	16.3	18.8	23.4	25.2	28.7	29.5	28.3	26.2	23.2	17.3	16.1		(34)
(35)	Mean Daily Temperature Range	MDBR	10.3	11.0	11.8	12.7	11.3	11.1	10.8	10.2	11.1	11.7	11.5	9.6		(35)
(36)		5% DB	MCDBR	13.2	13.4	14.8	14.3	13.6	12.7	12.3	11.7	13.2	13.1	13.4	10.6	(36)
(37)		MCWBR	8.9	7.6	7.3	5.9	4.7	4.1	3.6	3.7	4.2	5.8	8.4	7.1		(37)
(38)		5% WB	MCDBR	10.8	11.1	11.8	11.6	10.5	11.1	10.7	9.6	11.0	10.1	9.8	7.9	(38)
(39)		MCWBR	8.9	7.5	7.5	5.8	4.9	5.3	4.4	4.4	4.5	5.8	7.9	6.8		(39)
(40)	Clear-Sky Solar Irradiance	taub	0.316	0.325	0.363	0.406	0.462	0.488	0.539	0.518	0.435	0.389	0.338	0.317		(40)
(41)		taud	2.498	2.470	2.393	2.264	2.149	2.120	1.999	2.044	2.260	2.364	2.468	2.527		(41)
(42)		Ebn at Noon	892	922	908	880	832	807	763	771	824	836	856	869		(42)
(43)		Edh at Noon	84	96	113	135	153	157	177	166	127	106	86	77		(43)
(44)	All-Sky Solar Radiation	RadAvg	2.68	3.32	4.39	5.50	6.08	6.42	6.02	5.51	4.71	3.90	2.96	2.31		(44)
(45)		RadStd	0.15	0.37	0.32	0.43	0.50	0.46	0.39	0.26	0.41	0.47	0.24	0.22		(45)

Historical Trends

	DBAvg	Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)
(46) Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (61 neighbors)	+0.56	N/A	N/A	N/A	N/A	N/A	N/A	N/A	+175	+119

Nomenclature: See separate page