

SHELBY COUNTY AP, AL, USA

WMO: 722300

Lat: 33.178N

Lon: 86.782W

Elev: 172

StdP: 99.27

Time Zone: -6.00 (NAC)

Period: 99-19

WBAN: 53864

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-5.0	-2.8	-13.7	1.2	-1.3	-11.3	1.4	1.8	8.2	8.4	7.5	8.5	2.1	350	0.347

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	10.0	35.0	23.2	33.7	23.6	32.6	23.6	25.8	30.9	25.3	30.4	24.9	29.8	2.4	330

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
24.5	19.9	27.6	24.0	19.2	27.2	23.5	18.7	26.9	80.3	31.2	78.2	30.4	76.4	29.9	28.3

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 6.9	5.7	5.0	DB	-8.2	36.3	2.6	2.1	-10.0	37.8	-11.6	39.0	-13.1	40.1	-15.0	41.6	(4)
(5)			WB	-9.2	26.8	2.5	0.6	-11.1	27.2	-12.5	27.6	-13.9	27.9	-15.8	28.4	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	17.9	7.3	9.8	13.6	17.9	22.0	25.7	27.0	27.0	24.3	18.3	12.6	8.9	(6)	
	DBStd	8.05	5.66	5.15	4.81	3.76	3.15	1.90	1.62	1.92	2.95	4.36	4.61	5.03	(7)	
	HDD10.0	319	122	63	22	2	0	0	0	0	2	26	84	84	(8)	
	HDD18.3	1336	343	242	157	53	9	0	0	0	2	56	181	293	(9)	
	CDD10.0	3201	38	57	134	237	371	470	527	526	429	259	102	51	(10)	
	CDD18.3	1176	1	3	11	38	122	220	268	267	181	55	7	2	(11)	
	CDH23.3	10306	1	9	83	311	989	1939	2536	2488	1481	428	37	3	(12)	
(13) Wind	CDH26.7	4171	0	0	9	49	314	820	1131	1146	588	108	4	0	(13)	
	WSAvg	1.8	2.3	2.3	2.3	2.1	1.6	1.4	1.3	1.2	1.4	1.6	1.8	2.1	(14)	
	PrecAvg	1423	134	139	149	121	95	116	132	103	103	79	107	136	(15)	
	PrecMax	1800	234	235	251	243	241	239	281	233	259	226	260	265	(16)	
	PrecMin	795	65	48	36	38	9	48	48	0	7	6	26	63	(17)	
	PrecStd	232	49	50	57	49	50	57	62	52	70	53	49	52	(18)	
	DB	22.8	24.7	27.9	29.5	32.7	35.7	36.3	37.5	35.3	31.3	27.1	23.3	23.3	(19)	
(20) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	MCWB	17.6	18.6	17.8	19.8	22.1	22.4	23.9	23.5	22.1	21.2	19.2	19.1	19.1	(20)	
	DB	20.6	22.4	25.6	28.0	31.1	33.7	34.2	35.3	33.3	29.3	24.0	21.2	21.2	(21)	
	MCWB	16.4	16.8	17.2	19.2	21.6	23.0	24.4	23.5	22.5	20.4	17.4	17.7	17.7	(22)	
	DB	18.4	20.4	23.7	26.9	29.8	32.4	33.0	33.7	31.8	27.7	22.4	19.2	19.2	(23)	
	MCWB	15.5	15.8	16.4	18.6	21.1	23.1	24.4	23.7	22.5	19.5	17.0	16.5	16.5	(24)	
	DB	16.6	18.4	21.8	25.3	28.5	31.2	32.0	32.3	30.2	25.9	20.6	17.4	17.4	(25)	
	MCWB	14.0	14.2	15.5	17.6	20.7	23.0	24.2	23.9	22.4	19.0	16.5	14.8	14.8	(26)	
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	WB	19.0	19.8	20.2	22.3	24.3	25.7	26.8	26.4	25.1	24.3	21.7	20.7	20.7	(27)	
	MCDB	21.2	22.7	23.3	26.9	28.8	30.5	31.8	31.6	29.9	26.7	23.8	22.2	22.2	(28)	
	WB	17.8	18.6	19.2	21.0	23.3	25.1	25.9	25.7	24.5	22.9	20.3	18.7	18.7	(29)	
	MCDB	19.4	21.1	22.6	25.1	27.9	30.2	31.0	31.0	29.1	26.5	22.0	20.1	20.1	(30)	
	WB	16.4	17.4	18.1	20.2	22.6	24.6	25.5	25.2	24.0	21.9	18.7	17.2	17.2	(31)	
	MCDB	17.9	19.4	21.8	24.2	27.3	29.4	30.6	30.4	28.4	25.4	21.3	18.7	18.7	(32)	
	WB	14.4	15.4	16.9	19.3	22.0	24.1	25.0	24.8	23.4	20.7	17.1	15.2	15.2	(33)	
(34) Mean Daily Temperature Range	MCDB	16.1	17.5	20.5	23.2	26.6	28.6	29.9	29.6	27.5	23.8	19.7	17.1	17.1	(34)	
	MDBR	10.6	11.1	11.6	11.9	11.1	10.3	10.0	10.3	10.7	11.8	12.1	10.3	10.3	(35)	
	5% DB	11.6	12.7	13.1	13.2	12.4	12.4	11.4	12.7	12.5	13.6	13.4	11.7	11.7	(36)	
	MCWBR	8.0	7.9	6.4	5.7	4.6	4.1	3.6	3.7	4.0	5.8	7.6	8.5	8.5	(37)	
	5% WB	9.5	10.5	10.4	10.4	9.9	9.9	10.0	10.0	9.5	9.5	9.7	9.8	9.8	(38)	
	MCWBR	8.0	8.2	6.3	5.6	4.4	4.2	3.8	3.6	3.8	5.0	7.0	8.4	8.4	(39)	
	taub	0.319	0.327	0.359	0.390	0.451	0.475	0.526	0.524	0.431	0.368	0.342	0.322	0.322	(40)	
(41) Clear-Sky Solar Irradiance	taud	2.530	2.504	2.430	2.327	2.198	2.172	2.049	2.045	2.296	2.461	2.472	2.535	2.535	(41)	
	Ebn at Noon	901	928	918	898	843	819	775	770	834	869	862	876	876	(42)	
	Edh at Noon	83	94	110	127	146	150	168	167	124	98	88	79	79	(43)	
	RadAvg	2.67	3.21	4.36	5.54	6.06	6.17	5.97	5.52	4.86	4.07	3.02	2.28	2.28	(44)	
(45) All-Sky Solar Radiation	RadStd	0.20	0.42	0.40	0.40	0.46	0.47	0.40	0.31	0.43	0.52	0.31	0.24	0.24	(45)	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	+159	+104
Regional (46 neighbors)		+0.48	N/A	N/A	N/A	N/A	N/A	N/A	N/A	+156	+107

Nomenclature: See separate page