

LUCE COUNTY AP, MI, USA

WMO: 726394

Lat: 46.311N

Lon: 85.457W

Elev: 281

StdP: 97.99

Time Zone: -5.00 (NAE)

Period: 97-19

WBAN: 04874

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-21.4	-18.7	-24.2	0.4	-20.8	-22.2	0.5	-17.9	11.0	-3.8	9.8	-5.4	3.0	250	0.613

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	11.7	28.7	21.5	27.3	20.4	26.0	19.1	23.0	26.7	21.9	25.4	20.8	23.8	4.5	210

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
22.2	17.4	25.4	21.0	16.2	24.2	19.5	14.7	22.7	69.8	26.5	65.5	25.2	61.5	24.5	27.4

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 9.4	8.4	7.6	DB	-26.3	31.1	4.0	1.9	-29.2	32.4	-31.5	33.5	-33.7	34.6	-36.6	35.9	(4)
(5)			WB	-26.5	24.7	3.8	1.6	-29.2	25.9	-31.4	26.9	-33.6	27.8	-36.3	28.9	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
Temperatures, Degree-Days and Degree-Hours	DBAvg	5.7	-8.1	-7.5	-2.8	4.0	10.9	15.9	18.8	18.1	14.5	7.5	1.4	-4.7
	DBStd	10.71	5.83	5.94	6.15	4.93	4.55	3.78	3.42	3.14	4.33	4.52	4.79	5.35
	HDD10.0	2514	560	489	400	189	44	3	0	0	9	107	258	454
	HDD18.3	4717	818	722	657	431	234	91	36	43	129	336	507	713
	CDD10.0	961	0	0	2	8	72	181	273	251	143	30	2	0
	CDD18.3	122	0	0	0	0	3	19	51	36	13	1	0	0
	CDH23.3	991	0	0	1	1	48	178	442	244	76	2	0	0
	CDH26.7	182	0	0	0	0	6	27	103	36	10	0	0	0
Wind	WSAvg	3.4	3.7	3.7	3.6	3.7	3.6	3.1	3.0	2.9	3.3	3.5	3.6	3.7
Precipitation	PrecAvg	799	51	32	42	51	73	76	72	84	91	78	62	52
	PrecMax	1042	150	86	142	146	183	170	189	209	205	158	139	100
	PrecMin	596	0	0	0	6	16	7	18	4	28	14	8	0
	PrecStd	105	26	24	34	29	38	37	37	40	40	33	33	27
Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	5.2	7.7	17.2	21.4	27.3	29.1	32.0	29.1	27.8	22.6	16.0	9.2
		MCWB	3.5	5.8	11.4	12.3	18.6	20.2	22.2	22.2	21.1	17.1	12.0	8.4
	2%	DB	2.9	4.1	11.4	17.8	24.1	27.3	29.0	27.5	25.8	19.6	12.3	6.0
		MCWB	2.1	2.6	8.2	10.1	16.2	20.1	21.8	21.0	19.8	16.2	10.0	4.4
	5%	DB	1.9	2.5	7.7	14.9	22.3	25.6	27.5	26.1	23.7	17.5	10.0	3.8
		MCWB	1.3	1.5	4.8	8.2	14.9	18.2	20.7	19.7	18.7	14.3	8.3	2.8
	10%	DB	0.2	1.1	5.2	12.3	19.1	23.7	26.1	24.1	22.1	14.9	7.9	2.5
		MCWB	-0.2	0.2	2.8	6.9	13.3	17.4	19.3	18.6	18.1	12.4	6.5	1.8
Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	4.3	5.6	12.9	14.4	20.4	23.2	25.1	24.0	22.9	19.5	12.8	8.4
		MCDB	5.3	7.8	15.5	18.6	25.3	26.9	28.9	27.5	26.1	20.5	15.0	8.8
	2%	WB	2.4	3.1	8.6	11.6	18.4	21.5	23.5	22.6	21.1	16.7	10.4	4.7
		MCDB	3.0	4.2	10.6	15.5	22.5	25.8	27.2	25.8	23.7	18.8	11.8	5.7
	5%	WB	0.9	1.6	5.2	9.4	16.4	19.9	22.1	21.3	19.9	14.6	8.3	3.0
		MCDB	1.4	2.4	8.0	13.9	19.9	23.6	25.9	24.2	22.5	17.1	9.2	3.7
	10%	WB	-0.4	0.0	3.0	7.5	14.5	18.6	20.9	20.2	18.7	12.6	6.9	1.7
		MCDB	0.2	0.9	4.7	11.5	18.4	21.7	24.1	23.1	20.9	14.5	8.0	2.3
Mean Daily Temperature Range	5% DB	MDBR	6.9	8.2	9.0	10.0	11.9	12.0	11.7	11.1	10.4	8.5	6.6	6.4
		MCDBR	6.5	7.7	10.8	15.2	15.5	13.9	13.3	12.5	11.7	11.2	9.2	6.9
		MCWBR	5.9	6.5	7.5	9.2	8.8	7.8	7.2	7.0	6.8	7.7	7.2	6.3
	5% WB	MCDBR	6.1	6.9	9.9	13.6	12.8	11.4	11.2	10.4	10.0	8.3	6.6	6.6
		MCWBR	5.8	6.2	7.3	9.3	8.4	7.4	7.1	6.7	6.6	7.6	7.0	6.2
Clear-Sky Solar Irradiance	taub	0.275	0.280	0.305	0.347	0.367	0.385	0.384	0.372	0.358	0.328	0.298	0.267	
	taud	2.383	2.356	2.388	2.361	2.377	2.352	2.372	2.410	2.442	2.518	2.524	2.461	
	Ebn at Noon	831	901	926	910	898	880	876	874	856	838	804	807	
	Edh at Noon	71	89	101	114	117	121	117	108	96	77	63	59	
All-Sky Solar Radiation	RadAvg	1.08	2.01	3.30	4.48	5.58	6.02	6.06	5.13	3.84	2.23	1.17	0.83	
	RadStd	0.12	0.21	0.37	0.50	0.46	0.41	0.32	0.33	0.29	0.26	0.15	0.07	

Historical Trends

	DBAvg	Heating			Cooling			Degree-Days			
		99% DB		99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46) Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (36 neighbors)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page