

OSHKOSH WHITTMAN, WI, USA

WMO: 726456

Lat: 43.984N

Lon: 88.557W

Elev: 782

StdP: 14.29

Time Zone: -6.00 (NAC)

Period: 96-19

WBAN: 94855

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-6.3	-1.8	-15.4	2.4	-5.0	-11.1	3.1	-1.3	24.8	19.8	22.8	21.6	7.6	280	0.563

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	18.8	88.2	73.6	85.1	71.7	82.4	70.1	76.2	84.7	74.2	82.3	72.3	80.1	10.7	210

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
73.1	126.7	81.5	71.8	120.8	80.0	69.9	113.0	77.7	40.2	84.5	38.2	82.0	36.5	79.4	84.7

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 22.7	19.8	17.9	-13.2	92.5	5.0	3.2	-16.8	94.8	-19.8	96.7	-22.6	98.4	-26.2	100.7		
(5)			-13.8	79.3	4.8	2.3	-17.2	80.9	-20.0	82.3	-22.7	83.6	-26.2	85.3		

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	46.6	18.9	21.9	32.7	45.4	57.0	67.0	71.6	69.4	62.2	49.6	36.8	24.7
	DBStd	20.52	11.70	11.12	11.37	8.91	8.46	6.60	5.57	5.31	7.66	8.75	9.66	11.03
	HDD50	3833	964	787	550	190	27	0	0	0	5	116	408	786
	HDD65	7309	1429	1207	1002	590	278	55	10	19	140	482	847	1250
	CDD50	2574	0	0	14	52	243	509	668	600	372	105	10	1
	CDD65	575	0	0	1	2	28	113	213	154	58	6	0	0
	CDH74	4606	0	0	8	35	280	934	1787	1057	453	52	0	0
	CDH80	1238	0	0	0	5	67	261	546	249	103	7	0	0
	WSAvg	8.5	9.0	9.0	9.2	10.2	9.1	7.7	7.0	6.6	7.7	8.6	9.0	8.7
	PrecAvg	32.0	1.3	1.1	2.1	3.0	3.5	3.8	3.6	3.8	3.7	2.3	2.3	1.5
(15) Precipitation	PrecMax	40.5	3.1	3.4	6.4	6.5	9.0	10.6	8.4	10.9	11.5	7.3	6.3	4.6
	PrecMin	22.3	0.1	0.1	0.1	0.4	0.4	0.7	1.1	0.7	0.2	0.3	0.1	0.1
	PrecStd	4.6	0.7	0.7	1.3	1.3	1.9	2.2	1.6	2.2	2.4	1.4	1.4	0.9
	PrecStd	4.6	0.7	0.7	1.3	1.3	1.9	2.2	1.6	2.2	2.4	1.4	1.4	0.9
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	46.5	52.9	72.3	79.0	86.5	90.9	93.4	90.0	87.8	80.2	66.8	55.2
		MCWB	42.0	48.3	61.0	61.9	69.8	73.9	77.2	75.1	72.0	67.3	56.5	52.5
	2%	DB	40.2	44.8	62.0	71.9	81.3	86.2	89.0	85.6	82.6	73.3	60.1	46.5
		MCWB	36.6	39.9	54.6	58.1	66.8	71.5	74.9	72.6	69.8	63.3	52.8	43.0
	5%	DB	37.1	39.4	54.7	65.5	76.5	82.4	85.4	82.3	79.3	69.0	55.3	42.2
		MCWB	34.7	36.2	48.2	54.4	63.7	70.1	72.7	70.6	67.7	60.4	49.6	39.1
	10%	DB	34.7	36.5	48.2	60.8	72.1	79.5	82.4	80.1	75.3	63.6	51.0	38.0
		MCWB	32.8	33.7	42.7	50.6	61.5	67.5	70.6	68.9	65.8	56.9	45.9	35.4
	0.4%	WB	42.1	48.0	62.0	64.6	72.5	77.1	79.8	78.0	74.8	70.1	58.5	53.0
		MCDB	46.1	53.3	71.3	73.8	83.3	86.6	89.9	86.2	83.0	77.6	64.5	55.9
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	2%	WB	37.4	40.0	55.4	59.6	68.6	74.3	76.8	75.2	72.1	65.5	54.2	44.1
		MCDB	39.5	43.8	59.9	69.3	77.6	83.4	85.8	82.5	80.3	70.9	58.8	46.1
	5%	WB	34.9	36.7	48.8	55.6	66.0	71.9	74.7	72.7	69.8	61.6	50.1	39.2
		MCDB	36.7	39.6	54.5	64.4	74.7	80.5	82.6	79.9	76.1	67.4	55.2	41.7
	10%	WB	32.8	33.8	42.8	51.2	63.0	69.4	72.8	70.8	67.6	57.8	46.0	35.7
		MCDB	34.8	36.1	48.3	59.4	70.2	77.0	80.4	77.4	73.9	63.5	50.1	38.1
(35) Mean Daily Temperature Range	5% DB	MDBR	13.6	14.6	15.9	18.0	18.7	18.0	18.8	17.6	19.2	16.8	14.3	12.5
		MCDBR	14.1	15.6	22.8	27.3	24.5	21.9	21.4	20.0	23.0	23.2	21.1	15.3
		MCWBR	12.3	12.7	15.7	16.7	13.6	11.9	10.7	10.3	12.2	14.7	15.5	12.8
	5% WB	MCDBR	13.6	15.1	22.1	25.3	21.8	19.8	19.1	17.4	19.2	20.4	19.9	14.2
		MCWBR	12.2	12.5	15.9	16.9	13.3	11.9	11.1	10.2	11.6	15.1	16.0	12.7
(40) Clear-Sky Solar Irradiance	taub		0.271	0.322	0.335	0.376	0.403	0.413	0.402	0.399	0.370	0.331	0.297	0.274
	taud		2.394	2.227	2.354	2.293	2.265	2.276	2.310	2.309	2.383	2.487	2.510	2.439
	Ebn at Noon		274	272	286	281	276	272	274	271	271	269	263	262
	Edh at Noon		24	34	34	40	42	42	40	38	33	26	22	21
	RadAvg		515	854	1213	1444	1725	1900	1943	1661	1334	846	543	390
(45) All-Sky Solar Radiation	RadStd		64	84	134	140	137	136	90	107	107	91	48	39

Historical Trends

	DBAvg	Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD50	HDD65	CDD50	CDD65
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)
(46) Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (50 neighbors)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page