

REXBURG MADISON COUNTY AP, ID, USA

WMO: 726818

Lat: 43.832N

Lon: 111.808W

Elev: 1482

StdP: 84.74

Time Zone: -7.00 (NAM)

Period: 99-19

WBAN: 94194

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	-21.7	-18.2	-24.2	0.5	-21.1	-21.3	0.7	-17.5	11.8	0.4	10.7	0.0	1.6	50	0.635

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	18.2	32.6	15.9	31.2	15.5	29.5	15.0	17.7	28.7	16.8	27.8	16.0	26.9	3.9	210

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
13.8	11.8	21.0	12.7	11.0	20.6	11.9	10.4	20.0	55.4	28.9	52.5	27.7	49.9	26.7	21.5

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(4) 11.0	9.2	8.1	DB	-25.8	35.2	3.6	1.3	-28.4	36.1	-30.4	36.8	-32.4	37.5	-35.0	38.5	(4)
(5)			WB	-26.1	19.3	3.4	0.9	-28.5	20.0	-30.5	20.5	-32.4	21.0	-34.9	21.7	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	6.7	-6.8	-4.8	1.6	6.6	11.4	15.9	20.5	19.3	14.2	7.1	0.3	-5.8	(6)	
	DBStd	10.31	5.41	5.25	4.74	3.85	3.99	3.70	2.41	2.64	3.80	4.30	5.02	5.53	(7)	
	HDD10.0	2248	520	414	263	114	32	4	0	0	10	109	290	491	(8)	
	HDD18.3	4402	778	647	519	353	217	89	9	19	131	349	540	749	(9)	
	CDD10.0	1037	0	0	1	12	75	179	326	289	135	19	1	0	(10)	
	CDD18.3	149	0	0	0	0	1	14	77	51	6	0	0	0	(11)	
	CDH23.3	3152	0	0	0	4	84	396	1316	1071	272	9	0	0	(12)	
	CDH26.7	1153	0	0	0	0	13	111	545	419	65	1	0	0	(13)	
(14) Wind	WSAvg	3.1	2.3	2.8	3.7	4.1	3.7	3.6	3.1	3.0	3.0	3.0	3.0	2.5	(14)	
(15) Precipitation	PrecAvg	340	24	21	20	31	37	49	19	22	27	31	31	30	(15)	
	PrecMax	453	52	63	34	86	87	89	38	96	64	55	57	54	(16)	
	PrecMin	194	1	2	0	4	14	8	0	2	0	2	8	2	(17)	
	PrecStd	73	14	16	9	22	20	27	15	23	21	18	13	14	(18)	
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	5.1	8.7	18.5	23.6	28.3	32.1	34.7	34.0	31.2	24.4	16.6	7.7	(19)	
		MCWB	2.2	4.3	7.9	10.2	13.5	15.5	17.1	15.7	14.6	11.3	7.7	4.1	(20)	
	2%	DB	2.7	5.7	15.0	20.5	25.9	29.6	32.9	32.4	28.5	21.1	12.7	5.1	(21)	
		MCWB	1.1	2.4	6.4	9.0	12.4	15.0	16.3	15.3	13.4	10.3	6.3	2.6	(22)	
	5%	DB	1.4	3.8	11.8	17.7	23.1	27.7	31.7	31.0	26.6	18.2	10.2	3.0	(23)	
		MCWB	0.4	1.3	5.3	7.8	11.6	14.9	16.2	14.8	12.7	9.1	5.2	1.2	(24)	
	10%	DB	0.4	2.3	9.1	15.2	20.9	25.8	29.9	29.1	24.3	15.8	7.7	1.4	(25)	
		MCWB	-0.5	0.5	4.0	6.8	10.6	14.0	15.8	14.4	12.1	8.0	3.9	0.1	(26)	
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	3.0	4.9	8.5	11.3	15.1	17.6	19.2	17.9	16.0	12.7	8.5	4.9	(27)	
		MCDB	4.0	8.2	16.4	21.6	25.2	28.3	30.5	30.0	25.4	22.1	13.9	7.3	(28)	
	2%	WB	1.5	2.9	7.1	9.5	13.4	16.4	18.2	16.9	14.8	11.3	6.9	3.0	(29)	
		MCDB	2.4	5.0	13.9	18.6	23.2	27.3	29.3	28.1	25.2	18.5	12.1	4.7	(30)	
	5%	WB	0.6	1.8	5.7	8.4	12.2	15.3	17.4	16.0	13.8	10.0	5.5	1.5	(31)	
		MCDB	1.3	3.2	11.0	16.7	21.7	26.2	28.4	27.0	24.0	16.9	9.6	2.8	(32)	
	10%	WB	-0.4	0.7	4.4	7.3	11.1	14.3	16.6	15.3	12.7	8.7	4.2	0.3	(33)	
		MCDB	0.3	2.0	8.6	14.0	19.4	24.6	27.7	26.2	22.2	14.8	7.6	1.3	(34)	
(35) Mean Daily Temperature Range	5% DB	MDBR	8.3	9.0	10.7	12.7	14.0	15.4	18.2	18.6	16.9	13.5	10.2	8.0	(35)	
		MCDBR	7.7	9.0	14.7	18.2	18.7	19.4	20.6	21.4	21.3	18.4	14.5	8.0	(36)	
	5% WB	MCWBR	6.5	6.4	7.9	8.7	8.0	7.9	7.4	7.5	8.7	9.3	8.7	6.1	(37)	
		MCWBR	6.9	7.2	13.3	16.3	16.9	17.8	18.3	18.3	18.2	16.0	13.0	7.2	(38)	
(40) Clear-Sky Solar Irradiance	taub		0.240	0.252	0.268	0.303	0.312	0.316	0.334	0.331	0.304	0.277	0.258	0.242	(40)	
		taud	2.385	2.386	2.504	2.450	2.496	2.509	2.470	2.452	2.531	2.590	2.547	2.455	(41)	
	Ebn at Noon		911	959	984	964	959	952	930	922	929	922	889	878	(42)	
		Edh at Noon	74	90	92	106	105	104	107	105	89	73	64	63	(43)	
(44) All-Sky Solar Radiation	RadAvg		1.61	2.52	3.82	5.16	6.13	7.20	7.48	6.38	4.93	3.17	1.89	1.29	(44)	
	RadStd		0.19	0.30	0.32	0.39	0.60	0.59	0.34	0.35	0.37	0.24	0.18	0.16	(45)	

Historical Trends

		DBAvg	Heating			Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP		HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(47) Regional (11 neighbors)		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	

Nomenclature: See separate page