

DUPLIN COUNTY AP, NC, USA

WMO: 746929

Lat: 35.000N

Lon: 77.982W

Elev: 137

StdP: 14.62

Time Zone: -5.00 (NAE)

Period: 01-19

WBAN: 03702

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	20.5	24.8	2.7	6.3	31.6	8.5	8.6	34.4	18.9	44.4	17.0	45.2	2.5	330	0.353

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	19.4	95.2	75.9	92.6	75.0	90.4	74.5	79.4	88.3	78.3	86.7	77.4	85.5	5.0	240

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
77.2	142.5	82.4	75.4	133.9	81.0	75.0	132.0	80.7	43.1	87.1	41.7	87.8	40.7	85.5	84.4

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
1%	2.5%	5%	Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
16.4	13.0	11.4	DB	13.7	98.7	3.1	2.3	11.4	100.4	9.6	101.7	7.8	103.0	5.5	104.7	
			WB	12.2	81.1	3.9	1.9	9.4	82.5	7.1	83.6	4.9	84.6	2.1	86.0	

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	61.9	43.3	45.3	52.7	61.8	69.4	76.8	80.0	78.4	72.5	62.7	52.4	47.0
	DBStd	15.10	10.92	9.09	9.67	8.17	6.75	5.22	4.19	4.37	5.59	8.18	8.54	9.52
	HDD50	803	267	185	87	9	0	0	0	0	0	7	72	176
	HDD65	2912	674	555	393	154	38	1	0	0	10	140	385	562
	CDD50	5162	59	53	172	363	600	803	929	879	675	402	144	83
	CDD65	1797	1	3	13	58	173	354	464	415	235	70	7	4
	CDH74	16538	4	19	151	629	1571	3435	4690	3742	1730	506	47	14
	CDH80	6551	0	1	17	150	515	1459	2156	1590	563	98	2	0
(14) Wind	WSAvg	3.5	4.3	4.7	4.8	4.4	3.4	2.7	2.5	2.1	3.0	3.3	3.5	3.6
(15) Precipitation	PrecAvg	49.6	3.7	3.2	3.9	3.3	3.8	4.6	5.7	5.5	5.9	3.5	3.1	3.3
	PrecMax	65.0	6.2	7.4	6.5	5.7	8.0	11.8	9.3	12.6	26.1	8.7	8.0	7.2
	PrecMin	36.4	1.2	1.2	1.4	1.1	2.3	1.3	3.0	2.3	1.0	0.0	0.5	1.0
	PrecStd	7.0	1.5	1.6	1.3	1.2	1.5	2.3	1.7	2.2	4.8	1.9	1.9	1.5
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	74.1	77.2	82.1	88.2	92.7	97.1	99.0	97.4	91.7	87.7	79.0	76.1
		MCWB	64.0	65.0	62.8	66.4	69.9	73.8	76.5	75.6	73.1	72.9	66.2	67.6
	2%	DB	70.3	71.7	78.8	83.9	89.6	93.3	95.3	93.3	89.5	82.1	74.9	71.9
		MCWB	62.5	62.1	62.6	64.7	70.9	74.3	77.2	76.0	73.2	69.7	64.8	64.8
	5%	DB	65.8	66.2	74.5	81.3	85.7	90.8	92.7	90.6	86.1	79.4	72.0	68.0
		MCWB	60.6	59.0	60.9	64.4	69.5	73.6	75.8	75.8	72.9	68.0	63.7	63.7
	10%	DB	61.5	63.0	70.4	77.4	82.0	88.2	90.2	88.3	82.4	76.6	68.2	63.9
		MCWB	55.5	55.7	59.7	64.1	68.6	73.2	75.3	75.2	71.3	67.3	62.0	59.5
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	67.1	67.4	68.8	73.5	75.6	79.1	81.5	81.3	78.1	76.5	71.2	69.9
		MCDB	70.7	73.6	74.0	80.8	84.3	88.4	90.2	88.2	85.8	82.7	76.0	72.7
	2%	WB	64.3	64.9	66.3	70.5	73.7	77.7	80.0	79.1	76.6	74.7	68.5	67.1
		MCDB	67.9	69.4	72.8	77.0	81.8	87.0	89.1	87.0	83.6	79.0	72.0	70.1
	5%	WB	61.1	61.5	64.3	68.4	72.4	76.6	78.6	78.1	75.4	72.6	65.9	64.1
		MCDB	65.7	65.4	70.1	75.0	80.5	85.5	87.5	85.6	81.7	76.3	69.6	66.4
	10%	WB	57.2	56.4	62.1	66.3	71.1	75.5	77.5	77.2	74.2	70.1	63.0	60.8
		MCDB	61.0	61.0	68.0	73.7	79.0	83.7	86.2	84.5	79.5	74.1	66.5	64.2
(35) Mean Daily Temperature Range	5% DB	MDBR	20.9	22.2	24.1	24.5	22.1	20.5	19.4	18.9	18.8	21.8	23.4	21.2
		MCDBR	25.2	27.8	28.5	27.9	24.9	22.9	21.9	21.6	22.4	23.5	25.7	23.0
	5% WB	MCWBR	18.2	18.8	14.8	12.4	9.4	7.8	7.3	7.9	8.8	12.2	16.1	16.7
		MCWBR	22.5	26.0	22.5	21.6	20.2	19.5	19.0	19.0	17.3	16.7	20.2	20.5
(40) Clear-Sky Solar Irradiance	taub	taub	0.317	0.331	0.361	0.400	0.457	0.497	0.533	0.514	0.423	0.375	0.337	0.319
		taud	2.498	2.453	2.398	2.287	2.170	2.104	2.020	2.063	2.317	2.426	2.488	2.527
	Ebn at Noon	Ebn at Noon	282	290	289	281	265	253	244	246	265	270	272	274
		Edh at Noon	27	31	36	42	48	51	55	52	38	31	27	24
(44) All-Sky Solar Radiation	RadAvg	RadAvg	841	1060	1398	1758	1927	2021	1925	1734	1453	1207	927	741
	RadStd	RadStd	53	108	102	114	141	121	114	97	108	144	71	59

Historical Trends

		DBAvg	Heating			Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP		HDD50	HDD65	CDD50	CDD65
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)
(46) Station Only		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (52 neighbors)		+0.85	N/A	N/A	N/A	N/A	N/A	N/A	N/A	+293	+216	

Nomenclature: See separate page