

LEIGH CREEK, Australia

WMO: 946740

Lat: 30.5964S

Lon: 138.4219E

Elev: 11

StdP: 101.19

Time Zone: 9.50 (AUA)

Period: 94-08

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
7	2.8	3.9	-11.1	1.4	27.4	-8.5	1.8	24.6	11.3	14.7	10.5	14.3	1.8	140	0.510

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
1	13.2	40.1	19.1	38.3	18.4	36.7	17.9	22.7	30.0	21.6	30.8	20.6	31.0	5.5	340

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
21.0	15.7	25.8	18.9	13.7	24.8	16.9	12.1	24.3	67.2	30.0	62.9	31.1	59.4	30.7	25.8

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature									
			Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years			
1%	2.5%	5%	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)		
11.3	10.3	9.3	DB	0.1	42.3	1.2	0.9	-0.8	42.9	-1.5	43.4	-2.2	43.9	-3.1	44.6	(4)
			WB	-1.1	24.0	1.4	1.0	-2.1	24.7	-2.9	25.3	-3.6	25.9	-4.6	26.6	(5)

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
Temperatures, Degree-Days and Degree-Hours	DBAvg	19.4	28.1	27.8	24.1	19.3	15.0	11.8	10.8	12.6	16.6	19.2	22.9	25.7
	DBStd	6.91	4.05	3.99	3.66	3.34	2.82	2.49	2.18	2.88	3.93	4.06	4.40	4.02
	HDD10.0	30	0	0	0	0	1	8	15	5	1	1	0	0
	HDD18.3	877	0	0	2	27	111	197	232	182	81	37	7	1
	CDD10.0	3471	560	497	437	279	154	62	41	84	198	286	386	486
	CDD18.3	1277	302	264	181	56	7	1	0	3	28	64	143	228
	CDH23.3	16442	4245	3573	2039	519	48	3	1	31	337	818	1764	3064
	CDH26.7	8708	2528	2066	967	151	3	0	0	5	109	327	868	1685
Wind	WSAvg	4.3	5.1	4.7	4.3	3.9	3.4	3.5	3.6	3.9	4.6	4.7	4.9	4.9
Precipitation	PrecAvg	209	21	31	10	14	17	19	13	16	21	15	17	19
	PrecMax	450	96	167	52	90	61	73	38	62	99	63	74	74
	PrecMin	68	0	0	0	0	0	0	0	0	0	0	0	0
	PrecStd	85	27	37	14	21	17	20	12	18	23	18	17	17
Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	42.0	41.8	37.9	33.0	27.0	23.0	21.4	26.6	33.0	35.6	39.5	40.6
		MCWB	19.3	21.1	18.0	16.3	14.4	13.1	11.1	14.3	15.6	16.3	17.4	18.4
	2%	DB	40.3	39.5	35.9	30.3	24.7	20.5	19.3	23.3	29.8	32.8	36.8	38.5
		MCWB	19.4	19.6	17.6	15.2	13.7	12.4	10.5	11.9	14.6	15.8	17.0	17.5
	5%	DB	38.4	37.6	34.1	28.3	22.9	18.5	17.5	21.0	27.1	30.3	34.2	36.4
		MCWB	18.7	19.1	17.1	14.8	12.9	11.2	9.9	11.0	13.5	14.8	16.2	17.0
	10%	DB	36.4	35.8	31.8	26.3	21.1	17.0	16.1	18.8	24.6	27.8	31.7	34.4
		MCWB	18.0	18.8	16.7	14.2	12.3	10.5	9.4	9.9	12.6	13.8	15.8	16.8
Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	23.4	24.5	22.0	19.0	16.0	15.6	13.0	15.0	17.0	18.0	21.1	22.4
		MCDB	29.4	28.2	30.8	23.5	21.9	19.6	15.5	23.4	25.7	29.8	29.2	30.2
	2%	WB	22.0	23.3	20.2	17.4	14.8	13.8	11.7	13.1	15.7	16.9	19.4	20.9
		MCDB	30.8	29.5	29.7	24.1	21.7	17.5	16.2	20.4	25.9	28.7	28.8	28.5
	5%	WB	21.0	22.3	18.8	16.3	13.9	12.4	10.8	11.9	14.7	15.8	18.4	19.7
		MCDB	32.5	30.6	29.5	25.5	20.6	16.7	15.8	18.9	24.6	26.5	28.4	29.4
	10%	WB	20.0	21.1	17.7	15.3	13.0	11.2	10.1	11.0	13.5	14.9	17.4	18.5
		MCDB	32.7	30.7	29.7	25.2	20.0	15.5	15.0	17.3	22.9	25.4	28.1	30.5
Mean Daily Temperature Range	5% DB	MDBR	13.2	12.0	12.6	12.1	11.3	10.3	10.5	11.5	12.6	13.0	12.8	13.3
		MCDBR	14.4	13.6	14.2	14.1	13.2	12.2	12.5	14.7	15.5	16.1	15.4	15.3
		MCWBR	5.1	4.8	5.5	6.2	6.3	6.3	6.6	7.0	6.4	6.4	5.5	5.7
	5% WB	MCDBR	11.8	9.2	11.2	11.0	10.7	9.0	10.4	11.8	12.6	13.2	12.1	11.1
	MCWBR	4.6	3.6	4.8	5.2	5.5	5.3	6.0	6.1	6.0	5.8	5.3	5.3	
Clear-Sky Solar Irradiance	taub	0.363	0.354	0.335	0.325	0.307	0.294	0.297	0.316	0.354	0.357	0.364	0.354	
	taud	2.435	2.489	2.515	2.523	2.543	2.565	2.541	2.471	2.363	2.374	2.394	2.438	
	Ebn at Noon	977	967	953	911	881	872	883	906	917	953	969	988	
	Edh at Noon	122	112	103	92	80	74	79	95	118	125	127	123	
All-Sky Solar Radiation	RadAvg	8.06	7.34	6.39	4.94	3.73	3.18	3.47	4.48	5.84	6.98	7.64	8.15	
	RadStd	0.43	0.46	0.41	0.21	0.19	0.20	0.14	0.20	0.34	0.35	0.38	0.32	

Historical Trends

		DBAvg	Heating		Cooling			Degree-Days			
			99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)
(46)	Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47)	Regional (3 neighbors)	+0.40	N/A	N/A	+1.07	N/A	N/A	N/A	N/A	+158	+107

Nomenclature: See separate page