

MERAUKE MOPAH, Indonesia

WMO: 979800

Lat: 8.5183S

Lon: 140.4140E

Elev: 3

StdP: 101.29

Time Zone: 9.00 (E09)

Period: 05-19

WBAN: 99999

Annual Heating, Humidification, and Ventilation Design Conditions

Coldest Month	Heating DB		Humidification DP/MCDB and HR						Coldest Month WS/MCDB				MCWS/PCWD to 99.6% DB		WSF
			99.6%			99%			0.4%		1%				
	99.6%	99%	DP	HR	MCDB	DP	HR	MCDB	WS	MCDB	WS	MCDB	MCWS	PCWD	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
8	20.7	21.5	18.2	13.1	24.3	18.8	13.7	24.2	10.0	27.6	9.1	27.7	1.2	120	0.353

Annual Cooling, Dehumidification, and Enthalpy Design Conditions

Hottest Month	Hottest Month DB Range	Cooling DB/MCWB						Evaporation WB/MCDB						MCWS/PCWD to 0.4% DB	
		0.4%		1%		2%		0.4%		1%		2%			
		DB	MCWB	DB	MCWB	DB	MCWB	WB	MCDB	WB	MCDB	WB	MCDB	MCWS	PCWD
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)
12	6.5	32.7	26.2	32.2	26.2	31.8	26.1	27.4	30.9	27.1	30.7	26.8	30.4	3.9	100

Dehumidification DP/MCDB and HR									Enthalpy/MCDB						Extreme Max WB
0.4%			1%			2%			0.4%		1%		2%		
DP	HR	MCDB	DP	HR	MCDB	DP	HR	MCDB	Enth	MCDB	Enth	MCDB	Enth	MCDB	
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	
26.4	21.9	29.3	26.1	21.5	29.1	25.8	21.1	28.8	86.8	31.2	85.5	31.0	84.4	30.7	31.7

Extreme Annual Design Conditions

Extreme Annual WS			Extreme Annual Temperature				n-Year Return Period Values of Extreme Temperature								
1%	2.5%	5%	Mean		Standard Deviation		n=5 years		n=10 years		n=20 years		n=50 years		
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
(a)	(b)	(c)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	
8.5	7.5	6.4	DB	19.3	34.4	1.0	0.5	18.6	34.7	18.0	35.0	17.5	35.2	16.7	35.6
			WB	18.4	28.5	1.0	1.1	17.7	29.3	17.1	29.9	16.5	30.5	15.8	31.3

Monthly Climatic Design Conditions

		Annual	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	
(6) Temperatures, Degree-Days and Degree-Hours	DBAvg	27.1	27.8	27.8	27.7	27.7	27.2	26.3	25.6	25.5	26.1	27.2	28.0	28.3	(6)
	DBStd	1.33	0.95	0.91	0.86	0.85	0.88	0.95	0.97	1.03	1.09	1.05	0.74	0.88	(7)
	HDD10.0	0	0	0	0	0	0	0	0	0	0	0	0	0	(8)
	HDD18.3	0	0	0	0	0	0	0	0	0	0	0	0	0	(9)
	CDD10.0	6236	552	498	547	531	533	489	484	479	482	532	541	567	(10)
	CDD18.3	3194	294	265	289	281	275	239	226	221	232	274	291	309	(11)
	CDH23.3	31499	3126	2801	2991	2943	2679	1999	1622	1647	2036	2815	3291	3551	(12)
	CDH26.7	9464	1062	920	929	924	721	368	249	282	491	913	1233	1372	(13)
(14) Wind	WSAvg	2.8	2.6	2.5	2.3	2.1	2.7	3.0	3.2	3.4	3.4	3.1	2.7	2.2	(14)
(15) Precipitation	PrecAvg	1302	234	241	254	159	98	33	24	22	35	33	58	177	(15)
	PrecMax	2047	461	503	606	511	362	89	94	93	135	117	200	554	(16)
	PrecMin	507	50	18	34	8	7	1	1	0	0	0	0	39	(17)
	PrecStd	348	111	119	134	119	86	25	24	24	37	37	66	116	(18)
(19) Monthly Design Dry Bulb and Mean Coincident Wet Bulb Temperatures	0.4%	DB	33.0	32.5	32.5	32.6	32.2	31.1	30.6	30.7	31.7	33.0	33.1	33.4	(19)
		MCWB	26.6	26.7	26.4	26.0	26.1	25.4	24.3	23.7	24.6	25.4	26.1	26.4	(20)
	2%	DB	32.2	31.7	31.7	31.7	31.2	30.1	29.5	29.6	30.5	31.8	32.2	32.6	(21)
		MCWB	26.6	26.4	26.3	25.9	25.8	25.3	24.2	24.1	25.0	25.5	26.2	26.4	(22)
	5%	DB	31.6	31.3	31.1	31.1	30.5	29.3	28.7	28.8	29.7	30.9	31.7	32.1	(23)
		MCWB	26.4	26.3	26.2	25.9	25.7	25.1	24.1	24.1	24.8	25.5	26.0	26.3	(24)
	10%	DB	30.9	30.7	30.4	30.5	29.8	28.6	28.1	28.2	29.0	30.3	31.2	31.5	(25)
		MCWB	26.2	26.2	26.1	25.9	25.6	24.9	24.0	23.9	24.5	25.3	25.8	26.2	(26)
(27) Monthly Design Wet Bulb and Mean Coincident Dry Bulb Temperatures	0.4%	WB	27.6	27.5	27.6	27.5	27.4	26.7	26.0	26.7	27.0	27.6	27.6	27.6	(27)
		MCDB	31.4	31.2	30.7	30.6	30.3	29.2	28.5	28.9	29.8	30.7	31.5	31.6	(28)
	2%	WB	27.1	27.1	27.1	27.0	26.7	26.1	25.3	25.3	26.0	26.4	27.0	27.1	(29)
		MCDB	31.1	30.7	30.2	30.3	29.7	28.7	28.0	28.1	29.3	30.3	31.0	31.3	(30)
	5%	WB	26.7	26.7	26.7	26.6	26.3	25.7	24.9	24.8	25.4	26.1	26.6	26.8	(31)
		MCDB	30.5	30.2	29.8	29.7	29.3	28.3	27.6	27.6	28.6	30.0	30.6	30.8	(32)
	10%	WB	26.4	26.4	26.4	26.3	26.0	25.3	24.5	24.4	24.9	25.6	26.2	26.5	(33)
		MCDB	30.0	29.7	29.4	29.2	28.9	27.8	27.1	27.2	28.0	29.4	30.1	30.4	(34)
(35) Mean Daily Temperature Range	5% DB	MDBR	6.1	5.9	5.8	5.9	5.6	5.1	5.5	6.1	6.6	6.8	6.8	6.5	(35)
		MCDBR	7.1	6.6	6.6	6.9	6.6	5.9	6.4	6.9	7.3	7.5	7.4	7.4	(36)
	5% WB	MCWBR	2.7	2.5	2.4	2.4	2.5	2.3	2.6	2.9	3.2	3.0	2.8	2.8	(37)
		MCWBR	6.6	6.3	6.1	6.0	5.7	5.2	5.1	5.5	6.3	6.8	6.8	6.8	(38)
(40) Clear-Sky Solar Irradiance	taub	taub	0.418	0.414	0.406	0.421	0.432	0.428	0.421	0.426	0.440	0.466	0.462	0.445	(40)
		taud	2.495	2.502	2.531	2.481	2.438	2.446	2.465	2.443	2.398	2.296	2.320	2.394	(41)
	Ebn at Noon	Ebn at Noon	923	923	916	873	834	823	837	857	872	866	876	895	(42)
		Edh at Noon	115	114	109	110	109	106	105	113	123	139	136	127	(43)
(44) All-Sky Solar Radiation	RadAvg	RadAvg	5.13	5.21	5.03	4.90	4.61	4.17	4.29	4.92	5.56	6.07	5.96	5.47	(44)
	RadStd	RadStd	0.38	0.43	0.27	0.42	0.35	0.30	0.27	0.46	0.46	0.43	0.41	0.46	(45)

Historical Trends

	DBAvg	Heating		Cooling			Degree-Days			
		99% DB	99% DP	1% DB	1% WB	1% DP	HDD10.0	HDD18.3	CDD10.0	CDD18.3
		(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)
(46) Station Only	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
(47) Regional (0 neighbors)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Nomenclature: See separate page