## BOARD CHARACTERISTICS

| | | | |
|---|---|---|---|
| Copper Layer Count: | 2 | Board Thickness: | 1.6000 mm |
| Board overall dimensions: | 34.1220 mm x 44.1161 mm | | |
| Min track/spacing: | 0.0000 mm / 0.2032 mm | Min hole diameter: | 0.3000 mm |
| Copper Finish: | None | Impedance Control: | No |
| Castellated pads: | No | Plated Board Edge: | No |
| Edge card connectors: | No | | |

| Layer Name | Type | Material | Thickness (mm) | Color | Epsilon R | Loss Tangent |
|---|---|---|---|---|---|---|
| F.Silkscreen | Top Silk Screen | Not specified | 0 mm | Not specified | 1 | 0 |
| F.Paste | Top Solder Paste | | 0 mm | | 1 | 0 |
| F.Mask | Top Solder Mask | Not specified | 0.01 mm | Not specified | 3.3 | 0 |
| F.Cu | copper | | 0.035 mm | | 1 | 0 |
| Dielectric | core | FR4 | 1.51 mm | Not specified | 4.5 | 0.02 |
| B.Cu | copper | | 0.035 mm | | 1 | 0 |
| B.Mask | Bottom Solder Mask | Not specified | 0.01 mm | Not specified | 3.3 | 0 |
| B.Paste | Bottom Solder Paste | | 0 mm | | 1 | 0 |
| B.Silkscreen | Bottom Silk Screen | Not specified | 0 mm | Not specified | 1 | 0 |

## ORDERING NOTES

PCB:

* Product Type: Industrial/Consumer electronics
* Different Design: 1
* Delivery Format: Single PCB
* PCB Thickness: 1.6 mm
* PCB Colour: Black
* Silkscreen: White
* Material Type: FR4-Standard TG 135-140
* Surface Finish: ENIG
* Gold Thickness: 2 U"
* Outer Copper Weight: 1 oz
* Inner Copper Weight: 1 oz
* Specify Layer Sequence: No
* Impedance Control: No
* Layer Stackup: No requirement
* Via Covering: Epoxy Filled & Capped
* Min Via Hole Size/Diameter: 0.3mm/(0.4/0.45mm)
* Board Outline Tolerance: ±0.2mm(Regular)
* Confirm Production File: Yes
* Mark on PCB: 2D barcode (Serial Number)
    * Printing: Number Only
    * Prefix:
    * Unique Number: Keep
    * Starting Value: 0001
    * 2D Barcode Position: Specify Position
* Gold Fingers: No
* Castellated Holes: No
* Press-Fit Hole: No
* Edge Plating: No

PCB Advanced Options:

* 4-Wire Kelvin Test: Yes
* Paper Between PCBs: No
* Appearance Quality: IPC Class 2 Standard
* Silkscreen Technology: Ink-Jet/Screen Printing Silkscreen
* Package Box: With JLCPCB Logo

PCBA:

* PCBA Type: Economic
* Assembly Side: Top Side
* Edge Rails/Fiducials: Added by JLCPCB
* Confirm Parts Placement: Yes
* Parts Selection: By Customer

PCBA Advanced Options:

* Photo Confirmation: No
* Conformal Coating: No
* Packaging: Antistatic Bubble Film
* Solder Paste: Sn96.5%, Ag3.0%, Cu0.5%
* Add Paste for Unpopulated Pad Opening: No
* Others: No
* Board Cleaning: No
* Bake Components: No
* Depanel Boards & Edge Rail Before Delivery: No
* Flying Probe Test: No
* Nitrogen Reflow Soldering: No




BlueRobotics

**Item Number: BR-100060**

**Description: I2C level converter**

Tolerances Specified per Decimal Place Unless Otherwise Specified

| Linear: | Angular: |
|---|---|
| X. ±0.2 | X. ±1 |
| X.X ±0.1 | X.X ±0.5 |
| X.XX ±0.05 | X.XX ±0.1 |

Unpop. PCB: BR-100060-001 RevB | PCBA: BR-100060-002 RevB

Size: A4 | Date: | Scale: 1:1

KiCad E.D.A. 9.0.7 | Sheet: | Id: 1/2

## BOARD CHARACTERISTICS

| | | | |
|---|---|---|---|
| Copper Layer Count: | 2 | Board Thickness: | 1.6000 mm |
| Board overall dimensions: | 34.1220 mm x 44.1161 mm | | |
| Min track/spacing: | 0.0000 mm / 0.2032 mm | Min hole diameter: | 0.3000 mm |
| Copper Finish: | None | Impedance Control: | No |
| Castellated pads: | No | Plated Board Edge: | No |
| Edge card connectors: | No | | |

| Layer Name | Type | Material | Thickness (mm) | Color | Epsilon R | Loss Tangent |
|---|---|---|---|---|---|---|
| F.Silkscreen | Top Silk Screen | Not specified | 0 mm | Not specified | 1 | 0 |
| F.Paste | Top Solder Paste | | 0 mm | | 1 | 0 |
| F.Mask | Top Solder Mask | Not specified | 0.01 mm | Not specified | 3.3 | 0 |
| F.Cu | copper | | 0.035 mm | | 1 | 0 |
| Dielectric | core | FR4 | 1.51 mm | Not specified | 4.5 | 0.02 |
| B.Cu | copper | | 0.035 mm | | 1 | 0 |
| B.Mask | Bottom Solder Mask | Not specified | 0.01 mm | Not specified | 3.3 | 0 |
| B.Paste | Bottom Solder Paste | | 0 mm | | 1 | 0 |
| B.Silkscreen | Bottom Silk Screen | Not specified | 0 mm | Not specified | 1 | 0 |



## ORDERING NOTES

PCB:

* Product Type: Industrial/Consumer electronics
* Different Design: 1
* Delivery Format: Single PCB
* PCB Thickness: 1.6 mm
* PCB Colour: Black
* Silkscreen: White
* Material Type: FR4-Standard TG 135-140
* Surface Finish: ENIG
* Gold Thickness: 2 U"
* Outer Copper Weight: 1 oz
* Inner Copper Weight: 1 oz
* Specify Layer Sequence: No
* Impedance Control: No
* Layer Stackup: No requirement
* Via Covering: Epoxy Filled & Capped
* Min Via Hole Size/Diameter: 0.3mm/(0.4/0.45mm)
* Board Outline Tolerance: ±0.2mm(Regular)
* Confirm Production File: Yes
* Mark on PCB: 2D barcode (Serial Number)
    * Printing: Number Only
    * Prefix:
    * Unique Number: Keep
    * Starting Value: 0001
    * 2D Barcode Position: Specify Position
* Gold Fingers: No
* Castellated Holes: No
* Press-Fit Hole: No
* Edge Plating: No

PCB Advanced Options:

* 4-Wire Kelvin Test: Yes
* Paper Between PCBs: No
* Appearance Quality: IPC Class 2 Standard
* Silkscreen Technology: Ink-Jet/Screen Printing Silkscreen
* Package Box: With JLCPCB Logo

PCBA:

* PCBA Type: Economic
* Assembly Side: Top Side
* Edge Rails/Fiducials: Added by JLCPCB
* Confirm Parts Placement: Yes
* Parts Selection: By Customer

PCBA Advanced Options:

* Photo Confirmation: No
* Conformal Coating: No
* Packaging: Antistatic Bubble Film
* Solder Paste: Sn96.5%, Ag3.0%, Cu0.5%
* Add Paste for Unpopulated Pad Opening: No
* Others: No
* Board Cleaning: No
* Bake Components: No
* Depanel Boards & Edge Rail Before Delivery: No
* Flying Probe Test: No
* Nitrogen Reflow Soldering: No

BlueRobotics

**Item Number: BR-100060**

**Description: I2C level converter**

Tolerances Specified per Decimal Place Unless Otherwise Specified

| Linear: | Angular: |
|---|---|
| X. ±0.2 | X. ±1 |
| X.X ±0.1 | X.X ±0.5 |
| X.XX ±0.05 | X.XX ±0.1 |

Unpop. PCB: BR-100060-001 RevB | PCBA: BR-100060-002 RevB

Size: A4 | Date: | Scale: 1:1

KiCad E.D.A. 9.0.7 | Sheet: | Id: 2/2