

Autonomous Robots and Environmental Mapping

Mitchell Horning, Matthew Lin, Siddarth Srinivasan, Simon Zou

July 31, 2014

Abstract

Compressed sensing is a technique used to reconstruct sparse signals and images while sampling well below the Nyquist rate. Commonly used in fMRIs and medical imaging, we aim to use this technique to allow autonomous robots to map areas of interest within an environment. In our experiment, we programmed a robot equipped with a reflectance sensor to travel along straight-line paths, integrate sensor readings along the path, and send that sum to a remote server after each path. Each data point consists of the robot's start and end positions, tracked by an overhead camera, and the integral found along that path. Once all the data has been collected, the environment is reconstructed by minimizing the sum of the data fitting term and an L1 penalty term. When using an adaptive path selection scheme, preliminary simulations of our experiment show reconstruction of 100x100 images with only 100 data points (err. = 0.28), and we have begun trials with data collected by the robot.

Contents

1	Introduction	1
2	Experiment settings	2
2.1	Testbed	2
2.2	Vehicle hardware	2
2.3	Server	2
3	Models and assumptions	2
3.1	Constraints	2
4	Algorithm for solving the inverse problem	2
5	Conclusions and Further Work	2

1 Introduction

Compressed sensing describes a technique in which a signal is reconstructed by solving an under-determined linear system. Doing so allows a signal to be found from a relatively small amount of data.

- 2 Experiment settings
 - 2.1 Testbed
 - 2.2 Vehicle hardware
 - 2.3 Server
- 3 Models and assumptions
 - 3.1 Constraints
- 4 Algorithm for solving the inverse problem
- 5 Conclusions and Further Work