4.lab vjezba

U ovoj vježbi napravit ćemo usporedbu brzih i sporih kriptografskih hash funkcija.

Lozinke se spremaju na način da se spremi njihova hash vrijednost uz useni id. Poslije se hash izracunat od unesene lozinke usporeduje sa spremljenim hashom.

Napadaci mogu stvoriti svoj dictionary sa parovima najcesce koristenih sifri i njihovih hash vrijednostima.

Zastite se provodi na nekoliko nacina. Iterative hashing(postupak uzastopnog hashiranja), salt (dodaje se na lozinku prije samog hashiranja), memory hard functions(koriste se sporije funkcije kako bi se smanjila ekonomicnost napada)

Pomocu ovog koda se provjeravaju brzine pojedinih hash funkcija.

```python
from os import urandom
from prettytable import PrettyTable
from timeit import default_timer as time
from cryptography.hazmat.backends import default_backend
from cryptography.hazmat.primitives import hashes
from cryptography.hazmat.primitives.kdf.scrypt import Scrypt
from cryptography.hazmat.primitives.ciphers import Cipher, algorithms, modes
from passlib.hash import sha512_crypt, pbkdf2_sha256, argon2

def time_it(function):
    def wrapper(*args, **kwargs):
        start_time = time()
        result = function(*args, **kwargs)
        end_time = time()
        measure = kwargs.get("measure")
        if measure:
            execution_time = end_time - start_time
            return result, execution_time
        return result
    return wrapper

@time_it
def aes(**kwargs):
    key = bytes([
        0x00, 0x01, 0x02, 0x03, 0x04, 0x05, 0x06, 0x07,
        0x08, 0x09, 0x0a, 0x0b, 0x0c, 0x0d, 0x0e, 0x0f
    ])
    plaintext = bytes([
        0x00, 0x01, 0x02, 0x03, 0x04, 0x05, 0x06, 0x07,
        0x08, 0x09, 0x0a, 0x0b, 0x0c, 0x0d, 0x0e, 0x0f
    ])
    encryptor = Cipher(algorithms.AES(key), modes.ECB()).encryptor()
    encryptor.update(plaintext)
    encryptor.finalize()

@time_it
def md5(input, **kwargs):
    digest = hashes.Hash(hashes.MD5(), backend=default_backend())
    digest.update(input)
    hash = digest.finalize()
    return hash.hex()

@time_it
def sha256(input, **kwargs):
    digest = hashes.Hash(hashes.SHA256(), backend=default_backend())
    digest.update(input)
    hash = digest.finalize()
    return hash.hex()

@time_it
def sha512(input, **kwargs):
    digest = hashes.Hash(hashes.SHA512(), backend=default_backend())
    digest.update(input)
    hash = digest.finalize()
    return hash.hex()

@time_it
def pbkdf2(input, **kwargs):
    # for more precise measurements we use a fixed salt
    salt = b'ViQZpiAd'
    rounds = kwargs.get("rounds", 10000)
    return pbkdf2_sha256.hash(input, salt=salt, rounds=rounds)

@time_it
def argon2_hash(input, **kwargs):
    # for more precise measurements we use a fixed salt
    salt = b'ff'*16
    rounds = kwargs.get("rounds", 12)       # time_cost
    memory_cost = kwargs.get("memory_cost", 2**16)  # kilobytes
    parallelism = kwargs.get("rounds", 1)
    return argon2.using(
        salt=salt,
        rounds=rounds,
        memory_cost=memory_cost,
        parallelism=parallelism
    ).hash(input)

@time_it
def linux_hash_5(input, **kwargs):
    # for more precise measurements we use a fixed salt
    salt = "xdqiydd"
    return sha512_crypt.hash(input, salt=salt, rounds=5000)

@time_it
def linux_hash(input, **kwargs):
    # for more precise measurements we use a fixed salt
    salt = kwargs.get("salt")
    rounds = kwargs.get("rounds", 5000)
    if salt:
        return sha512_crypt.hash(input, salt=salt, rounds=rounds)
    return sha512_crypt.hash(input, rounds=rounds)

@time_it
def scrypt_hash(input, **kwargs):
    salt = kwargs.get("salt", urandom(16))
    length = kwargs.get("length", 32)
    n = kwargs.get("n", 2**14)
    r = kwargs.get("r", 8)
    p = kwargs.get("p", 1)
    kdf = Scrypt(
        salt=salt,
        length=length,
        n=n,
        r=r,
        p=p
    )
    hash = kdf.derive(input)
    return {
        "hash": hash,
        "salt": salt
    }

if __name__ == "__main__":
    ITERATIONS = 100
    password = b"super secret password"
    NUMBER_HARD_TESTS = []
    LOW_MEMORY_TESTS = []

    TESTS = [
        {
            "name": "AES",
            "service": lambda: aes(measure=True)
        },
        {
            "name": "HASH_MD5",
            "service": lambda: md5(password, measure=True)
        },
        {
            "name": "HASH_SHA256",
            "service": lambda: sha256(password, measure=True)
        }
    ]

    table = PrettyTable()
    column_1 = "Function"
    column_2 = f"Avg. Time ({ITERATIONS} runs)"
    table.field_names = [column_1, column_2]
    table.align[column_1] = "l"
    table.align[column_2] = "l"
    table.sortby = column_2

    for test in TESTS:
        name = test.get("name")
        service = test.get("service")
        total_time = 0
        for iteration in range(0, ITERATIONS):
            print(f"Testing {name:>8} [iteration]/{ITERATIONS}", end="\r")
            _, execution_time = service()
            total_time += execution_time
        average_time = round(total_time/ITERATIONS, 6)
        table.add_row([name, average_time])
    print(f"{table}\n\n")
```

U kod smo dodali

```python
{
    "name": "LINUX CRYPT 5k",
    "service": lambda: linux_hash(password, measure=True)
},
{
    "name": "LINUX CRYPT 1M",
    "service": lambda: linux_hash(password, rounds=10**6, measure=True)
}
```

Ispis vremena za linux_hash za 5k i 1M iteracija.

Function	Avg. Time (100 runs)
HASH_SHA256	1.1e-05
HASH_MD5	3.2e-05
AES	0.000589
LINUX CRYPT 5k	0.008499
LINUX CRYPT 1M	1.205571

Neke od njih su popriclno brze, sto moze omoguciti napadacu da u kratkom vremenu sastavi dictionary.

Ako povecamo broj iteracija na 5000 a pogotovo na miljun to ce usporiti napadaca, ali moramo imati na umu da sami sebi ne napravimo DoS napad.

Zakljucak: sto su funkcije brze to su manje sigurne, povecanjem broja iteracija povecavamo sigurnost funkcije.