

NETWORK CONNECTIONS

UNIT-2

☆ Establishing a Single Switched Network (Easy & Detailed)

A **single switched network** means building a simple LAN (Local Area Network) using **one switch** to interconnect multiple end devices such as PCs, printers, or servers. The switch acts as the central device that forwards frames based on **MAC addresses**. To establish this network, devices are connected to the switch using **Ethernet cables**. The switch automatically learns the **MAC addresses** of connected devices through its **MAC address table**, allowing efficient forwarding of data frames. This type of network is commonly used in **small offices, labs, or home networks** because it's easy to set up and manage.

☆ Steps to Establish a Single Switched Network (Detailed)

1. Select and Power On the Switch

Choose an **unmanaged or managed Ethernet switch** with enough ports for your devices. Plug in the power cable, and the switch will start operating immediately.

2. Connect End Devices

Use **Ethernet (RJ-45) cables** to connect PCs, laptops, printers, or servers to the switch's ports. Each connected port will show link/activity lights.

3. Assign IP Addresses

Each device in the network should have a **unique IPv4 address** within the same subnet. Example:

- PC1 → 192.168.1.10
 - PC2 → 192.168.1.20
 - Printer → 192.168.1.30
- Subnet mask → 255.255.255.0

4. Switch Learns MAC Addresses

When devices send data, the switch learns their **MAC addresses** and stores them in its **MAC Address Table**, mapping MAC → Port.

5. Communication Begins

When PC1 sends a message to PC2:

- Frame reaches the switch
- Switch checks MAC table

- Forwards frame only to the correct port

This prevents unnecessary broadcasting and improves efficiency.

6. Optional: Configure VLANs (if using managed switch)

You can logically divide one physical switch into multiple virtual networks to improve security and traffic control.

☆ Why a Single Switched Network is Used?

- Easy to set up
- Low cost
- No complex configuration needed
- Ideal for small networks.

Spanning Tree Protocol (STP)

•
In Ethernet networks, switches use frames to forward data between devices. However, if there are multiple active paths between switches (such as when switches are interconnected), a loop can occur, causing frames to circulate indefinitely. This loop results in broadcast storms, high CPU utilization, and network congestion, severely affecting performance. **Spanning Tree Protocol (STP)** is a network protocol used to prevent loops in such Ethernet networks.

It uses a tree-like structure where switches elect one root switch and then calculate the shortest path to this root. The network topology is adjusted to create a loop-free path structure while the redundant paths are put in a standby state.

☆ How STP Works (Simple 5-Step Explanation)

Step 1: All Switches Talk to Each Other

All switches send special messages called **BPDUs** (Bridge Protocol Data Units). They use these messages to decide who is the **main switch**.

Step 2: Root Bridge is Selected

The switch with the **lowest ID** becomes the **Root Bridge**. Think of it as the **boss switch**.

All other switches will forward traffic toward this Root Bridge.

Step 3: Choose Root Ports

Every non-root switch selects **one port** that has the **best path** to reach the Root Bridge.

This port is called the **Root Port (RP)**.

→ RP = *"My best road to reach the boss switch"*

Step 4: Choose Designated Ports

On every link, one switch becomes responsible for forwarding traffic.

The port on that switch becomes the **Designated Port (DP)**.

→ DP = *"Port that forwards traffic on its segment"*

Step 5: Block Redundant Ports

If there are **two or more paths**, STP **blocks extra ports** to stop loops.

Blocked ports:

- Do NOT forward traffic
- Do NOT learn MAC addresses
- ONLY listen for BPDU messages

→ These are backup ports.

If the main path fails, STP quickly activates the blocked port.

Types of Spanning Tree Protocol (STP)

Several variations of [STP](#) are used to address different network requirements, each with specific enhancements and optimizations over the original standard. The most common types of STP include:

IEEE 802.1D

This is also known as CST (Common Spanning Tree). It is a spanning tree standard developed by IEEE which elects only one [root bridge](#) per whole topology. All the traffic flows over the same path (the best path to the root bridge) but this doesn't hold good always as there can be scenarios in which the optimised path to reach a [VLAN](#) is different than the path obtained on electing the root bridge. CST prevents loops by blocking redundant paths and allowing only one active path between any two switches. However, it is slow to react to changes, taking up to 32 seconds to converge.

Advantages:

- Less [CPU](#) and memory required.
- Simple and widely supported across different network devices for easy implementation.

Disadvantages:

- Lesser optimization as the path calculated as the best cost to root bridge might not be the best path to reach a network.
- No load balancing.

Multiple STP (MSTP)

This standard is developed by IEEE in which grouping of VLANs is done and for each single group, RSTP is run. This is basically a Spanning Tree Protocol running over another Spanning Tree Protocol. It prevents loops by creating multiple spanning tree instances that block redundant paths within each VLAN group, ensuring loop-free and efficient forwarding across the network.

Advantages:


- High redundancy
- load balancing can be achieved.
- lower CPU and memory usage is required

Disadvantages:

- More configuration is required and not easy to implement.
- Complex troubleshooting due to multiple spanning tree instances running simultaneously.

Rapid Spanning Tree Protocol (RSTP)

It is a spanning standard developed on [IEEE 802.1w](#) which provides faster convergence than CST but holds the same idea of finding a single root bridge in the topology. RSTP prevents loops by quickly detecting link failures and using rapid state transitions on ports to block redundant paths, allowing only loop-free active paths. The bridge resources needed in RSTP is higher than CST but less than PVST+ .



Port Roles in RSTP

There are four-port roles in RSTP

1. **Root Port:** The port with the best path cost is elected as the root port. A non-root bridge can only have one root port. Root ports forward data to the bridge.
2. **Designated Port:** It is a non-root port that is used as a forwarding port for every LAN segment.
3. **Backup Port:** It is a backup path to a segment where another bridge port is already connected. These ports receive BPDUs from their switches but they remain in a blocked state.
4. **Alternate Port:** It is a Backup port with a less desirable path cost. All such ports remain in a blocked state.

Types of ports in RSTP

There are three types of ports in RSTP

1. **Edge:** It is a port that connects to a host.

2. **Root:** It is a port that connects to another switch, and it has the best path cost to the root bridge.
3. **Point-to-point:** It is a port that connects to another switch and it has the potential of becoming the designated port for a segment.

Advantages:

- Prevents network loops.
- Prevents redundancy.
- Faster Convergence.
- Backward compatible with STP.

Disadvantages:

- It requires more CPU and memory than Classic STP.
- It can be complex to configure in large networks.
- It does not support per-VLAN load balancing since it uses a single spanning tree for all VLANs

Segmenting IP Networking

Segmenting an IP Network means dividing one large network into smaller, logical parts. This is done to improve performance, security, and manageability.

Here's the explanation in the simplest and easiest way:

What is IP Network Segmentation?

IP network segmentation is the process of breaking a big network (like 192.168.0.0/16) into many small networks called subnets.

Why do we segment a network?

☒ 1. Reduce Network Congestion

Fewer devices per network → less traffic → faster communication.

☒ 2. Improve Security

Different departments (HR, Finance, IT) can be placed in **separate secure networks**.

☒ 3. Better Management

Easier to troubleshoot and control smaller networks.

☒ 4. Efficient IP Address Usage

Helps avoid wasting IP addresses.

How it works

- **Subnetting:** A large IP network is logically divided into smaller logical networks (subnets). This is done by borrowing bits from the host portion of an IP address to create a subnet identifier.
- **Physical segmentation:** This involves using actual physical hardware, like dedicated routers, switches, and firewalls, to physically separate network segments.
- **Virtual segmentation:** This can be achieved using technologies like Virtual LANs (VLANs) to create separate segments on the same physical hardware.
- **Policy enforcement:** Segmentation involves creating policies that define how traffic can flow between the different segments. For instance, a policy might block all traffic from a guest network from accessing a corporate server network.

Example

Imagine a large company's network. Instead of one "flat" network, it can be segmented into several smaller networks:

- **Segment 1:** HR department
- **Segment 2:** Engineering department
- **Segment 3:** Guest Wi-Fi
- **Segment 4:** Server room containing financial data

In this setup, a firewall between the segments can be configured to only allow specific traffic. For example, HR computers can access the financial servers, but guest devices from the guest Wi-Fi segment cannot.

Benefits

- **Improved security:** By isolating segments, a breach in one part of the network does not automatically give attackers access to the entire system. Sensitive data can be placed in a protected segment, and security teams can limit access to it.
- **Better performance:** Broadcast traffic is contained within its own segment, rather than flooding the entire network. This reduces network congestion and improves overall speed.
- **Simplified management:** Dividing a large network into smaller, logical parts makes it easier to troubleshoot issues and manage network resources by function, department, or location.

★ IP Static Routing (Easy & Detailed Explanation)

✓ What is Static Routing?

Static Routing is also known as **non-adaptive** routing which doesn't change the routing table unless the network administrator changes or modifies them manually. Static routing does not use complex routing algorithms and It provides higher or more security than dynamic routing.

Static routing means the **network administrator manually enters routes** into the router's routing table.

The router does **not** learn routes automatically — instead, it uses **fixed, predefined paths** to reach specific networks.

It is like giving the router a **manual map** showing “**to reach this network, go from this path.**”

★ Key Features of Static Routing

1. **Manually Configured**
Admin must enter every route by hand.
2. **Does NOT change automatically**
If a link goes down, the router **still keeps the same route**, even if it is broken.
3. **Fast and Secure**
Since there is no route calculation, static routing is **fast** and more **secure** than dynamic routing.
4. **Used in Small Networks**
Best for small office networks or when there are only a few routers.

★ Why Static Routing is Used?

- Simple to configure for small networks
- Predictable paths
- Low CPU and memory usage
- More secure (no routing updates shared)

★ When NOT to Use Static Routing?

- In **large networks**
- When the network topology changes frequently
- When redundant paths are needed

★ Distance Vector Routing with RIP

Distance Vector Routing (DVR) and the Routing Information Protocol (RIP) are two closely related concepts in computer networking. RIP is a specific implementation of the distance vector routing algorithm, where routers exchange full routing tables with their neighbours at regular intervals to

learn about network paths. RIP uses hop count as its metric, has a maximum hop limit of 15, and includes mechanisms to prevent routing loops.

- **Distance:** How far away? In the routing world, we use metrics.
- **Vector:** Which direction? In the routing world, we care about which interface and the IP address of the next router to send it to.

☆ Key Features of Distance Vector Routing

1. **Uses Hop Count as Metric**
Hop = one router
Less hop count = better path.
2. **Routers Periodically Advertise their Routing Table**
Every **30 seconds** (RIP timing).
3. **Routers only know their neighbors, not the whole network**
This is why it is simple but not very fast.

☆ Routing Information Protocol (RIP)

RIP is the **most common Distance Vector routing protocol**.

✚ RIP Uses:

- **Hop count** as metric
- Maximum **15 hops** allowed
(16 hop = infinity → destination unreachable)

✚ Types of RIP

1. **RIP v1** – Classful, no subnet mask
2. **RIP v2** – Classless, supports VLSM, authentication

□ Basic Idea of RIP Working

1. Every router knows only its **directly connected networks**.
2. Every 30 seconds, it **broadcasts its routing table** to neighbors.
3. When a router receives the routing table:
 - It **adds 1 hop** to each route.
 - It compares the route with its own table.
 - If it is better (less hop), it updates the table.
4. Routers calculate the **best path** based on **minimum hop count**.
5. If hop count becomes **16**, route is considered **unreachable**.

☆ Step-by-Step Working (Easy Explanation)

Let's take a simple network:

Net A -- R1 -- R2 -- R3 -- Net B

☆ Step 1: Each Router Knows Only Direct Networks

- R1 knows Net A
- R2 knows only about R1 and R3
- R3 knows Net B

Each router's initial routing table contains only its connected networks with hop = 0.

☆ Step 2: Routers Exchange Routing Tables

Every **30 seconds**, routers send their routing tables.

- R1 sends table to R2
- R2 sends table to R1 and R3
- R3 sends table to R2

This is called **Periodic Updates**.

☆ Step 3: Router Updates Routing Table

Example:

R1 says to R2:
"Net A = 0 hops"

R2 adds **+1 hop**:

So R2 stores:
"Net A = 1 hop (via R1)"

Similarly,
R3 tells R2: "Net B = 0 hop"
R2 adds +1 → "Net B = 1 hop (via R3)"

Now R2 knows both Net A and Net B.

☆ Step 4: Best Path Selection

If a router learns the same network from multiple neighbors:

- ✓ It chooses the **path with the lowest hop count**.

Example:
If R2 learns Net A with 1 hop via R1 and 3 hops via R3,
R2 selects: **1 hop via R1**.

☆ Step 5: Failure Handling

If a link goes down:

- Router marks that route as **hop = 16**, which means **unreachable** (called **Route Poisoning**)

Then all routers gradually remove this route from the table.

☆ LINK STATE ROUTING WITH OSPF

Link State Routing is a method where every router learns the complete network topology by exchanging link-state information with all other routers. OSPF (Open Shortest Path First) is the most widely used link-state routing protocol. In OSPF, each router generates **Link State Advertisements (LSAs)** that describe its interfaces and neighbors. These LSAs are flooded across the area so that every router builds the same **Link State Database (LSDB)**. Using this database, each router runs **Dijkstra's Shortest Path First algorithm** to calculate the shortest and most accurate paths. OSPF uses **cost** as its metric and ensures fast, loop-free, and reliable routing. It also supports **areas** to reduce overhead and improve scalability. Thus, OSPF provides efficient and stable routing in medium and large networks.

Each router:

- Discovers its neighbors
- Measures the link cost (bandwidth, delay etc.)
- Sends this information to all routers
- Builds the same network map
- Uses **Dijkstra's algorithm** to calculate the shortest path

☆ Working of Link State Routing with OSPF (Detailed Explanation)

OSPF (Open Shortest Path First) is a **link-state routing protocol**, meaning it works by sharing detailed link-state information between routers so that all routers know the full network topology.

Below is the complete working:

Step 1: Neighbor Discovery (Hello Protocol)

- Each OSPF router starts by sending **Hello packets** out of its OSPF-enabled interfaces.
- Any router that receives the Hello packet checks important parameters such as:
 - Area ID
 - Hello & Dead timers
 - Network type
 - Authentication
- If all parameters match, the routers become **neighbors**.
- This step helps routers detect who is directly connected.

👉 **Purpose:** Find neighbors and establish basic communication.

Step 2: Forming Adjacencies

- Not all neighbors become *adjacent*; adjacency forms only with selected routers.
- On broadcast networks (like Ethernet), OSPF elects:
 - **DR (Designated Router)**
 - **BDR (Backup Designated Router)**
- Other routers form adjacencies only with DR/BDR to reduce traffic.

👉 **Purpose:** Reduce LSA flooding and organize routers efficiently.

Step 3: Exchange of Link State Advertisements (LSAs)

Once adjacency is formed, routers exchange **Link State Advertisements (LSAs)**.
An LSA contains:

- Router ID
- Links/interfaces
- Link cost (based on bandwidth)
- Connected networks
- Neighbor router IDs

These LSAs are **flooded** across the entire area, meaning every router receives them.

👉 **Purpose:** Share each router's local information with all routers.

Step 4: Building the Link State Database (LSDB)

- Every router stores all received LSAs in a special database called the **LSDB**.
- Importantly, all routers inside the same area have **identical LSDBs**.
- This ensures all routers see the same network topology.

👉 **Purpose:** Create a synchronized map of the area.

Step 5: Running the SPF (Dijkstra's Algorithm)

- With the LSDB ready, each router independently runs the **Shortest Path First (SPF)** algorithm.
- SPF creates a **shortest path tree** with the router itself as the root.
- The algorithm calculates:
 - Best path to every network
 - Total cost to each destination
 - Equal-cost routes (load balancing)

👉 **Purpose:** Determine the best possible routes using cost values.

Step 6: Building the OSPF Routing Table

- The result of the SPF calculation is stored in the **OSPF routing table**.
- Only the **lowest-cost routes** are installed.
- If two or more paths have equal cost, OSPF performs **ECMP (Equal-Cost Multi-Path)** load balancing.

👉 **Purpose:** Store final decisions for packet forwarding.

Step 7: Handling Network Changes (Fast Convergence)

OSPF quickly reacts to changes:

- If a link or router goes down, an updated LSA is generated immediately.
- Routers flood this new LSA.
- All routers update their LSDBs and rerun SPF only for changed parts.

👉 **Result:** Very fast convergence and stable routing.

Dynamic Host Configuration Protocol (DHCP)

Last Updated : 11 Oct, 2025

•
Dynamic Host Configuration Protocol (DHCP) is a network protocol used to automate the process of assigning IP addresses and other network configuration parameters to devices such as computers, smartphones and printers. Instead of manually configuring each device, DHCP enables devices to join a network and automatically receive:

- IP Address
- Subnet Mask
- Default Gateway
- DNS Server addresses
- Other TCP/IP configuration options

Components of DHCP

- **DHCP Server:** Stores IP addresses and configuration details. Allocates addresses dynamically to clients.
- **DHCP Relay:** Acts as a bridge between clients and servers when they are not on the same subnet.
- **DHCP Client:** A device (PC, phone, printer, etc.) that requests and receives network configuration from the DHCP server.
- **IP Address Pool:** A predefined range of IP addresses that the DHCP server can lease to devices.
- **Subnets:** Logical partitions of an IP network to organize and manage IP allocation.
- **Lease:** The time period for which an IP address is assigned to a client. After expiry, the client must renew or request a new lease.
- **DNS Servers:** DHCP can provide DNS server information to clients for resolving domain names.

- **Default Gateway:** The gateway router information is provided to clients so they can communicate outside their subnet.
- **Options:** Additional parameters like subnet mask, domain name and time servers.

DHCP Packet Format

- **Hardware Length (8 bits):** Length of MAC address (e.g., 6 for Ethernet).
- **Hop Count (8 bits):** Maximum number of hops the packet can travel.
- **Transaction ID (32 bits):** Set by client, used to match requests and replies.
- **Number of Seconds (16 bits):** Time elapsed since the client started booting.
- **Flags (16 bits):** Leftmost bit indicates broadcast reply requirement.
- **Client IP Address (4 bytes):** Filled if the client already has an IP, else 0.

DHCP Packet Format

Operation Code	Hardware Type	Hardware Length	Hop Count
Transition ID			
Number of Seconds		Flags	
Client IP Address			
Your IP Address			
Server IP Address			
Gateway IP Address			
Client Hardware Address (16 Byte)			
Server Name (64 Byte)			
Boot File Name (128 Byte)			
Option (Variable Length)			

DHCP Packet Format

- **Your IP Address (4 bytes):** Client IP assigned by the server.
- **Server IP Address (4 bytes):** IP address of the responding DHCP server.
- **Gateway IP Address (4 bytes):** Router IP address (if applicable).
- **Client Hardware Address:** The device's MAC address.
- **Server Name (64 bytes):** Optional server hostname.
- **Boot Filename (128 bytes):** Pathname of boot file (for diskless clients).
- **Options (variable):** Vendor-specific or additional configuration.

***Note:** Each field in the DHCP packet plays a crucial role in identifying, addressing and enabling smooth communication.*

☆ Working of DHCP (Step-by-Step Easy Explanation)

DHCP works using a famous 4-step process called **DORA**:

1. DHCP Discover (Client → Server)

- When a device connects to a network, it has **no IP address**.
- It sends a **DHCP Discover** broadcast message:
“Is there any DHCP server? Please give me an IP!”
- This message goes to **all devices** in the network.

👉 Purpose: To find a DHCP server.

2. DHCP Offer (Server → Client)

- All DHCP servers that receive the Discover message respond with a **DHCP Offer**.
- Offer includes:
 - Available IP address
 - Subnet mask
 - Default gateway
 - DNS server
 - Lease time

👉 Purpose: DHCP server offers a suitable IP to the client.

3. DHCP Request (Client → Server)

- The client receives one or more Offers.
- It selects **one server's offer** and sends back a **DHCP Request** message:
“I accept the IP you offered.”
- This is also broadcasted to inform other DHCP servers that their offer is rejected.

👉 Purpose: Client confirms which IP it wants.

4. DHCP Acknowledgement (Server → Client)

- The chosen DHCP server sends a **DHCP ACK** (Acknowledgement).
- This finalizes the IP allocation.
- Now the client is officially assigned the IP address and can communicate in the network.

📖 Purpose: Server confirms the IP assignment.

★ DHCP Renewal

- Every IP has a **lease time** (example: 24 hours).
 - When half the time passes (called **T1 timer**), the client sends a Request again to renew the IP.
 - If approved, the server sends another ACK.
-

★ DHCP Rebinding

- If the main DHCP server does not respond, the client tries other DHCP servers.
-

★ Summary of DHCP Working (Very Short)

1. **Discover** – Client looks for DHCP server
2. **Offer** – Server offers an IP
3. **Request** – Client accepts the offer
4. **Acknowledge** – Server confirms the IP

This is the complete **DORA** process.

★ FTP (File Transfer Protocol)

FTP is one of the oldest and most widely used protocols for **transferring files** between computers on a network.



1. What is FTP?

FTP (File Transfer Protocol) is an **application layer protocol** used to upload, download, rename, delete, and manage files on remote servers. It works using **TCP**, which ensures reliable data transfer.



2. How FTP Works (Step-by-Step)

FTP uses **Client–Server architecture**:

✓ Step 1: User connects to an FTP server

- User provides:
 - Server address
 - Username
 - Password*(Anonymous login is also allowed in some servers)*

✓ Step 2: Two connections are created

FTP uses **two separate channels**:

Connection	Port	Purpose
Control connection	21	Login, commands
Data connection	20	Actual file transfer

Control and data channels make FTP efficient.

✓ Step 3: User sends commands

Examples:

- LIST – show files
- GET – download
- PUT – upload
- DELETE – remove file

- ✓ Step 4: Server responds and transfers files

All files are transferred using the **data connection**.

3. FTP Modes

FTP can work in 2 modes:

- ✓ Active Mode

Server initiates the data connection back to client.

- ✓ Passive Mode

Client initiates data connection.

Used when clients are behind firewalls.

4. Security Issue with FTP

FTP sends:

- Username
 - Password
 - Files
- in plain text (unencrypted)**
Therefore, it is not secure.

Secure alternatives:

- **FTPS** (FTP over SSL)
 - **SFTP** (Secure File Transfer Protocol – uses SSH)
-

5. Uses of FTP

- Website file upload
- Software download servers
- Remote backup
- Sharing large files

★ TELNET Protocol

Telnet is used for **remote login** to another computer.

1. What is Telnet?

TELNET (TERminal NETwork) is a protocol that allows a user to **remotely log into another computer** over a network.

It creates a **virtual terminal session** where the user can run commands as if sitting at the remote machine.

2. How Telnet Works (Step-by-Step)

✓ Step 1: Initiate connection

Client connects to **TCP port 23** on the remote machine.

✓ Step 2: Username & Password Login

The user enters login credentials to access the remote system.

✓ Step 3: Remote Command Execution

After login, the user gets a **command-line interface** of the remote system.

They can execute commands such as:

- Creating files
- Viewing logs
- Running programs
- Admin tasks

✓ Step 4: Server responds

Each command is processed and output is sent back to the client.

✓ Step 5: Session closes

When the user logs out, Telnet ends the virtual terminal session.

3. Features of Telnet

- Remote access
 - Command execution
 - CLI-based control
 - Works over TCP
 - Useful for network device management
-

4. Security Issues with Telnet

Telnet is **NOT secure** because:

- Sends username & password in **plain text**
- No encryption
- Vulnerable to eavesdropping and hacking

Therefore, Telnet is replaced by SSH (Secure Shell).

5. Uses of Telnet

- Managing remote servers (older systems)
 - Configuring routers & switches (historically)
 - Testing network services
 - Remote terminal access in legacy systems
-

★ Difference Between FTP and Telnet (Quick Table)

Feature	FTP	Telnet
Purpose	File transfer	Remote login/command execution

Feature	FTP	Telnet
Protocol	TCP	TCP
Port	21 (control), 20 (data)	23
Security	Not secure	Not secure
Data sent	Files	Commands
Alternative	SFTP/FTPS	SSH

☆ Simple Network Management Protocol (SNMP)

SNMP is a protocol used to **monitor, manage, and control network devices** such as routers, switches, servers, printers, and firewalls from a central location.

It works in the **Application Layer** of the TCP/IP model and uses **UDP ports 161 and 162**.

☆ Why SNMP is Used?

Network administrators use SNMP to:

- Check device performance
- Monitor network traffic
- Detect faults
- Receive alerts
- Change device configurations

It helps in **centralized network management**.

☆ Components of SNMP

1. SNMP Manager

- Central system that controls and manages devices
- Example: Network Monitoring Server (NMS)

2. SNMP Agent

- Small software running on each network device
- Collects information like CPU usage, memory, interfaces, errors, temperature etc.

3. MIB (Management Information Base)

- A database on each device
- Stores organized information (parameters and values)

4. Managed Devices

- Devices that SNMP controls
- Routers, switches, access points, firewalls etc.

☆ How SNMP Works (Easy Explanation)

SNMP uses simple messages between Manager and Agent:

✓ 1. Get Request

Manager → Agent

Asks for information (example: “What is CPU usage?”)

✓ 2. Get Response

Agent → Manager

Sends back the requested information.

✓ 3. Set Request

Manager → Agent

Changes a parameter (example: “Change interface status to up/down.”)

✓ 4. Trap Message

Agent → Manager

Device sends an alert automatically when a problem happens (e.g., link failure).

✓ 5. Inform Message

Confirmed notification from Agent to Manager.

☆ SNMP Versions

Version	Features
SNMPv1	Basic, simple, less secure
SNMPv2	Improved performance
SNMPv3	Secure version, supports encryption

☆ Advantages of SNMP

- ✓ Easy monitoring of all network devices
 - ✓ Automatic alerts (traps)
 - ✓ Remote management
 - ✓ Reduces manual work
 - ✓ Scalable for large networks
-

☆ Short 6–7 Lines Exam Answer

SNMP (Simple Network Management Protocol) is an application-layer protocol used to monitor and manage network devices like routers and switches. It works using a manager–agent model where the SNMP manager collects data from agents running on devices. Information is stored in a Management Information Base (MIB). The manager uses Get, Set, and Trap messages to communicate with agents. SNMP helps detect faults, monitor performance, and manage configurations. It uses UDP ports 161 and 162 and is available in versions SNMPv1, v2, and secure SNMPv3.

🌐 IPv6 Routing Technologies (Easy Explanation)

IPv6 supports several routing methods that help move data between networks. These technologies ensure IPv6 packets reach the correct destination, even across large and complex networks.

Below are the main IPv6 routing technologies:



1. Static IPv6 Routing

- Routes are **manually configured** by the network admin.
- Simple, secure, and predictable.
- Good for **small networks**.
- Example command (Cisco):

```
ipv6 route 2001:db8:2::/64 2001:db8:1::1
```



2. Dynamic IPv6 Routing Protocols

Dynamic routing updates routes **automatically** using algorithms.

a. RIPng (RIP Next Generation)

- IPv6 version of RIP.
- Distance-vector routing protocol.
- Sends updates every 30 seconds.
- Good for small networks.

b. OSPFv3 (Open Shortest Path First version 3)

- IPv6 version of OSPF.
- Link-state routing protocol.
- Fast, scalable, and secure.
- Best for **medium and large enterprise networks**.

c. IS-IS for IPv6

- Supports IPv6 routing using extensions.
- Used in large service provider networks.
- Highly stable and scalable.

d. BGP4+ (Border Gateway Protocol for IPv6)

- Used on the **Internet** between ISPs.
- Supports both IPv4 and IPv6 routing.
- Handles huge routing tables.



3. IPv6 Tunneling Technologies

Used when IPv6 traffic must pass through IPv4 networks.

a. 6to4 Tunnel

- Automatically wraps IPv6 packets inside IPv4 headers.
- Used for IPv6 communication over IPv4 Internet.

b. ISATAP (Intra-Site Automatic Tunnel Addressing Protocol)

- Allows sending IPv6 traffic within a private IPv4 network.

c. GRE Tunnels

- Manually configured tunnels for sending IPv6 through IPv4.

d. Teredo

- IPv6 tunneling for devices behind NAT.

✓ 4. Dual Stack

- Devices run **both IPv4 and IPv6 simultaneously**.
- Most common transition technique today.
- Helps migrate networks gradually from IPv4 to IPv6.

☆ IPv6 Application Services (Detailed Explanation)

IPv6 is not just a new addressing system—it also provides several **enhanced application services** that improve performance, security, mobility, and communication on modern networks.

These application services operate on top of the IPv6 protocol and make the internet more efficient and scalable.

🌐 1. Stateless Address Auto Configuration (SLAAC)

- SLAAC is an IPv6 feature that allows devices to **automatically generate their own IP address** without a DHCP server.
 - Devices listen for **Router Advertisements (RA)** and create IPv6 addresses using prefixes.
 - It simplifies network configuration and supports plug-and-play connectivity.
 - ✓ Used in laptops, mobiles, IoT devices.
-

2. DHCPv6 (Dynamic Host Configuration Protocol for IPv6)

- Provides **stateful and stateless address assignment** to IPv6 devices.
 - Can supply extra information such as DNS servers and domain names.
 - Works alongside SLAAC or independently.
 - ✓ Used in enterprise networks for controlled IP management.
-

3. DNS over IPv6 (AAAA Records)

- IPv6 uses **AAAA (Quad-A)** DNS records instead of A records.
- AAAA maps a domain name to an IPv6 address.
- IPv6 DNS supports:
 - Larger address space
 - Faster queries
 - Reverse DNS lookup (ip6.arpa)

✓ Used for websites, servers, cloud deployments.

4. IPv6 Anycast Services

- Anycast allows **multiple servers** to share the same IPv6 address.
- The network routes a client to the **nearest or best-performing server**.
Used for:
 - DNS root servers
 - CDN networks
 - Load balancing
 - Faster service access

✓ Greatly improves performance and reduces latency.

5. IPv6 Multicast Services

- IPv6 uses multicast instead of broadcast (broadcast is removed).
- Applications using multicast:
 - Online streaming
 - IPTV

- Conference calls
- Live video distribution
- Managed using **MLD (Multicast Listener Discovery)**.

✓ Results in efficient bandwidth usage.

6. Mobile IPv6 (MIPv6)

- Supports **seamless mobility** of devices across different networks.
- A mobile device keeps the same IPv6 address even when moving between Wi-Fi, cellular, and other networks.

Used in:

- Smartphones
- Vehicular networks
- IoT mobility applications

✓ Ensures uninterrupted communication.

7. IPsec for Security Services (Mandatory in IPv6)

IPv6 natively supports **IPsec**, providing:

- Authentication
- Encryption
- Integrity
- Secure remote access (VPNs)

Used for:

- Secure communication
- Enterprise VPNs
- Encrypted data transmission

✓ Improves security at the network layer.

8. Peer-to-Peer Applications

IPv6's large address space allows direct end-to-end communication.
Used in:

- VoIP
- Video calling
- Online gaming
- File sharing
- IoT device communication

✓ No NAT required, making connections faster and simpler.

9. Cloud and IoT Services

IPv6 is essential for modern services like:

- Smart homes
- Smart sensors
- Cloud-based systems
- Large-scale IoT networks

IPv6 provides unique addressing for billions of devices.

☆ Difference Between Routing and Switching (T-Form)

Routing	Switching
Routing works at the Network Layer (Layer 3) of OSI model.	Switching works at the Data Link Layer (Layer 2) .
Uses IP addresses to forward packets.	Uses MAC addresses to forward frames.
Used to connect different networks .	Used to connect devices within the same network (LAN) .
Makes path selection for data to reach destination.	Performs frame forwarding within a LAN.
Devices used: Routers, Layer 3 Switches .	Devices used: Switches, Bridges .
Packet forwarding is slower , because it uses logical addressing and routing tables.	Frame forwarding is faster , because it uses hardware-based switching (CAM table).
Can perform NAT, ACL, QoS, load balancing .	Performs VLAN creation and segmentation .

Routing

Works with **routing protocols** like RIP, OSPF, BGP.

Switching

Works with **switching protocols** like STP, RSTP.