



FH Salzburg
MultiMediaTechnology

***Identifying the Ideal Length of Time to Record
Smartphone Data, in Order to Obtain Distinct
Clusters to Predict Eating Crises***

Bachelor Thesis 2

Author: Natasha Lauren Troth

Advisor: FH-Prof. DI Dr. Simon Ginzinger, MSc.

Salzburg, Austria, 10.05.2020

Affidavit

I herewith declare on oath that I wrote the present thesis without the help of third persons and without using any other sources and means listed herein; I further declare that I observed the guidelines for scientific work in the quotation of all unprinted sources, printed literature and phrases and concepts taken either word for word or according to meaning from the Internet and that I referenced all sources accordingly.

This thesis has not been submitted as an exam paper of identical or similar form, either in Austria or abroad and corresponds to the paper graded by the assessors.

Date

Signature

First Name *Last Name*

Kurzfassung

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Aenean venenatis nulla vestibulum dignissim molestie. Quisque tristique tortor vitae condimentum egestas. Donec vitae odio et quam porta iaculis ut non metus. Sed fermentum mauris non viverra pretium. Nullam id facilisis purus, et aliquet sapien. Pellentesque eros ex, faucibus non finibus a, pellentesque eu nibh. Aenean odio lacus, fermentum eu leo in, dapibus varius dolor. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Proin sit amet ornare velit. Donec sit amet odio eu leo viverra blandit. Ut feugiat justo eget sapien porttitor, sit amet venenatis lacus auctor. Curabitur interdum ligula nec metus sollicitudin vestibulum. Fusce placerat augue eu orci maximus, id interdum tortor efficitur.

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Aenean venenatis nulla vestibulum dignissim molestie. Quisque tristique tortor vitae condimentum egestas. Donec vitae odio et quam porta iaculis ut non metus. Sed fermentum mauris non viverra pretium. Nullam id facilisis purus, et aliquet sapien. Pellentesque eros ex, faucibus non finibus a, pellentesque eu nibh. Aenean odio lacus, fermentum eu leo in, dapibus varius dolor. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Proin sit amet ornare velit. Donec sit amet odio eu leo viverra blandit. Ut feugiat justo eget sapien porttitor, sit amet venenatis lacus auctor. Curabitur interdum ligula nec metus sollicitudin vestibulum. Fusce placerat augue eu orci maximus, id interdum tortor efficitur.

Contents

1	Introduction	1
2	Related work	2
3	Theory	2
3.1	Data mining	3
3.1.1	Data preprocessing	3
3.2	Cluster Analysis	4
3.2.1	Overview of clustering algorithms	4
3.2.2	Dimensionality reduction	4
4	Experiment	4
4.1	Preparation of the data set	4
4.2	Clustering	4
4.3	Clustering after dimensionality reduction	4
4.4	Comparison and evaluation of clusters of different time lengths	4
5	Discussion	5
6	Conclusion	5
	Appendices	7
A	git-Repository	7
B	Vorlagen für Studienmaterial	7
C	Archivierte Webseiten	8

List of Figures

Listings

List of Tables

1 Introduction

Han, Pei, and Kamber (2011)[18, 32, 362, 363, 367] declare, that data mining is used to discover patterns and knowledge from data. Cluster Analysis is a type of machine learning algorithm known as unsupervised machine learning. It is used in data mining to divide data into groups (clusters). Each cluster contains data that is similar to each other, but dissimilar to the data allocated to other clusters. Cluster Analysis can be used to acquire knowledge on the distribution of the data, discover characteristics, detect outliers and reduce noise, or to pre-process data for other algorithms.

There are several different methods to create clustering. Han, Pei, and Kamber (2011)[362, 364, 366-367, 385, 392] explain, that objects are often arranged into clusters using distance measures (e.g. Euclidean or Manhattan distance measures).

Bermad and Kechadi (2016) introduce in their paper, how clustering can be used in digital forensics to provide information on all the events that led up to a certain crime. They used ascending hierarchical clustering to receive clusters of events (e.g. phone calls, SMS) ordered in time, thus creating a timeline of events leading up to the incident.

Dey and Chakraborty (2015)[1,2,6,7] give an example, where clustering was implemented to predict future weather. Air pollutant data was preprocessed and then arranged into clusters using (incremental) DBSCAN clustering. Finally, priority based protocol was used on them to predict weather conditions and a temperature range. The accuracy of the technique, based on hit and miss times, was calculated to approximately 74.5%.

SmartEater¹ is an upcoming mHealth (mobile health) app, with the goal to provide the user with content-dependent feedback, to avert a food craving episode. The app will predict future eating crises based on the user's past behaviour. In order to reduce intense user input, the app records and uses various smartphone sensor data. With the help of data mining, machine learning algorithms, and pattern recognition, this recorded situational context data will aid in predicting stress. The following data is recorded by the app:

1. Background volume
2. Relative movement of the smartphone (gyro and accel)
3. Time and duration of phone calls (without storing the numbers)
4. Time of messages (e.g. SMS, WhatsApp) (without collecting identifying information such as content, addresses, numbers)
5. Screen activity (so-called touch events)
6. Screen-on-time (illuminated display)
7. Ambient brightness

1. <https://sites.google.com/site/eatingandanxietylab/resources/smart eater>

8. Data volume per unit of time (summary value of all smartphone activities on the internet)
9. Switch-on and switch-off times of the smartphone

This sensor data will be recorded for different lengths of time. It is necessary to establish which time period will be most fitting to make accurate predictions for the future. This thesis will use cluster analysis to determine which time period is most significant.

According to Han, Pei, and Kamber (2011)[414], the above-mentioned clustering methods work well with data sets that are not high-dimensional and have less than 10 attributes. Since the SmartEater data set only has 9 dimensions, it is not considered high-dimensional. This paper will therefore utilise these clustering methods. Since different clustering algorithms can yield different results, multiple methods will be used and compared.

To reduce the size and amount of data, dimensionality reduction will be used. Han, Pei, and Kamber (2011)[93] define dimensionality reduction as a type of data reduction, which removes random attributes and creates a smaller data set with close to equal integrity. This thesis will use principal component analysis (PCA) to reduce the dimensionality. Furthermore, T-Distributed Stochastic Neighbor Embedding (t-SNE) will be employed to depict the data set in this thesis. Maaten and Hinton (2008)[2579] first introduce t-SNE, which is used to visualise data with a higher dimensionality.

The clustering methods will be implemented using a Python machine learning platform or library (e.g. Anaconda², scikit-learn³). Next, these will be implemented on the other time lengths. The resulting clusters of each time length will be compared to one another and evaluated. Berkhin (2006)[39] states, that the Silhouette Coefficient (Kaufman and Rousseeuw 2009)[87] can be used to measure the separation between clusters.

The thesis will be structured as follows: The first section will briefly present existing work relating to this subject. The following chapter will concentrate on the theory of data mining and cluster analysis. After covering these topics, the next section will describe the conducted experiment and its results. In the final sections, the findings of the experiment will be discussed and summarised.

2 Related work

Related Work

page 3 book from library

3 Theory

in theory

2. <https://www.anaconda.com/>

3. <https://scikit-learn.org/stable/>

3.1 Data mining

Larose and Larose (2015)[4] declares that data mining is used to recognise patterns and trends in large amounts of data.

Data mining requires continuous human supervision for quality monitoring and evaluation. Data mining software alone will server wrong results.

Data mining is used for description of patterns and trends, estimation of numerical values, prediction of future results, classification of categorical variables, clustering of similar objects and association of attributes.

3.1.1 Data preprocessing

Data sets first need to undergo a data preprocessing step, including data cleaning and data transformation. This aids in making the data useful in data mining. Raw data extracted directly from databases can be incomplete (values are missing) or be noisy (contains outliers), or may contain out-dated or redundant data. This unpreprocessed data may also not be in a correct form for data mining models. The goal is to decrease garbage in, garbage out (GIGO). Reducing the irrelevant data that is fed into the model (garbage in), the amount of irrelevant data received out of the model is reduced (garbage out).

There are some data mining that have trouble functioning correctly when fed outliers. Moreover, outliers may be data errors. Graphical methods used to identify outliers include, histograms or two-dimensional scatter plots. The Z-score method can be used to numerically calculate outliers. Outliers should not automatically be removed from the data set.

Data cleaning is used to handle outliers, errors and unusual values found in the data set.

One approach to handle records with missing values, is to delete said record. The author does not recommend this, since it could lead to a biased subset of data, if the missing values are systematic. Furthermore, it would mean wasting the data stored in the other fields of that record. A preferred approach is to substitute the missing value. The value can be replaced, either with a constant determined by the data analyst, with a field mean (for numerical values) or mode (for categorical values), with a random value, or with imputed values based on different features of the record. Replacing missing values can be a gamble, since it can possibly lead to invalid results. For example, the authors experimented with a database of cars. Substituting a missing brand with a random value (here "Japan") led to a car, that doesn't even exist. Data imputation takes into account the other attributes stored in the record and from these, calculates what the missing value would most likely be.

Another step in data preprocessing is identifying misclassifications. An example given by the authors, is classifying a record as USA instead of US, or France instead of Europe. These classes only contained one record in comparison to the other more frequently used classes.

In some data mining algorithms, variables with higher ranges can unjustly influence the results, having more influence than smaller ones. Therefore, the authors recommend to normalise numerical data. Typical nomalisation techniques includ "min-max normalization" and "Z-score standardization".

Flag variables can be used to transform categorical variables into numerical. A flag variable can take on one of two values: 0 and 1 (e.g. female = 0, male = 1). When $k_i=3$ (k being the amount of categorical predictors), the variables can be transformed into $k-1$ flag variables. Assigning categorical variables numerical values is not advised, since this orders the categorical variables. For example, if North = 1, East = 2, South = 3 and West = 4, West would be closer to South than to North, etc.

3.2 Cluster Analysis

in cluster analysis

3.2.1 Overview of clustering algorithms

Overview Clustering Algs

3.2.2 Dimensionality reduction

Dimensionality Reduction

4 Experiment

in experiment

4.1 Preparation of the data set

in prep of data set

4.2 Clustering

in clustering

4.3 Clustering after dimensionality reduction

in clustering after dim red

4.4 Comparison and evaluation of clusters of different time lengths

in comparison of diff time lengths

5 Discussion

in discussion.tex

6 Conclusion

in conclusion

References

- Berkhin, P. 2006. "A Survey of Clustering Data Mining Techniques." In *Grouping Multidimensional Data: Recent Advances in Clustering*, edited by Jacob Kogan, Charles Nicholas, and Marc Teboulle, 25–71. Berlin, Heidelberg: Springer Berlin Heidelberg. ISBN: 978-3-540-28349-2. doi:10.1007/3-540-28349-8_2. https://doi.org/10.1007/3-540-28349-8_2.
- Bermad, N., and M. T. Kechadi. 2016. "Evidence analysis to basis of clustering: Approach based on mobile forensic investigation." In *2016 7th International Conference on Sciences of Electronics, Technologies of Information and Telecommunications (SETIT)*, 300–307. Hammamet, Tunisia, December. doi:10.1109/SETIT.2016.7939884.
- Dey, R., and S. Chakraborty. 2015. "Convex-hull DBSCAN clustering to predict future weather." In *2015 International Conference and Workshop on Computing and Communication (IEMCON)*, 1–8. Vancouver, BC, Canada, October. doi:10.1109/IEMCON.2015.7344438.
- Han, Jiawei, Jian Pei, and Micheline Kamber. 2011. *Data mining: concepts and techniques*. Burlington, Massachusetts: Elsevier.
- Kaufman, Leonard, and Peter J Rousseeuw. 2009. *Finding groups in data: an introduction to cluster analysis*. Vol. 344. Hoboken, New Jersey: John Wiley & Sons.
- Larose, Daniel T, and Chantal D Larose. 2015. *Data mining and predictive analytics*. 2. ed.. Wiley series on methods and applications in data mining. Hoboken, New Jersey: John Wiley & Sons. ISBN: 9781118116197.
- Maaten, Laurens van der, and Geoffrey Hinton. 2008. "Visualizing data using t-SNE." *Journal of Machine Learning research* 9 (Nov): 2579–2605.

Appendices

Anhänge löschen, die nicht verwendet werden.

A git-Repository

Das Repository dient zur Dokumentation und Nachvollziehbarkeit der Arbeitsschritte. Stellen Sie sicher, dass der/die BetreuerIn Zugriff auf das Repository hat. Stellen im Sinne des Datenschutzes sicher, dass das Repository nicht für andere zugänglich ist.

Verpflichtende Daten für Bachelorarbeit 1 und 2:

- LaTeX-Code der finalen Version der Arbeit
- alle Publikationen, die als pdf verfügbar sind.
- alle Webseiten als pdf

Verpflichtende Daten für Bachelorarbeit 2:

- Quellcode für praktischen Teil
- Vorlagen für Studienmaterial (Fragebögen, Einverständniserklärung, ...)
- eingescanntes, ausgefülltes Studienmaterial (Fragebögen, Einverständniserklärung, ...)
- Rohdaten und aufbereitete Daten der Evaluierungen (Log-Daten, Tabellen, Graphen, Scripts, ...)

Link zum Repository auf dem MMT-git-Server `gitlab.mediacube.at`:

`https://gitlab.mediacube.at/fhs123456/Abschlussarbeiten-Max-Muster`

B Vorlagen für Studienmaterial

Vorlagen für Studienmaterial müssen in den Anhang.

C Archivierte Webseiten

http://web.archive.org/web/20160526143921/http://www.gamedev.net/page/resources/_/technical/game-programming/understanding-component-entity-systems-r3013, letzter Zugriff 1.1.2016

http://web.archive.org/web/20160526144551/http://scottbilas.com/files/2002/gdc_san_jose/game_objects_slides_with_notes.pdf, letzter Zugriff 1.1.2016