

---

---

```
Y gp" lpi "l k"h " g k p"e p n"o cp "rg rmg"
g"l k d"c "c"r meg" " rf" go g"gr k lg ."
cpf"r " gk"gr k lg " g g "K gegp n" c gf"
lpi "DkD eng"cn ."cpf" cp gf" "dg"cdmg" "
lo ncp g n" rfc g"o "l k d"cpf"DkD eng"
gr k lg " gp"e cpi g " g g"o c f g"
V "dgi lp." gpcog" "e gp" go g" o "hmg"
pcogf"origin" "c" f kmg gp "pcog" "f" gpcog" k" "
g"pcog" h' g" g leg" "c g" lpi ." e "
c "github" "bitbucket"
```

```
git remote rename origin github
```

```
"ecp" gp"cff" g" go g"h " " ge pf"
go g"gr k ."lp" k"ec g."c"DkD eng"
gr k "
```

```
git remote add bitbucket git@bitbucket
.org:username/example.git
```

```
Chg c f ." )m cp" " g" r" "origin" go g"
"r " "d " h' g g "K g" g" h m lpi "
e o o cpf "
```

```
git config -e
```

```

    "kldg"i gg gf" k " "l k"e phk c k p" o "
    rlngn" kpi " ko "Cf f" g"[remote
    "origin"]" ge k p" " g"d o" h' g"hg" k " g"
    WT "h o"gce "go g"gr k " )f"rlng" "r "
    "

```

i k e phk "

```

[core]
    repositoryformatversion = 0
    filemode = true
    bare = false
    logallrefupdates = true
    ignorecase = true
    precomposeunicode = false
[branch "master"]
    remote = github
    merge = refs/heads/master
[remote "github"]
    url = git@github.com:username/repo.git
    fetch = +refs/heads/*:refs/remotes/github/*
[remote "bitbucket"]

```

```
url = git@bitbucket.org:username/repo.git
```

```
fetch = +refs/heads/*:refs/remotes/bitbucket/*
```

```
[remote "origin"]
```

```
url = git@github.com:username/repo.git
```

```
url = git@bitbucket.org:username/repo.git
```

```
"ecp" gp"r " "d " gr k kg "d "k lpi "
```

```
git push origin master
```

```
" "c" lpi ng" pg"d "k lpi "gk g " h" g g"  
e o o cpf "
```

```
git push github master
```

```
git push bitbucket master
```