

# npm-profile

## Change settings on your registry profile

### SYNOPSIS

```
npm profile get [--json|--parseable] [<property>]
npm profile set [--json|--parseable] <property> <value>
npm profile set password
npm profile enable-2fa [auth-and-writes|auth-only]
npm profile disable-2fa
```

### DESCRIPTION

Change your profile information on the registry. This not be available if you're using a non-npmjs registry.

- **npm profile get [<property>]** : Display all of the properties of your profile, or one or more specific properties. It looks like:

```
+-----+-----+
| name           | example           |
+-----+-----+
| email          | me@example.com (verified) |
+-----+-----+
| two factor auth | auth-and-writes    |
+-----+-----+
| fullname       | Example User      |
+-----+-----+
| homepage       |                    |
+-----+-----+
| freenode       |                    |
+-----+-----+
| twitter        |                    |
+-----+-----+
| github         |                    |
+-----+-----+
| created        | 2015-02-26T01:38:35.892Z |
```

```
+-----+-----+
| updated      | 2017-10-02T21:29:45.922Z |
+-----+-----+
```

- **npm profile set <property> <value>** : Set the value of a profile property. You can set the following properties this way: email, fullname, homepage, freenode, twitter, github
- **npm profile set password** : Change your password. This is interactive, you'll be prompted for your current password and a new password. You'll also be prompted for an OTP if you have two-factor authentication enabled.
- **npm profile enable-2fa [auth-and-writes|auth-only]** : Enables two-factor authentication. Defaults to **auth-and-writes** mode. Modes are:
  - **auth-only** : Require an OTP when logging in or making changes to your account's authentication. The OTP will be required on both the website and the command line.
  - **auth-and-writes** : Requires an OTP at all the times **auth-only** does, and also requires one when publishing a module, setting the **latest** dist-tag, or changing access via **npm access** and **npm owner** .
- **npm profile disable-2fa** : Disables two-factor authentication.

## DETAILS

All of the **npm profile** subcommands accept **--json** and **--parseable** and will tailor their output based on those. Some of these commands may not be available on non npmjs.com registries.