Mail Events Summary

Scope

The application defines **15 mail events**. Each event inserts a `Class_tb_mailer` record into the shared mail queue; this repository does not send SMTP mail directly.

Recipient email addresses are read from `acpl_common.dbo.employees.empl_mail` using the IDs listed below.

Recipient ID Definitions

- **Plan creator ID**: `test_plan_hdr.plan_by_slno`
- **Plan verifier IDs**: `test_plan_verifiers.ver_empl_slno` for the current `tp_hdr_slno`
- **Validation creator ID**: `validation_hdr.created_by_slno`
- **Conditional verifier ID**: `validation_hdr.verified_by`
- **Final-release verifier ID**: `validation_hdr.finalrel_verified_by`
- **QA head IDs**: all `employees.empl_slno` values where `dept_slno IN (39, 40)`, `department_head = 1`, and `del_status = 0`

Test Plan Mail Events

#	Event / Subject	Screen Name	To ID	CC ID
TP-1	Test Plan Submitted	Test Plan	All plan verifier IDs (`test_plan_verifiers.ver_empl_slno`)	Plan creator ID (`plan_by_slno`)
TP-2	Test Plan Verified	Test Plan	All active QA head IDs (departments 39/40)	Plan creator ID + all plan verifier IDs
TP-3	Test Plan Verification Rejected	Test Plan	Plan creator ID	All plan verifier IDs
TP-4	Test Plan Approved	Test Plan	Plan creator ID + all plan verifier IDs	All active QA head IDs (departments 39/40)
TP-5	Test Plan Approval Rejected	Test Plan	Plan creator ID + all plan verifier IDs	All active QA head IDs (departments 39/40)

Conditional Release Mail Events

#	Event / Subject	Screen Name	To ID	CC ID
CR-1	Conditional Release - Best Trial Submitted	Test Plan Qualification	Conditional verifier ID (`verified_by`)	Validation creator ID (`created_by_slno`)

#	Event / Subject	Screen Name	To ID	CC ID
CR-2	Conditional Release - Trial Details Verified	Conditional Release Verification	All active QA head IDs (departments 39/40)	Validation creator ID + conditional verifier ID
CR-3	Conditional Release - Trial Details Verification Rejected	Conditional Release Verification	Validation creator ID	Conditional verifier ID
CR-4	Conditional Release - Trial Details Approved	Conditional Release Approval	Validation creator ID + conditional verifier ID	All active QA head IDs (departments 39/40)
CR-5	Conditional Release - Trial Details Approval Rejected	Conditional Release Approval	Validation creator ID + conditional verifier ID	All active QA head IDs (departments 39/40)

Final Release Mail Events

#	Event / Subject	Screen Name	To ID	CC ID
FR-1	Final Release - Best Trial Submitted	Test Plan Qualification	Final-release verifier ID (`finalrel_verified_by`)	Validation creator ID (`created_by_slno`)
FR-2	Final Release - Trial Details Verified	Final Release Verification	All active QA head IDs (departments 39/40)	Validation creator ID + final-release verifier ID
FR-3	Final Release - Trial Details Verification Rejected	Final Release Verification	Validation creator ID	Final-release verifier ID
FR-4	Final Release - Trial Details Approved	Final Release Approval	Validation creator ID + final-release verifier ID	All active QA head IDs (departments 39/40)
FR-5	Final Release - Trial Details Approval Rejected	Final Release Approval	Validation creator ID + final-release verifier ID	All active QA head IDs (departments 39/40)

Event Flow Summary

1. A submission mail goes to the assigned verifier, with the creator copied.
2. After verification, a mail goes to the QA department heads, with the creator and verifier(s) copied.
3. A verification rejection goes to the creator, with the verifier(s) copied.
4. After approval, the creator and verifier(s) are notified, with the QA department heads copied.
5. An approval rejection uses the same recipient pattern as approval completion.

Implementation References

- Test Plan mail methods: `Controllers/TestPlanController.cs`, lines 1818-2398
- Validation mail methods: `Controllers/ValidationController.cs`, lines 2425-3606
- Mail queue fields: `screen_name`, `send_reason`, `subject`, `send_to`, and `cc_to`

Notes

- Recipient IDs are dynamic database values, so this source code does not contain fixed employee numbers or email addresses.
- Multiple recipient email addresses are combined into comma-separated strings.
- Null or blank employee email addresses may result in an empty or partial `send_to`/`cc_to` value because mail records are queued without recipient validation.
- Conditional and final submission mails are generated only for Machine or Material qualifications with a matching release type.