```
-- -- this is a new sql file
use master;
GO

--alter database [] set single_user with rollback immediate;
--GO

IF EXISTS (select name from master.dbo.sysdatabases where name = N'dbpetstore')
drop database dbpetstore;
GO

-- Create and use the database (optional)
IF NOT EXISTS (select name from master.dbo.sysdatabases where name = N'dbpetstore')
CREATE DATABASE dbpetstore;
GO

USE dbpetstore;
GO

IF OBJECT_ID(N'dbo.petstore', N'U') IS NOT NULL
DROP TABLE dbo.petstore;
GO

CREATE TABLE dbo.petstore
(
    pst_id        TINYINT        NOT NULL IDENTITY(1,1),
    pst_name      VARCHAR(30)    NOT NULL,
    pst_street    VARCHAR(30)    NOT NULL,
    pst_city      VARCHAR(30)    NOT NULL,
    pst_state     CHAR(2)        NOT NULL DEFAULT 'AZ',
    pst_zip       INT            NOT NULL CHECK (pst_zip > 0 and pst_zip <= 999999999),
    pst_phone     BIGINT         NOT NULL,
    pst_email     VARCHAR(100)   NOT NULL,
    pst_url       VARCHAR(100)   NOT NULL,
    pst_ytd_sales DECIMAL(10,2)  NOT NULL CHECK (pst_ytd_sales > 0),
    pst_notes     VARCHAR(255)   NULL,
    PRIMARY KEY (pst_id)

);

SELECT * FROM information_schema.tables;

INSERT INTO dbo.petstore
(pst_name, pst_street, pst_city, pst_state, pst_zip, pst_phone, pst_email, pst_url, pst_ytd_sales,
    pst_notes)

VALUES
('PETCO', '123 Main St', 'Phoenix', 'AZ', 85008, 6025551234, 'petco@gmail.com', 'https://www.petco.com',
    100000.00, 'No notes for PETCO'),
('PETSMART', '456 Elm St', 'Tucson', 'AZ', 85701, 5205551234, 'petsmart@gmail.com',
    'https://www.petsmart.com', 200000.00, 'No notes for PETSMART'),
('PETLAND', '789 Oak St', 'Mesa', 'AZ', 85201, 4805551234, 'petland@gmail.com', 'https://www.petland.com',
    150000.00, 'No notes for PETLAND'),
('PETWORLD', '101 Pine St', 'Scottsdale', 'AZ', 85251, 4805555678, 'petworld@gmail.com',
    'https://www.petworld.com', 175000.00, 'No notes for PETWORLD'),
('PETZONE', '202 Maple St', 'Chandler', 'AZ', 85224, 4805559876, 'petzone@gmail.com',
    'https://www.petzone.com', 160000.00, 'No notes for PETZONE');
select * from dbo.petstore;


-- Drop tables if they exist (child first)
IF OBJECT_ID(N'dbo.pet', N'U') IS NOT NULL
DROP TABLE dbo.pet;
GO

-- PET table
CREATE TABLE dbo.pet
```

```
(
    pet_id        SMALLINT       NOT NULL IDENTITY(1,1),
    pst_id        TINYINT        NOT NULL,
    pet_type      VARCHAR(45)    NOT NULL,
    pet_sex       CHAR(1)        NOT NULL CHECK (pet_sex IN ('m', 'f')),
    pet_cost      DECIMAL(6,2)   NOT NULL CHECK (pet_cost > 0),
    pet_price     DECIMAL(6,2)   NOT NULL CHECK (pet_price > 0),
    pet_age       SMALLINT       NOT NULL CHECK (pet_age > 0 and pet_age <= 10500),
    pet_color     VARCHAR(30)    NOT NULL,
    pet_sale_date DATE           NULL,
    pet_vaccine   CHAR(1)        NOT NULL CHECK (pet_vaccine IN ('y', 'n')),
    pet_neuter    CHAR(1)        NOT NULL CHECK (pet_neuter IN ('y', 'n')),
    pet_notes     VARCHAR(255)   NULL,
    PRIMARY KEY (pet_id),
    CONSTRAINT FK_pet_petstore
        FOREIGN KEY (pst_id)
        REFERENCES dbo.petstore (pst_id)
        ON DELETE CASCADE
        ON UPDATE CASCADE
);

SELECT * FROM information_schema.tables;

INSERT INTO dbo.pet
(pst_id, pet_type, pet_sex, pet_cost, pet_price, pet_age, pet_color, pet_sale_date, pet_vaccine,
    pet_neuter, pet_notes)
VALUES
(1, 'Dog', 'm', 500.00, 1000.00, 3, 'Brown', '2024-01-01', 'y', 'y', 'No notes for Dog'),
(2, 'Cat', 'f', 300.00, 600.00, 2, 'Black', '2024-02-01', 'y', 'n', 'No notes for Cat'),
(3, 'Rabbit', 'm', 100.00, 200.00, 1, 'White', '2024-03-01', 'n', 'y', 'No notes for Rabbit'),
(4, 'Hamster', 'f', 50.00, 100.00, 1, 'Gray', '2024-04-01', 'n', 'n', 'No notes for Hamster'),
(5,'Parrot', 'm', 200.00, 400.00, 5, 'Green', '2024-05-01', 'y', 'y', 'No notes for Parrot');


EXEC sp_help 'dbo.pet';

select * from dbo.pet;
```