

# Du capteur à la mesure : rapport de projet

## Introduction

À venir. GitHub repo ici

## Analyse de la datasheet du capteur OP599

Le capteur OP599 est un phototransistor qui est sensible aux longueurs d'onde infrarouges. L'avantage du phototransistor par rapport à la photodiode est qu'il est facilement possible de récupérer une tension en sortie sans composants actifs additionnels. Nous disposons de la variante OP599A.

### Caractéristiques mécaniques

- Package T-1¾ avec base TO-18 (2 fils).  
*Le package est l'apparence physique du composant, permettant de prévoir son montage dans le circuit. Ici, les deux fils du capteur sont espacés de 2.54mm, ce qui est l'espacement de pins standard sur une breadboard ou une Arduino.*
- Angle de réception directif de 20 degrés (10 degrés de chaque côté du centre).  
*Il sera nécessaire de placer la partie bombée du capteur bien en face de l'émetteur.*
- Le schéma et la photo montrent que le package est asymétrique et que le fil le plus long, du côté du rebord saillant, sera l'émetteur (pin 1) et l'autre le collecteur (pin 2) du phototransistor.  
*Information indispensable pour monter le capteur dans le bon sens.*

### Caractéristiques électroniques

- Valeurs limites de voltage :
  - Collecteur-émetteur : 30V.  
*Collecteur vers la tension d'alimentation, émetteur vers la masse. Nous utiliserons ce montage.*
  - Émetteur-collecteur : 5V.  
*Émetteur vers la tension d'alimentation, collecteur vers la masse.*
- Ampérage consommé par le transistor en condition d'éclairage maximal :
$$I_{C(on)} \begin{cases} \min = 2.35 \text{ mA} \\ \max = 3.85 \text{ mA} \end{cases}$$
*Sera utile pour dimensionner la résistance à utiliser dans le circuit du*

*capteur*

- Ampérage consommé par le transistor en condition d'éclairage minimal :  
 $I_{CEO} = 100 \text{ nA}$   
*Ne consomme presque aucun courant dans le noir*
- Voltage de saturation minimal :  $V_{CE(SAT)} = 0.40 \text{ V}$   
*Ne consomme presque aucun courant dans le noir*




Figure 1: Montage de type 1





Figure 2: Montage de type 2

Le transistor intégré est un NPN et il sera passant quant le capteur sera éclairé

en infrarouge. Si l'on veut que **la tension perçue en sortie monte quand le capteur est éclairé** il faudra utiliser le montage de **type 1**, si l'on veut qu'elle baisse, on utilisera le **type 2**.

# NPN Silicon Phototransistor

## OP599 Series



### Features:

- Dark blue injection-molded plastic package
- Variety of sensitivity ranges
- T-1 $\frac{3}{4}$  package style with TO-18 base
- Excellent optical lens surface
- Excellent chip placement

### Description:

Each device in this series consists of a NPN silicon phototransistor mounted in a dark blue plastic injection molded shell package, with a narrow receiving angle that provides excellent on-axis coupling and optical/mechanical axis alignment. The shell also provides excellent optical lens surface, control of chip placement and consistency of the outside package dimensions.


The **OP599** series sensors are 100% production tested for close correlation with OPTEK GaAlAs emitters.

Please refer to Application Bulletins 208 and 210 for additional design information and reliability (degradation) data.

### Applications:

- Applications requiring a narrow receiving angle
- Applications that are space-limited

Ordering Information			
Part Number	Sensor	Viewing Angle	Lead Length
OP599A	Transistor	20°	0.75"
OP599B			
OP599C			



DIMENSIONS ARE IN: [MILLIMETERS]  
INCHES



RoHS

Pin #	Sensor
1	Emitter
2	Collector

### CONTAINS POLYSULFONE

To avoid stress cracking, we suggest using ND Industries' **Vibra-Tite** for thread-locking. **Vibra-Tite** evaporates fast without causing structural failure in OPTEK's molded plastics.

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

# NPN Silicon Phototransistor

## OP599 Series



### Electrical Specifications

Absolute Maximum Ratings ( $T_A = 25^\circ\text{C}$ unless otherwise noted)	
Storage and Operating Temperature Range	$-40^\circ\text{C}$ to $+100^\circ\text{C}$
Collector-Emitter Voltage	30 V
Emitter-Collector Voltage	5 V
Continuous Collector Current	50 mA
Lead Soldering Temperature [1/16 inch (1.6 mm) from case for 5 seconds with soldering iron]	$260^\circ\text{C}^{(1)}$
Power Dissipation	100 mW <sup>(2)</sup>

Electrical Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise noted)						
SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
$I_{C(ON)}$	On-State Collector Current					See Note (3).
	OP599A	2.35	-	3.85	mA	
	OP599B	1.20	-	1.95	mA	
	OP599C	0.40	-	-	mA	
$I_{CEO}$	Collector-Dark Current	-	-	100	nA	$V_{CE} = 10.0\text{ V}$ , $E_E = 0$
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	30	-	-	V	$I_C = 100\text{ }\mu\text{A}$
$V_{(BR)ECO}$	Emitter-Collector Breakdown Voltage	5.0	-	-	V	$I_E = 100\text{ }\mu\text{A}$
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage	-	-	0.40	V	$I_C = 100\text{ }\mu\text{A}$ , $E_E = 0.25\text{ mW/cm}^2^{(3)}$

#### Notes:

1. RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering. A maximum 20 grams force may be applied to the leads when soldering.
2. Derate linearly 1.33 mW/ $^\circ\text{C}$  above  $25^\circ\text{C}$ .
3.  $V_{CE} = 5\text{ V}$ . Light source is an unfiltered GaAlAs emitting diode operating at peak emission wavelength of 890 nm and  $E_{E(APT)}$  of  $0.25\text{ mW/cm}^2$ .
4. This dimension is held to within  $\pm 0.005''$  on the flange edge and may vary up to  $\pm 0.020''$  in the area of the leads.

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.



OPTEK Technology, Inc.  
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
www.optekinc.com | www.ttelectronics.com

# NPN Silicon Phototransistor

## OP599 Series



### Performance



General Note  
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TT Electronics:](#)

[OP599A](#) [OP599B](#) [OP599C](#) [OP599D](#)